

GENERAL NOTES

ANY DISCREPANCIES FOUND AMONG THE DRAWINGS, THE SPECIFICATIONS, THESE GENERAL NOTES AND THE SITE CONDITIONS SHALL BE REPORTED TO THE ARCHITECT, WHO SHALL CORRECT SUCH DISCREPANCY IN WRITING. ANY WORK DONE BY THE GENERAL CONTRACTOR AFTER DISCOVERY OF SUCH DISCREPANCY SHALL BE DONE AT THE GENERAL CONTRACTOR'S RISK. THE GENERAL CONTRACTOR SHALL VERIFY AND COORDINATE DIMENSIONS AMONG ALL DRAWINGS PRIOR TO PROCEEDING WITH ANY WORK OR FABRICATION. THE STRUCTURE HAS BEEN DESIGNED TO RESIST CODE SPECIFIED VERTICAL AND LATERAL FORCES AFTER THE CONSTRUCTION OF ALL STRUCTURAL ELEMENTS HAS BEEN COMPLETED. STABILITY OF THE STRUCTURE PRIOR TO COMPLETION IS THE SOLE RESPONSIBILITY OF THE GENERAL CONTRACTOR. THIS RESPONSIBILITY INCLUDES BUT IS NOT LIMITED TO JOB SITE SAFETY; ERECTION MEANS, METHODS, AND SEQUENCES; TEMPORARY SHORING, FORMWORK, BRACING; USE OF EQUIPMENT AND CONSTRUCTION PROCEDURES. CONSTRUCTION OBSERVATION BY THE STRUCTURAL ENGINEER IS FOR GENERAL CONFORMANCE WITH DESIGN ASPECTS ONLY AND IS NOT INTENDED IN ANY WAY TO REVIEW THE CONTRACTOR'S CONSTRUCTION PROCEDURES.

STANDARDS
ALL METHODS, MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE 2015 INTERNATIONAL RESIDENTIAL CODE (IRC) AS AMENDED AND ADOPTED BY THE LOCAL BUILDING OFFICIAL OR APPLICABLE JURISDICTION.

APPLICABLE STRUCTURAL PROVISIONS:

- 2015 INTERNATIONAL BUILDING CODE (IBC)

DESIGN CRITERIA

VERTICAL LOADS

AREA	DESIGN DEAD LOAD	LIVE LOAD
ROOF	15 PSF	25 PSF (SNOW)
OTHER ROOMS FLOORS	ACTUAL	40 PSF (2)
STAIRS	ACTUAL	40 PSF (OR 300# PER TREAD)
DECKS	ACTUAL	60 PSF

- (1) LIVE LOAD REDUCTION NOT PERMITTED EXCEPT AS NOTED IN IBC SECTION 1607.10.
(2) 30 PSF FOR SLEEPING AREAS

SNOW: (MINIMUM ROOF SNOW LOAD = 25 PSF)

Pg = 25 PSF = GROUND SNOW LOAD
Pf = 0.7CeCt IsPg = FLAT ROOF SNOW LOAD
Ps = CsPf = SLOPED ROOF SNOW LOAD
Is = 1.0 Ce = 1.0, Ct = 1.0, Cs = VARIES

LATERAL FORCES

THE BUILDING MEETS THE CRITERIA TO USE THE "SIMPLIFIED ENVELOPE PROCEDURE" PER ASCE 7-10.

WIND:

IBC

- EXPOSURE CATEGORY = B
- BASIC WIND SPEED, (3 SEC. GUST), V_{ULT} = 110 MPH; V_{ASD} = 85 MPH
- WIND IMPORTANCE FACTOR, Iw = 1.0
- OCCUPANCY BUILDING CATEGORY PER TABLE 1-1 = II
- INTERNAL PRESSURE COEFFICIENT (ENCLOSED) = ± 0.18
- TOPOGRAPHIC FACTOR KZT = 1.0

SEISMIC:

SEISMIC IMPORTANCE FACTOR! e = 1.0
RISK CATEGORY OF BUILDING PER TABLE 1.5-1 = D
SPECTRAL RESPONSE ACCELERATIONS Ss = 1.253 & S1 = 0.482
SITE CLASS PER TABLE 20.3-1 = D
DESIGN SPECTRAL RESPONSE ACCELERATIONS Sds = 0.836 & SD1 = 0.488
SEISMIC DESIGN CATEGORY = D
ANALYSIS PROCEDURE USED = SIMPLIFIED LATERAL FORCE ANALYSIS
RESPONSE MODIFICATION FACTOR PER TABLE 12.2-1, R = 6.5
Cs = 0.142 (ULTIMATE)

THE APPROVED CONSTRUCTION PLANS, DOCUMENTS AND ALL ENGINEERING MUST BE POSTED ON THE JOB AT ALL INSPECTIONS IN A VISIBLE AND READILY ACCESSIBLE LOCATION.

FULL SIZED LEDGIBLE COLOR PLANS ARE REQUIRED TO BE PROVIDED BY THE PERMITEE ON SITE FOR INSPECTION

Approval of submitted plans is not an approval of omissions or oversight by this office or noncompliance with any applicable regulations of local government. The contractor is responsible for making sure that the building complies with all applicable building codes and regulations of the local government.

FOUNDATION DESIGN CRITERIA

SOIL BEARING PRESSURE: 1500 PSF (ASSUMED)*

ACTIVE PRESSURE - RESTRAINED: 55 PCF +14H SEISMIC SURCHARGE (ASSUMED)
ACTIVE PRESSURE - UNRESTRAINED: 35 PCF +6H SEISMIC SURCHARGE (ASSUMED)
PASSIVE RESISTANCE: 200 PCF (INCLUDES F.O.S. ≥ 1.5) (ASSUMED)
COEFFICIENT OF FRICTION: .35 (INCLUDES F.O.S. ≥ 1.5) (ASSUMED)

ALL FOOTINGS SHALL BEAR ON FIRM, UNDISTURBED EARTH OR "STRUCTURAL BACKFILL". NATIVE EARTH BEARING SHALL BE SURFACE COMPACTED. AREAS OVER-EXCAVATED SHALL BE BACKFILLED WITH LEAN CONCRETE (F'c= 2000 PSI) OR "STRUCTURAL BACKFILL". AREAS DESIGNATED "STRUCTURAL BACKFILL" SHALL BE FILLED WITH APPROVED WELL-GRADED BANKRUN MATERIAL. MAXIMUM SIZE OF ROCK 4". FROZEN SOIL, ORGANIC MATERIAL AND DELETERIOUS MATTER NOT ALLOWED. COMPACT TO AT LEAST 95% OF ITS MAXIMUM DENSITY AS DETERMINED BY ASTM D1557. PROVIDE DRAINAGE AND DEWATERING AROUND ALL WORK TO AVOID WATER-SOFTENED FOOTINGS.

FREE DRAINING BACKFILL MATERIAL FOR RETAINING & BASEMENT WALLS

A CLEAN, FREE DRAINING, WELL GRADED GRANULAR MATERIAL CONFORMING TO ASTM D2487 GW OR SW WHOSE MAXIMUM PARTICLE SIZE DOES NOT EXCEED 3/4" AND WHOSE FINES CONTENT (MATERIAL PASSING THE NO. 200 SIEVE) DOES NOT EXCEED 5%,

WITH A MAXIMUM DUST RATIO $\frac{\% \text{ PASSING U.S. NO. 200 SIEVE}}{\% \text{ PASSING U.S. NO. 40 SIEVE}} = 2/3 \text{ MAX.}$

CONCRETE

CONCRETE: MODERATE WEATHERING POTENTIAL SHALL BE MADE WITH PORTLAND CEMENT SHALL BE MADE WITH PORTLAND CEMENT ASTM C-150 TYPE II OR TYPE I, COARSE AND FINE AGGREGATE ASTM C-33, WATER CLEAN AND POTABLE AND SHALL BE READY MIXED PER ASTM C-94. NO ALUMINUM (CONDUIT, MISCELLANEOUS ITEMS, ETC.) SHALL BE EMBEDDED IN ANY CONCRETE. COORDINATE FORMWORK AND FINISH TYPES ACCEPTABLE TO THE OWNER.

ITEM	DESIGN f'c (PSI) (AT 28 DAYS U.N.O.)	MAX. W/C RATIO	MIN. FLYASH OR SLAG (PCY)	AGGREGATE GRADING ASTM AASHTO	NOTES
SLAB ON GRADE	2500	0.45	100	57 OR 67	1
FOUNDATIONS - UNO	2500	0.50	--	57 OR 67	
STEM WALLS	2500	0.45	100	57 OR 67	

CONCRETE MIX NOTES:

1. FIBROUS CONCRETE REINFORCEMENT SHALL BE "FIBERMESH" MANUFACTURED BY PROPEX CONCRETE SYSTEMS OR PRE-APPROVED EQUAL. DOSAGE SHALL FOLLOW MANUFACTURER'S RECOMMENDATION BUT NOT LESS THAN 1.5 LB/CU. YD.
2. PROVIDE 3000 PSI AT 28 DAYS MINIMUM FOR DURABILITY AT BASEMENT WALLS, FOUNDATION WALLS, EXTERIOR WALLS, PORCHES, CARPORT SLABS AND STEPS EXPOSED TO THE WEATHER AND FOR ALL GARAGE FLOOR SLABS. CONCRETE SHALL BE AIR ENTRAINED CONFORMING TO ASTM C-260. TOTAL AIR CONTENT (PERCENT BY VOLUME OF CONCRETE) SHALL NOT BE LESS THAN 5% OR MORE THAN 7%.

PLACE CONCRETE: PER ACI 304 AND CONFORM TO ACI 305 AND 306 FOR HOT AND COLD WEATHER PLACEMENT AND CURING PROTECTION. USE INTERIOR MECHANICAL VIBRATORS WITH 7000 RPM MINIMUM FREQUENCY. DO NOT OVER-VIBRATE. CONCRETE SHALL BE POURED MONOLITHICALLY BETWEEN CONSTRUCTION OR EXPANSION JOINTS. PROTECT ALL FRESHLY PLACED CONCRETE FROM PREMATURE DRYING, EXCESSIVE HOT OR COLD TEMPERATURE FOR SEVEN DAYS AFTER POURING.

GROUT

NON-SHRINK GROUT: GROUT SHALL CONFORM TO CRD-C621. F'c = 5000 PSI IN 28 DAYS. FILL OR PACK ENTIRE SPACE UNDER PLATES OR SHAPES. FOLLOW MANUFACTURER'S RECOMMENDATIONS FOR PREPARATION, INSTALLATION, AND CURING.

REINFORCING STEEL

REINFORCING STEEL SHALL CONFORM TO ASTM A615, GRADE 60. DETAIL, FABRICATE AND PLACE PER ACI 315 AND ACI 378. LAP SPLICES SHALL BE 48 BAR DIAMETERS UNLESS NOTED OTHERWISE. PROVIDE CORNER BARS AT ALL HORIZONTAL BARS IN FOOTINGS AND WALLS. WELDED WIRE REINFORCEMENT SHALL CONFORM TO A185. LAP ONE FULL MESH ON SIDES AND ENDS BUT NOT LESS THAN 8 INCHES. PLACE AT MID-DEPTH OF SLAB OR AS SHOWN.

POST-INSTALLED ANCHORS

POST-INSTALLED ANCHORS: SHALL ONLY BE USED WHERE SPECIFIED ON THE CONSTRUCTION DOCUMENTS. THE CONTRACTOR SHALL OBTAIN APPROVAL FROM THE STRUCTURAL ENGINEER PRIOR TO INSTALLING POST-INSTALLED ANCHORS IN PLACE OF MISSING OR MISPLACED CAST-IN-PLACE ANCHORS. CARE SHALL BE TAKEN IN PLACING POST-INSTALLED ANCHORS TO AVOID CONFLICTS WITH REBAR. INSTALL IN ACCORDANCE WITH THE MANUFACTURER'S PUBLISHED INSTALLATION INSTRUCTIONS. INSTALLER SHALL BE QUALIFIED AND TRAINED BY THE MANUFACTURER. HOLES SHALL BE HAMMER DRILLED ONLY (ROTARY DRILLED ONLY AT UNREINFORCED MASONRY - NO HAMMER TOOLS).

SUBSTITUTION REQUESTS, FOR PRODUCTS OTHER THAN THOSE SPECIFIED BELOW, SHALL BE SUBMITTED FOR APPROVAL A MINIMUM OF 2 WEEKS PRIOR TO BID, ALONG WITH CALCULATIONS THAT ARE PREPARED AND SEALED BY A REGISTERED PROFESSIONAL ENGINEER (LICENSED IN THE STATE IN WHICH THE PROJECT OCCURS) DEMONSTRATING THAT THE SUBSTITUTED PRODUCT IS CAPABLE OF ACHIEVING EQUIVALENT PERFORMANCE VALUES (MINIMUM) OF THE SPECIFIED PRODUCT USING THE APPROPRIATE DESIGN PROCEDURE AND/OR STANDARD(S) AS REQUIRED BY THE BUILDING CODE.

CONCRETE ANCHORS:

- ADHESIVE ANCHORS: HILTI HIT-HY 200 (ICC-ESR-3187)
 - *CONCRETE SHALL BE A MINIMUM OF 21 DAYS OLD AT TIME OF INSTALLATION.
 - *CONCRETE SHALL BE IN THE TEMPERATURE RANGE AS REQUIRED BY THE CONCRETE MANUFACTURER.
 - *HOLE SHALL BY HAMMER-DRILLED ONLY.
 - *HOLE SHALL BE DRY AT TIME OF INSTALLATION.
 - *INSTALLER OF HORIZONTAL OR UPWARDLY INCLINED (ANY POSITION EXCEPT DIRECTLY DOWNWARD) ANCHORS SHALL ALSO BE CERTIFIED BY THE ACI/CRSI ADHESIVE ANCHOR INSTALLER CERTIFICATION PROGRAM.
- EXPANSION ANCHORS: KWIKBOLT TZ (ICC ESR-1917) BY HILTI, INC. OR STRONG-BOLT 2 (ICC ESR-3037) BY SIMPSON STRONG TIE, INC.
- SCREW ANCHORS: KWIK HUS-EZ (ICC ESR-3027) BY HILTI, INC. OR TITEN HD (ICC ESR-2713) BY SIMPSON STRONG TIE, INC.

STRUCTURAL STEEL

DETAILING, FABRICATION AND ERECTION

ALL WORKMANSHIP SHALL CONFORM TO THE AISC MANUAL OF STEEL CONSTRUCTION, 14TH EDITION.

MATERIAL PROPERTIES

WIDE FLANGE SECTIONS: ASTM A992 (Fy = 50 KSI)

OTHER SHAPES AND PLATES: ASTM A36 (Fy = 36 KSI) TYP. U.N.O.; ASTM A572 (Fy = 50 KSI) WHERE INDICATED

HOLLOW STRUCTURAL SECTIONS: RECTANGULAR & SQUARE - ASTM A500 GRADE B (Fy = 46 KSI) ROUND - ASTM A500 GRADE B (Fy = 42 KSI)

STRUCTURAL STEEL PIPES: ASTM A53, GRADE B, TYPE E OR S (Fy = 35 KSI)

MACHINE BOLTS (M.B.): ASTM A307, GRADE A

ANCHOR BOLTS (A.B.): ASTM F1554, GRADE 55, UNLESS OTHERWISE NOTED, ASTM F1554, GRADE 105 WHERE INDICATED.

WELDING

STRUCTURAL STEEL: WELD IN ACCORDANCE WITH "STRUCTURAL WELDING CODE" AWS D1.1.

CERTIFICATION : ALL WELDING SHALL BE PERFORMED BY WABO/AWS CERTIFIED WELDERS. WELDERS SHALL BE PREQUALIFIED FOR EACH POSITION AND WELD TYPE WHICH THE WELDER WILL BE PERFORMING.

ELECTRODES: USE E70 ELECTRODES.

GENERAL REQUIREMENTS

ADHESIVE ANCHOR RODS: ASTM F1554, GRADE 36 UNLESS NOTED OTHERWISE.

FINISH : STRUCTURAL STEEL SHALL BE PRIMER PAINTED, UNLESS NOTED OTHERWISE. WHERE STRUCTURAL STEEL IS NOTED TO BE GALVANIZED, IT SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH ASTM A123, A384, AND A385.

STRUCTURAL DRAWING INDEX	
SHEET NUMBER	SHEET DESCRIPTION
S0.0	General Notes
S0.1	General Notes
S1.0	Foundation and First Floor Framing Plans
S2.0	Second Floor Framing Plans
S3.0	Roof Framing Plan
S4.0	Shearwall and Holdown Layout
S5.0	Foundation and First Floor Framing Details
S6.0	Floor and Wall Framing Connection Details
S7.0	Roof Framing Connection Details
S8.0	Shearwall Schedule and Holdown Details
Grand total: 10	

City of Puyallup Development & Permitting Services ISSUED PERMIT	
Building	Planning
Engineering	Public Works
Fire	Traffic



Reviewed for Compliance

Approved for Construction

By Janelle Montgomery

B-20-0741

10/25/2021

Structural Works, PLLC

Erin Sahlin, PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0835
es@STRUCTURALWORKS.NET



Jan 29, 2020

City of Puyallup Development & Permitting Services ISSUED PERMIT			
Building	Planning	Engineering	Public Works
Fire	Traffic		

PROJECT

Foster Residence

24xx West Stewart Ave.
Puyallup, WA 98371

TITLE

GENERAL NOTES

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021

JOB NO
202012

SHEET

S0.0

CARPENTRY:

NAILS: CONNECTION DESIGNS ARE BASED ON "COMMON WIRE" NAILS WITH THE FOLLOWING PROPERTIES:

PENNYWEIGHT	DIAMETER (INCHES)	LENGTH (INCHES)	TRACKER** COLOR CODED NAILS
8d	0.131	2-1/2	BLUE
10d	0.148	3	PURPLE
16d	0.162	3-1/2	ORANGE
20d	0.192	4	-

FOR DIAPHRAGM OR SHEAR WALL NAILING THE FOLLOWING FASTENER TYPES MAY BE USED AT EQUIVALENT SPACING TO THAT SPECIFIED ON PLANS:

FASTENER TYPE	DIAMETER (INCHES)	LENGTH (INCHES)	EQUIVALENT SPACING (INCHES)			TRACKER** COLOR CODED NAILS
8d COMMON WIRE	0.131	2-1/2	6	4	3	BLUE
8d "DIPPED GALV. BOX"	0.131	2-1/2	6	4	3	-
8d "SHINY BOX"	0.113	2-1/2	4-1/2	3	2-1/2	YELLOW
12 GA. STAPLES	0.1055	1-7/8*	6	5-1/2	4	-
14 GA. STAPLES	0.080	1-1/2*	6	4	3	-
15 GA STAPLES	0.072	1-1/2*	5	3	2-1/2	-
10d COMMON WIRE	0.148	3	6	4	3	PURPLE
10d "HOT DIPPED GALV. BOX"	0.148	3	6	4	3	-
10d "SHINY BOX"	0.128	3	4-1/2	3	2-1/4	WHITE

*BASED ON 15/32" PLYWOOD OR OSB.
**REFERENCE TO COLOR CODED NAILS PER TRACKERS SYSTEM.

WOOD SHEATHING (STRUCTURAL): SHEATHING SHALL BE PLYWOOD OR ORIENTED STRAND BOARD. PLYWOOD SHEATHING SHALL BE 5-PLY MINIMUM WHERE INDICATED AS 3/4" OR THICKER. WOOD SHEATHING SHALL BE "STRUCTURAL I" CONFORMING TO PS1-09 AND/OR PS2-10. ALL PANELS SHALL BEAR THE STAMP OF AN APPROVED GRADING AGENCY. SPAN RATING SHALL BE PROVIDED AS FOLLOWS: ROOF FRAMING AT 32"O.C. (48/24); ROOF FRAMING AT 24"O.C. (32/16); WALLS (32/16); FLOORS (48/24) ALL WOOD SHEATHED WALLS SHALL BE BLOCKED AT ALL PANEL EDGES UNLESS NOTED OTHERWISE.

GLUE-LAMINATED MEMBERS: CONFORM TO ANSI/AITC A190.1. MEMBERS SHALL BE COMBINATION 24F-V4 DOUGLAS FIR (DF) FOR SIMPLE SPANS AND 24F-V8 DF FOR CANTILEVERED SPANS (Fb=2400 PSI, Fv=265 PSI, E= 1.8X10⁶ PSI) AND DF COMBINATION 2 FOR COLUMNS. ARCHITECTURAL APPEARANCE GRADE WHERE EXPOSED TO VIEW; INDUSTRIAL APPEARANCE GRADE WHERE NOT EXPOSED TO VIEW. ALL MEMBER TO HAVE EXTERIOR GLUE AND HAVE AITC OR APA-EWS STAMP. CAMBER AS SHOWN ON STRUCTURAL DRAWINGS.

FRAMING LUMBER: STANDARDS. EACH PIECE SHALL BEAR THE GRADE TRADEMARK OF THE WEST COAST LUMBER INSPECTION BUREAU (WCLIB), WESTERN WOOD PRODUCTS ASSOCIATION (WWPA), OR OTHER AGENCY ACCREDITED BY THE AMERICAN LUMBER STANDARD COMMITTEE (ALSC) TO GRADE UNDER ALSC CERTIFIED GRADING RULES.

SPECIES AND GRADE (BASE DESIGN VALUE)

- 6x BEAMS AND HEADERS. "DOUG FIR-LARCH" NO. 1 (Fb=1350 PSI, Fv=170 PSI)
- 2x TO 4x JOISTS, PURLINS AND HEADERS. "DOUG FIR-LARCH" NO. 2 (Fb=900 PSI, Fv=180 PSI) OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fv=150 PSI)
- 6x POSTS AND COLUMNS. "DOUG FIR-LARCH" NO. 1 (Fc=1000 PSI)
- EXTERIOR STUDS, INTERIOR BEARING WALLS AND 4x COLUMNS. "DOUG FIR-LARCH" NO. 2 (Fb= 900 PSI, Fc= 1350 PSI) OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fc=1350 PSI).
- INTERIOR NON-BEARING STUD WALLS. "DOUG FIR-LARCH" NO. 2 (Fb=900 PSI. Fc=1350 PSI) OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fc=1350 PSI)

STRUCTURAL COMPOSITE LUMBER (SCL): SHALL BE MANUFACTURED BY WEYERHOUSER, OR PRE-APPROVED EQUAL IN ACCORDANCE WITH APPROVED SHOP AND INSTALLATION DRAWINGS CONFORMING TO A CURRENT ICC EVALUATION REPORT.

MINIMUM DESIGN VALUES:

- 2x LVL: Fb = 1700 PSI, Fv = 285 PSI, E = 1300 KSI
- 1-3/4" LVL: Fb = 2600 PSI, Fv = 285 PSI, E = 1800 KSI
- 3-1/2" LVL: Fb = 2900 PSI, Fv = 285 PSI, E = 2000 KSI
- 5-1/4" LVL: Fb = 2900 PSI, Fv = 285 PSI, E = 2000 KSI
- RIMBOARD:APA/EWS PERFORMANCE RATED RIM (PRR-401) 1-1/4" MINIMUM THICKNESS

PRESERVATIVE TREATED WOOD REQUIREMENTS:

TREATMENTS OTHER THAN THOSE LISTED BELOW ARE NOT PERMITTED.

EXPOSURE		APPLICATION	SPECIFIED MATERIAL	PRESERVATIVE TREATMENT (1)	CONNECTORS & FASTENERS (2)(3)
WET	DRY	FOUNDATION SILL PLATES, TOP PLATES & LEDGERS ON CONCRETE OR MASONRY WALLS (4)	2x, 4x, 6x (FIR), OR GLULAM (SP)	SBX	GALV (G60)
				ACQ, CBA, CA	GALV (G185)
	WET	FRAMING, DECKING, POSTS & LEDGERS	2x, & 4x (FIR)	ACQ, CBA, CA	GALV (G185)
			2x, & 4x (CEDAR)	NONE	GALV (G90)
		BEAMS & COLUMNS	6x (FIR), OR GLULAM (SP)	ACQ, CBA, CA	GALV (G185)
			6x OR GLULAM (CEDAR)	NONE	GALV (G90)

1.

CCA: CHROMATED COPPER ARSENATE NOT PERMITTED
SBX: DOT SODIUM BORATE
ACQ: ALKALINE COPPER QUAT
CBA & CA: COPPER AZOLE

FIR: DOUG-FIR OR HEM-FIR
SP: SOUTHERN PINE
2.

CONNECTORS: JOIST HANGERS, STRAPS, FRAMING CONNECTORS, COLUMN CAPS AND BASES, ETC.
FASTENERS: MACHINE BOLTS, ANCHOR BOLTS AND LAG SCREWS WITH ASSOCIATED PLATE WASHERS AND NUTS. NAILS, SPIKES, WOOD SCREWS, ETC.
3.

G60, G90 & G185 PER ASTM A653 FOR COLD-FORMED STEEL CONNECTORS. BATCH/POST HOT-DIP GALVANIZED PER ASTM A123 FOR CONNECTORS. HOT-DIP GALVANIZED PER ASTM A153 FOR FASTENERS OR MECHANICALLY GALVANIZED FASTENERS PER ASTM B695, CLASS 55 OR GREATER.

GENERAL REQUIREMENTS: PROVIDE MINIMUM NAILING PER IBC TABLE 2304.10.1 OR MORE, AS OTHERWISE SHOWN. STAGGER ALL NAILING TO PREVENT SPLITTING OF WOOD MEMBERS. ALL WOOD IN CONTACT WITH CONCRETE OR MASONRY SHALL BE PRESERVATIVE TREATED WITH THE EXCEPTION OF INTERIOR CONCRETE TOPPINGS ON WOOD FLOOR SYSTEMS. HOLES AND CUTS IN 3x OR 4x PLATES SHOULD BE TREATED WITH A 9% SOLUTION OF COPPER NAPHTHENATE. BOLT HOLES IN WOOD MEMBERS SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM OF 1/16" LARGER THAN THE BOLT DIAMETER. PROVIDE CUT WASHERS WHERE BOLT HEADS, NUTS AND LAG SCREW HEADS BEAR ON WOOD. PROVIDE A MINIMUM 3"x3"x0.229" PLATE WASHER ON ALL ANCHOR BOLTS WHICH CONNECT MUD SILLS TO FOUNDATION. DO NOT NOTCH OR DRILL STRUCTURAL MEMBERS, EXCEPT AS ALLOWED BY IBC SECTIONS 2308.4.2.4, 2308.5.9, 2308.5.10 AND 2308.7.4 OR AS RESTRICTED BY PLANS OR DETAILS, OR AS APPROVED PRIOR TO INSTALLATION. REFER TO PRESERVATIVE TREATED WOOD REQUIREMENTS IN THESE GENERAL NOTES FOR GALVANIZING REQUIREMENTS FOR CONNECTORS AND FASTENERS.

FASTENING SCHEDULE FOR WOOD STRUCTURAL MEMBERS (UNLESS NOTED OTHERWISE ON PLANS)		
ITEM	TYPE	CONNECTION
RAFTER OR TRUSS TO TOP PLATE	TOENAIL & CONNECTOR	(3) 16d H2.5 @ 48" O.C.
CEILING JOIST TO TOP PLATE	TOENAIL	(3) 8d
CEILING JOIST TO PARALLEL RAFTER	FACE NAIL	(3) 16d
CEILING JOIST: LAP OVER PARTITION	FACE NAIL	(3) 16d
COLLAR TIE	FACE NAIL	(3) 16d
BLOCKING TO RAFTER	TOENAIL	(3) 8d
RIM BOARD TO RAFTER	END NAIL	(2) 16d
TOP PLATE TO TOP PLATE	FACE NAIL	(2) 16d @ 12" O.C.
TOP PLATE AT INTERSECTIONS	FACE NAIL	(4) 16d
TOP PLATE LAP	FACE NAIL	(8) 16d
STUD TO STUD	FACE NAIL	(2) 16d @ 24" O.C.
HEADER TO HEADER	FACE NAIL	16d @ 16" O.C. EA. EDGE
TOP OR BOTTOM PLATE TO STUD	END NAIL	(2) 16d
STUD TO SOLE PLATE	TOE NAIL	(4) 8d
	END NAIL	(2) 16d
BOTTOM PLATE TO FLOOR JOIST AT BRACED PANEL	TOE NAIL	16d @ 16" O.C.
	FACE NAIL	(3) 16d @ 16" O.C.
JOISTS TO TOP PLATE, SILL OR GIRDER	TOE NAIL	(4) 8d
BRIDGING TO JOIST	TOE NAIL	(2) 8d
BLOCKING TO JOISTS	TOE NAIL	(3) 8d
BLOCKING TO TOP PLATE	TOE NAIL	(3) 8d
RIM JOIST TO JOIST	FACE NAIL	(3) 16d
RIM JOIST TO SILL OR TOP PLATE	CONNECTOR	A35 @ 24" O.C.
CONTINUOUS HEADER TO STUD	CONNECTOR	A35
BUILT-CORNER STUDS	FACE NAIL	16d @ 24" O.C.
BUILT-UP BEAMS (PER LAYER)	FACE NAIL	16d @ 16" O.C. EA. EDGE
RAFTERS TO RIDGE BOARD	TOE NAIL	(4) 16d
	FACE NAIL	(3) 16d
RAFTERS TO HIP	TOE NAIL	(4) 16d
	FACE NAIL	(3) 16d

FRAMING CONNECTORS: SHALL HAVE ICC APPROVAL AND BE MANUFACTURED BY SIMPSON STRONG-TIE COMPANY, SAN LEANDRO, CA., OR PRE-APPROVED EQUAL. PROVIDE MAXIMUM SIZE AND QUANTITY OF NAILS OR BOLTS PER MANUFACTURER, EXCEPT AS NOTED OTHERWISE. PROVIDE LEAD HOLES AS REQUIRED TO PREVENT SPLITTING OF WOOD MEMBERS. REFER TO PRESERVATIVE TREATED WOOD REQUIREMENTS IN THESE GENERAL NOTES FOR GALVANIZING REQUIREMENTS FOR CONNECTORS AND FASTENERS.

LAG SCREWS: SHALL CONFORM TO ANSI/ASME STANDARD B18.2.1. LAG SCREWS SHALL BE OF A DIAMETER INDICATED ON DRAWINGS WITH A MINIMUM OF 8x DIA. EMBEDMENT IN SUPPORTING MEMBER UNLESS NOTED OTHERWISE. CLEARANCE HOLE FOR THE SHANK SHALL BE THE SAME DIAMETER AS THE SHANK AND THE SAME DEPTH OF PENETRATION AS THE UNTHREADED PORTION OF THE SHANK. THE LEAD HOLE FOR THE THREADED PORTION SHALL HAVE A DIAMETER EQUAL TO 60 TO 75 PERCENT OF THE SHANK DIAMETER AND A LENGTH EQUAL TO AT LEAST THE LENGTH OF THE THREADED PORTION. THE THREADED PORTION OF THE SCREW SHALL BE INSERTED IN ITS LEAD HOLE BY TURNING WITH A WRENCH. SOAP OR OTHER LUBRICANT SHALL BE USED ON THE SCREWS OR IN THE LEAD HOLE TO FACILITATE INSERTION AND PREVENT DAMAGE TO THE SCREW. LAG SCREWS SHALL NOT BE DRIVEN WITH A HAMMER. REFER TO PRESERVATIVE TREATED WOOD REQUIREMENTS IN THESE GENERAL NOTES FOR GALVANIZING REQUIREMENTS FOR CONNECTORS AND FASTENERS.

METAL-PLATE-CONNECTED WOOD TRUSSES: SHALL BE MANUFACTURED AND INSTALLED WITHIN THE JURISDICTION REQUIREMENTS, AND DESIGNED AND DETAILED IN ACCORDANCE WITH ANSI/TP-1, INCLUDING BRACING AND WIND UPLIFT. PROVIDE 2x6 TOP CHORDS, AND 2x4 BOTTOM CHORDS AND WEBS, UNLESS COORDINATED AND APPROVED. TRUSSES SHALL BE DESIGNED TO CARRY THE LOADS LISTED IN THE DESIGN CRITERIA AND ANY ADDITIONAL LOADS INDICATED ON THE FRAMING PLANS AND DETAILS. TRUSSES INDICATED ON PLANS ARE FOR TYPICAL UNIFORMLY LOADED CONDITIONS. MANUFACTURER SHALL PROVIDE ADDITIONAL OR SPECIAL TRUSSES AS REQUIRED TO SUPPORT SPECIAL LOADING CONDITIONS AS INDICATED ON DRAWINGS. PROVIDE INSTALLATION FRAMING PLANS AND DRAWINGS.

PROVIDE CERTIFICATE OF CONFORMANCE FROM AN INDEPENDENT TESTING LABORATORY OR A LICENSED PROFESSIONAL ENGINEER CERTIFYING THAT THEY HAVE INSPECTED THE FINISHED TRUSSES AND THAT ALL TRUSSES ARE CONSTRUCTED IN CONFORMANCE WITH THE TRUSS DESIGN DRAWINGS.


I-JOISTS: SHALL BE APA EWS PERFORMANCE RATED I-JOISTS (PRI) OR PRE-APPROVED EQUAL. I-JOISTS SHALL BE MANUFACTURED IN CONFORMANCE WITH APA PRI-400 CONFORMING TO APPROVED SHOP AND INSTALLATION DRAWINGS.

B-21-20-0741
CITY OF PUYALLUP

Structural Works, PLLC
Erin Sahlin, PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0635
es@STRUCTURALWORKS.NET



Jan 29, 2020




PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371

TITLE
GENERAL NOTES

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012
SHEET

S0.1



Foundation & Main Floor Framing Plan - PHS19.056 - Danny Foster
1/4 in = 1 ft

FOOTING SCHEDULE:

F1 -> 3'x2'x12" concrete ftg w/ 5#4 transverse and 3#4 long. bars
F2 -> 2'x2'x12" concrete ftg w/ 3#4 bars e.w.
F3 -> 3'-6"x3'-6"x10" concrete ftg w/ 4#4 bars e.w.

B-21-20-0741
CITY OF PUYALLUP



City of Puyallup Development & Permitting Services ISSUED PERMIT	
Building	Planning
Engineering	Public Works
Fire	Traffic


PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371

TITLE
Foundation and First Floor Plans

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012

SHEET

S1.0



B-21-20-0741
CITY OF PUYALLUP

FLOOR FRAMING NOTES:

1. DO NOT SCALE DRAWINGS, REFER TO ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS.
2. FLOOR SHEATHING SHALL BE 3/4" TONGUE AND GROOVE A.P.A. RATED PANELS. (EXPOSURE 1, SPAN RATING 48/24). GLUE AND NAIL SHEATHING AT ALL FRAMED PANEL EDGES WITH 10d AT 6" O.C. AND TO ALL INTERMEDIATE FRAMING AT 12" O.C
3. HEADERS OVER LOAD BEARING DOORS AND WINDOW OPENINGS SHALL BE MINIMUM 4x10 U.N.O.
4. PROVIDE (2) STUDS MINIMUM AT EACH END OF ALL BEAMS U.N.O. ON PLANS. BEAR BEAM FULLY ON BUILT UP COLUMN AND PROVIDE POSITIVE CONNECTION BY EITHER A35 OR LTP4 CLIPS ON EACH SIDE OF BEAM
5. REFER TO GENERAL STRUCTURAL NOTE PAGE ON S0.0 FOR ADDITIONAL REQUIREMENTS

Structural Works, PLLC
Erin Sahlin, PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0835
es@STRUCTURALWORKS.NET



PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371


TITLE _____

Upper Floor Plan

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021

JOB NO
202012

S2.0




Roof Framing Plan - PHS19.056 - Danny Foster
1/4 in = 1 ft

- ROOF FRAMING NOTES:**
- 1. DO NOT SCALE DRAWINGS, REFER TO ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS.
 - 2. PRE-MANUFACTURED ROOF TRUSS DESIGN IS TO BE PROVIDED BY MANUFACTURER. SEE STRUCTURAL NOTES ON S0.0 FOR REQUIREMENTS.
 - 3. ROOF SHEATHING SHALL BE 1/2" A.P.A. RATED PANELS. (EXPOSURE 1, SPAN RATING 32/16). NAIL SHEATHING AT ALL FRAMED PANEL EDGES WITH 8d AT 6" O.C. AND TO ALL INTERMEDIATE FRAMING AT 12" O.C. NAILS SHALL BE LOCATED AT LEAST 3/8" FROM THE EDGES OF PANELS.
 - 4. HEADERS OVER LOAD BEARING DOORS AND WINDOW OPENINGS SHALL BE MINIMUM 4x10 U.N.O.
 - 5. PROVIDE (2) STUDS MINIMUM AT EACH END OF ALL BEAMS U.N.O. ON PLANS. BEAR BEAM FULLY ON BUILT UP COLUMN AND PROVIDE POSITIVE CONNECTION BY EITHER A35 OR LTP4 CLIPS ON EACH SIDE OF BEAM
 - 6. REFER TO GENERAL STRUCTURAL NOTE PAGE ON S0.0 FOR ADDITIONAL REQUIREMENTS
 - 7. PANELS SHALL NOT BE LESS THAN 4' X 8' EXCEPT AT BOUNDARIES AND CHANGES IN FRAMING WHERE MINIMUM PANEL DIMENSION SHALL BE 24".

B-21-20-0741
CITY OF PUYALLUP

Structural Works, PLLC
Erin Sahlin, PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0835
es@STRUCTURALWORKS.NET




PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371

TITLE
Roof Framing Plan

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012

SHEET


S3.0



Main Floor Plan - PHS19.056 - Danny Foster
1/4 in = 1 ft


B-21-20-0741
CITY OF PUYALLUP






Upper Floor Plan - PHS19.056 - Danny Foster
1/4 in = 1 ft


B-21-20-0741
CITY OF PUYALLUP




- NOTES:**
1. BASE PLATE NAILING PER SHEARWALL SCHEDULE
 2. PLYWOOD SHEATHING
 3. PLYWOOD WEB JOISTS PER PLAN
 4. RIM JOIST BY JOIST MANUFACTURER – ATTACH WITH (2) 10d NAILS PER JOIST
 5. #4 BAR CONTINUOUS (AT TOP) PROVIDE #4 BARS AT 10" O.C. HORIZONTAL
 6. 5/8" DIAMETER ANCHOR BOLTS PER SHEARWALL SCHEDULE, EMBEDMENT PER GSN
 7. #4 BARS AT 18" O.C. MAXIMUM, ALTERNATE BENDS
 8. (2) #4 BARS CONTINUOUS
 9. EDGE NAILING
 10. SIMPSON A35, SPACING PER SHEARWALL SCHEDULE
 11. 8" CONCRETE STEM WALL (MINIMUM) AND FOOTING, WIDEN FOOTING AS REQ'D FOR VENEER – SEE ARCHITECTURAL FOR ADDITIONAL INFORMATION




- NOTES:**
1. BASE PLATE NAILING PER SHEARWALL SCHEDULE
 2. EDGE NAILING
 3. PLYWOOD SHEATHING
 4. PLYWOOD WEB JOISTS PER PLAN
 5. PLYWOOD WEB JOIST BLOCKING AT 32" O.C.
 6. #4 BAR CONTINUOUS (AT TOP) PROVIDE #4 BARS AT 10" O.C. HORIZONTAL
 7. 5/8" DIAMETER ANCHOR BOLTS PER SHEARWALL SCHEDULE, EMBEDMENT PER GSN
 8. #4 BARS AT 18" O.C. MAXIMUM, ALTERNATE BENDS
 9. (2) #4 BARS CONTINUOUS
 10. RIM JOIST BY JOIST MANUFACTURER – ATTACH WITH (2) 10d NAILS PER BLOCK
 11. SIMPSON A35, SPACING PER SHEARWALL SCHEDULE
 12. (6) 10d NAILS PER BLOCK
 13. 8" CONCRETE STEM WALL (MINIMUM) AND FOOTING, WIDEN FOOTING AS REQ'D FOR VENEER – SEE ARCHITECTURAL FOR ADDITIONAL INFORMATION




- NOTES:**
1. 10d NAILS TO MATCH SPACING OF EDGE NAILING
 2. PLYWOOD WEB JOISTS PER PLAN
 3. PLYWOOD SHEATHING
 4. BLOCKING BY JOIST MANUFACTURER
 5. 2x PONY WALL, SHEATHING AND ATTACHMENT PER SHEARWALL SCHEDULE
 6. EDGE NAILING
 7. ANCHOR BOLTS PER SHEARWALL SCHEDULE
 8. CONCRETE FOOTING PER PLAN




- NOTES:**
1. WOOD STUD WALL
 2. 5/8" DIAMETER ANCHOR BOLTS PER SHEARWALL SCHEDULE
 3. TREATED BASE PLATE PER SHEARWALL SCHEDULE
 4. CONCRETE SLAB ON GRADE
 5. #4 HOOKED DOWELS AT 18" O.C., ALTERNATE BENDS
 6. SHEATHING AND ATTACHMENT PER SHEARWALL SCHEDULE
 7. EDGE NAILING
 8. FINISH GRADE OR CONCRETE SLAB AS OCCURS
 9. 6" CONCRETE STEM WALL (MINIMUM)
 10. (2) #4 BARS CONTINUOUS
 11. (1) #4 BAR CONTINUOUS (AT TOP) – PROVIDE #4 BARS AT 10" O.C., (HORIZONTAL), FOR WALLS TALLER THAN 12"




- NOTES:**
1. CONCRETE SLAB ON GRADE
 2. STUD WALL BEYOND
 3. TOOLED EDGE
 4. FINISH GRADE OR CONCRETE SLAB AS OCCURS
 5. 8" CONCRETE STEM WALL (MINIMUM) AND FOOTING WITH REINFORCING CONTINUOUS FROM BEYOND
 6. #4 HOOKED DOWELS AT 18" O.C., ALTERNATE BENDS
 7. (2) #4 BARS CONTINUOUS




- NOTES:**
1. WOOD STUD WALL
 2. TREATED BASE PLATE PER SHEARWALL SCHEDULE
 3. SHEATHING AND ATTACHMENT PER SHEARWALL SCHEDULE
 4. EDGE NAILING
 5. CONCRETE SLAB ON GRADE PER PLAN
 6. (2) #4 BARS, CONTINUOUS




- NOTES:**
1. CORNER BARS SAME SIZE AND SPACING AS HORIZONTAL REINFORCING LAP PER GSN (24" MINIMUM)
 2. CONCRETE STEM WALL OR FOOTING
 3. ALTERNATE BENDS
 4. REINFORCING PER PLANS AND/OR DETAILS




- NOTES:**
1. ANCHOR BOLT PER SHEAR WALL SCHEDULE
 2. SLOTTED PLATE WASHER
 3. STANDARD CUT WASHER




- NOTES:**
1. CONCRETE SLAB ON GRADE
 2. (1) #4 BAR CONTINUOUS TOP AND BOTTOM
 3. TOOLED EDGE
 4. CONCRETE SLAB OR FINISH GRADE AS OCCURS




- NOTES:**
1. CONCRETE SLAB ON GRADE
 2. SAWCUT – 1/8" WIDE x 1/4 SLAB THICKNESS IN DEPTH – CUT SHALL BE MADE SOON ENOUGH TO PREVENT SHRINKAGE CRACKING, BUT NOT TO CAUSE SPALLING OF THE CONCRETE WHILE SAWING – WORK MUST BE ACCOMPLISHED WITHIN (24) HOURS OF CONCRETE PLACEMENT
 3. CONTINUOUS KEY – SEE TYPICAL DETAIL
- NOTES:**
- A. KEYED JOINTS NEED ONLY OCCUR AT EXPOSED EDGES DURING PLACEMENT UNLESS SPECIFICALLY NOTED ON THE PLANS



- NOTES:**
1. CONCRETE SLAB
 2. KEYED JOINT – REMOVE FORM MATERIAL PRIOR TO PLACING ADJACENT CONCRETE
- NOTES:**
- A. ALL DIMENSIONS ARE ±1/2"




- NOTES:**
1. CONCRETE SLAB
 2. KEYED JOINT – REMOVE FORM MATERIAL PRIOR TO PLACING ADJACENT CONCRETE
- NOTES:**
- A. ALL DIMENSIONS ARE ±1/2"



- NOTES:**
1. TYPICAL 2X STUDS AT 16" O.C. U.N.O. W/ (2) 16d END NAILS OR (4) 8d TOE NAILS EACH END TO TOP & SILL PLATES.
 2. CORNER STUDS OR POST PER PLAN.
 3. PLYWOOD SHEAR PANEL PER PLAN.
 4. POST AT END OF SHEAR PANEL PER PLAN.
 5. NAIL CORNER & MULTI-STUDS TOGETHER W/ 16d'S @ 16" O.C. STAGGERED @ SHEAR WALLS & 24" O.C. @ NON-SHEAR WALLS.
 6. EDGE NAILING
 7. 16d'S @ 4" O.C. STAGGERED
 8. 2x STUD @ SHEAR BREAK.

NOTE: NAILS SPACED @ 2" O.C. SHOULD BE STAGGERED MIN. 1/8".



- NOTES:**
1. CONCRETE SLAB ON GRADE
 2. SAWCUT – 1/8" WIDE x 1/4 SLAB THICKNESS IN DEPTH – CUT SHALL BE MADE SOON ENOUGH TO PREVENT SHRINKAGE CRACKING, BUT NOT TO CAUSE SPALLING OF THE CONCRETE WHILE SAWING – WORK MUST BE ACCOMPLISHED WITHIN (24) HOURS OF CONCRETE PLACEMENT
 3. CONTINUOUS KEY – SEE TYPICAL DETAIL
- NOTES:**
- A. KEYED JOINTS NEED ONLY OCCUR AT EXPOSED EDGES DURING PLACEMENT UNLESS SPECIFICALLY NOTED ON THE PLANS


BORED HOLES			
STUD SIZE	EXT. & BRN'G. WALLS	NON-BRN'G. WALLS	
2x4	1 7/16"	2 1/8"	
2x6	2 3/16"	3 5/16"	
2-2x4	2 1/8"	2 1/8"	
2-2x6	3 5/16"	3 5/16"	

NOTCH DEPTH			
STUD SIZE	EXT. & BRN'G. WALLS	NON-BRN'G. WALLS	
2x4	1 7/16"	1 7/16"	
2x6	1 3/8"	2 3/16"	

B-21-20-0741
CITY OF PUYALLUP

Structural Works, PLLC

Eric Sahlin, PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0835
es@STRUCTURALWORKS.NET







PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371

TITLE
Foundation & First Floor
Framing Details





DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012

SHEET


S5.0



HEADER AND BEAM SCHEDULE FOR LOAD BEARING WALLS					
OPENING SIZE	HEADER SIZE	TRIMMERS REQ'D		KING STUDS REQ'D	
		2X4	2X6	2X4	2X6
UP TO 3'-6"	SEE PLAN	1	1	1	1
3'-6"> TO 5'-0"	SEE PLAN	1	2	2	2
5'-0"> TO 8'-0"	SEE PLAN	1	2	2	2
8'-0"> TO 10'-6"	SEE PLAN	2	3	3	3
10'-6"> TO 16'-0"	SEE PLAN	3	4	3	3



Structural Works, PLLC
Eric Sahlin, PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0835
es@STRUCTURALWORKS.NET



PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371


TITLE
Floor and Wall Framing Details

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012


SHEET

S6.0


B-21-20-0741
CITY OF PUYALLUP




- NOTES:
1. WOOD TRUSS PER PLAN
 2. PLYWOOD SHEATHING
 3. EDGE NAILING
 4. 2x BLOCKING WITH (3) 16d NAILS PER BLOCK
 5. WOOD FASCIA WITH (2) 10d NAILS PER TRUSS MANUFACTURER
 6. SHEATHING AND ATTACHMENT PER SHEARWALL SCHEDULE
 7. SIMPSON H1 AT EACH TRUSS - USE SIMPSON H2.5 EACH SIDE OF GIRDER TRUSS
 8. SIMPSON A35 CLIP AT 24" O.C.



- NOTES:
1. WOOD TRUSS PER PLAN
 2. SIMPSON H1 CLIP AT EACH TRUSS
 3. PLYWOOD SHEATHING
 4. EDGE NAILING
 5. SOLID 2X BLOCKING
 6. WOOD BEAM
 7. WOOD FASCIA WITH (2) 10d NAILS PER TRUSS
 8. SIMPSON A35 AT 24" O.C.
 9. PRE-MFR'D WOOD TRUSS



- NOTES:
1. EDGE NAILING
 2. RIDGE VENTS
 3. WOOD TRUSS PER PLAN
 4. PLYWOOD SHEATHING
 5. 2x SOLID BLOCKING




- NOTES:
1. PLYWOOD SHEATHING
 2. 2x BLOCKING
 3. ARCHITECTURAL FASCIA
 4. 2x4 OUTRIGGERS AT 24" O.C.
 5. 2x STRUCTURAL FASCIA
 6. (2) 10d EACH OUTRIGGER
 7. EDGE NAILING
 8. 2x4 BRACE AT 48" O.C.
 9. 2x DOUBLE TOP PLATE
 10. WOOD STUD WALL
 11. PRE-MFR'D WOOD TRUSS
 12. (3) 10d EACH END
 13. SIMPSON A35 AT 24" O.C.

1 WOOD TRUSS AT WOOD STUD WALL
SCALE: N.T.S.

2 WOOD TRUSS AT WOOD BEAM
SCALE: N.T.S.


3 TRUSS RIDGE
SCALE: N.T.S.

4 GABLE END TRUSS AT WOOD STUD WALL
SCALE: N.T.S.




- NOTES:
1. EDGE NAILING
 2. PLYWOOD SHEATHING
 3. (2) 16d NAILS PER STUD
 4. CONTINUOUS 2x LEDGER
 5. SIMPSON LU TYPE HANGER
 6. WOOD TRUSS PER PLAN
 7. 2x SOLID BLOCKING
 8. WOOD STUD WALL
 9. (2) 16d NAILS PER STUD

5 WOOD TRUSS AT WOOD STUD WALL
SCALE: N.T.S.



- NOTES:
1. BEAM PER PLAN
 2. SIMPSON LPCZ POST CAP
 3. POST PER PLAN

8 TYPICAL LPC POST CAP CONNECTION
SCALE: N.T.S.



PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371

TITLE
Roof Framing Details

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012
SHEET


S7.0

B-21-20-0741
CITY OF PUYALLUP


SHEAR WALL SCHEDULE									
WALL MARK	SHEATHING	SIDES	PANEL EDGE NAILING	FIELD NAILING	FRAMING AT ADJACENT PANEL EDGES	BASE PLATE ATTACHMENT	ANCHOR BOLT SPACING	FOUNDATION SILL PLATE/FLOOR BASE PLATE	BLOCKING/RIM JOIST ATTACHMENT
SW1	15/32" OSB	ONE	10d NAILS AT 6" O.C.	12" O.C.	2x	16d NAILS AT 6" O.C.	5/8" DIAMETER BOLTS AT 48" O.C.	2x	SIMPSON A35 CLIPS AT 18" O.C.
SW2	15/32" OSB	ONE	10d NAILS AT 4" O.C.	12" O.C.	3x OR (2) 2x	16d NAILS AT 3" O.C.	5/8" DIAMETER BOLTS AT 32" O.C.	3x	SIMPSON A35 CLIPS AT 12" O.C.
							5/8" DIAMETER BOLTS AT 12" O.C.	2x	
SW3	15/32" OSB	ONE	10d NAILS AT 3" O.C.	12" O.C.	3x	(2) 16d NAILS AT 4" O.C.	5/8" DIAMETER BOLTS AT 24" O.C.	3x	SIMPSON A35 CLIPS AT 8" O.C.
							5/8" DIAMETER BOLTS AT 8" O.C.	2x	

SHEAR WALL SCHEDULE NOTES:
FRAMING STUDS SHALL BE DOUGLAS-FIR #2 SPACED AT 16" O.C. MAXIMUM. THICKNESS OF STUDS SHALL BE 2x UNLESS OTHERWISE NOTED IN SCHEDULE.
SHEATHING PANELS MAY BE PLACED VERTICAL OR HORIZONTAL. BLOCK ALL HORIZONTAL EDGES WITH 2x OR 3x BLOCKING TO MATCH STUD WIDTH UNLESS NOTED OTHERWISE.
ALL EXTERIOR WALLS NOT DESIGNATED AS SHEARWALLS SHALL RECEIVE APA RATED SHEATHING, FULLY BLOCKED WITH MINIMUM EDGE ATTACHMENT OF 10d NAILS @ 6" O.C., 12" O.C. FIELD. NAILING APPLIES TO ALL STUDS, TOP AND BOTTOM PLATES AND BLOCKING.
MINIMUM ANCHOR BOLT SPACING OF 48" O.C. UNLESS OTHERWISE NOTED IN SCHEDULE. MINIMUM OF 2 ANCHORS PER WALL. PROVIDE 3"x3"x0.25" SQUARE WASHERS AT EACH ANCHOR BETWEEN THE SILL PLATE AND WASHER. A DIAGONAL SLOT IN THE PLATE WASHER MAY BE USED WITH A WIDTH OF UP TO 3/16" LARGER THAN THE BOLT DIAMETER AND A SLOT NOT TO EXCEED 1-3/4", PROVIDED A STANDARD CUT WASHER IS PLACED BETWEEN THE PLATE WASHER AND THE NUT. DO NOT RECESS BOLTS.
8d NAILS (2 1/2" LONG x 0.113" COMMON OR 2 1/2" x 0.113" GALVANIZED BOX).
BLOCKING/RIM JOIST ATTACHMENT NEED NOT BE USED WHERE THE SHEATHING IS DIRECTLY ATTACHED WITH EDGE NAILING TO THE DOUBLE TOP PLATES AT UPPER STORY SHEARWALLS AND TO THE BASE/SILL PLATE BELOW AT LOWER STORY SHEARWALLS.
WHERE 3x BASE/SILL ARE SPECIFIED, 20d COMMON NAILS SHALL BE USED FOR THE BASE PLATE ATTACHMENT IN LIEU OF THE ORIGINALLY SPECIFIED 16d COMMON NAILS.
IF NEEDED, 5/8" x 8" TITEN-HD SCREW IN ANCHORS CAN BE USED AS AN ALTERNATE TO J BOLTS


1 SHEARWALL SCHEDULE
SCALE: N.T.S.



4 TYPICAL PORTAL FRAME CONSTRUCTION
SCALE: N.T.S.




2 SHEARWALL DETAIL WITH SIMPSON STRAP TIE HOLDOWN AT FLOOR SUPPORTED BY FOUNDATION
SCALE: N.T.S.




5 TWO-STORY SHEAR WALL ELEVATION
SCALE: N.T.S.

NOTES:
1. (2) STUDS, U.N.O. AT EACH END OF PANEL NAILED AS BUILT-UP POST, TYPICAL
2. WOOD STUDS
3. SHEATHING MATERIAL
4. BLOCKING REQUIRED AT SHEATHING PANEL JOINTS
5. SIMPSON STRAP PER PLANS AND DETAILS
6. HOLD DOWNS AS OCCURS
7. ANCHOR BOLTS FIRST FLOOR LINE
8. FIRST FLOOR LINE
9. SECOND FLOOR LINE



3 SHEARWALL DETAIL WITH SIMPSON HDU/HDQ/HHDQ HOLDOWN AT FLOOR SUPPORTED BY FOUNDATION
SCALE: N.T.S.




6 SIMPSON PHD HOLDOWN AT UPPER FLOOR
SCALE: N.T.S.

NOTES:
1. CONTINUOUS DOUBLE (OR TRIPLE IF NEEDED) STUDS AT SHEARWALL EDGES - ATTACH STUDS TOGETHER WITH 10d NAILS AT 12" O.C. - SHEARWALL SHEATHING AND ATTACHMENT NOT SHOWN FOR CLARITY
2. BLOCKING OR RIM JOIST AS OCCURS - SILD BLOCK BELOW SHEARWALL HOLDOWN
3. SIMPSON HDU TYPE HOLDOWN PER PLAN
4. ASTM A307 THREADED ROD CONNECTING HDU TYPE HOLDOWNS - THREADED ROD DIAMETER TO MATCH DIAMETER OF SIMPSON SSBT ANCHOR BOLT SPECIFIED FOR THE TYPE OF HOLDOWN USED
5. BASE PLATE AND ATTACHMENT PER SHEARWALL SCHEDULE
6. DOUBLE TOP PLATE

B-21-20-0741
CITY OF PUYALLUP

Structural Works, PLLC
Eric Sahlin PE
1412 Beach Drive NE, Tacoma, WA 98402
253-533-0835
es@STRUCTURALWORKS.NET



PROJECT
Foster Residence
24xx West Stewart Ave.
Puyallup, WA 98371

TITLE
Shearwall Schedule and Holdown Details

DATE
1/27/20 PERMIT SET
REV1: 8/10/2021
JOB NO
202012
SHEET

S8.0