

PRRWF20230497

Revision:

Wall height/design.

See Civil permit and plans for
site plan and location.

Approval of submitted plans is not an approval of
omissions or oversight by this office or
noncompliance with any applicable regulations of
local government. The contractor is responsible for
making sure that the building complies with all
applicable building codes and regulations of the
local government.

THE APPROVED CONSTRUCTION PLANS AND ALL
ENGINEERING MUST BE POSTED ON THE JOB AT ALL
INSPECTIONS IN A VISIBLE AND READILY
ACCESSIBLE LOCATION.

SOUTH HILL BUSINESS & TECHNOLOGY CENTER PARKING EXPANSION STORMWATER PLANTER WALLS

Draft submittal provided need to
provide final design for review. Pg 1
calculations.

Draft Submittal



July 17, 2023



CITY OF
PUYALLUP

Prepared for
City of Puyallup

PMX#253-604-6600

July 17, 2023

Prepared by
Parametrix

SOUTH HILL BUSINESS AND TECHNOLOGY CENTER

(East Parking Lot Expansion)

Description of Calculation

In this calculation package the structural design of stormwater planter walls located at the South Hill Business and Technology Center in Puyallup, Washington is presented. Construction of the stormwater planer walls is a portion of the east parking lot expansion project.

Design Codes

The following design codes were used for this design:

- International Building Code (IBC) – 2018 – Global Stability
- AASHTO LRFD Bridge Design Specification – 9th Edition – Structural Design

Summary of Results

The expanded parking lot will contain several stormwater planters whose wall heights range from 3'-0" to 6'-9" (i.e., measured from top of the wall to the bottom of footing). For walls with a height up to 3' the City of Tacoma's standard plans for walled bioretention walls and structural footing can be used, however, for walls taller than 3', four different wall design are prepared in this calculation package. Only the footing width changes by design height change, so that the footing width are 6', 7', 8', and 9' for walls with 3.75', 4.75', 5.75' and 6.75' height, respectively.


TABLE OF CONTENTS

Stability Check- Stormwater planter wall (H=3.75')	4
Stability Check- Stormwater planter wall (H=4.75'):	7
Stability Check- Stormwater planter wall (H=5.75'):	10
Stability Check- Stormwater planter wall (H=6.75'):	13
Wall Flexural Resistance.....	16
Interface Shear Resistance	17
Wall Shrinkage and Temperature Reinforcement	18
Footing Flexural Resistance.....	19
Footing Shrinkage and Temperature Reinforcement	20
Wall Sketch	21

Stability Check- Stormwater planter wall (H=3.75'):

Summary - Factor of Safeties (FOS):

Load Set	FOS	Allowable Factor of Safety
Overturning (1)	11.3	1.5
Overturning (2)	9.6	1.1
Sliding (1)	1.9	1.5
Sliding (2)	1.6	1.1
Bearing (1)	6.4	1
Bearing (2)	6.4	1



Geometry

t_stem	1 ft	Stem thickness
h_stem	2.25 ft	Stem height
t_footing	1.5 ft	Footing thickness
B	6 ft	Footing width
w_toe	1.5 ft	Toe width

H	3.75 ft	Design height
h_backfill	2.25 ft	Backfill height
w_backfill	3.5 ft	Backfill width
h_front fill	0	Frontfill height
w_frontfill	1.5 ft	Frontfill width

w-c	0.155 kcf	Concrete unit weight - per WSDOT BDM Table 3.8-1
w_soil_b	0.125 kcf	Backfill unit weight - per geotech engineer report
w_soil_f	0.11 kcf	Frontfill unit weight - per geotech engineer report

EH_active	35 pcf	equivalent fluid density (active condition)
EH_passive	300 pcf	equivalent fluid density (passive condition)
LS_H	70 psf	Live load surcharge pressure = $K_a \cdot 250$ psf
EQ	30 psf	Seismic earth pressure, per Geotech engineer report = $8H$ (H is design height)

μ_n	0.35	Soil sliding coefficient
qn	3.00 ksf	Allowable soil bearing resistance (per geotech engineer report)

Considered Loads:

DC - dead load of structural components and nonstructural attachments
EH - horizontal earth pressure load
EV - vertical pressure from dead load of earth fill
EQ - earthquake load
LS - live load surcharge

Summary of Unfactored loads and moments

Vertical Loads & Moments				
Load Type	Description	V (kip/ft)	Moment Arm (ft)	MV (kip-ft.)/ft
DC1	Stem dead load	0.35	2.00	0.70
DC2	Footing dead load	1.40	3.00	4.19
EV1	Vertical pressure from dead load of fill on heel	0.98	4.25	4.18
EV2	Vertical pressure from dead load of fill on toe	0.00	0.75	0.00

Horizontal Loads & Moments				
Load Type	Description	H (kip/ft)	Moment Arm (ft)	MH (kip-ft.)/ft
EH_H	Horizontal component of active earth pressure	0.25	1.25	0.31
LS_H	Horizontal component of live load surcharge	0.26	1.88	0.49
EQ	Earthquake load	0.11	1.88	0.21

Stability check per IBC 2018 - section 1807-2.3:

1807.2.3 Safety factor.

Retaining walls shall be designed to resist the lateral action of soil to produce sliding and overturning with a minimum safety factor of 1.5 in each case. The load combinations of Section 1605 shall not apply to this requirement. Instead, design shall be based on 0.7 times nominal earthquake loads, 1.0 times other *nominal loads*, and investigation with one or more of the variable loads set to zero. The safety factor against lateral sliding shall be taken as the available soil resistance at the base of the retaining wall foundation divided by the net lateral force applied to the retaining wall.

Exception: Where earthquake loads are included, the minimum safety factor for retaining wall sliding and overturning shall be 1.1.

load sets:

1. D + EH: Dead load + Soil lateral load
2. D + EH + 0.7*EQ: Dead load + Soil lateral load + 0.7 * Earthquake load

Summary of two load sets:

Load set	Vertical Loads & Moments		Horizontal Loads & Moments	
	V_u (kip/ft)	MV_u (kip-ft.)/ft	H_u (kip/ft)	MH_u (kip-ft.)/ft
D + EH	2.73	9.07	0.51	0.80
D + EH + 0.7 * EQ	2.73	9.07	0.59	0.95

Overturning Check:

1. D + EH:

Resisting Moments: 9.07 (kip-ft.)/ft

Overturning Moments: 0.80 (kip-ft.)/ft

Safety factor = Resisting moments / Overturning moments = **11.34 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Moments: 9.07

Overturning Moments: 0.95

Safety factor = Resisting moments / Overturning moments = **9.6 > 1.1 Okay**

Sliding Check:

1. D + EH:

Resisting Force: 0.95 (kip-ft.)/ft

Sliding Load: 0.51 (kip-ft.)/ft

Safety factor * = Resisting Force / Sliding Load = **1.88 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Force: 0.95

Sliding Load: 0.59

Safety factor * = Resisting Force / Sliding Load = **1.6 > 1.1 Okay**

Bearing Check:

1. D + EH:

Eccentricity (e): 0.03 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.47 (kip-ft.)/ft

Safety factor = Soil Bearing Resistance / Bearing Stresses = **6.41 > 1.0 Okay**

2. D + EH + 0.7*EQ:

Eccentricity (e): 0.02 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.47 (kip-ft.)/ft


Safety factor = Soil Bearing Resistance / Bearing Stresses = **6.4 > 1.0 Okay**

* conservatively passive resistance associated with soil above the footing toe are disregarded

Stability Check- Stormwater planter wall (H=4.75'):

Summary - Factor of Safeties (FOS):

Load Set	FOS	Allowable Factor of Safety
Overturning (1)	10.9	1.5
Overturning (2)	9.0	1.1
Sliding (1)	1.9	1.5
Sliding (2)	1.6	1.1
Bearing (1)	5.2	1
Bearing (2)	5.1	1



Geometry

t_stem	1 ft	Stem thickness
h_stem	3.25 ft	Stem height
t_footing	1.5 ft	Footing thickness
B	7 ft	Footing width
w_toe	1.5 ft	Toe width

H	4.75 ft	Design height
h_backfill	3.25 ft	Backfill height
w_backfill	4.5 ft	Backfill width
h_front fill	0	Frontfill height
w_frontfill	1.5 ft	Frontfill width

w-c	0.155 kcf	Concrete unit weight - per WSDOT BDM Table 3.8-1
w_soil_b	0.125 kcf	Backfill unit weight - per geotech engineer report
w_soil_f	0.11 kcf	Frontfill unit weight - per geotech engineer report

EH_active	35 pcf	equivalent fluid density (active condition)
EH_passive	300 pcf	equivalent fluid density (passive condition)
LS_H	70 psf	Live load surcharge pressure = $K_a \cdot 250$ psf
EQ	38 psf	Seismic earth pressure, per Geotech engineer report = $8H$ (H is design height)

μ_n	0.35	Soil sliding coefficient
qn	3.00 ksf	Allowable soil bearing resistance (per geotech engineer report)

Considered Loads:

DC - dead load of structural components and nonstructural attachments
EH - horizontal earth pressure load
EV - vertical pressure from dead load of earth fill
EQ - earthquake load
LS - live load surcharge

Summary of Unfactored loads and moments

Vertical Loads & Moments				
Load Type	Description	V (kip/ft)	Moment Arm (ft)	MV (kip-ft.)/ft
DC1	Stem dead load	0.50	2.00	1.01
DC2	Footing dead load	1.63	3.50	5.70
EV1	Vertical pressure from dead load of fill on heel	1.83	4.75	8.68
EV2	Vertical pressure from dead load of fill on toe	0.00	0.75	0.00

Horizontal Loads & Moments				
Load Type	Description	H (kip/ft)	Moment Arm (ft)	MH (kip-ft.)/ft
EH_H	Horizontal component of active earth pressure	0.39	1.58	0.63
LS_H	Horizontal component of live load surcharge	0.33	2.38	0.79
EQ	Earthquake load	0.18	2.38	0.43

Stability check per IBC 2018 - section 1807-2.3:

1807.2.3 Safety factor.

Retaining walls shall be designed to resist the lateral action of soil to produce sliding and overturning with a minimum safety factor of 1.5 in each case. The load combinations of Section 1605 shall not apply to this requirement. Instead, design shall be based on 0.7 times nominal earthquake loads, 1.0 times other *nominal loads*, and investigation with one or more of the variable loads set to zero. The safety factor against lateral sliding shall be taken as the available soil resistance at the base of the retaining wall foundation divided by the net lateral force applied to the retaining wall.

Exception: Where earthquake loads are included, the minimum safety factor for retaining wall sliding and overturning shall be 1.1.

load sets:

1. D + EH: Dead load + Soil lateral load
2. D + EH + 0.7*EQ: Dead load + Soil lateral load + 0.7 * Earthquake load

Summary of two load sets:

Load set	Vertical Loads & Moments		Horizontal Loads & Moments	
	V_u (kip/ft)	MV_u (kip-ft.)/ft	H_u (kip/ft)	MH_u (kip-ft.)/ft
D + EH	3.96	15.39	0.73	1.41
D + EH + 0.7 * EQ	3.96	15.39	0.85	1.71

Overturning Check:

1. D + EH:

Resisting Moments: 15.39 (kip-ft.)/ft

Overturning Moments: 1.41 (kip-ft.)/ft

Safety factor = Resisting moments / Overturning moments = **10.88 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Moments: 15.39

Overturning Moments: 1.71

Safety factor = Resisting moments / Overturning moments = **9.0 > 1.1 Okay**

Sliding Check:

1. D + EH:

Resisting Force: 1.39 (kip-ft.)/ft

Sliding Load: 0.73 (kip-ft.)/ft

Safety factor * = Resisting Force / Sliding Load = **1.91 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Force: 1.39

Sliding Load: 0.85

Safety factor * = Resisting Force / Sliding Load = **1.6 > 1.1 Okay**

Bearing Check:

1. D + EH:

Eccentricity (e): 0.03 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.58 (kip-ft.)/ft

Safety factor = Soil Bearing Resistance / Bearing Stresses = **5.18 > 1.0 Okay**

2. D + EH + 0.7*EQ:

Eccentricity (e): 0.05 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.59 (kip-ft.)/ft


Safety factor = Soil Bearing Resistance / Bearing Stresses = **5.1 > 1.0 Okay**

* conservatively passive resistance associated with soil above the footing toe are disregarded

Stability Check- Stormwater planter wall (H=5.75'):

Summary - Factor of Safeties (FOS):

Load Set	FOS	Allowable Factor of Safety
Overturning (1)	10.6	1.5
Overturning (2)	8.6	1.1
Sliding (1)	1.9	1.5
Sliding (2)	1.6	1.1
Bearing (1)	4.4	1
Bearing (2)	4.1	1



Geometry

t_stem	1 ft	Stem thickness
h_stem	4.25 ft	Stem height
t_footing	1.5 ft	Footing thickness
B	8 ft	Footing width
w_toe	1.5 ft	Toe width
H	5.75 ft	Design height
h_backfill	4.25 ft	Backfill height
w_backfill	5.5 ft	Backfill width
h_front fill	0	Frontfill height
w_frontfill	1.5 ft	Frontfill width
w-c	0.155 kcf	Concrete unit weight - per WSDOT BDM Table 3.8-1
w_soil_b	0.125 kcf	Backfill unit weight - per geotech engineer report
w_soil_f	0.11 kcf	Frontfill unit weight - per geotech engineer report
EH_active	35 pcf	equivalent fluid density (active condition)
EH_passive	300 pcf	equivalent fluid density (passive condition)
LS_H	70 psf	Live load surcharge pressure = $K_a \cdot 250$ psf
EQ	46 psf	Seismic earth pressure, per Geotech engineer report = $8H$ (H is design height)
μ_n	0.35	Soil sliding coefficient
qn	3.00 ksf	Allowable soil bearing resistance (per geotech engineer report)

Considered Loads:

DC - dead load of structural components and nonstructural attachments
EH - horizontal earth pressure load
EV - vertical pressure from dead load of earth fill
EQ - earthquake load
LS - live load surcharge

Summary of Unfactored loads and moments

Vertical Loads & Moments				
Load Type	Description	V (kip/ft)	Moment Arm (ft)	MV (kip-ft.)/ft
DC1	Stem dead load	0.66	2.00	1.32
DC2	Footing dead load	1.86	4.00	7.44
EV1	Vertical pressure from dead load of fill on heel	2.92	5.25	15.34
EV2	Vertical pressure from dead load of fill on toe	0.00	0.75	0.00

Horizontal Loads & Moments				
Load Type	Description	H (kip/ft)	Moment Arm (ft)	MH (kip-ft.)/ft
EH_H	Horizontal component of active earth pressure	0.58	1.92	1.11
LS_H	Horizontal component of live load surcharge	0.40	2.88	1.16
EQ	Earthquake load	0.26	2.88	0.76

Stability check per IBC 2018 - section 1807-2.3:

1807.2.3 Safety factor.

Retaining walls shall be designed to resist the lateral action of soil to produce sliding and overturning with a minimum safety factor of 1.5 in each case. The load combinations of Section 1605 shall not apply to this requirement. Instead, design shall be based on 0.7 times nominal earthquake loads, 1.0 times other *nominal loads*, and investigation with one or more of the variable loads set to zero. The safety factor against lateral sliding shall be taken as the available soil resistance at the base of the retaining wall foundation divided by the net lateral force applied to the retaining wall.

Exception: Where earthquake loads are included, the minimum safety factor for retaining wall sliding and overturning shall be 1.1.

load sets:

1. D + EH: Dead load + Soil lateral load
2. D + EH + 0.7*EQ: Dead load + Soil lateral load + 0.7 * Earthquake load

Summary of two load sets:

Load set	Vertical Loads & Moments		Horizontal Loads & Moments	
	V_u (kip/ft)	MV_u (kip-ft.)/ft	H_u (kip/ft)	MH_u (kip-ft.)/ft
D + EH	5.44	24.10	0.98	2.27
D + EH + 0.7 * EQ	5.44	24.10	1.17	2.80

Overturning Check:

1. D + EH:

Resisting Moments: 24.10 (kip-ft.)/ft

Overturning Moments: 2.27 (kip-ft.)/ft

Safety factor = Resisting moments / Overturning moments = **10.63 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Moments: 24.10

Overturning Moments: 2.80

Safety factor = Resisting moments / Overturning moments = **8.6 > 1.1 Okay**

Sliding Check:

1. D + EH:

Resisting Force: 1.90 (kip-ft.)/ft

Sliding Load: 0.98 (kip-ft.)/ft

Safety factor * = Resisting Force / Sliding Load = **1.94 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Force: 1.90

Sliding Load: 1.17

Safety factor * = Resisting Force / Sliding Load = **1.6 > 1.1 Okay**

Bearing Check:

1. D + EH:

Eccentricity (e): 0.01 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.69 (kip-ft.)/ft

Safety factor = Soil Bearing Resistance / Bearing Stresses = **4.37 > 1.0 Okay**

2. D + EH + 0.7*EQ:

Eccentricity (e): 0.09 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.72 (kip-ft.)/ft


Safety factor = Soil Bearing Resistance / Bearing Stresses = **4.1 > 1.0 Okay**

* conservatively passive resistance associated with soil above the footing toe are disregarded

Stability Check- Stormwater planter wall (H=6.75'):

Summary - Factor of Safeties (FOS):

Load Set	FOS	Allowable Factor of Safety
Overturning (1)	10.5	1.5
Overturning (2)	8.4	1.1
Sliding (1)	2.0	1.5
Sliding (2)	1.6	1.1
Bearing (1)	3.7	1
Bearing (2)	3.5	1



Geometry

t_stem	1 ft	Stem thickness
h_stem	5.25 ft	Stem height
t_footing	1.5 ft	Footing thickness
B	9 ft	Footing width
w_toe	1.5 ft	Toe width

H	6.75 ft	Design height
h_backfill	5.25 ft	Backfill height
w_backfill	6.5 ft	Backfill width
h_front fill	0	Frontfill height
w_frontfill	1.5 ft	Frontfill width

w-c	0.155 kcf	Concrete unit weight - per WSDOT BDM Table 3.8-1
w_soil_b	0.125 kcf	Backfill unit weight - per geotech engineer report
w_soil_f	0.11 kcf	Frontfill unit weight - per geotech engineer report

EH_active	35 pcf	equivalent fluid density (active condition)
EH_passive	300 pcf	equivalent fluid density (passive condition)
LS_H	70 psf	Live load surcharge pressure = $K_a \cdot 250$ psf
EQ	54 psf	Seismic earth pressure, per Geotech engineer report = $8H$ (H is design height)

μ_n	0.35	Soil sliding coefficient
qn	3.00 ksf	Allowable soil bearing resistance (per geotech engineer report)

Considered Loads:

DC - dead load of structural components and nonstructural attachments
EH - horizontal earth pressure load
EV - vertical pressure from dead load of earth fill
EQ - earthquake load
LS - live load surcharge

Summary of Unfactored loads and moments

Vertical Loads & Moments				
Load Type	Description	V (kip/ft)	Moment Arm (ft)	MV (kip-ft.)/ft
DC1	Stem dead load	0.81	2.00	1.63
DC2	Footing dead load	2.09	4.50	9.42
EV1	Vertical pressure from dead load of fill on heel	4.27	5.75	24.53
EV2	Vertical pressure from dead load of fill on toe	0.00	0.75	0.00

Horizontal Loads & Moments				
Load Type	Description	H (kip/ft)	Moment Arm (ft)	MH (kip-ft.)/ft
EH_H	Horizontal component of active earth pressure	0.80	2.25	1.79
LS_H	Horizontal component of live load surcharge	0.47	3.38	1.59
EQ	Earthquake load	0.36	3.38	1.23

Stability check per IBC 2018 - section 1807-2.3:

1807.2.3 Safety factor.

Retaining walls shall be designed to resist the lateral action of soil to produce sliding and overturning with a minimum safety factor of 1.5 in each case. The load combinations of Section 1605 shall not apply to this requirement. Instead, design shall be based on 0.7 times nominal earthquake loads, 1.0 times other *nominal loads*, and investigation with one or more of the variable loads set to zero. The safety factor against lateral sliding shall be taken as the available soil resistance at the base of the retaining wall foundation divided by the net lateral force applied to the retaining wall.

Exception: Where earthquake loads are included, the minimum safety factor for retaining wall sliding and overturning shall be 1.1.

load sets:

1. D + EH: Dead load + Soil lateral load
2. D + EH + 0.7*EQ: Dead load + Soil lateral load + 0.7 * Earthquake load

Summary of two load sets:

Load set	Vertical Loads & Moments		Horizontal Loads & Moments	
	V_u (kip/ft)	MV_u (kip-ft.)/ft	H_u (kip/ft)	MH_u (kip-ft.)/ft
D + EH	7.17	35.57	1.27	3.39
D + EH + 0.7 * EQ	7.17	35.57	1.52	4.25

Overturning Check:

1. D + EH:

Resisting Moments: 35.57 (kip-ft.)/ft

Overturning Moments: 3.39 (kip-ft.)/ft

Safety factor = Resisting moments / Overturning moments = **10.50 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Moments: 35.57

Overturning Moments: 4.25

Safety factor = Resisting moments / Overturning moments = **8.4 > 1.1 Okay**

Sliding Check:

1. D + EH:

Resisting Force: 2.51 (kip-ft.)/ft

Sliding Load: 1.27 (kip-ft.)/ft

Safety factor * = Resisting Force / Sliding Load = **1.98 > 1.5 Okay**

2. D + EH + 0.7*EQ:

Resisting Force: 2.51

Sliding Load: 1.52

Safety factor * = Resisting Force / Sliding Load = **1.6 > 1.1 Okay**

Bearing Check:

1. D + EH:

Eccentricity (e): 0.01 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.80 (kip-ft.)/ft

Safety factor = Soil Bearing Resistance / Bearing Stresses = **3.73 > 1.0 Okay**

2. D + EH + 0.7*EQ:

Eccentricity (e): 0.13 ft

Soil Bearing Resistance: 3.00 (kip-ft.)/ft

Bearing Stresses: 0.87 (kip-ft.)/ft


Safety factor = Soil Bearing Resistance / Bearing Stresses = **3.5 > 1.0 Okay**

* conservatively passive resistance associated with soil above the footing toe are disregarded

Wall Flexural Resistance (at critical section):

#6 vertical bars spaced at 12" with a staggered pattern is used:

The top view of wall:



Concrete Properties

$f'_c = 4$ ksi
 $w_c = 0.150$ kcf
 $E_c = 4266$ ksi

Reinforcement Properties

$F_y = 60$ ksi
 $E_s = 29000$ ksi

Design Moments

$M_u = 2.95$ k-ft

Section Geometry

$b = 12.00$ in
 $h = 12.00$ in
Cover = 2 in

Flexural Reinforcement

Layer	Bar Size	# of Bars	A_s (in ²)	d (in)
1	#6	1.000	0.44	9.63
2				
3				
4				

$A_s = 0.44$ in²
 $d = 9.63$ in
 $dt = 9.63$ in
 $S = 12.00$ in

Reinforcement Spacing

Flexural Strength Check

$c = 0.761$ in Solve for c using goal seek. (Press Control + i to run macro)
 $\epsilon_c = 0.003$ Concrete compression strain limit per LRFD 5.6.2.1
 $B_1 = 0.85$ Rectangular stress distribution factor per LRFD 5.6.2.2
 $a = 0.647$ in $a = B_1 c$ per LRFD 5.6.2.2
 $C = 26.4$ kip Concrete Compression Force: $C = 0.85 f'_c a b_f$
 $\epsilon_s = 0.03493$ Reinforcement Strain: $\epsilon_s = \epsilon_c (d/c - 1)$
 $f_s = 60.0$ ksi Reinforcement Tension Stress: $f_s = \min(\epsilon_s E_s, F_y)$
 $T = 26.4$ kip Reinforcement Tension Force: $T = f_s A_s$
 $T - C = 0.000$ kip Sum of Forces
 $M_n = 20.5$ k-ft Nominal Moment Strength: $M_n = T(d - a/2)$
 $\phi = 0.9$ $\phi = 0.75 + 0.15(\epsilon_t - \epsilon_{cl}/\epsilon_{tl} - \epsilon_{cl}) < 0.9$ per LRFD 5.5.4.2-2
 $\phi M_n = 18.4$ k-ft Factored Moment Strength

18.4 > 3 OK

Flexural Crack Control

$\gamma_e = 0.75$ Exposure factor per LRFD 5.6.7
 $d_c = 2.38$ in Distance from extreme tension fiber to CG of closest bar
 $s = 12.00$ in Spacing of steel reinforcement
 $n = 6.80$ Modular Ratio: $n = E_s/E_c$
 $\rho = 0.00381$ Reinforcement Ratio: $\rho = A_s/(b \cdot d)$

$$k = 0.203 \quad k = \text{SQRT}[(pn)^2 + 2pn] - pn$$

$$j = 0.932 \quad j = 1 - k/3$$

$$f_{s_{\text{service}}} = 9.0 \text{ ksi} \quad f_{s_{\text{service}}} = M_{\text{service}} / (A_s * j * d)$$

$$\beta_s = 1.35 \quad \beta_s = 1 + d_c / [0.7 * (h - d_c)]$$

$$s_{\text{max}} = 38.48 \text{ in}$$

12 < 38.5 OK

Minimum Reinforcement Check

$$I = 1728 \text{ in}^4 \quad \text{Moment of Inertia}$$

$$S_t = 288 \text{ in}^3 \quad \text{Section Modulus for Extreme Tensile Fiber}$$

$$\gamma_1 = 1.6 \quad \text{flexural cracking variability factor LRFD 5.6.3.3}$$

$$\gamma_3 = 0.67 \quad \text{ratio of specified minimum yield strength to ultimate tensile of the nonprestressed reinforcement}$$

$$f_r = 0.480 \text{ ksi} \quad \text{Modulus of Rupture per LRFD 5.4.2.6}$$

$$M_{cr} = 12.3 \text{ k-ft} \quad \text{Cracking Moment: } M_{cr} = \gamma_3 * [\gamma_1 * f_r] S_c$$

$$M_{cr} = 12.3 \text{ k-ft}$$

$$1.33M_u = 3.9 \text{ k-ft} \quad 1.33M_u \text{ Controls}$$

3.9 < 18.4 OK

Interface Shear Resistance (at Stem - Footing Connection, AASHTO 5.7.4.3)

$$f_y = 60.00 \text{ ksi} \quad \text{Specified minimum yield strength of reinforcement (ksi)}$$

$$f'_c = 4.00 \text{ ksi} \quad \text{Compressive strength of concrete for use on design (ksi)}$$

$$c = 0.24 \text{ ksi} \quad \text{for normal weight concrete placed against roughened surface to 0.25'}$$

$$\mu = 1.00 \quad \text{for normal weight concrete placed against roughened surface to 0.25'}$$

$$t = 12.00 \text{ in} \quad \text{the wall thickness}$$

$$A_{vc} = 144.00 \text{ in}^2/\text{ft} \quad \text{area of concrete considered to be engaged in interface shear transfer}$$

$$A_{vf} = 0.88 \text{ in}^2/\text{ft} \quad \text{area of interface shear reinforcement crossing the shear plane}$$

$$P_c = 0.00 \text{ kip} \quad \text{permanent net compressive force normal to the shear plane}$$

$$K_1 = 0.25 \quad \text{fraction of concrete strength available to resist interface shear (AASHTO 5.7.4.4)}$$

$$K_2 = 1.50 \quad \text{limiting interface shear resistance (AASHTO 5.7.4.4)}$$

$$\phi = 1.00 \quad \text{AASHTO 5.5.4.2}$$

$$V_{ni} = 87.36 \text{ kip/ft}$$

$$\phi V_{ni} = 87.36 \text{ kip/ft}$$

$$\phi V_{ni} > V_u = 1.37 \text{ kips/ft} \quad \text{Ok}$$

Wall Shear Strength (at critical section):

$$V_u = 1.37 \text{ kip/ft}$$

$$\phi = 0.9$$

$$b_v = 12.00 \text{ in}$$

$$d_v = 9.30 \text{ in} \quad = \max(d_s - a/2 = 9.3 \text{ in}, 0.9 * d_e = 8.66 \text{ in}, 0.72 * h = 8.64 \text{ in})$$

$$\beta = 2 \quad \text{AASHTO 5.7.3.4.1}$$


$$V_c = 14.11 \text{ kip} \quad V_c = 0.0316 * \beta * \sqrt{f'_c} [b_v * d_v]$$

$$\phi V_c = 12.70 \text{ kip} \quad \text{Ok}$$

Footing Flexural Resistance (at critical section):

#6 vertical bars spaced at 12" with a staggered pattern is used:

Footing side view:



Concrete Properties

$f'_c = 4$ ksi
 $w_c = 0.150$ kcf
 $E_c = 4266$ ksi

Section Geometry

$b = 12.00$ in
 $h = 18.00$ in
Cover = 2 in

Reinforcement Properties

$F_y = 60$ ksi
 $E_s = 29000$ ksi

Design Moments

$M_u = 20.01$ k-ft moment due to soil bearing
 2.95 k-ft moment due to wall loads

Flexural Reinforcement

Layer	Bar Size	# of Bars	A_s (in ²)	d (in)
1	#6	1.000	0.44	15.63
2				
3				
4				

$A_s = 0.44$ in²
 $d = 15.63$ in
 $dt = 15.63$ in
 $S = 12.00$ in

Reinforcement Spacing

Flexural Strength Check

$c = 0.761$ in Solve for c using goal seek. (Press Control + i to run macro)
 $\epsilon_c = 0.003$ Concrete compression strain limit per LRFD 5.6.2.1
 $B_1 = 0.85$ Rectangular stress distribution factor per LRFD 5.6.2.2
 $a = 0.647$ in $a = B_1 c$ per LRFD 5.6.2.2
 $C = 26.4$ kip Concrete Compression Force: $C = 0.85 f'_c a b_f$
 $\epsilon_s = 0.05858$ Reinforcement Strain: $\epsilon_s = \epsilon_c (d/c - 1)$
 $f_s = 60.0$ ksi Reinforcement Tension Stress: $f_s = \min(\epsilon_s E_s, F_y)$
 $T = 26.4$ kip Reinforcement Tension Force: $T = f_s A_s$
 $T - C = 0.000$ kip Sum of Forces
 $M_n = 33.7$ k-ft Nominal Moment Strength: $M_n = T(d - a/2)$
 $\phi = 0.9$ $\phi = 0.75 + 0.15(\epsilon_t - \epsilon_{cl}/\epsilon_{tl} - \epsilon_{cl}) < 0.9$ per LRFD 5.5.4.2-2
 $\phi M_n = 30.3$ k-ft Factored Moment Strength

30.3 > 20 OK

Flexural Crack Control

$\gamma_e = 0.75$ Exposure factor per LRFD 5.6.7
 $dc = 2.38$ in Distance from extreme tension fiber to CG of closest bar
 $s = 12.00$ in Spacing of steel reinforcement
 $n = 6.80$ Modular Ratio: $n = E_s/E_c$
 $\rho = 0.00235$ Reinforcement Ratio: $\rho = A_s/(b \cdot d)$

k =	0.163	$k = \text{SQRT}[(pn)^2 + 2pn] - pn$
j =	0.946	$j = 1 - k/3$
$f_{s_service} =$	5.5 ksi	$f_{s_service} = M_{service} / (A_s * j * d)$
$\beta_s =$	1.22	$\beta_s = 1 + dc / [0.7 * (h - dc)]$
smax =	74.34 in	
12 < 74.3 OK		

Minimum Reinforcement Check


I =	5832 in ⁴	Moment of Inertia
St =	648 in ³	Section Modulus for Extreme Tensile Fiber
γ_1	1.6	flexural cracking variability factor LRFD 5.6.3.3
γ_3	0.67	ratio of specified minimum yield strength to ultimate tensile of the nonprestressed reinforcement
$f_r =$	0.480 ksi	Modulus of Rupture per LRFD 5.4.2.6
$M_{cr} =$	27.8 k-ft	Cracking Moment: $M_{cr} = \gamma_3 * [\gamma_1 * f_r] S_c$
$M_{cr} =$	27.8 k-ft	
$1.33M_u =$	3.9 k-ft	1.33Mu Controls
3.9 < 30.3 OK		

Shrinkage and temperature reinforcement (AASHTO 5.10.6)

A_s	0.11 in ² /ft	$1.3bh / (2 * (b + h) * f_y)$ area of reinforcement in each direction and each face $0.11 \leq A_s \leq 0.6$
b	12 in	
h	18 in	

#4 @ 12" reinforcement should be used for bars that are parallel to barrier

Wall Sketch:



** GRAVEL BACKFILL FOR FOUNDATIONS CLASS A

$A = 6.75' \Rightarrow B = 9'$
 $A = 5.75' \Rightarrow B = 8'$
 $A = 4.75' \Rightarrow B = 7'$
 $A = 3.75' \Rightarrow B = 6'$

