



THE APPROVED CONSTRUCTION PLANS AND ALL ENGINEERING MUST BE POSTED ON THE JOB AT ALL INSPECTIONS IN A VISIBLE AND READILY ACCESSIBLE LOCATION.

Approval of submitted plans is not an approval of omissions or oversight by this office or noncompliance with any applicable regulations of local government. The contractor is responsible for making sure that the building complies with all applicable building codes and regulations of the local government.



/ POST-TENS	IONED SLAB
3/8" ATR	HILTI HDI-P CONCRETE HANGER ATTACHMENT
RING HANGER	UP TO 4" PIPE




## F1 HANGER DETAIL

SCALE: NONE

D1 HANGER DETAIL

A A A

SCALE: NONE





						Δ	H "U			LE	GE	ND	I	
	City of Puyallup					A "U" HOOK B COACH SCREW ROD D BM. CLAMP W/ "STRAP								
• / • > /	lopment & Permitting Services					E EYELET F HDIP								
ISS	SUE	) PER	MIT			G H			FLA EAM			ET		
Buildin	α	A.	Plannin	α		к М	SH	ORT	CLIP					
	ອ		i idinini g			M ALL THREAD ROD N TOGGLE NUT P POWDER DRIVEN STUD								
Engineering Public Works				R S	EX		SION				,			
Enginoor	mg					Т								
Fire	0		Traffic			U V								
The Misherianic						W X								
						Y Z								
	ST.	ATE (		CATIC	)N	SPRINKLER LEGEND								
	L.2	/31/24 FIR	SHINGTON STATE ITIFICATE OF CON E PROTECTION SP	PETENCY RINKLER SYST	TEMS	SPKR THRDS			AND TYPE			UPRIGHT PENDENT TEE		
	9819		ne Level 3 otection, Inc	G.		<u>1</u> 2	<u>5</u> 16	<u>3</u> 7 816	<u>1</u> SPF	RAY	$\odot$		1/2 1"	
		RIFP099		- 8-28-2	24	<u>3</u> 4	<u>17</u> 32		SPI	RAY			3/4 1"	
		Signatu		Date		<u>1</u> 2	3	$\frac{7}{16}$ $\frac{1}{2}$	SIDE	WALL		 ▼	1/2 1"	
						1"	<u>1</u> 2		DRY T	YPE		Ì ♦	1" 1"	
		2 - 1	WAY EARTHQ	UAKE BRAG	CE		TEMF	P RATIN	G	SN SN SN SN SN SN SN SN SN SN SN SN SN S			OPENING DOWN	
			WAY EARTHQ			-(	) ÷	165° 212°		SPRINKLERS UP AND DOWN	а- а- 1/2"	$ \bigcirc$	ао 1"	
		) STRUC LINE	OF PIPE			Ξ	) €	286° 350°			1" 1"		1/2' 1"	
	P	PIPE-C				∃	) €	500°	///		1/2" I    P	$\square$	1/2	
	F SN	GROOV	END FIT FIT	NIPPLE		APPROVAL REQUIRED CITY OF PUYALLUP								
	TSN	IHREAD	DED SHAPED											
	SYM	MANUF		RINKLEF			DS HREAD SIZE	USED ORIFICE SIZE	) HEAD FINISH	ESCUT		ЕМР	QTY	
	00	RELIABLE	F1FR 56	QR UPRICH			1⁄2"	K=5.6	BRONZE	N/#		155	10	
		Reliable	F1FR 56	QR PENDEI	NI		1/2"	K=5.6	BRONZE	N/#		155*	1	
	QUAL	ITY CONTR	OL BY						DAT	E	тот	AL	11	
	QUALITY CONTROL BY APPROVED FOR FABRICATION BY						DATE							
	SI 3. EAR NI 4. PIPI 5. PIPI 6. JOII 6. JOII 6. JOII 7. OWW 9. 8. ALL BY 9. PAII BY	HOWN THUS THQUAKE BR/ TPA PAMPHLE E HANGERS A TPA PAMPHLE NG SHALL BE NING OF PIPE TH NFPA PAM NER TO PROV STEM TO PROV STEM TO PROV STEM TO PROV STEM TO PROV STEM TO PROV THING OF PIPE OTHER RING OF PIPE	e & equipment S E & equipment	ICH ARE EN PROVIDED IN <u>6</u> EDITION. HANGING TO <u>6</u> EDITION. E WITH NFPA THREADED & <u>2016</u> EDITI HEAT IN AREAS PIPES FROM CES (IF REQUIRED (IF REQUIRED) (IF REQUIRED)	ND TO ACCOR BE IN . PAMPH WELDET ION. S PROTI S PROTI INC BI ) TO BI	END DANCI ACCOR LET N D, SHA SCTED E PRO E PRO	: WITH DANCE DANCE ITEF	WITH 2016 e IN ACCORI WET PIPE ED RIA	DITION		S			
	1. 	ALL TH	READED F	PIPE TO		SCH	S							
		RACT WITH:	CARE		гш	<b>C</b> 1	<u>(ст</u>	F M						
	F F	ю вох	5299 M/ WA 984	'S 737–			JI	L I¥I						
	(	401 15	D SAI 5th ave .up, wa	E SE		L	RC		1					
			PROTE		-			tro	/WW.PA avis.mac	key@p	DTFIR Datrio	RE.C	OM	
		ТАСОМА	OTH AVEI A, WA 9	8424					EL: (25 AX: (25					
	DATE	-	TRAVIS N 8/28/	2024		SHE 0	ET F <b>1</b>	-	F	Ρ	_	1		
	JOB	NO.	12238	809	1	υ	1		Í	1		1		

## GENERAL NOTES

1. — — — DENOTES EXISTING FIRE SPRINKLER PIPING.
 2. \_ \_\_\_\_\_ DENOTES NEW FIRE SPRINKLER PIPING.
 3. 

 DENOTES EXISTING FIRE SPRINKLER PENDENT TO REMAIN.
 DENOTES EXISTING FIRE SPRINKLER TO RELOCATE.

## SCOPE OF WORK

REPLACE PIPING IN MAINTENANCE ROOM. INSTALL BRANCHLINES AND PROTECTION AT DECK IN POOL ROOM AND PLUG OFF EXISTING SIDEWALL SPRINKLERS.

