

Project Information	
East Town Crossing, Unit 101	
Building G	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

Messages / Results *	
UA Reduction = 2.41, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

ANALYSIS SET UP	
What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 795 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,207	67.6	0.054	1,207	65.2
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	134	72.1	0.540	134	72.1
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		186.4	Proposed UA Total		184.0
	Required Credits		4.5	Proposed Credits		6.5
				UA Percent Reduction		1.3%
				UA Reduction		2.4
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0		
7	Appliance Package		0.0		
Energy Credits			5.5		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**





Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		134	72
Sum of Perimeter and FP					134	72

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		795 ft2
Conditioned Volume		6,758 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		184
Envelope Heat Load		9,383 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,722 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		13,105 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		13,105 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		16,382 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>	
East Town Crossing, Unit 102	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.26, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



**ANALYSIS SET UP**

What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 765 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

**RESULTS - Comparison of Baseline and Proposed Design**

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,128	63.1	0.054	1,128	60.9
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	126	67.9	0.540	126	67.9
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
<b>Baseline UA Total</b>			<b>177.7</b>			<b>175.5</b>
<b>Required Credits</b>			<b>4.5</b>			<b>6.5</b>
				<b>Proposed Credits</b>		<b>6.5</b>
				<b>UA Percent Reduction</b>		<b>1.3%</b>
				<b>UA Reduction</b>		<b>2.3</b>

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	<b>Heat Pump, air-to-air or air to water</b>	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	<b>Option 3.6</b>	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	<b>Option 5.5</b>	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**





Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		126	68
Sum of Perimeter and FP					126	68

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet		<a href="#">Prescriptive Checklist Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		765 ft2
Conditioned Volume		6,503 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		175
Envelope Heat Load		8,949 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,582 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		12,531 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		12,531 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		15,664 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>
East Town Crossing, Unit 103 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.17, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 45 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 624 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>						
	<b>Baseline</b>			<b>Proposed Design</b>		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,083	60.6	0.054	1,083	58.5
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	115	62.0	0.540	115	62.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		149.0	<b>Proposed UA Total</b>		146.9
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b> 1.5%		
				<b>UA Reduction</b> 2.2		
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	624	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
2	6	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	0	6	0	24.0	7.20	
<b>Sum of Area and UA</b>									<b>48.0</b>	<b>14.4</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,083	58
<b>Sum of Area and UA</b>									<b>1,083</b>	<b>58</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>





Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	R10 2' vertical (Code Baseline)	10-2	0.540		115	62	
Sum of Perimeter and FP					115	62	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	1		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	45 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link	
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>	
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>		
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>		
	New Construction <a href="#">Affidavit, New</a>		
Prescriptive Checklist for 2018 WSEC	<a href="#">Prescriptive Checklist</a>		
Alterations (Remodel) Worksheet	<a href="#">Worksheet</a>		

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>	
Nearest Weather Station	Puyallup		
Indoor Design Temperature	70 F		
Outdoor Design Temperature	19 F		
Design Temperature Difference (ΔT)	51 F		
Conditioned Floor Area, Proposed Design	624 ft2		
Conditioned Volume	5,304 ft3		
Leave blank to use default of 8.5 ft. ceiling height			
HVAC System Type	Heat Pump		
Location of HVAC Distribution System	Unducted		
Sum of UA, including exempt door and window	147		
Envelope Heat Load	7,490 Btu / Hour		
Sum of UA X ΔT			
Air Leakage Heat Load	2,921 Btu / Hour		
((Volume X 0.6) X ΔT) X 0.18)			
Building Design Heat Load	10,412 Btu / Hour		
Air Leakage + Envelope Heat Loss			
Building and Duct Heat Load	10,412 Btu / Hour		
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1			
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1			
Maximum Heat Equipment Output	13,015 Btu / Hour		
Building and Duct Heat Loss X 1.25 for heat pumps			
Building and Duct Heat Loss X 1.40 for all other systems			

<b>Project Information</b>
East Town Crossing, Unit 104 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>City of Puyallup Development &amp; Permitting Services <b>ISSUED PERMIT</b></p> <p>Building Planning Engineering Public Works Fire Traffic</p> <p>UA Reduction = 2.29, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>

\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

**ANALYSIS SET UP**

What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 732 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

**RESULTS - Comparison of Baseline and Proposed Design**

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,144	64.1	0.054	1,144	61.8
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	122	66.0	0.540	122	66.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
<b>Baseline UA Total</b>			<b>161.0</b>			<b>158.7</b>
<b>Required Credits</b>			<b>4.5</b>			<b>6.5</b>
				<b>Proposed Credits</b>		<b>6.5</b>
				<b>UA Percent Reduction</b>		<b>1.4%</b>
				<b>UA Reduction</b>		<b>2.3</b>

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	732	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3 U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40		
2	5 U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	6	0	15.0	4.50		
<b>Sum of Area and UA</b>									<b>63.0</b>	<b>18.9</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,144	62
<b>Sum of Area and UA</b>									<b>1,144</b>	<b>62</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		122	66
Sum of Perimeter and FP					122	66

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements		
Number of Bedrooms	2	
Run-Time Percent in Each 4-Hour Segment	100%	
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403	
Whole House Mechanical Ventilation Airflow Rate	55 CFM	

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required?	No	

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>	
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>	
	New Construction <a href="#">Affidavit, New</a>	
Prescriptive Checklist for 2018 WSEC	<a href="#">Prescriptive Checklist</a>	
Alterations (Remodel) Worksheet	<a href="#">Worksheet</a>	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	732 ft2	
Conditioned Volume	6,222 ft3	
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type	Heat Pump	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	159	
Envelope Heat Load	8,096 Btu / Hour	
Sum of UA X ΔT		
Air Leakage Heat Load	3,427 Btu / Hour	
((Volume X 0.6) X ΔT) X 0.18)		
Building Design Heat Load	11,523 Btu / Hour	
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load	11,523 Btu / Hour	
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output	14,404 Btu / Hour	
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		

<b>Project Information</b>
East Town Crossing, Unit 105 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.17, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 45 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 624 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>			<b>Proposed Design</b>			
	<b>U</b>	<b>Area</b>	<b>UA</b>	<b>U</b>	<b>Area</b>	<b>UA</b>
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,083	60.6	0.054	1,083	58.5
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	115	62.0	0.540	115	62.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		149.0	<b>Proposed UA Total</b>		146.9
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		1.5%
				<b>UA Reduction</b>		2.2
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0		
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	624	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3 U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20		
2	6 U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	0	6	0	24.0	7.20		
<b>Sum of Area and UA</b>									<b>48.0</b>	<b>14.4</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,083	58
<b>Sum of Area and UA</b>									<b>1,083</b>	<b>58</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	R10 2' vertical (Code Baseline)	10-2	0.540		115	62	
Sum of Perimeter and FP					115	62	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	1		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	45 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link	
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>	
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>		
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>		
	New Construction <a href="#">Affidavit, New</a>		
Prescriptive Checklist for 2018 WSEC	<a href="#">Prescriptive Checklist</a>		
Alterations (Remodel) Worksheet	<a href="#">Worksheet</a>		

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>	
Nearest Weather Station	Puyallup		
Indoor Design Temperature	70 F		
Outdoor Design Temperature	19 F		
Design Temperature Difference (ΔT)	51 F		
Conditioned Floor Area, Proposed Design	624 ft2		
Conditioned Volume	5,304 ft3		
Leave blank to use default of 8.5 ft. ceiling height			
HVAC System Type	Heat Pump		
Location of HVAC Distribution System	Unducted		
Sum of UA, including exempt door and window	147		
Envelope Heat Load	7,490 Btu / Hour		
Sum of UA X ΔT			
Air Leakage Heat Load	2,921 Btu / Hour		
((Volume X 0.6) X ΔT) X 0.18)			
Building Design Heat Load	10,412 Btu / Hour		
Air Leakage + Envelope Heat Loss			
Building and Duct Heat Load	10,412 Btu / Hour		
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1			
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1			
Maximum Heat Equipment Output	13,015 Btu / Hour		
Building and Duct Heat Loss X 1.25 for heat pumps			
Building and Duct Heat Loss X 1.40 for all other systems			

<b>Project Information</b>
East Town Crossing, Unit 106 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.29, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 732 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>			<b>Proposed Design</b>			
	<b>U</b>	<b>Area</b>	<b>UA</b>	<b>U</b>	<b>Area</b>	<b>UA</b>
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,144	64.1	0.054	1,144	61.8
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	122	66.0	0.540	122	66.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
			<b>Baseline UA Total</b>			<b>Proposed UA Total</b>
			161.0			158.7
			<b>Required Credits</b>			<b>Proposed Credits</b>
			4.5			6.5
						1.4% from Tables 406.2 and 406.3
						<b>UA Reduction</b>
						2.3
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**



Conditioned Floor Area, Proposed Design	732	sq. ft
Classification	Small Dwelling Unit	
Notes		

City of Payalup  
Development & Permitting Services  
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show	
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	5	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	6	0	15.0	4.50	
Sum of Area and UA									63.0	18.9		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U					Area	UA	
	No ceiling/roof in thermal envelope	NA	-						0.0	
Sum of Area and UA								0	0.0	

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U					Net Area	UA	
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054					1,144	62	
Sum of Area and UA								1,144	62	

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U					Area	UA	
Sum of Area and UA								0	0	



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	R10 2' vertical (Code Baseline)	10-2	0.540		122	66	
Sum of Perimeter and FP					122	66	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	55 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		732 ft2
Conditioned Volume		6,222 ft3
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		159
Envelope Heat Load		8,096 Btu / Hour
Sum of UA X ΔT		
Air Leakage Heat Load		3,427 Btu / Hour
((Volume X 0.6) X ΔT) X 0.18)		
Building Design Heat Load		11,523 Btu / Hour
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load		11,523 Btu / Hour
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output		14,404 Btu / Hour
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		

<b>Project Information</b>
East Town Crossing, Unit 107 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>City of Puyallup Development &amp; Permitting Services <b>ISSUED PERMIT</b></p> <p>Building Planning Engineering Public Works Fire Traffic</p> <p>UA Reduction = 2.41, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>

\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 795 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>																																																																																																								
<table border="1"> <thead> <tr> <th rowspan="2">Component Performance, R occupancies</th> <th colspan="3">Baseline</th> <th colspan="3">Proposed Design</th> </tr> <tr> <th>U</th> <th>Area</th> <th>UA</th> <th>U</th> <th>Area</th> <th>UA</th> </tr> </thead> <tbody> <tr> <td>Doors U =</td> <td>0.300</td> <td>40</td> <td>12.0</td> <td>0.300</td> <td>40</td> <td>12.0</td> </tr> <tr> <td>Overhead Glazing U =</td> <td>0.500</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Vertical Glazing U =</td> <td>0.300</td> <td>116</td> <td>34.7</td> <td>0.300</td> <td>116</td> <td>34.7</td> </tr> <tr> <td>Flat/Vaulted Ceilings U =</td> <td>0.027</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Wall (above grade) U =</td> <td>0.056</td> <td>1,207</td> <td>67.6</td> <td>0.054</td> <td>1,207</td> <td>65.2</td> </tr> <tr> <td>Floors over Crawlspace U =</td> <td>0.029</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Slab on Grade F =</td> <td>0.540</td> <td>134</td> <td>72.1</td> <td>0.540</td> <td>134</td> <td>72.1</td> </tr> <tr> <td>Below Grade Wall U =</td> <td>0.042</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Slab F =</td> <td>0.570</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td></td> <td colspan="2"><b>Baseline UA Total</b></td> <td>186.4</td> <td colspan="2"><b>Proposed UA Total</b></td> <td>184.0</td> </tr> <tr> <td></td> <td colspan="2"><b>Required Credits</b></td> <td>4.5</td> <td colspan="2"><b>Proposed Credits</b></td> <td>6.5</td> </tr> <tr> <td></td> <td colspan="2"></td> <td></td> <td colspan="2"><b>UA Percent Reduction</b></td> <td>1.3%</td> </tr> <tr> <td></td> <td colspan="2"></td> <td></td> <td colspan="2"><b>UA Reduction</b></td> <td>2.4</td> </tr> </tbody> </table> <p>from Tables 406.2 and 406.3</p> <p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>	Component Performance, R occupancies	Baseline			Proposed Design			U	Area	UA	U	Area	UA	Doors U =	0.300	40	12.0	0.300	40	12.0	Overhead Glazing U =	0.500	0	0.0		0	0.0	Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7	Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0	Wall (above grade) U =	0.056	1,207	67.6	0.054	1,207	65.2	Floors over Crawlspace U =	0.029	0	0.0		0	0.0	Slab on Grade F =	0.540	134	72.1	0.540	134	72.1	Below Grade Wall U =	0.042	0	0.0		0	0.0	Below Grade Slab F =	0.570	0	0.0		0	0.0		<b>Baseline UA Total</b>		186.4	<b>Proposed UA Total</b>		184.0		<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5					<b>UA Percent Reduction</b>		1.3%					<b>UA Reduction</b>		2.4
Component Performance, R occupancies		Baseline			Proposed Design																																																																																																			
	U	Area	UA	U	Area	UA																																																																																																		
Doors U =	0.300	40	12.0	0.300	40	12.0																																																																																																		
Overhead Glazing U =	0.500	0	0.0		0	0.0																																																																																																		
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7																																																																																																		
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0																																																																																																		
Wall (above grade) U =	0.056	1,207	67.6	0.054	1,207	65.2																																																																																																		
Floors over Crawlspace U =	0.029	0	0.0		0	0.0																																																																																																		
Slab on Grade F =	0.540	134	72.1	0.540	134	72.1																																																																																																		
Below Grade Wall U =	0.042	0	0.0		0	0.0																																																																																																		
Below Grade Slab F =	0.570	0	0.0		0	0.0																																																																																																		
	<b>Baseline UA Total</b>		186.4	<b>Proposed UA Total</b>		184.0																																																																																																		
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5																																																																																																		
				<b>UA Percent Reduction</b>		1.3%																																																																																																		
				<b>UA Reduction</b>		2.4																																																																																																		

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	795	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	3
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80		
2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60		
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25		
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,207	65
<b>Sum of Area and UA</b>									<b>1,207</b>	<b>65</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		134	72
Sum of Perimeter and FP					134	72

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		795 ft2
Conditioned Volume		6,758 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		184
Envelope Heat Load		9,383 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,722 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		13,105 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		13,105 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		16,382 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>	
East Town Crossing, Unit 108	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.26, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>	
What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 765 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,128	63.1	0.054	1,128	60.9
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	126	67.9	0.540	126	67.9
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		177.7	<b>Proposed UA Total</b>		175.5
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		1.3%
				<b>UA Reduction</b>		2.3

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	765	sq. ft
<b>Classification</b>		Small Dwelling Unit
<b>Notes</b>		

City of Payahup  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,128	61
<b>Sum of Area and UA</b>									<b>1,128</b>	<b>61</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		126	68
Sum of Perimeter and FP					126	68

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>	
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>	New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	<a href="#">Prescriptive Checklist Worksheet</a>	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	765 ft2	
Conditioned Volume	6,503 ft3	
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type	Heat Pump	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	175	
Envelope Heat Load	8,949 Btu / Hour	
Sum of UA X ΔT		
Air Leakage Heat Load	3,582 Btu / Hour	
((Volume X 0.6) X ΔT) X .018))		
Building Design Heat Load	12,531 Btu / Hour	
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load	12,531 Btu / Hour	
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output	15,664 Btu / Hour	
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		



<b>Project Information</b>	
East Town Crossing, Unit 201	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.41, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



<b>ANALYSIS SET UP</b>	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 795 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,207	67.6	0.054	1,207	65.2
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		114.3	<b>Proposed UA Total</b>		111.8
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		2.1%
				<b>UA Reduction</b>		2.4

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>		795	sq. ft
<b>Classification</b>		Small Dwelling Unit	
<b>Notes</b>			



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
									-	-	
1	2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
2	3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
3	4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>	
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>	
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>	

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,207	65
<b>Sum of Area and UA</b>									<b>1,207</b>	<b>65</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F			Slab Perim	FP
<b>Sum of Perimeter and FP</b>						<b>0</b>	<b>0</b>

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
<b>Sum of Area, Length and UA</b>				<b>0</b>	<b>0.0</b>	<b>0</b>	<b>0</b>	<b>0</b>

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>	
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>	New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	<a href="#">Prescriptive Checklist Worksheet</a>	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltinw.com/resources/hvac-sizing-tool">https://betterbuiltinw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	795 ft2	
Conditioned Volume	6,758 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	Heat Pump	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	112	
Envelope Heat Load	5,704 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	3,722 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X 0.18))</small>		
Building Design Heat Load	9,426 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	9,426 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	11,782 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>
East Town Crossing, Unit 202 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.26, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 765 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>																																																																																																								
<table border="1"> <thead> <tr> <th rowspan="2">Component Performance, R occupancies</th> <th colspan="3">Baseline</th> <th colspan="3">Proposed Design</th> </tr> <tr> <th>U</th> <th>Area</th> <th>UA</th> <th>U</th> <th>Area</th> <th>UA</th> </tr> </thead> <tbody> <tr> <td>Doors U =</td> <td>0.300</td> <td>40</td> <td>12.0</td> <td>0.300</td> <td>40</td> <td>12.0</td> </tr> <tr> <td>Overhead Glazing U =</td> <td>0.500</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Vertical Glazing U =</td> <td>0.300</td> <td>116</td> <td>34.7</td> <td>0.300</td> <td>116</td> <td>34.7</td> </tr> <tr> <td>Flat/Vaulted Ceilings U =</td> <td>0.027</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Wall (above grade) U =</td> <td>0.056</td> <td>1,128</td> <td>63.1</td> <td>0.054</td> <td>1,128</td> <td>60.9</td> </tr> <tr> <td>Floors over Crawlspace U =</td> <td>0.029</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Slab on Grade F =</td> <td>0.540</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Wall U =</td> <td>0.042</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Slab F =</td> <td>0.570</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td><b>Baseline UA Total</b></td> <td></td> <td></td> <td>109.8</td> <td><b>Proposed UA Total</b></td> <td></td> <td>107.5</td> </tr> <tr> <td><b>Required Credits</b></td> <td></td> <td></td> <td>4.5</td> <td><b>Proposed Credits</b></td> <td>6.5</td> <td>from Tables 406.2 and 406.3</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td><b>UA Percent Reduction</b></td> <td>2.1%</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td><b>UA Reduction</b></td> <td>2.3</td> <td></td> </tr> </tbody> </table> <p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>	Component Performance, R occupancies	Baseline			Proposed Design			U	Area	UA	U	Area	UA	Doors U =	0.300	40	12.0	0.300	40	12.0	Overhead Glazing U =	0.500	0	0.0		0	0.0	Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7	Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0	Wall (above grade) U =	0.056	1,128	63.1	0.054	1,128	60.9	Floors over Crawlspace U =	0.029	0	0.0		0	0.0	Slab on Grade F =	0.540	0	0.0		0	0.0	Below Grade Wall U =	0.042	0	0.0		0	0.0	Below Grade Slab F =	0.570	0	0.0		0	0.0	<b>Baseline UA Total</b>			109.8	<b>Proposed UA Total</b>		107.5	<b>Required Credits</b>			4.5	<b>Proposed Credits</b>	6.5	from Tables 406.2 and 406.3					<b>UA Percent Reduction</b>	2.1%						<b>UA Reduction</b>	2.3	
Component Performance, R occupancies		Baseline			Proposed Design																																																																																																			
	U	Area	UA	U	Area	UA																																																																																																		
Doors U =	0.300	40	12.0	0.300	40	12.0																																																																																																		
Overhead Glazing U =	0.500	0	0.0		0	0.0																																																																																																		
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7																																																																																																		
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0																																																																																																		
Wall (above grade) U =	0.056	1,128	63.1	0.054	1,128	60.9																																																																																																		
Floors over Crawlspace U =	0.029	0	0.0		0	0.0																																																																																																		
Slab on Grade F =	0.540	0	0.0		0	0.0																																																																																																		
Below Grade Wall U =	0.042	0	0.0		0	0.0																																																																																																		
Below Grade Slab F =	0.570	0	0.0		0	0.0																																																																																																		
<b>Baseline UA Total</b>			109.8	<b>Proposed UA Total</b>		107.5																																																																																																		
<b>Required Credits</b>			4.5	<b>Proposed Credits</b>	6.5	from Tables 406.2 and 406.3																																																																																																		
				<b>UA Percent Reduction</b>	2.1%																																																																																																			
				<b>UA Reduction</b>	2.3																																																																																																			

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>				
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*
1	Efficient Building Envelope		0.0	
2	Air Leakage Control and Efficient Ventilation		0.0	
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas
4	High Efficiency HVAC Distribution System		NA	
5.1	Efficient Water Heating		0.0	
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater
6	Renewable Electric Energy		0.0	
7	Appliance Package		0.0	
<b>Energy Credits</b>			<b>5.5</b>	

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	765	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payson  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
			-						-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60	
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>	
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>	
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>	

Flat/Vaulted Ceilings							
Plan ID	Component Description	Ref.	Attic U			Area	UA
	No ceiling/roof in thermal envelope	NA	-				0.0
<b>Sum of Area and UA</b>						<b>0</b>	<b>0.0</b>

Walls (Above Grade)							
Plan ID	Component Description	Ref.	Wall U			Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054			1,128	61
<b>Sum of Area and UA</b>						<b>1,128</b>	<b>61</b>

Floor (over crawl or exterior)							
Plan ID	Component Description	Ref.	Floor U			Area	UA
	No floors in thermal envelope	NA	-				0
<b>Sum of Area and UA</b>						<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		765 ft2
Conditioned Volume		6,503 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		108
Envelope Heat Load		5,485 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,582 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		9,066 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		9,066 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		11,333 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>	
East Town Crossing, Unit 203	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.17, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 45 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



<b>ANALYSIS SET UP</b>	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 628 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,083	60.6	0.054	1,083	58.5
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		87.0	Proposed UA Total		84.9
	Required Credits		4.5	Proposed Credits		6.5
				UA Percent Reduction		2.5%
				UA Reduction		2.2
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0		
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	628	sq. ft
<b>Classification</b>	Small Dwelling Unit	
<b>Notes</b>		

City of Payson  
Development & Permitting Services  
**ISSUED PERMIT**

Building Planning  
Engineering Public Works  
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
2	6	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	0	6	0	24.0	7.20	
<b>Sum of Area and UA</b>									<b>48.0</b>	<b>14.4</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,083	58
<b>Sum of Area and UA</b>									<b>1,083</b>	<b>58</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	





Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	1		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	45 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required?	No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		628 ft2
Conditioned Volume		5,338 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		85
Envelope Heat Load		4,329 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		2,940 Btu / Hour
<small>((Volume X 0.6) X ΔT) X 0.018)</small>		
Building Design Heat Load		7,269 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		7,269 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		9,086 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>
East Town Crossing, Unit 204 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.29, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

**ANALYSIS SET UP**

What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 732 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

**RESULTS - Comparison of Baseline and Proposed Design**

Component Performance, R occupancies	Baseline			Proposed Design			
	U	Area	UA	U	Area	UA	
Doors U =	0.300	40	12.0	0.300	40	12.0	
Overhead Glazing U =	0.500	0	0.0		0	0.0	
Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9	
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0	
Wall (above grade) U =	0.056	1,144	64.1	0.054	1,144	61.8	
Floors over Crawlspace U =	0.029	0	0.0		0	0.0	
Slab on Grade F =	0.540	0	0.0		0	0.0	
Below Grade Wall U =	0.042	0	0.0		0	0.0	
Below Grade Slab F =	0.570	0	0.0		0	0.0	
<b>Baseline UA Total</b>			<b>95.0</b>	<b>Proposed UA Total</b>			<b>92.7</b>
<b>Required Credits</b>			<b>4.5</b>	<b>Proposed Credits</b>			<b>6.5</b>
				<b>UA Percent Reduction</b>			<b>2.4%</b>
				<b>UA Reduction</b>			<b>2.3</b>

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	732	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	5	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	6	0	15.0	4.50	
<b>Sum of Area and UA</b>									<b>63.0</b>	<b>18.9</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,144	62
<b>Sum of Area and UA</b>									<b>1,144</b>	<b>62</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	55 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		732 ft2
Conditioned Volume		6,222 ft3
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		93
Envelope Heat Load		4,728 Btu / Hour
Sum of UA X ΔT		
Air Leakage Heat Load		3,427 Btu / Hour
((Volume X 0.6) X ΔT) X 0.18)		
Building Design Heat Load		8,155 Btu / Hour
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load		8,155 Btu / Hour
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output		10,194 Btu / Hour
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		

<b>Project Information</b>
East Town Crossing, Unit 205 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.17, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 45 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 628 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>			<b>Proposed Design</b>			
	<b>U</b>	<b>Area</b>	<b>UA</b>	<b>U</b>	<b>Area</b>	<b>UA</b>
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,083	60.6	0.054	1,083	58.5
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		87.0	<b>Proposed UA Total</b>		84.9
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b> 2.5%		
				<b>UA Reduction</b> 2.2		
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0		
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	628	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payson  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule										
										Rows to Show
2										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	0	6	0	24.0	7.20
<b>Sum of Area and UA</b>									<b>48.0</b>	<b>14.4</b>
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,083	58
<b>Sum of Area and UA</b>									<b>1,083</b>	<b>58</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	1		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	45 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required?	No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		Existing Construction <a href="#">Affidavit, Existing</a> New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		628 ft2
Conditioned Volume		5,338 ft3
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		85
Envelope Heat Load		4,329 Btu / Hour
Sum of UA X ΔT		
Air Leakage Heat Load		2,940 Btu / Hour
((Volume X 0.6) X ΔT) X 0.018)		
Building Design Heat Load		7,269 Btu / Hour
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load		7,269 Btu / Hour
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output		9,086 Btu / Hour
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		

<b>Project Information</b>	
East Town Crossing, Unit 206	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.29, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



<b>ANALYSIS SET UP</b>	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 732 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Baseline		Proposed Design	
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,144	64.1	0.054	1,144	61.8
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		95.0	<b>Proposed UA Total</b>		92.7
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		2.4%
				<b>UA Reduction</b>		2.3
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**



<b>Conditioned Floor Area, Proposed Design</b>	732	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	5	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	6	0	15.0	4.50	
<b>Sum of Area and UA</b>									<b>63.0</b>	<b>18.9</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,144	62
<b>Sum of Area and UA</b>									<b>1,144</b>	<b>62</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced		Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed		Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	55	CFM	

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required?	No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		Existing Construction <a href="#">Affidavit, Existing</a> New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>	
Nearest Weather Station		Puyallup	
Indoor Design Temperature		70	F
Outdoor Design Temperature		19	F
Design Temperature Difference (ΔT)		51	F
Conditioned Floor Area, Proposed Design		732	ft2
Conditioned Volume		6,222	ft3
Leave blank to use default of 8.5 ft. ceiling height			
HVAC System Type		Heat Pump	
Location of HVAC Distribution System		Unducted	
Sum of UA, including exempt door and window		93	
Envelope Heat Load		4,728	Btu / Hour
Sum of UA X ΔT			
Air Leakage Heat Load		3,427	Btu / Hour
((Volume X 0.6) X ΔT) X 0.18)			
Building Design Heat Load		8,155	Btu / Hour
Air Leakage + Envelope Heat Loss			
Building and Duct Heat Load		8,155	Btu / Hour
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1			
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1			
Maximum Heat Equipment Output		10,194	Btu / Hour
Building and Duct Heat Loss X 1.25 for heat pumps			
Building and Duct Heat Loss X 1.40 for all other systems			

<b>Project Information</b>	
East Town Crossing, Unit 207	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.41, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



**ANALYSIS SET UP**

What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 795 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

**RESULTS - Comparison of Baseline and Proposed Design**

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,207	67.6	0.054	1,207	65.2
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
<b>Baseline UA Total</b>			<b>114.3</b>			<b>111.8</b>
<b>Required Credits</b>			<b>4.5</b>			<b>6.5</b>
				<b>Proposed Credits</b>		<b>6.5</b>
				<b>UA Percent Reduction</b>		<b>2.1%</b>
				<b>UA Reduction</b>		<b>2.4</b>

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	<b>Heat Pump, air-to-air or air to water</b>	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	<b>Option 3.6</b>	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	<b>Option 5.5</b>	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	795	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									40	12.0
<b>Exterior Doors Area Weighted U</b>									<b>0.300</b>	

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									0	0
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule										Rows to Show	3
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt			-						-	-	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60	
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25	
<b>Sum of Area and UA</b>									115.5	34.7	
<b>Vertical Glazing Area Weighted U</b>									<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>									<b>0.300</b>		

Flat/Vaulted Ceilings								
Plan ID	Component Description	Ref.	Attic U				Area	UA
	No ceiling/roof in thermal envelope	NA	-					0.0
<b>Sum of Area and UA</b>							0	0.0

Walls (Above Grade)								
Plan ID	Component Description	Ref.	Wall U				Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054				1,207	65
<b>Sum of Area and UA</b>							1,207	65

Floor (over crawl or exterior)								
Plan ID	Component Description	Ref.	Floor U				Area	UA
	No floors in thermal envelope	NA	-					0
<b>Sum of Area and UA</b>							0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		795 ft2
Conditioned Volume		6,758 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		112
Envelope Heat Load		5,704 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,722 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		9,426 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		9,426 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		11,782 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>	
East Town Crossing, Unit 208	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.26, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



<b>ANALYSIS SET UP</b>	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 764 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,128	63.1	0.054	1,128	60.9
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		109.8	<b>Proposed UA Total</b>		107.5
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		2.1%
				<b>UA Reduction</b>		2.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	764	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payson  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0.0</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,128	61
<b>Sum of Area and UA</b>									<b>1,128</b>	<b>61</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F			Slab Perim	FP
	No slab on grade	NA	-				0
Sum of Perimeter and FP						0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		764 ft2
Conditioned Volume		6,494 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		108
Envelope Heat Load		5,485 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,577 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		9,062 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		9,062 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		11,327 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		



<b>Project Information</b>
East Town Crossing, Unit 301 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.12, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 795 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>			<b>Proposed Design</b>			
	<b>U</b>	<b>Area</b>	<b>UA</b>	<b>U</b>	<b>Area</b>	<b>UA</b>
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	795	21.5	0.027	795	21.5
Wall (above grade) U =	0.056	1,060	59.4	0.054	1,060	57.3
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		127.5	<b>Proposed UA Total</b>		125.4
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		1.7%
				<b>UA Reduction</b>		2.1
<p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	795	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payalup  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule												
										Rows to Show		
										3		
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
									-	-		
1	2		U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
2	3		U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
3	4		U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027							795	21.5
<b>Sum of Area and UA</b>									<b>795</b>	<b>21.5</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,060	57
<b>Sum of Area and UA</b>									<b>1,060</b>	<b>57</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>	
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>	New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	<a href="#">Prescriptive Checklist Worksheet</a>	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	795 ft2	
Conditioned Volume	6,758 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	Heat Pump	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	125	
Envelope Heat Load	6,394 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	3,722 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load	10,116 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	10,116 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	12,645 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>
East Town Crossing, Unit 302 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 1.98, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

**ANALYSIS SET UP**

What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 765 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

**RESULTS - Comparison of Baseline and Proposed Design**

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	765	20.7	0.027	765	20.7
Wall (above grade) U =	0.056	989	55.4	0.054	989	53.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
<b>Baseline UA Total</b>			122.7	<b>Proposed UA Total</b>		120.7
<b>Required Credits</b>			4.5	<b>Proposed Credits</b>	6.5	from Tables 406.2 and 406.3
				<b>UA Percent Reduction</b>	1.6%	
				<b>UA Reduction</b>	2.0	

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	765	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payson  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule										
										Rows to Show
										3
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
			-						-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027							765	20.7
<b>Sum of Area and UA</b>									<b>765</b>	<b>20.7</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							989	53
<b>Sum of Area and UA</b>									<b>989</b>	<b>53</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		Existing Construction <a href="#">Affidavit, Existing</a> New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet		<a href="#">Prescriptive Checklist</a> <a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		765 ft2
Conditioned Volume		6,503 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		121
Envelope Heat Load		6,157 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		3,582 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		9,739 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		9,739 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		12,173 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>	
East Town Crossing, Unit 303	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 1.91, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 45 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



**ANALYSIS SET UP**

What code compliance pathway are you using?	<b>Prescriptive Path Compliance with Option 1 (preferred)</b>
Project Building Type?	<b>New Construction</b>
Occupancy Type?	<b>R2 Multifamily</b>
Code Version?	<b>WSEC 2018</b>
Classification:	Small Dwelling Unit -- 628 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

**RESULTS - Comparison of Baseline and Proposed Design**

Component Performance, R occupancies	Baseline			Proposed Design			
	U	Area	UA	U	Area	UA	
Doors U =	0.300	40	12.0	0.300	40	12.0	
Overhead Glazing U =	0.500	0	0.0		0	0.0	
Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4	
Flat/Vaulted Ceilings U =	0.027	628	17.0	0.027	628	17.0	
Wall (above grade) U =	0.056	957	53.6	0.054	957	51.7	
Floors over Crawlspace U =	0.029	0	0.0		0	0.0	
Slab on Grade F =	0.540	0	0.0		0	0.0	
Below Grade Wall U =	0.042	0	0.0		0	0.0	
Below Grade Slab F =	0.570	0	0.0		0	0.0	
<b>Baseline UA Total</b>			<b>96.9</b>	<b>Proposed UA Total</b>			<b>95.0</b>
<b>Required Credits</b>			<b>4.5</b>	<b>Proposed Credits</b>			<b>6.5</b> from Tables 406.2 and 406.3
				<b>UA Percent Reduction</b>			<b>2.0%</b>
				<b>UA Reduction</b>			<b>1.9</b>

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.


Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	<b>Heat Pump, air-to-air or air to water</b>	1.0	5.5	6.5

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	<b>Option 3.6</b>	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	<b>Option 5.5</b>	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	628	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
					Feet	Inch	Feet	Inch				
Exempt			-						-	-		
1	3 U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20		
2	6 U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	0	6	0	24.0	7.20		
Sum of Area and UA									48.0	14.4		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						628	17.0
Sum of Area and UA									628	17.0

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						957	52
Sum of Area and UA									957	52

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
Sum of Area and UA									0	0





Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	1		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	45 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required?	No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		628 ft2
Conditioned Volume		5,338 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		95
Envelope Heat Load		4,846 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		2,940 Btu / Hour
<small>((Volume X 0.6) X ΔT) X 0.018)</small>		
Building Design Heat Load		7,786 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		7,786 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		9,733 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

<b>Project Information</b>	
East Town Crossing, Unit 304	
Building G	
Pioneer & Shaw, Puyallup	
<b>Contact Information</b>	
Synthesis 9, LLC	
Brett Lindsay	
<a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a>	
253-468-4117	

<b>Messages / Results *</b>	
UA Reduction = 2.02, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



<b>ANALYSIS SET UP</b>	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 732 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>			<b>Proposed Design</b>			
		<b>Baseline</b>		<b>U</b>	<b>Area</b>	<b>UA</b>
		<b>U</b>	<b>Area</b>			
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9
Flat/Vaulted Ceilings U =	0.027	732	19.8	0.027	732	19.8
Wall (above grade) U =	0.056	1,010	56.6	0.054	1,010	54.5
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
		<b>Baseline UA Total</b>	107.2		<b>Proposed UA Total</b>	105.2
		<b>Required Credits</b>	4.5		<b>Proposed Credits</b>	6.5 from Tables 406.2 and 406.3
				<b>UA Percent Reduction</b>		1.9%
				<b>UA Reduction</b>		2.0
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0		kWh
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	732	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	5	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	6	0	15.0	4.50	
<b>Sum of Area and UA</b>									<b>63.0</b>	<b>18.9</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						732	19.8
<b>Sum of Area and UA</b>									<b>732</b>	<b>19.8</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,010	55
<b>Sum of Area and UA</b>									<b>1,010</b>	<b>55</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	55 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>
Duct Testing Affidavits		
	Existing Construction	<a href="#">Affidavit, Existing</a>
	New Construction	<a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		732 ft2
Conditioned Volume		6,222 ft3
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type		Heat Pump
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		105
Envelope Heat Load		5,365 Btu / Hour
Sum of UA X ΔT		
Air Leakage Heat Load		3,427 Btu / Hour
((Volume X 0.6) X ΔT) X 0.18)		
Building Design Heat Load		8,792 Btu / Hour
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load		8,792 Btu / Hour
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output		10,990 Btu / Hour
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		

<b>Project Information</b>
East Town Crossing, Unit 305 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>City of Puyallup Development &amp; Permitting Services <b>ISSUED PERMIT</b></p> <p>Building Planning Engineering Public Works Fire Traffic</p> <p>UA Reduction = 1.91, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 45 CFM with Run Time Percent of 100%, Balanced, Distributed</p>

\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 628 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>																																																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Component Performance, R occupancies</th> <th colspan="3">Baseline</th> <th colspan="3">Proposed Design</th> </tr> <tr> <th>U</th> <th>Area</th> <th>UA</th> <th>U</th> <th>Area</th> <th>UA</th> </tr> </thead> <tbody> <tr> <td>Doors U =</td> <td>0.300</td> <td>40</td> <td>12.0</td> <td>0.300</td> <td>40</td> <td>12.0</td> </tr> <tr> <td>Overhead Glazing U =</td> <td>0.500</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Vertical Glazing U =</td> <td>0.300</td> <td>48</td> <td>14.4</td> <td>0.300</td> <td>48</td> <td>14.4</td> </tr> <tr> <td>Flat/Vaulted Ceilings U =</td> <td>0.027</td> <td>628</td> <td>17.0</td> <td>0.027</td> <td>628</td> <td>17.0</td> </tr> <tr> <td>Wall (above grade) U =</td> <td>0.056</td> <td>957</td> <td>53.6</td> <td>0.054</td> <td>957</td> <td>51.7</td> </tr> <tr> <td>Floors over Crawlspace U =</td> <td>0.029</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Slab on Grade F =</td> <td>0.540</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Wall U =</td> <td>0.042</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Slab F =</td> <td>0.570</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td><b>Baseline UA Total</b></td> <td colspan="2"></td> <td>96.9</td> <td><b>Proposed UA Total</b></td> <td colspan="2"></td> <td>95.0</td> </tr> <tr> <td><b>Required Credits</b></td> <td colspan="2"></td> <td>4.5</td> <td><b>Proposed Credits</b></td> <td colspan="2"></td> <td>6.5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td><b>UA Percent Reduction</b></td> <td colspan="2"></td> <td>2.0%</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td><b>UA Reduction</b></td> <td colspan="2"></td> <td>1.9</td> </tr> </tbody> </table> <p>from Tables 406.2 and 406.3</p> <p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>	Component Performance, R occupancies	Baseline			Proposed Design			U	Area	UA	U	Area	UA	Doors U =	0.300	40	12.0	0.300	40	12.0	Overhead Glazing U =	0.500	0	0.0		0	0.0	Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4	Flat/Vaulted Ceilings U =	0.027	628	17.0	0.027	628	17.0	Wall (above grade) U =	0.056	957	53.6	0.054	957	51.7	Floors over Crawlspace U =	0.029	0	0.0		0	0.0	Slab on Grade F =	0.540	0	0.0		0	0.0	Below Grade Wall U =	0.042	0	0.0		0	0.0	Below Grade Slab F =	0.570	0	0.0		0	0.0	<b>Baseline UA Total</b>			96.9	<b>Proposed UA Total</b>			95.0	<b>Required Credits</b>			4.5	<b>Proposed Credits</b>			6.5					<b>UA Percent Reduction</b>			2.0%					<b>UA Reduction</b>			1.9
Component Performance, R occupancies		Baseline			Proposed Design																																																																																																							
	U	Area	UA	U	Area	UA																																																																																																						
Doors U =	0.300	40	12.0	0.300	40	12.0																																																																																																						
Overhead Glazing U =	0.500	0	0.0		0	0.0																																																																																																						
Vertical Glazing U =	0.300	48	14.4	0.300	48	14.4																																																																																																						
Flat/Vaulted Ceilings U =	0.027	628	17.0	0.027	628	17.0																																																																																																						
Wall (above grade) U =	0.056	957	53.6	0.054	957	51.7																																																																																																						
Floors over Crawlspace U =	0.029	0	0.0		0	0.0																																																																																																						
Slab on Grade F =	0.540	0	0.0		0	0.0																																																																																																						
Below Grade Wall U =	0.042	0	0.0		0	0.0																																																																																																						
Below Grade Slab F =	0.570	0	0.0		0	0.0																																																																																																						
<b>Baseline UA Total</b>			96.9	<b>Proposed UA Total</b>			95.0																																																																																																					
<b>Required Credits</b>			4.5	<b>Proposed Credits</b>			6.5																																																																																																					
				<b>UA Percent Reduction</b>			2.0%																																																																																																					
				<b>UA Reduction</b>			1.9																																																																																																					

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>				
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*
1	Efficient Building Envelope		0.0	
2	Air Leakage Control and Efficient Ventilation		0.0	
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas
4	High Efficiency HVAC Distribution System		NA	
5.1	Efficient Water Heating		0.0	
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater
6	Renewable Electric Energy		0.0	
7	Appliance Package		0.0	
<b>Energy Credits</b>			<b>5.5</b>	

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>		628	sq. ft
<b>Classification</b>		Small Dwelling Unit	
<b>Notes</b>			

City of Payalup  
Development & Permitting Services  
**ISSUED PERMIT**

Building Planning  
Engineering Public Works  
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	2
2	6	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	0	6	0	24.0	7.20	
<b>Sum of Area and UA</b>									<b>48.0</b>	<b>14.4</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						628	17.0
<b>Sum of Area and UA</b>									<b>628</b>	<b>17.0</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						957	52
<b>Sum of Area and UA</b>									<b>957</b>	<b>52</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	1		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	45 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required?	No		

Links to Download Forms, Checklists and Other Resources		Link	
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>	
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>		
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a>		
	New Construction <a href="#">Affidavit, New</a>		
Prescriptive Checklist for 2018 WSEC	<a href="#">Prescriptive Checklist</a>		
Alterations (Remodel) Worksheet	<a href="#">Worksheet</a>		

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>	
Nearest Weather Station	Puyallup		
Indoor Design Temperature	70 F		
Outdoor Design Temperature	19 F		
Design Temperature Difference (ΔT)	51 F		
Conditioned Floor Area, Proposed Design	628 ft2		
Conditioned Volume	5,338 ft3		
<small>Leave blank to use default of 8.5 ft. ceiling height</small>			
HVAC System Type	Heat Pump		
Location of HVAC Distribution System	Unducted		
Sum of UA, including exempt door and window	95		
Envelope Heat Load	4,846 Btu / Hour		
<small>Sum of UA X ΔT</small>			
Air Leakage Heat Load	2,940 Btu / Hour		
<small>((Volume X 0.6) X ΔT) X 0.018)</small>			
Building Design Heat Load	7,786 Btu / Hour		
<small>Air Leakage + Envelope Heat Loss</small>			
Building and Duct Heat Load	7,786 Btu / Hour		
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>			
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>			
Maximum Heat Equipment Output	9,733 Btu / Hour		
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>			
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>			

<b>Project Information</b>
East Town Crossing, Unit 306 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.02, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 732 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>																																																																																																								
<table border="1"> <thead> <tr> <th rowspan="2">Component Performance, R occupancies</th> <th colspan="3">Baseline</th> <th colspan="3">Proposed Design</th> </tr> <tr> <th>U</th> <th>Area</th> <th>UA</th> <th>U</th> <th>Area</th> <th>UA</th> </tr> </thead> <tbody> <tr> <td>Doors U =</td> <td>0.300</td> <td>40</td> <td>12.0</td> <td>0.300</td> <td>40</td> <td>12.0</td> </tr> <tr> <td>Overhead Glazing U =</td> <td>0.500</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Vertical Glazing U =</td> <td>0.300</td> <td>63</td> <td>18.9</td> <td>0.300</td> <td>63</td> <td>18.9</td> </tr> <tr> <td>Flat/Vaulted Ceilings U =</td> <td>0.027</td> <td>732</td> <td>19.8</td> <td>0.027</td> <td>732</td> <td>19.8</td> </tr> <tr> <td>Wall (above grade) U =</td> <td>0.056</td> <td>1,010</td> <td>56.6</td> <td>0.054</td> <td>1,010</td> <td>54.5</td> </tr> <tr> <td>Floors over Crawlspace U =</td> <td>0.029</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Slab on Grade F =</td> <td>0.540</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Wall U =</td> <td>0.042</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Slab F =</td> <td>0.570</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td></td> <td colspan="2"><b>Baseline UA Total</b></td> <td>107.2</td> <td colspan="2"><b>Proposed UA Total</b></td> <td>105.2</td> </tr> <tr> <td></td> <td colspan="2"><b>Required Credits</b></td> <td>4.5</td> <td colspan="2"><b>Proposed Credits</b></td> <td>6.5</td> </tr> <tr> <td></td> <td colspan="2"></td> <td></td> <td colspan="2"><b>UA Percent Reduction</b></td> <td>1.9%</td> </tr> <tr> <td></td> <td colspan="2"></td> <td></td> <td colspan="2"><b>UA Reduction</b></td> <td>2.0</td> </tr> </tbody> </table> <p>from Tables 406.2 and 406.3</p> <p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>	Component Performance, R occupancies	Baseline			Proposed Design			U	Area	UA	U	Area	UA	Doors U =	0.300	40	12.0	0.300	40	12.0	Overhead Glazing U =	0.500	0	0.0		0	0.0	Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9	Flat/Vaulted Ceilings U =	0.027	732	19.8	0.027	732	19.8	Wall (above grade) U =	0.056	1,010	56.6	0.054	1,010	54.5	Floors over Crawlspace U =	0.029	0	0.0		0	0.0	Slab on Grade F =	0.540	0	0.0		0	0.0	Below Grade Wall U =	0.042	0	0.0		0	0.0	Below Grade Slab F =	0.570	0	0.0		0	0.0		<b>Baseline UA Total</b>		107.2	<b>Proposed UA Total</b>		105.2		<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5					<b>UA Percent Reduction</b>		1.9%					<b>UA Reduction</b>		2.0
Component Performance, R occupancies		Baseline			Proposed Design																																																																																																			
	U	Area	UA	U	Area	UA																																																																																																		
Doors U =	0.300	40	12.0	0.300	40	12.0																																																																																																		
Overhead Glazing U =	0.500	0	0.0		0	0.0																																																																																																		
Vertical Glazing U =	0.300	63	18.9	0.300	63	18.9																																																																																																		
Flat/Vaulted Ceilings U =	0.027	732	19.8	0.027	732	19.8																																																																																																		
Wall (above grade) U =	0.056	1,010	56.6	0.054	1,010	54.5																																																																																																		
Floors over Crawlspace U =	0.029	0	0.0		0	0.0																																																																																																		
Slab on Grade F =	0.540	0	0.0		0	0.0																																																																																																		
Below Grade Wall U =	0.042	0	0.0		0	0.0																																																																																																		
Below Grade Slab F =	0.570	0	0.0		0	0.0																																																																																																		
	<b>Baseline UA Total</b>		107.2	<b>Proposed UA Total</b>		105.2																																																																																																		
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5																																																																																																		
				<b>UA Percent Reduction</b>		1.9%																																																																																																		
				<b>UA Reduction</b>		2.0																																																																																																		

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>				
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*
1	Efficient Building Envelope		0.0	
2	Air Leakage Control and Efficient Ventilation		0.0	
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas
4	High Efficiency HVAC Distribution System		NA	
5.1	Efficient Water Heating		0.0	
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater
6	Renewable Electric Energy		0.0	
7	Appliance Package		0.0	
<b>Energy Credits</b>			<b>5.5</b>	

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**



<b>Conditioned Floor Area, Proposed Design</b>	732	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payalshup  
Development & Permitting Services  
**ISSUED PERMIT**

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											
										Rows to Show	
2											
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
									-	-	
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40
2	5	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	6	0	15.0	4.50
<b>Sum of Area and UA</b>									<b>63.0</b>	<b>18.9</b>	
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>	
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>	

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027							732	19.8
<b>Sum of Area and UA</b>									<b>732</b>	<b>19.8</b>	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,010	55
<b>Sum of Area and UA</b>									<b>1,010</b>	<b>55</b>	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>	



Slab on Grade (less than 2 feet below grade)							
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP	
	No slab on grade	NA	-			0	
Sum of Perimeter and FP					0	0	

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'	
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'	
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	55 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Conditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link	
Compliance Certificate		<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>
Insulation Certificate for Residential New Construction		<a href="#">Insulation Certificate</a>	
Duct Testing Affidavits		Existing Construction <a href="#">Affidavit, Existing</a>	
		New Construction <a href="#">Affidavit, New</a>	
Prescriptive Checklist for 2018 WSEC		<a href="#">Prescriptive Checklist</a>	
Alterations (Remodel) Worksheet		<a href="#">Worksheet</a>	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>	
Nearest Weather Station		Puyallup	
Indoor Design Temperature		70 F	
Outdoor Design Temperature		19 F	
Design Temperature Difference (ΔT)		51 F	
Conditioned Floor Area, Proposed Design		732 ft2	
Conditioned Volume		6,222 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>			
HVAC System Type		Heat Pump	
Location of HVAC Distribution System		Unducted	
Sum of UA, including exempt door and window		105	
Envelope Heat Load		5,365 Btu / Hour	
<small>Sum of UA X ΔT</small>			
Air Leakage Heat Load		3,427 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X 0.18)</small>			
Building Design Heat Load		8,792 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>			
Building and Duct Heat Load		8,792 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>			
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>			
Maximum Heat Equipment Output		10,990 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>			
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>			

<b>Project Information</b>
East Town Crossing, Unit 307 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 2.12, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 795 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>			<b>Proposed Design</b>			
	<b>U</b>	<b>Area</b>	<b>UA</b>	<b>U</b>	<b>Area</b>	<b>UA</b>
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	795	21.5	0.027	795	21.5
Wall (above grade) U =	0.056	1,060	59.4	0.054	1,060	57.3
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		127.5	<b>Proposed UA Total</b>		125.4
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		1.7%
				<b>UA Reduction</b>		2.1
<p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	795	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payson  
 Development & Permitting Services  
**ISSUED PERMIT**  
 Building Planning  
 Engineering Public Works  
 Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule											Rows to Show	3
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80		
2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60		
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25		
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>		
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>		
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						795	21.5
<b>Sum of Area and UA</b>									<b>795</b>	<b>21.5</b>

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,060	57
<b>Sum of Area and UA</b>									<b>1,060</b>	<b>57</b>

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	<a href="#">Compliance Certificate</a> <a href="#">Instructions</a>
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a> New Construction <a href="#">Affidavit, New</a>
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	<a href="#">Prescriptive Checklist</a> <a href="#">Worksheet</a>

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	795 ft2	
Conditioned Volume	6,758 ft3	
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type	Heat Pump	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	125	
Envelope Heat Load	6,394 Btu / Hour	
Sum of UA X ΔT		
Air Leakage Heat Load	3,722 Btu / Hour	
((Volume X 0.6) X ΔT) X .018))		
Building Design Heat Load	10,116 Btu / Hour	
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load	10,116 Btu / Hour	
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1 For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output	12,645 Btu / Hour	
Building and Duct Heat Loss X 1.25 for heat pumps Building and Duct Heat Loss X 1.40 for all other systems		

<b>Project Information</b>
East Town Crossing, Unit 308 Building G Pioneer & Shaw, Puyallup
<b>Contact Information</b>
Synthesis 9, LLC Brett Lindsay <a href="mailto:blindsay@synthesis9.com">blindsay@synthesis9.com</a> 253-468-4117

<b>Messages / Results *</b>
<p>UA Reduction = 1.98, Proposed UA is better than baseline by 2%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed</p>



\* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

<b>ANALYSIS SET UP</b>
<p>What code compliance pathway are you using? <b>Prescriptive Path Compliance with Option 1 (preferred)</b></p> <p>Project Building Type? <b>New Construction</b></p> <p>Occupancy Type? <b>R2 Multifamily</b></p> <p>Code Version? <b>WSEC 2018</b></p> <p>Classification: Small Dwelling Unit -- 764 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

<b>RESULTS - Comparison of Baseline and Proposed Design</b>						
<b>Component Performance, R occupancies</b>						
	<b>Baseline</b>			<b>Proposed Design</b>		
	<b>U</b>	<b>Area</b>	<b>UA</b>	<b>U</b>	<b>Area</b>	<b>UA</b>
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	116	34.7	0.300	116	34.7
Flat/Vaulted Ceilings U =	0.027	764	20.6	0.027	764	20.6
Wall (above grade) U =	0.056	989	55.4	0.054	989	53.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	<b>Baseline UA Total</b>		122.7	<b>Proposed UA Total</b>		120.7
	<b>Required Credits</b>		4.5	<b>Proposed Credits</b>		6.5
				<b>UA Percent Reduction</b>		1.6%
				<b>UA Reduction</b>		2.0
<p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>						

<b>Table R406.2 Fuel Normalization Credits</b>					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
2	For an initial heating system using a heat pump that meets federal standards for the equipment listed in Table C403.3.2(1)C or C403.3.2(2) OR Air to water heat pump units that are configured to provide both heating and cooling and are rated in accordance with AHRI 550/590. Heat pump with electric resistance or fossil-fuel supplemental heat requires compliance with WSEC 403.1.2 "Heat Pump Supplementary Heat". Packaged Terminal Heat Pumps (PTAC-HP) requires an HSPF tested value (See SBC Interpretation dated December 2020).	Heat Pump, air-to-air or air to water	1.0	5.5	6.5

<b>Table R406.3 Energy Credits</b>					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation		0.0		
3	High Efficiency HVAC	Option 3.6	3.0	Ductless Split System with no electric resistance in primary living areas	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
<b>Energy Credits</b>			<b>5.5</b>		

\*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

**THERMAL ENVELOPE DETAILS - Proposed Design**

<b>Conditioned Floor Area, Proposed Design</b>	764	sq. ft
<b>Classification</b> Small Dwelling Unit		
<b>Notes</b>		

City of Payalshup  
Development & Permitting Services

ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
<b>Sum of Area and UA</b>									<b>40</b>	<b>12.0</b>
<b>Exterior Doors Area Weighted U</b>										<b>0.300</b>

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0
									0	0
									0	0
									0	0
									0	0
<b>Sum of Area and UA</b>									<b>0</b>	<b>0</b>
<b>Overhead Glazing Area Weighted U</b>										

Vertical Glazing Schedule										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
3	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
<b>Sum of Area and UA</b>									<b>115.5</b>	<b>34.7</b>
<b>Vertical Glazing Area Weighted U</b>										<b>0.300</b>
<b>Vertical Glazing and Doors Area Weighted U</b>										<b>0.300</b>

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U	Area	UA					
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027	764	20.6					
<b>Sum of Area and UA</b>				<b>764</b>	<b>20.6</b>					

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U	Net Area	UA					
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	989	53					
<b>Sum of Area and UA</b>				<b>989</b>	<b>53</b>					

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U	Area	UA					
	No floors in thermal envelope	NA	-		0					
<b>Sum of Area and UA</b>				<b>0</b>	<b>0</b>					



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) <a href="http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20">http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20</a>
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Conditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	<a href="#">Compliance Certificate</a>	<a href="#">Instructions</a>
Insulation Certificate for Residential New Construction	<a href="#">Insulation Certificate</a>	
Duct Testing Affidavits	Existing Construction <a href="#">Affidavit, Existing</a> New Construction <a href="#">Affidavit, New</a>	
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	<a href="#">Prescriptive Checklist Worksheet</a>	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: <a href="https://betterbuiltnw.com/resources/hvac-sizing-tool">https://betterbuiltnw.com/resources/hvac-sizing-tool</a>
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	764 ft2	
Conditioned Volume	6,494 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	Heat Pump	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	121	
Envelope Heat Load	6,156 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	3,577 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load	9,733 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	9,733 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	12,166 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		