


Project Information
East Town Crossing, Unit # 101 Building B Pioneer & Shaw, Puyallup
Contact Information
Synthesis 9, LLC Brett Lindsay blindsay@synthesis9.com 253-468-4117

Messages / Results *
 <p>UA Reduction = 2.61, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed</p>

* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

ANALYSIS SET UP
<p>What code compliance pathway are you using? Prescriptive Path Compliance with Option 1 (preferred)</p> <p>Project Building Type? New Construction</p> <p>Occupancy Type? R2 Multifamily</p> <p>Code Version? WSEC 2018</p> <p>Classification: Small Dwelling Unit -- 1109 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>


RESULTS - Comparison of Baseline and Proposed Design																																																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Component Performance, R occupancies</th> <th colspan="3">Baseline</th> <th colspan="3">Proposed Design</th> </tr> <tr> <th>U</th> <th>Area</th> <th>UA</th> <th>U</th> <th>Area</th> <th>UA</th> </tr> </thead> <tbody> <tr> <td>Doors U =</td> <td>0.300</td> <td>40</td> <td>12.0</td> <td>0.300</td> <td>40</td> <td>12.0</td> </tr> <tr> <td>Overhead Glazing U =</td> <td>0.500</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Vertical Glazing U =</td> <td>0.300</td> <td>128</td> <td>38.3</td> <td>0.300</td> <td>128</td> <td>38.3</td> </tr> <tr> <td>Flat/Vaulted Ceilings U =</td> <td>0.027</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Wall (above grade) U =</td> <td>0.056</td> <td>1,307</td> <td>73.2</td> <td>0.054</td> <td>1,307</td> <td>70.6</td> </tr> <tr> <td>Floors over Crawlspace U =</td> <td>0.029</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Slab on Grade F =</td> <td>0.540</td> <td>146</td> <td>78.8</td> <td>0.540</td> <td>146</td> <td>78.8</td> </tr> <tr> <td>Below Grade Wall U =</td> <td>0.042</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Slab F =</td> <td>0.570</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Baseline UA Total</td> <td colspan="2"></td> <td>202.3</td> <td>Proposed UA Total</td> <td colspan="2"></td> <td>199.7</td> </tr> <tr> <td>Required Credits</td> <td colspan="2"></td> <td>4.5</td> <td>Proposed Credits</td> <td colspan="2"></td> <td>6.0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>UA Percent Reduction</td> <td colspan="2"></td> <td>1.3%</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>UA Reduction</td> <td colspan="2"></td> <td>2.6</td> </tr> </tbody> </table> <p>from Tables 406.2 and 406.3</p> <p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>	Component Performance, R occupancies	Baseline			Proposed Design			U	Area	UA	U	Area	UA	Doors U =	0.300	40	12.0	0.300	40	12.0	Overhead Glazing U =	0.500	0	0.0		0	0.0	Vertical Glazing U =	0.300	128	38.3	0.300	128	38.3	Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0	Wall (above grade) U =	0.056	1,307	73.2	0.054	1,307	70.6	Floors over Crawlspace U =	0.029	0	0.0		0	0.0	Slab on Grade F =	0.540	146	78.8	0.540	146	78.8	Below Grade Wall U =	0.042	0	0.0		0	0.0	Below Grade Slab F =	0.570	0	0.0		0	0.0	Baseline UA Total			202.3	Proposed UA Total			199.7	Required Credits			4.5	Proposed Credits			6.0					UA Percent Reduction			1.3%					UA Reduction			2.6
Component Performance, R occupancies		Baseline			Proposed Design																																																																																																							
	U	Area	UA	U	Area	UA																																																																																																						
Doors U =	0.300	40	12.0	0.300	40	12.0																																																																																																						
Overhead Glazing U =	0.500	0	0.0		0	0.0																																																																																																						
Vertical Glazing U =	0.300	128	38.3	0.300	128	38.3																																																																																																						
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0																																																																																																						
Wall (above grade) U =	0.056	1,307	73.2	0.054	1,307	70.6																																																																																																						
Floors over Crawlspace U =	0.029	0	0.0		0	0.0																																																																																																						
Slab on Grade F =	0.540	146	78.8	0.540	146	78.8																																																																																																						
Below Grade Wall U =	0.042	0	0.0		0	0.0																																																																																																						
Below Grade Slab F =	0.570	0	0.0		0	0.0																																																																																																						
Baseline UA Total			202.3	Proposed UA Total			199.7																																																																																																					
Required Credits			4.5	Proposed Credits			6.0																																																																																																					
				UA Percent Reduction			1.3%																																																																																																					
				UA Reduction			2.6																																																																																																					

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design



Conditioned Floor Area, Proposed Design 1,109 sq. ft

Classification Small Dwelling Unit

Notes

Exterior Doors

Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
101A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
101B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule

Rows to Show 4

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	2	0	12.0	3.60
Sum of Area and UA									127.5	38.3
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Flat/Vaulted Ceilings

Plan ID	Component Description	Ref.	Attic U	Area	UA
	No ceiling/roof in thermal envelope	NA	-		0.0
Sum of Area and UA				0	0.0

Walls (Above Grade)

Plan ID	Component Description	Ref.	Wall U	Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,307	71
Sum of Area and UA				1,307	71

Floor (over crawl or exterior)

Plan ID	Component Description	Ref.	Floor U	Area	UA
Sum of Area and UA				0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		146	79
Sum of Perimeter and FP					146	79

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0


Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		1,109 ft2
Conditioned Volume		9,427 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		200
Envelope Heat Load		10,183 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		5,192 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		15,375 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		15,375 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		21,526 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information
East Town Crossing, Unit #102 Building B Pioneer & Shaw, Puyallup
Contact Information
Synthesis 9, LLC Brett Lindsay blindsay@synthesis9.com 253-468-4117

Messages / Results *
<p>City of Puyallup Development & Permitting Services ISSUED PERMIT</p>  <p>UA Reduction = 2.79, Proposed UA is better than baseline by 1%</p> <p>Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed</p>

* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.

ANALYSIS SET UP
<p>What code compliance pathway are you using? Prescriptive Path Compliance with Option 1 (preferred)</p> <p>Project Building Type? New Construction</p> <p>Occupancy Type? R2 Multifamily</p> <p>Code Version? WSEC 2018</p> <p>Classification: Small Dwelling Unit -- 1061 sq. ft.</p> <p>Baseline Description: Code Baseline - Baseline and proposed window areas are equal.</p> <p>About Your Selection: Up to 15 sf exempt window and 24 sf exempt door allowable</p>

RESULTS - Comparison of Baseline and Proposed Design																																																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Component Performance, R occupancies</th> <th colspan="3">Baseline</th> <th colspan="3">Proposed Design</th> </tr> <tr> <th>U</th> <th>Area</th> <th>UA</th> <th>U</th> <th>Area</th> <th>UA</th> </tr> </thead> <tbody> <tr> <td>Doors U =</td> <td>0.300</td> <td>40</td> <td>12.0</td> <td>0.300</td> <td>40</td> <td>12.0</td> </tr> <tr> <td>Overhead Glazing U =</td> <td>0.500</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Vertical Glazing U =</td> <td>0.300</td> <td>91</td> <td>27.4</td> <td>0.300</td> <td>91</td> <td>27.4</td> </tr> <tr> <td>Flat/Vaulted Ceilings U =</td> <td>0.027</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Wall (above grade) U =</td> <td>0.056</td> <td>1,397</td> <td>78.2</td> <td>0.054</td> <td>1,397</td> <td>75.4</td> </tr> <tr> <td>Floors over Crawlspace U =</td> <td>0.029</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Slab on Grade F =</td> <td>0.540</td> <td>151</td> <td>81.7</td> <td>0.540</td> <td>151</td> <td>81.7</td> </tr> <tr> <td>Below Grade Wall U =</td> <td>0.042</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Below Grade Slab F =</td> <td>0.570</td> <td>0</td> <td>0.0</td> <td></td> <td>0</td> <td>0.0</td> </tr> <tr> <td>Baseline UA Total</td> <td colspan="2"></td> <td>199.3</td> <td>Proposed UA Total</td> <td colspan="2"></td> <td>196.5</td> </tr> <tr> <td>Required Credits</td> <td colspan="2"></td> <td>4.5</td> <td>Proposed Credits</td> <td colspan="2"></td> <td>6.0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>UA Percent Reduction</td> <td colspan="2"></td> <td>1.4%</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>UA Reduction</td> <td colspan="2"></td> <td>2.8</td> </tr> </tbody> </table> <p>from Tables 406.2 and 406.3</p> <p>If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.</p>	Component Performance, R occupancies	Baseline			Proposed Design			U	Area	UA	U	Area	UA	Doors U =	0.300	40	12.0	0.300	40	12.0	Overhead Glazing U =	0.500	0	0.0		0	0.0	Vertical Glazing U =	0.300	91	27.4	0.300	91	27.4	Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0	Wall (above grade) U =	0.056	1,397	78.2	0.054	1,397	75.4	Floors over Crawlspace U =	0.029	0	0.0		0	0.0	Slab on Grade F =	0.540	151	81.7	0.540	151	81.7	Below Grade Wall U =	0.042	0	0.0		0	0.0	Below Grade Slab F =	0.570	0	0.0		0	0.0	Baseline UA Total			199.3	Proposed UA Total			196.5	Required Credits			4.5	Proposed Credits			6.0					UA Percent Reduction			1.4%					UA Reduction			2.8
Component Performance, R occupancies		Baseline			Proposed Design																																																																																																							
	U	Area	UA	U	Area	UA																																																																																																						
Doors U =	0.300	40	12.0	0.300	40	12.0																																																																																																						
Overhead Glazing U =	0.500	0	0.0		0	0.0																																																																																																						
Vertical Glazing U =	0.300	91	27.4	0.300	91	27.4																																																																																																						
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0																																																																																																						
Wall (above grade) U =	0.056	1,397	78.2	0.054	1,397	75.4																																																																																																						
Floors over Crawlspace U =	0.029	0	0.0		0	0.0																																																																																																						
Slab on Grade F =	0.540	151	81.7	0.540	151	81.7																																																																																																						
Below Grade Wall U =	0.042	0	0.0		0	0.0																																																																																																						
Below Grade Slab F =	0.570	0	0.0		0	0.0																																																																																																						
Baseline UA Total			199.3	Proposed UA Total			196.5																																																																																																					
Required Credits			4.5	Proposed Credits			6.0																																																																																																					
				UA Percent Reduction			1.4%																																																																																																					
				UA Reduction			2.8																																																																																																					

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits				
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*
1	Efficient Building Envelope		0.0	
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.
4	High Efficiency HVAC Distribution System		NA	
5.1	Efficient Water Heating		0.0	
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater
6	Renewable Electric Energy		0.0	
7	Appliance Package		0.0	
Energy Credits			6.0	

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design 1,061 sq. ft

Classification Small Dwelling Unit

Notes

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building Planning
Engineering Public Works
Fire Traffic

Exterior Doors

Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
102A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
102B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule

Rows to Show 3

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	4	6	3	6	47.3	14.18
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
7	U=0.30 (Code Baseline)	Table 406.2	0.30	1	7	0	2	0	14.0	4.20
Sum of Area and UA									91.3	27.4
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Flat/Vaulted Ceilings


Plan ID	Component Description	Ref.	Attic U	Area	UA
	No ceiling/roof in thermal envelope	NA	-		0.0
Sum of Area and UA				0	0.0

Walls (Above Grade)

Plan ID	Component Description	Ref.	Wall U	Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,397	75
Sum of Area and UA				1,397	75

Floor (over crawl or exterior)

Plan ID	Component Description	Ref.	Floor U	Area	UA
Sum of Area and UA				0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		151	82
Sum of Perimeter and FP					151	82

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,061 ft2	
Conditioned Volume	9,019 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	197	
Envelope Heat Load	10,022 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,967 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018)</small>		
Building Design Heat Load	14,989 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	14,989 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	20,985 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 103	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.54, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1008 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	78	23.4	0.300	78	23.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,271	71.2	0.054	1,271	68.6
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	138	74.3	0.540	138	74.3
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		180.8	Proposed UA Total		178.3
	Required Credits		4.5	Proposed Credits		6.0
						from Tables 406.2 and 406.3
						UA Percent Reduction
						1.4%
						UA Reduction
						2.5


If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design



Conditioned Floor Area, Proposed Design 1,008 sq. ft

Classification Small Dwelling Unit

Notes

Exterior Doors

Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
103A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
103B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule

Rows to Show 2

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
Sum of Area and UA									78.0	23.4
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Fiat/Vaulted Ceilings

Plan ID	Component Description	Ref.	Attic U	Area	UA
	No ceiling/roof in thermal envelope	NA	-		0.0
Sum of Area and UA				0	0.0

Walls (Above Grade)

Plan ID	Component Description	Ref.	Wall U	Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,271	69
Sum of Area and UA				1,271	69

Floor (over crawl or exterior)

Plan ID	Component Description	Ref.	Floor U	Area	UA
Sum of Area and UA				0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		138	74
Sum of Perimeter and FP					138	74

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements		
Number of Bedrooms	2	
Run-Time Percent in Each 4-Hour Segment	100%	
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403	
Whole House Mechanical Ventilation Airflow Rate	70 CFM	

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC	Prescriptive Checklist
Alterations (Remodel) Worksheet	Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,008 ft2	
Conditioned Volume	8,568 ft3	
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	178	
Envelope Heat Load	9,092 Btu / Hour	Sum of UA X ΔT
Air Leakage Heat Load	4,719 Btu / Hour	((Volume X 0.6) X ΔT) X 0.018)
Building Design Heat Load	13,811 Btu / Hour	Air Leakage + Envelope Heat Loss
Building and Duct Heat Load	13,811 Btu / Hour	For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1 For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1
Maximum Heat Equipment Output	19,335 Btu / Hour	Building and Duct Heat Loss X 1.25 for heat pumps Building and Duct Heat Loss X 1.40 for all other systems

Project Information	
East Town Crossing, Unit # 104	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.7, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 976 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	Baseline		U	Area	UA	
Doors U =	0.300	40	0.300	40	12.0	12.0
Overhead Glazing U =	0.500	0		0	0.0	0.0
Vertical Glazing U =	0.300	70	0.300	70	20.9	20.9
Flat/Vaulted Ceilings U =	0.027	0		0	0.0	0.0
Wall (above grade) U =	0.056	1,352	0.054	1,352	73.0	73.0
Floors over Crawlspace U =	0.029	0		0	0.0	0.0
Slab on Grade F =	0.540	145	0.540	145	78.1	78.1
Below Grade Wall U =	0.042	0		0	0.0	0.0
Below Grade Slab F =	0.570	0		0	0.0	0.0
	Baseline UA Total				Proposed UA Total	184.1
	186.8				Proposed Credits	6.0
	Required Credits				UA Percent Reduction	1.4%
	4.5				UA Reduction	2.7
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0		kWh
7	Appliance Package		0.0		
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	976	sq. ft	
Classification Small Dwelling Unit			
Notes			

City of Puyallup
 Development & Permitting Services
 ISSUED PERMIT
Building Planning
Engineering Public Works
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
104A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
104B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show	3
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
			-						-	-		
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20		
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	6	3	6	15.8	4.73		
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00		
Sum of Area and UA									69.8	20.9		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
Sum of Area and UA									0	0.0

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,352	73
Sum of Area and UA									1,352	73

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
Sum of Area and UA									0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		145	78
Sum of Perimeter and FP					145	78

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	976 ft2	
Conditioned Volume	8,296 ft3	
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	184	
Envelope Heat Load	9,387 Btu / Hour	
Sum of UA X ΔT		
Air Leakage Heat Load	4,569 Btu / Hour	
((Volume X 0.6) X ΔT) X .018)		
Building Design Heat Load	13,956 Btu / Hour	
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load	13,956 Btu / Hour	
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1 For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output	19,539 Btu / Hour	
Building and Duct Heat Loss X 1.25 for heat pumps Building and Duct Heat Loss X 1.40 for all other systems		

Project Information	
East Town Crossing, Unit # 105	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.54, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1008 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	78	23.4	0.300	78	23.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,271	71.2	0.054	1,271	68.6
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	138	74.3	0.540	138	74.3
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		180.8	Proposed UA Total		178.3
	Required Credits		4.5	Proposed Credits		6.0 from Tables 406.2 and 406.3
				UA Percent Reduction		1.4%
				UA Reduction		2.5

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	1,008	sq. ft
Classification Small Dwelling Unit		
Notes		

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
105A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
105B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show	2
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
1	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40		
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00		
Sum of Area and UA									78.0	23.4		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
Sum of Area and UA									0	0.0

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,271	69
Sum of Area and UA									1,271	69

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
Sum of Area and UA									0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		138	74
Sum of Perimeter and FP					138	74

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced		Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed		Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	70 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Unconditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits		
	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool	
Nearest Weather Station		Puyallup	
Indoor Design Temperature		70 F	
Outdoor Design Temperature		19 F	
Design Temperature Difference (ΔT)		51 F	
Conditioned Floor Area, Proposed Design		1,008 ft2	
Conditioned Volume		8,568 ft3	
	Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type		All Other Systems (not heat pump)	
Location of HVAC Distribution System		Unducted	
Sum of UA, including exempt door and window		178	
Envelope Heat Load		9,092 Btu / Hour	
	Sum of UA X ΔT		
Air Leakage Heat Load		4,719 Btu / Hour	
	((Volume X 0.6) X ΔT) X 0.018))		
Building Design Heat Load		13,811 Btu / Hour	
	Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load		13,811 Btu / Hour	
	For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
	For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output		19,335 Btu / Hour	
	Building and Duct Heat Loss X 1.25 for heat pumps		
	Building and Duct Heat Loss X 1.40 for all other systems		

Project Information	
East Town Crossing, Unit # 106	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.7, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 976 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
		Baseline		U	Area	UA
		U	Area	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	70	20.9	0.300	70	20.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,352	75.7	0.054	1,352	73.0
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	145	78.1	0.540	145	78.1
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total	186.8		Proposed UA Total	184.1	
	Required Credits	4.5		Proposed Credits	6.0	
				UA Percent Reduction	1.4%	
				UA Reduction	2.7	
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	976	sq. ft
Classification Small Dwelling Unit		
Notes		

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
106A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
106B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	6	3	6	15.8	4.73
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
Sum of Area and UA									69.8	20.9
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
Sum of Area and UA									0	0.0	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,352	73
Sum of Area and UA									1,352	73	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
Sum of Area and UA									0	0	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		145	78
Sum of Perimeter and FP					145	78

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced
Is the system Distributed?	Distributed
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		976 ft2
Conditioned Volume		8,296 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		184
Envelope Heat Load		9,387 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		4,569 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		13,956 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		13,956 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		19,539 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 107	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.61, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1108 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	130	38.9	0.300	130	38.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,305	73.1	0.054	1,305	70.5
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	146	78.8	0.540	146	78.8
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		202.8	Proposed UA Total		200.2
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		1.3%
				UA Reduction		2.6

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

City of Payalip
Development & Permitting Services
ISSUED PERMIT

Building Planning
Engineering Public Works
Fire Traffic

Conditioned Floor Area, Proposed Design 1,108 sq. ft

Classification Small Dwelling Unit

Notes

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
107A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
107B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	7	0	2	0	14.0	4.20
Sum of Area and UA									129.5	38.9
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	No ceiling/roof in thermal envelope	NA	-							0.0
Sum of Area and UA									0	0.0

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,305	70
Sum of Area and UA									1,305	70

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
Sum of Area and UA									0	0

Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		146	79
Sum of Perimeter and FP					146	79

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits		
	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		1,108 ft2
Conditioned Volume		9,418 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		200
Envelope Heat Load		10,208 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		5,187 Btu / Hour
<small>((Volume X 0.6) X ΔT) X 0.018</small>		
Building Design Heat Load		15,396 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		15,396 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		21,554 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit #108	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.77, Proposed UA is better than baseline by 1%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1061 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	101	30.4	0.300	101	30.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,387	77.7	0.054	1,387	74.9
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	151	81.7	0.540	151	81.7
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		201.7	Proposed UA Total		199.0
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		1.4%
				UA Reduction		2.8

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design



Conditioned Floor Area, Proposed Design 1,061 sq. ft

Classification Small Dwelling Unit

Notes

Exterior Doors

Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
108A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
108B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule

Rows to Show 3

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	4	6	3	6	47.3	14.18
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20
Sum of Area and UA									101.3	30.4
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Flat/Vaulted Ceilings


Plan ID	Component Description	Ref.	Attic U	Area	UA
	No ceiling/roof in thermal envelope	NA	-		0.0
Sum of Area and UA				0	0.0

Walls (Above Grade)

Plan ID	Component Description	Ref.	Wall U	Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,387	75
Sum of Area and UA				1,387	75

Floor (over crawl or exterior)

Plan ID	Component Description	Ref.	Floor U	Area	UA
Sum of Area and UA				0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	R10 2' vertical (Code Baseline)	10-2	0.540		151	82
Sum of Perimeter and FP					151	82

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	Compliance Certificate	Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate	
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New	
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,061 ft2	
Conditioned Volume	9,019 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	199	
Envelope Heat Load	10,147 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,967 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018)</small>		
Building Design Heat Load	15,115 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	15,115 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	21,161 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 201	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.64, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1106 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	128	38.3	0.300	128	38.3
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,322	74.0	0.054	1,322	71.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		124.3	Proposed UA Total		121.6
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		2.1%
				UA Reduction		2.6

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design 1,106 sq. ft

Classification Small Dwelling Unit

Notes

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building Planning
Engineering Public Works
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
201A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
201B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show	4
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
									-	-		
1	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60		
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80		
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25		
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	2	0	12.0	3.60		
Sum of Area and UA									127.5	38.3		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
Sum of Area and UA									0	0.0	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,322	71
Sum of Area and UA									1,322	71	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
Sum of Area and UA									0	0	

Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs									
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA	
Sum of Area, Length and UA				0	0.0		0	0	

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits		
	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		1,106 ft2
Conditioned Volume		9,401 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		122
Envelope Heat Load		6,203 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		5,178 Btu / Hour
<small>((Volume X 0.6) X ΔT) X 0.18)</small>		
Building Design Heat Load		11,381 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		11,381 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		15,933 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 202	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.83, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1061 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable


RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Baseline		Proposed Design	
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	89	26.8	0.300	89	26.8
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,413	79.1	0.054	1,413	76.3
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
Baseline UA Total			117.9	Proposed UA Total		
Required Credits			4.5	Proposed Credits		
				6.0 from Tables 406.2 and 406.3		
				UA Percent Reduction		
				2.4%		
				UA Reduction		
				2.8		
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits				
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*
1	Efficient Building Envelope		0.0	
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.
4	High Efficiency HVAC Distribution System		NA	
5.1	Efficient Water Heating		0.0	
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater
6	Renewable Electric Energy		0.0	
7	Appliance Package		0.0	
Energy Credits			6.0	

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design



Conditioned Floor Area, Proposed Design	1,061	sq. ft
Classification Small Dwelling Unit		
Notes		

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
202A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
202B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule										Rows to Show	3
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
1	2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	4	6	3	6	47.3	14.18
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
1	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	2	0	12.0	3.60
Sum of Area and UA									89.3	26.8	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings						
Plan ID	Component Description	Ref.	Attic U		Area	UA
	No ceiling/roof in thermal envelope	NA	-			0.0
Sum of Area and UA					0	0.0

Walls (Above Grade)						
Plan ID	Component Description	Ref.	Wall U		Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054		1,413	76
Sum of Area and UA					1,413	76

Floor (over crawl or exterior)						
Plan ID	Component Description	Ref.	Floor U		Area	UA
	No floors in thermal envelope	NA	-			0
Sum of Area and UA					0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	Compliance Certificate	Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate	
Duct Testing Affidavits	Existing Construction Affidavit, Existing	New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,061 ft2	
Conditioned Volume	9,019 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	115	
Envelope Heat Load	5,869 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,967 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load	10,836 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	10,836 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	15,171 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 203	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.57, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 1008 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies						
	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	78	23.4	0.300	78	23.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,285	71.9	0.054	1,285	69.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		107.3	Proposed UA Total		104.8
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction 2.4%		
				UA Reduction 2.6		
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	1,008	sq. ft
Classification		Small Dwelling Unit
Notes		

City of Payson
 Development & Permitting Services
ISSUED PERMIT
 Building Planning
 Engineering Public Works
 Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
203A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
203B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U									0.300	


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt			-						-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
Sum of Area and UA									78.0	23.4	
Vertical Glazing Area Weighted U									0.300		
Vertical Glazing and Doors Area Weighted U									0.300		

Flat/Vaulted Ceilings							
Plan ID	Component Description	Ref.	Attic U	Area	UA		
	No ceiling/roof in thermal envelope	NA	-		0.0		
Sum of Area and UA				0	0.0		

Walls (Above Grade)							
Plan ID	Component Description	Ref.	Wall U	Net Area	UA		
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,285	69		
Sum of Area and UA				1,285	69		

Floor (over crawl or exterior)							
Plan ID	Component Description	Ref.	Floor U	Area	UA		
	No floors in thermal envelope	NA	-		0		
Sum of Area and UA				0	0		



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced		Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed		Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	70 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Unconditioned Space		
Is Duct Testing Required?	No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design	1,008 ft2	
Conditioned Volume	8,568 ft3	
Leave blank to use default of 8.5 ft. ceiling height		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		105
Envelope Heat Load		5,343 Btu / Hour
Sum of UA X ΔT		
Air Leakage Heat Load		4,719 Btu / Hour
((Volume X 0.6) X ΔT) X 0.18)		
Building Design Heat Load		10,062 Btu / Hour
Air Leakage + Envelope Heat Loss		
Building and Duct Heat Load		10,062 Btu / Hour
For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1		
For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1		
Maximum Heat Equipment Output		14,087 Btu / Hour
Building and Duct Heat Loss X 1.25 for heat pumps		
Building and Duct Heat Loss X 1.40 for all other systems		

Project Information	
East Town Crossing, Unit # 204	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.73, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 976 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
	Baseline		U	Area	UA	
Doors U =	0.300	40	0.300	40	12.0	12.0
Overhead Glazing U =	0.500	0		0	0.0	0.0
Vertical Glazing U =	0.300	70	0.300	70	20.9	20.9
Flat/Vaulted Ceilings U =	0.027	0		0	0.0	0.0
Wall (above grade) U =	0.056	1,366	0.054	1,366	73.8	73.8
Floors over Crawlspace U =	0.029	0		0	0.0	0.0
Slab on Grade F =	0.540	0		0	0.0	0.0
Below Grade Wall U =	0.042	0		0	0.0	0.0
Below Grade Slab F =	0.570	0		0	0.0	0.0
	Baseline UA Total				Proposed UA Total	106.7
	109.4				Proposed Credits	6.0
	Required Credits				UA Percent Reduction	2.5% from Tables 406.2 and 406.3
	4.5				UA Reduction	2.7
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		0.0	kWh	
7	Appliance Package		0.0		
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	976	sq. ft
Classification Small Dwelling Unit		
Notes		

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors											
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
									0	0.0	
204A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0	
204B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
Sum of Area and UA									40	12.0	
Exterior Doors Area Weighted U										0.300	

Overhead Glazing											
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
									0		
									0		
									0		
									0		
									0		
									0		
									0		
									0		
Sum of Area and UA									0	0	
Overhead Glazing Area Weighted U											

Vertical Glazing Schedule												Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
			-						-	-		
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20		
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	6	3	6	15.8	4.73		
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00		
Sum of Area and UA									69.8	20.9		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings													
Plan ID	Component Description	Ref.	Attic U									Area	UA
	No ceiling/roof in thermal envelope	NA	-										0.0
Sum of Area and UA									0	0.0			

Walls (Above Grade)													
Plan ID	Component Description	Ref.	Wall U									Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054									1,366	74
Sum of Area and UA									1,366	74			

Floor (over crawl or exterior)													
Plan ID	Component Description	Ref.	Floor U									Area	UA
	No floors in thermal envelope	NA	-										0
Sum of Area and UA									0	0			



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	Compliance Certificate	Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate	
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New	
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	976 ft2	
Conditioned Volume	8,296 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	107	
Envelope Heat Load	5,442 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,569 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load	10,011 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	10,011 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	14,016 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 205	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.57, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1008 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	78	23.4	0.300	78	23.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,285	71.9	0.054	1,285	69.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
Baseline UA Total			107.3	Proposed UA Total		104.8
Required Credits			4.5	Proposed Credits		6.0
				UA Percent Reduction		2.4%
				UA Reduction		2.6

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design			1,008	sq. ft
Classification			Small Dwelling Unit	
Notes				

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
205A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
205B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt									-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
Sum of Area and UA									78.0	23.4	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U					Area	UA	
	No ceiling/roof in thermal envelope	NA	-						0.0	
Sum of Area and UA								0	0.0	

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U					Net Area	UA	
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054					1,285	69	
Sum of Area and UA								1,285	69	

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U					Area	UA	
	No floors in thermal envelope	NA	-						0	
Sum of Area and UA								0	0	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements			
Number of Bedrooms	2		
Run-Time Percent in Each 4-Hour Segment	100%		
Is the system Balanced?	Balanced		Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed		Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403		
Whole House Mechanical Ventilation Airflow Rate	70 CFM		

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Unconditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool	
Nearest Weather Station		Puyallup	
Indoor Design Temperature		70 F	
Outdoor Design Temperature		19 F	
Design Temperature Difference (ΔT)		51 F	
Conditioned Floor Area, Proposed Design	1,008 ft2		
Conditioned Volume	8,568 ft3		
<small>Leave blank to use default of 8.5 ft. ceiling height</small>			
HVAC System Type		All Other Systems (not heat pump)	
Location of HVAC Distribution System		Unducted	
Sum of UA, including exempt door and window		105	
Envelope Heat Load		5,343 Btu / Hour	
<small>Sum of UA X ΔT</small>			
Air Leakage Heat Load		4,719 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X 0.18)</small>			
Building Design Heat Load		10,062 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>			
Building and Duct Heat Load		10,062 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>			
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>			
Maximum Heat Equipment Output		14,087 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>			
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>			

Project Information	
East Town Crossing, Unit # 206	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.73, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 976 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	70	20.9	0.300	70	20.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,366	76.5	0.054	1,366	73.8
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		109.4	Proposed UA Total		106.7
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		2.5%
				UA Reduction		2.7

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design		976	sq. ft
Classification		Small Dwelling Unit	
Notes			

City of Payson
Development & Permitting Services
ISSUED PERMIT

Building Planning
Engineering Public Works
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
206A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
206B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt			-						-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	6	3	6	15.8	4.73	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
Sum of Area and UA									69.8	20.9	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
Sum of Area and UA									0	0.0	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,366	74
Sum of Area and UA									1,366	74	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
Sum of Area and UA									0	0	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		976 ft2
Conditioned Volume		8,296 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		107
Envelope Heat Load		5,442 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		4,569 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018))</small>		
Building Design Heat Load		10,011 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		10,011 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		14,016 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 207	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.64, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1105 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	130	38.9	0.300	130	38.9
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,320	73.9	0.054	1,320	71.3
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		124.8	Proposed UA Total		122.1
	Required Credits		4.5	Proposed Credits		6.0
						2.1%
						2.6

from Tables 406.2 and 406.3


If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design



Conditioned Floor Area, Proposed Design	1,105	sq. ft
Classification Small Dwelling Unit		
Notes		

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
207A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
207B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
			-						-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25	
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	7	0	2	0	14.0	4.20	
Sum of Area and UA									129.5	38.9	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U	Area	UA					
	No ceiling/roof in thermal envelope	NA	-		0.0					
Sum of Area and UA				0	0.0					

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U	Net Area	UA					
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,320	71					
Sum of Area and UA				1,320	71					

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U	Area	UA					
	No floors in thermal envelope	NA	-		0					
Sum of Area and UA				0	0					



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		1,105 ft2
Conditioned Volume		9,393 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		122
Envelope Heat Load		6,228 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		5,173 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018</small>		
Building Design Heat Load		11,401 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		11,401 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		15,962 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 208	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.8, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1061 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	101	30.4	0.300	101	30.4
Flat/Vaulted Ceilings U =	0.027	0	0.0		0	0.0
Wall (above grade) U =	0.056	1,401	78.5	0.054	1,401	75.7
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		120.8	Proposed UA Total		118.0
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		2.3%
				UA Reduction		2.8

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design		1,061	sq. ft
Classification Small Dwelling Unit			
Notes			

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building Planning
Engineering Public Works
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
208A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
208B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	4	6	3	6	47.3	14.18	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
Sum of Area and UA									101.3	30.4	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	No ceiling/roof in thermal envelope	NA	-								0.0
Sum of Area and UA									0	0.0	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,401	76
Sum of Area and UA									1,401	76	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
Sum of Area and UA									0	0	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	Compliance Certificate	Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate	
Duct Testing Affidavits	Existing Construction Affidavit, Existing	New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,061 ft2	
Conditioned Volume	9,019 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	118	
Envelope Heat Load	6,019 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,967 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018)</small>		
Building Design Heat Load	10,987 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	10,987 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	15,382 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 301	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.64, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1106 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	128	38.3	0.300	128	38.3
Flat/Vaulted Ceilings U =	0.027	1,106	29.9	0.027	1,106	29.9
Wall (above grade) U =	0.056	1,322	74.0	0.054	1,322	71.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		154.1	Proposed UA Total		151.5
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		1.7%
				UA Reduction		2.6

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design		1,106	sq. ft
Classification Small Dwelling Unit			
Notes			

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
301A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
301B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt			-							-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60	4
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25	
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	2	0	12.0	3.60	
Sum of Area and UA									127.5	38.3	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						1,106	29.9
Sum of Area and UA									1,106	29.9

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,322	71
Sum of Area and UA									1,322	71

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
Sum of Area and UA									0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		1,106 ft2
Conditioned Volume		9,401 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		151
Envelope Heat Load		7,726 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		5,178 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018</small>		
Building Design Heat Load		12,904 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		12,904 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		18,065 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 302	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.83, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1061 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	89	26.8	0.300	89	26.8
Flat/Vaulted Ceilings U =	0.027	1,061	28.6	0.027	1,061	28.6
Wall (above grade) U =	0.056	1,413	79.1	0.054	1,413	76.3
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
Baseline UA Total			146.5	Proposed UA Total		143.7
Required Credits			4.5	Proposed Credits		6.0
				UA Percent Reduction		1.9%
				UA Reduction		2.8

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design 1,061 sq. ft

Classification Small Dwelling Unit

Notes

Exterior Doors

Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
302A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
302B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U									0.300	

Overhead Glazing

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule

Rows to Show 3

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	4	6	3	6	47.3	14.18
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	2	0	12.0	3.60
Sum of Area and UA									89.3	26.8
Vertical Glazing Area Weighted U									0.300	
Vertical Glazing and Doors Area Weighted U									0.300	

Flat/Vaulted Ceilings

Plan ID	Component Description	Ref.	Attic U	Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027	1,061	28.6
Sum of Area and UA				1,061	28.6

Walls (Above Grade)

Plan ID	Component Description	Ref.	Wall U	Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,413	76
Sum of Area and UA				1,413	76

Floor (over crawl or exterior)

Plan ID	Component Description	Ref.	Floor U	Area	UA
	No floors in thermal envelope	NA	-		0
Sum of Area and UA				0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	Compliance Certificate	Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate	
Duct Testing Affidavits	Existing Construction Affidavit, Existing	New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,061 ft2	
Conditioned Volume	9,019 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	144	
Envelope Heat Load	7,330 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,967 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X .018)</small>		
Building Design Heat Load	12,297 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	12,297 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	17,216 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 303	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.57, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 1007 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Baseline		Proposed Design	
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	78	23.4	0.300	78	23.4
Flat/Vaulted Ceilings U =	0.027	1,007	27.2	0.027	1,007	27.2
Wall (above grade) U =	0.056	1,285	71.9	0.054	1,285	69.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
			Baseline UA Total			134.5
			Required Credits			4.5
			Proposed UA Total		132.0	
			Proposed Credits		6.0	
			UA Percent Reduction		1.9%	
			UA Reduction		2.6	
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits				
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*
1	Efficient Building Envelope		0.0	
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.
4	High Efficiency HVAC Distribution System		NA	
5.1	Efficient Water Heating		0.0	
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater
6	Renewable Electric Energy		0.0	
7	Appliance Package		0.0	
Energy Credits			6.0	

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design



Conditioned Floor Area, Proposed Design 1,007 sq. ft

Classification Small Dwelling Unit

Notes

Exterior Doors

Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
303A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
303B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule

Rows to Show 2

Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt			-						-	-
1	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00
Sum of Area and UA									78.0	23.4
Vertical Glazing Area Weighted U										0.300
Vertical Glazing and Doors Area Weighted U										0.300

Flat/Vaulted Ceilings


Plan ID	Component Description	Ref.	Attic U	Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027	1,007	27.2
Sum of Area and UA				1,007	27.2

Walls (Above Grade)

Plan ID	Component Description	Ref.	Wall U	Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,285	69
Sum of Area and UA				1,285	69

Floor (over crawl or exterior)

Plan ID	Component Description	Ref.	Floor U	Area	UA
	No floors in thermal envelope	NA	-		0
Sum of Area and UA				0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements		
Number of Bedrooms	2	
Run-Time Percent in Each 4-Hour Segment	100%	
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403	
Whole House Mechanical Ventilation Airflow Rate	70 CFM	

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC	Prescriptive Checklist
Alterations (Remodel) Worksheet	Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,007 ft2	
Conditioned Volume	8,560 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	132	
Envelope Heat Load	6,730 Btu / Hour	<small>Sum of UA X ΔT</small>
Air Leakage Heat Load	4,715 Btu / Hour	<small>((Volume X 0.6) X ΔT) X 0.18)</small>
Building Design Heat Load	11,444 Btu / Hour	<small>Air Leakage + Envelope Heat Loss</small>
Building and Duct Heat Load	11,444 Btu / Hour	<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1 For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>
Maximum Heat Equipment Output	16,022 Btu / Hour	<small>Building and Duct Heat Loss X 1.25 for heat pumps Building and Duct Heat Loss X 1.40 for all other systems</small>

Project Information	
East Town Crossing, Unit # 304	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.73, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 976 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	70	20.9	0.300	70	20.9
Flat/Vaulted Ceilings U =	0.027	976	26.4	0.027	976	26.4
Wall (above grade) U =	0.056	1,366	76.5	0.054	1,366	73.8
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		135.8	Proposed UA Total		133.1
	Required Credits		4.5	Proposed Credits		6.0
						2.0%
						UA Reduction
						2.7

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	976	sq. ft
Classification Small Dwelling Unit		
Notes		

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
304A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
304B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
Exempt					Feet	Inch	Feet	Inch			
									-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	6	3	6	15.8	4.73	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
Sum of Area and UA									69.8	20.9	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027							976	26.4
Sum of Area and UA									976	26.4	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,366	74
Sum of Area and UA									1,366	74	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
Sum of Area and UA									0	0	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	976 ft2	
Conditioned Volume	8,296 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	133	
Envelope Heat Load	6,786 Btu / Hour	<small>Sum of UA X ΔT</small>
Air Leakage Heat Load	4,569 Btu / Hour	<small>((Volume X 0.6) X ΔT) X 0.18)</small>
Building Design Heat Load	11,355 Btu / Hour	<small>Air Leakage + Envelope Heat Loss</small>
Building and Duct Heat Load	11,355 Btu / Hour	<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1 For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>
Maximum Heat Equipment Output	15,897 Btu / Hour	<small>Building and Duct Heat Loss X 1.25 for heat pumps Building and Duct Heat Loss X 1.40 for all other systems</small>

Project Information	
East Town Crossing, Unit # 305	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.57, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 1007 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
		Baseline		U	Area	UA
		U	Area			
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	78	23.4	0.300	78	23.4
Flat/Vaulted Ceilings U =	0.027	1,007	27.2	0.027	1,007	27.2
Wall (above grade) U =	0.056	1,285	71.9	0.054	1,285	69.4
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		134.5	Proposed UA Total		132.0
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		1.9%
				UA Reduction		2.6
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design		1,007	sq. ft
Classification		Small Dwelling Unit	
Notes			



Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
305A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
305B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	2
Exempt					Feet	Inch	Feet	Inch			
									-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	2	6	0	4	0	48.0	14.40	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
Sum of Area and UA									78.0	23.4	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						1,007	27.2
Sum of Area and UA									1,007	27.2

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,285	69
Sum of Area and UA									1,285	69

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
Sum of Area and UA									0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements		
Number of Bedrooms	2	
Run-Time Percent in Each 4-Hour Segment	100%	
Is the system Balanced?	Balanced	Verify system meets definition of 'Balanced Whole-House Ventilation'
Is the system Distributed?	Distributed	Verify system meets definition of 'Distributed Whole-House Ventilation'
Ventilation Code Section	IMC, Section 403	
Whole House Mechanical Ventilation Airflow Rate	70 CFM	

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20	
Is this a hydronic heating system?	No		
Location of Ducts	Unducted		
Location of Air Handler	Unconditioned Space		
Is Duct Testing Required? No			

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design	1,007 ft2	
Conditioned Volume	8,560 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window	132	
Envelope Heat Load	6,730 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,715 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X 0.018)</small>		
Building Design Heat Load	11,444 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	11,444 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	16,022 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 306	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.73, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 55 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 976 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	70	20.9	0.300	70	20.9
Flat/Vaulted Ceilings U =	0.027	976	26.4	0.027	976	26.4
Wall (above grade) U =	0.056	1,366	76.5	0.054	1,366	73.8
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		135.8	Proposed UA Total		133.1
	Required Credits		4.5	Proposed Credits		6.0
				UA Percent Reduction		2.0%
				UA Reduction		2.7

from Tables 406.2 and 406.3

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	976	sq. ft
Classification	Small Dwelling Unit	
Notes		



Exterior Doors											
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt									0	0.0	
306A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0	
306B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
									0	0.0	
Sum of Area and UA									40	12.0	
Exterior Doors Area Weighted U											0.300


Overhead Glazing											
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
									0		
									0		
									0		
									0		
									0		
Sum of Area and UA									0	0	
Overhead Glazing Area Weighted U											

Vertical Glazing Schedule											
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	Rows to Show
					Feet	Inch	Feet	Inch			
Exempt			-						-	-	3
1	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	4	6	3	6	15.8	4.73	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
Sum of Area and UA									69.8	20.9	
Vertical Glazing Area Weighted U											0.300
Vertical Glazing and Doors Area Weighted U											0.300

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U	Area	UA						
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027	976	26.4						
Sum of Area and UA				976	26.4						

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U	Net Area	UA						
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054	1,366	74						
Sum of Area and UA				1,366	74						

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U	Area	UA						
	No floors in thermal envelope	NA	-		0						
Sum of Area and UA				0	0						



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	2
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	55 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate	Compliance Certificate	Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate	
Duct Testing Affidavits	Existing Construction Affidavit, Existing	New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet	

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	976 ft2	
Conditioned Volume	8,296 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	133	
Envelope Heat Load	6,786 Btu / Hour	
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load	4,569 Btu / Hour	
<small>((Volume X 0.6) X ΔT) X 0.18)</small>		
Building Design Heat Load	11,355 Btu / Hour	
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load	11,355 Btu / Hour	
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output	15,897 Btu / Hour	
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit #307	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.64, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP	
What code compliance pathway are you using? Project Building Type? Occupancy Type? Code Version? Classification: Baseline Description: About Your Selection:	Prescriptive Path Compliance with Option 1 (preferred) New Construction R2 Multifamily WSEC 2018 Small Dwelling Unit -- 1105 sq. ft. Code Baseline - Baseline and proposed window areas are equal. Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design						
Component Performance, R occupancies			Proposed Design			
		Baseline		U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	130	38.9	0.300	130	38.9
Flat/Vaulted Ceilings U =	0.027	1,105	29.8	0.027	1,105	29.8
Wall (above grade) U =	0.056	1,320	73.9	0.054	1,320	71.3
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
		Baseline UA Total	154.6		Proposed UA Total	151.9
		Required Credits	4.5		Proposed Credits	6.0
					UA Percent Reduction	1.7%
					UA Reduction	2.6
If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.						

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
Energy Credits			6.0		

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design		1,105	sq. ft
Classification		Small Dwelling Unit	
Notes			

City of Puyallup
Development & Permitting Services
ISSUED PERMIT

Building	Planning
Engineering	Public Works
Fire	Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
Exempt									0	0.0
307A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
307B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300


Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA	
					Feet	Inch	Feet	Inch			
Exempt			-						-	-	
1	U=0.30 (Code Baseline)	Table 406.2	0.30	3	6	0	4	0	72.0	21.60	
2	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	6	0	36.0	10.80	
3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	2	6	3	0	7.5	2.25	
4	U=0.30 (Code Baseline)	Table 406.2	0.30	1	7	0	2	0	14.0	4.20	
Sum of Area and UA									129.5	38.9	
Vertical Glazing Area Weighted U										0.300	
Vertical Glazing and Doors Area Weighted U										0.300	

Flat/Vaulted Ceilings										
Plan ID	Component Description	Ref.	Attic U						Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027						1,105	29.8
Sum of Area and UA									1,105	29.8

Walls (Above Grade)										
Plan ID	Component Description	Ref.	Wall U						Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054						1,320	71
Sum of Area and UA									1,320	71

Floor (over crawl or exterior)										
Plan ID	Component Description	Ref.	Floor U						Area	UA
	No floors in thermal envelope	NA	-							0
Sum of Area and UA									0	0



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources		Link
Compliance Certificate		Compliance Certificate Instructions
Insulation Certificate for Residential New Construction		Insulation Certificate
Duct Testing Affidavits	Existing Construction	Affidavit, Existing
	New Construction	Affidavit, New
Prescriptive Checklist for 2018 WSEC		Prescriptive Checklist
Alterations (Remodel) Worksheet		Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station		Puyallup
Indoor Design Temperature		70 F
Outdoor Design Temperature		19 F
Design Temperature Difference (ΔT)		51 F
Conditioned Floor Area, Proposed Design		1,105 ft2
Conditioned Volume		9,393 ft3
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type		All Other Systems (not heat pump)
Location of HVAC Distribution System		Unducted
Sum of UA, including exempt door and window		152
Envelope Heat Load		7,749 Btu / Hour
<small>Sum of UA X ΔT</small>		
Air Leakage Heat Load		5,173 Btu / Hour
<small>((Volume X 0.6) X ΔT) X .018</small>		
Building Design Heat Load		12,923 Btu / Hour
<small>Air Leakage + Envelope Heat Loss</small>		
Building and Duct Heat Load		12,923 Btu / Hour
<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1</small>		
<small>For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>		
Maximum Heat Equipment Output		18,092 Btu / Hour
<small>Building and Duct Heat Loss X 1.25 for heat pumps</small>		
<small>Building and Duct Heat Loss X 1.40 for all other systems</small>		

Project Information	
East Town Crossing, Unit # 308	
Building B	
Pioneer & Shaw, Puyallup	
Contact Information	
Synthesis 9, LLC	
Brett Lindsay	
blindsay@synthesis9.com	
253-468-4117	

Messages / Results *	
UA Reduction = 2.8, Proposed UA is better than baseline by 2%	
Whole House Mechanical Ventilation Airflow Rate: 70 CFM with Run Time Percent of 100%, Balanced, Distributed	
* Results assume your inputs are complete and correct. Results do not constitute an approval. Analysis should be reviewed by your AHJ.	



ANALYSIS SET UP

What code compliance pathway are you using?	Prescriptive Path Compliance with Option 1 (preferred)
Project Building Type?	New Construction
Occupancy Type?	R2 Multifamily
Code Version?	WSEC 2018
Classification:	Small Dwelling Unit -- 1061 sq. ft.
Baseline Description:	Code Baseline - Baseline and proposed window areas are equal.
About Your Selection:	Up to 15 sf exempt window and 24 sf exempt door allowable

RESULTS - Comparison of Baseline and Proposed Design

Component Performance, R occupancies	Baseline			Proposed Design		
	U	Area	UA	U	Area	UA
Doors U =	0.300	40	12.0	0.300	40	12.0
Overhead Glazing U =	0.500	0	0.0		0	0.0
Vertical Glazing U =	0.300	101	30.4	0.300	101	30.4
Flat/Vaulted Ceilings U =	0.027	1,061	28.6	0.027	1,061	28.6
Wall (above grade) U =	0.056	1,401	78.5	0.054	1,401	75.7
Floors over Crawlspace U =	0.029	0	0.0		0	0.0
Slab on Grade F =	0.540	0	0.0		0	0.0
Below Grade Wall U =	0.042	0	0.0		0	0.0
Below Grade Slab F =	0.570	0	0.0		0	0.0
	Baseline UA Total		149.5	Proposed UA Total		146.7
	Required Credits		4.5	Proposed Credits		6.0
						1.9% from Tables 406.2 and 406.3
						UA Percent Reduction
						UA Reduction
						2.8

If the Proposed UA ≤ the Target UA, and the Proposed Credits from Table 406 are ≥ those required in Section R406, then the home meets the WSEC.

Table R406.2 Fuel Normalization Credits					
System No.	Full Description	Select System Type	Fuel Normalization Credits (406.2)	Energy Credits (406.3)	Total Credits (406.2 & 406.3)
4	For heating system based on electric resistance with a ductless mini-split heat pump system in accordance with Section R403.7.1 including the exception	Electric Resistance with Ductless Heat Pump	N/A for R2	6.0	6.0

Table R406.3 Energy Credits					
Option No.	Category	Select Options	Energy Credits	Brief Description of Selected Options*	
1	Efficient Building Envelope		0.0		
2	Air Leakage Control and Efficient Ventilation	Option 2.2	1.5	2.0 ACH50 / Heat Recovery Ventilation min eff 65% / For R2, 0.25 cfm per ft2 at 50 Pa / HRV with min SHR eff of 0.65	
3	High Efficiency HVAC	Option 3.4	2.0	Ductless Split System, Zonal Control. Min HSPF of 10.	
4	High Efficiency HVAC Distribution System		NA		
5.1	Efficient Water Heating		0.0		
5.2-5.6	Efficient Water Heating	Option 5.5	2.5	NEEA Tier 3 heat pump water heater	
6	Renewable Electric Energy		kWh	0.0	
7	Appliance Package			0.0	
			Energy Credits	6.0	

*Refer to WSEC 2018 Table R406.3 for complete option descriptions and requirements

THERMAL ENVELOPE DETAILS - Proposed Design

Conditioned Floor Area, Proposed Design	1,061	sq. ft
Classification Small Dwelling Unit		
Notes		

City of Puyallup
 Development & Permitting Services
ISSUED PERMIT
Building Planning
Engineering Public Works
Fire Traffic

Exterior Doors										
Plan ID	Component Description	Ref.	Door U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	0.0
308A	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
308B	Code Baseline, U=0.30	-	0.30	1	3	0	6	8	20	6.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
									0	0.0
Sum of Area and UA									40	12.0
Exterior Doors Area Weighted U										0.300

Overhead Glazing										
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA
Exempt					Feet	Inch	Feet	Inch		
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
									0	
Sum of Area and UA									0	0
Overhead Glazing Area Weighted U										

Vertical Glazing Schedule											Rows to Show	
Plan ID	Component Description	Ref.	Glazing U	Qt.	Width		Height		Area	UA		
Exempt					Feet	Inch	Feet	Inch				
									-	-		
1	2	U=0.30 (Code Baseline)	Table 406.2	0.30	3	4	6	3	6	47.3	14.18	3
	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	5	0	6	0	30.0	9.00	
	3	U=0.30 (Code Baseline)	Table 406.2	0.30	1	6	0	4	0	24.0	7.20	
Sum of Area and UA									101.3	30.4		
Vertical Glazing Area Weighted U										0.300		
Vertical Glazing and Doors Area Weighted U										0.300		

Flat/Vaulted Ceilings											
Plan ID	Component Description	Ref.	Attic U							Area	UA
	R49 blown Attic STD baffled (Code Baseline, Option 1.1-1.4)	10-7	0.027							1,061	28.6
Sum of Area and UA									1,061	28.6	

Walls (Above Grade)											
Plan ID	Component Description	Ref.	Wall U							Net Area	UA
	R21 cavity+R0 foam INT 2X6W Lap (Code Baseline)	10-5	0.054							1,401	76
Sum of Area and UA									1,401	76	

Floor (over crawl or exterior)											
Plan ID	Component Description	Ref.	Floor U							Area	UA
	No floors in thermal envelope	NA	-								0
Sum of Area and UA									0	0	



Slab on Grade (less than 2 feet below grade)						
Plan ID	Component Description	Ref.	Slab F		Slab Perim	FP
	No slab on grade	NA	-			0
Sum of Perimeter and FP					0	0

Below Grade Walls and Slabs								
Plan ID	Component Description	Ref.	Wall U	Wall Area	Wall UA	Slab F	Slab Perim	Slab UA
Sum of Area, Length and UA				0	0.0		0	0

Ventilation Requirements	
Number of Bedrooms	3
Run-Time Percent in Each 4-Hour Segment	100%
Is the system Balanced?	Balanced <small>Verify system meets definition of 'Balanced Whole-House Ventilation'</small>
Is the system Distributed?	Distributed <small>Verify system meets definition of 'Distributed Whole-House Ventilation'</small>
Ventilation Code Section	IMC, Section 403
Whole House Mechanical Ventilation Airflow Rate	70 CFM

HVAC Thermal Distribution System		Download RS-33 (2018) http://www.energy.wsu.edu/Documents/Duct%20Testing%20Standards%20
Is this a hydronic heating system?	No	
Location of Ducts	Unducted	
Location of Air Handler	Unconditioned Space	
Is Duct Testing Required? No		

Links to Download Forms, Checklists and Other Resources	Link
Compliance Certificate	Compliance Certificate Instructions
Insulation Certificate for Residential New Construction	Insulation Certificate
Duct Testing Affidavits	Existing Construction Affidavit, Existing New Construction Affidavit, New
Prescriptive Checklist for 2018 WSEC Alterations (Remodel) Worksheet	Prescriptive Checklist Worksheet

Heating System Sizing - Proposed Design		Try Out BetterBuiltNW's HVAC Sizing Tool: https://betterbuiltnw.com/resources/hvac-sizing-tool
Nearest Weather Station	Puyallup	
Indoor Design Temperature	70 F	
Outdoor Design Temperature	19 F	
Design Temperature Difference (ΔT)	51 F	
Conditioned Floor Area, Proposed Design	1,061 ft2	
Conditioned Volume	9,019 ft3	
<small>Leave blank to use default of 8.5 ft. ceiling height</small>		
HVAC System Type	All Other Systems (not heat pump)	
Location of HVAC Distribution System	Unducted	
Sum of UA, including exempt door and window	147	
Envelope Heat Load	7,480 Btu / Hour	<small>Sum of UA X ΔT</small>
Air Leakage Heat Load	4,967 Btu / Hour	<small>((Volume X 0.6) X ΔT) X .018))</small>
Building Design Heat Load	12,448 Btu / Hour	<small>Air Leakage + Envelope Heat Loss</small>
Building and Duct Heat Load	12,448 Btu / Hour	<small>For ducts located in unconditioned space: Sum of Building Heat Loss X 1.1 For ducts located in conditioned space or ductless: Sum of Building Heat Loss X 1</small>
Maximum Heat Equipment Output	17,427 Btu / Hour	<small>Building and Duct Heat Loss X 1.25 for heat pumps Building and Duct Heat Loss X 1.40 for all other systems</small>