Refer to the City standard details 02.03.02 & 05.02.01 for typical erosion and sedimentation control methods.

Any public curb, gutter, or sidewalk broken now or during the course of construction shall be removed and replaced per City Standards.

A 10" diameter core drill is allowed for potholing. For pothole windows larger than 10" in diameter or trenching completed in existing roadway, the contractor shall restore the pavement by installing the trench patch and then grinding/overlaying. All roadway restoration and street patches shall comply with City Standard Detail 01.01.20.



Job #: 109139591 10/29/24 Date: PUYALLUP **Jurisdiction: ROW Permit:** Yes 11/4/24 **Est. Start Date: Est. Duration:** 4 Days (32 Hours)

3303 8TH AVE SE **Service Address:**

PUYALLUP **Zip:** 98372 JASON CORNELL (253) 241-1293 **Site Contact:** Phone:

Site Contact Email: jasoncornell@stepbystepfamily.org **LUTHER RIMORIN** PM / Inspector:

(253) 278-1118 Phone: jasoncornell@stepbystepfamily.org Phone: (253) 241-1293 **Customer Email:**

Job Description

Project Scope: INTERCEPT EXISTING 6" PE MAIN 536' NCL OF 8TH AVE SE. NEWLY INSTALLED 6" PE GAS MAIN CURRENTLY CROSSING THE NE DRIVEWAY INTO PPTY IS IN THE WAY OF NEW SEWER LINE TO BE INSTALLED. WILL NEED TO RELOCATE 150' OF EXISTING 6" PE GAS MAIN 24' ECL. ON SITE CONTACT: JASON CORNELL 253-241-1293, PM/LUTHER RIMORIN 253-278-1118**DRILL

City

AUTHORIZED, **PRIVATE LOCATES AUTHORIZED ****

New Construction: Construction Method Directional Drill **Building Foundation Type**

