

202501080233

Electronically Recorded

Pierce County, WA ACLARK1  
01/08/2025 12:00 PM

Pages: 52 Fee: \$354.50

After recording return to:

City Clerk  
City of Puyallup  
333 South Meridian  
Puyallup, WA 98371

info@puyallupwa.gov

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	1/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

---

**Document Title:** Stormwater Outfall Management & BMP Facilities Agreement  
**Grantee:** City of Puyallup, a Washington State municipal corporation  
**Grantor:** Pierce College, a public community college of the State of Washington  
**Legal Description:** Section 03, Township 19, Range 04  
**Complete Legal Description on Page 5 of this Document**  
**Assessor's Tax Parcel or Account Numbers:** 0419034039  
**Reference Number of Related Document(s):** N/A

## Stormwater Management & BMP Facilities Agreement

- A. Parties.** The parties to this agreement are Grantee City of Puyallup, a Washington State municipal corporation (City), and Grantor landowner Pierce College, a public community college of the State of Washington (Landowner).
- B. Property.** Landowner is the owner of certain real property (Property), which is legally described in this document and is located at the following address: 1601 39th Ave SE, Puyallup, WA 98374.
- C. Development Plan & Stormwater Facilities.** The site, subdivision or other development plan (Plan) for the Property, specifically known, entitled or described as Puyallup Campus Parking Expansion for Lot A, provides for detention, retention, treatment or management of stormwater that is associated with the Property through the use of identified stormwater facilities or best management practices (collectively, Stormwater Facilities). Upon approval of the Plan by the City, the Plan shall be incorporated herein by this reference. In accordance with the Plan, Landowner shall adequately construct, operate, use, maintain and repair the Stormwater Facilities.

RANGE	TOWNSHIP	SECTION	QUARTER	016	2/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

- D. Agreement.** On the terms and conditions set forth herein, the City and Landowner agree as follows:
1. The Stormwater Facilities shall be constructed, operated, used, maintained and repaired by Landowner in accordance with the requirements of the Plan, and any other applicable law or regulation.
  2. Landowner (which expressly includes its agents, successors and assigns, including any homeowners association) shall adequately and properly operate, use, maintain and repair the Stormwater Facilities as described in the maintenance and operations manual, which is on file with the City, and may be attached and recorded herewith as Exhibit A. This duty extends to all associated pipes and channels, as well as all structures, improvements, and vegetation that are provided to control the quantity and quality of the stormwater. Adequate maintenance shall mean maintenance that is sufficient to keep the Stormwater Facilities in good working order and operating so as to satisfy the design and performance standards of the Plan.
  3. Landowner shall regularly inspect the Stormwater Facilities and shall submit an inspection report to the City at least once a year on a date prescribed by the City. The purpose of the inspection(s) is to ensure that the Stormwater Facilities are safe and functioning properly. The scope of the inspection shall include the entire Stormwater Facilities, including but not limited to, berms, outlet structures, pond areas, access roads, and so forth. Deficiencies and any performance or other related issues shall be noted by Landowner in the inspection report. The annual report shall be in a form and include content as prescribed from time to time by the City. An example copy of the report form may be attached hereto as Exhibit B.
  4. Landowner hereby grants permission to the City to enter upon the Property to inspect the Stormwater Facilities. Except in case of emergency, the City shall provide Landowner with at least forty-eight (48) hours written notice prior to entering on to the Property. Landowner shall be entitled to have a representative accompany the City during such inspection. The City shall provide Landowner with copies of written inspection reports.
  5. If Landowner fails to adequately and properly operate, use, maintain or repair the Stormwater Facilities, the City shall notify Landowner in writing and provide Landowner with a reasonable opportunity to cure. If Landowner fails to timely cure, then the City may enter upon the Property and remedy the issue(s) identified in the notice and those reasonably related thereto; Furthermore, if the City performs work of any nature, or expends any funds in performance of said work for labor, use of equipment, supplies, materials, and the like while remedying the identified issues, the City may charge the cost of the remedy to Landowner, and Landowner shall promptly pay the costs to the City. Notwithstanding the foregoing, the City shall be under no obligation to inspect, maintain or repair the Stormwater Facilities.
  6. Landowner shall defend, indemnify and hold the City, its officers, officials, employees and volunteers harmless from any and all claims, injuries, damages, losses or suits including attorney fees, arising out of or in connection with activities or operations, performed by Landowner, or on Landowner's behalf, that relate to the Stormwater Facilities and the subject matter of this agreement. The City shall defend, indemnify and hold the Landowner, its officers, officials, employees and volunteers harmless from any and all claims, injuries, damages, losses or suits including attorney fees, arising out of or in connection with negligent activities or operations, performed by the City, or on City's behalf, that relate to the Stormwater Facilities and the subject matter of this agreement.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	3/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER


- E. Covenant.** The terms and provisions of this agreement constitute a covenant, which is subject to the following: This covenant is an equitable covenant. It touches and concerns the land that is described as the Property herein. The parties intend that this covenant shall bind the parties' successor and assigns. This covenant shall run with the land that is described as the Property herein, and shall bind whoever has possession of the land, in whole or in part, without regard to whether the possessor has title, or has succeeded to the same estate that granting parties have or had. Possessors shall include, but are not limited to, leasehold tenants, contract purchasers, subtenants, and adverse possessors. This covenant shall run with the land even in the absence of the transfer of some interest in land, other than the covenant itself, between Landowner and the City. This covenant shall not be governed by the mutuality rule. The burden of the covenant can run independently from the benefit of the covenant, and the benefit need not run. The benefit may be in gross or personal to Landowner or the City. Landowner waives its right to assert any defenses to the enforcement of this covenant, including, but not limited to, the change of neighborhood doctrine, laches, estoppel, balancing of hardships, and abandonment. If Landowner breaches any term of this covenant and agreement, then all remedies in equity and at law, including, but not limited to, injunctions, mandamus, declaratory judgments, and damages, shall be available to the City.
- F. Governing Law & Venue.** This agreement shall be governed by and construed in accordance with the laws of the State of Washington. The venue for any action that arises from or out of this instrument shall be the Pierce County Superior Court.

*<signature page to follow>*

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	4/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER


State of Washington  
State Board for Community and Technical Colleges

Dated: 12/30/24

BY:   
~~Paul Francis~~ CHRISTOPHER BAILEY  
Executive Director for the Washington State Board  
for Community and Technical Colleges


City of Puyallup

Dated: 1/9/2025


BY:   
Kenneth Cook  
Development Engineering Manager

City of Puyallup


Dated: 12/4/2024

BY: DocuSigned by:   
EF58AD0C2E5574B  
Approved as to form:  
Joseph N. Beck  
City Attorney

STATE OF WASHINGTON )  
)  
COUNTY OF PIERCE ) -ss

Signed or attested before me on 12.30.24 by  ~~Paul Francis~~ as Executive Director for the Washington State Board for Community and Technical Colleges.

Dated: 12.30.24



Susan Locke  
Printed Name:  
Notary Public, State of: WASHINGTON  
My appointment expires: 4.12.27

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	5/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

**Parcel 0419034039 Legal Description**

THAT PORTION OF THE SOUTHWEST QUARTER OF SECTION 2 AND OF THE SOUTHEAST QUARTER OF SECTION 3, TOWNSHIP 19 NORTH, RANGE 4 EAST, WILLAMETTE MERIDIAN, PIERCE COUNTY, WASHINGTON, DESCRIBED AS FOLLOWS:  
 BEGINNING AT A POINT ON THE EAST LINE OF SAID SECTION 3, SAID POINT BEARS NORTH 00°13'37" EAST 60.10 FEET FROM THE SOUTHEAST CORNER OF SAID SECTION 3 AND IS ALSO THE NORTH MARGIN OF 112TH STREET EAST (39TH AVENUE SE); THENCE ALONG SAID NORTH MARGIN NORTH 86°30'40" WEST 1015.14 FEET TO THE EAST LINE OF THE PARCEL OF LAND DESCRIBED IN PIERCE COUNTY AUDITOR'S NUMBER 2362554; THENCE NORTH 00°13'59" EAST 1758.59 FEET; THENCE NORTH 45°03'08" EAST 722.96 FEET TO THE WESTERLY MARGIN OF WILDWOOD PARK DRIVE (SCHOOL ROAD EAST), AS CONVEYED TO PIERCE COUNTY BY INSTRUMENT RECORDED UNDER AUDITOR'S NO. 3125764 AND 2135764; THENCE ALONG SAID WESTERLY MARGIN THE FOLLOWING COURSE: SOUTH 08°28'11" EAST 195.80 FEET TO THE BEGINNING OF A CURVE, CONCAVE TO THE NORTHEAST, HAVING A RADIUS OF 331.56 FEET; THENCE ALONG THE ARC OF SAID CURVE, PASSING THROUGH A CENTRAL ANGLE OF 79°33'34" A DISTANCE OF 460.40 FEET; THENCE SOUTH 88°01'45" EAST 289.96 FEET TO THE BEGINNING OF A CURVE, CONCAVE TO THE SOUTHWEST, HAVING A RADIUS OF 760.23 FEET; THENCE ALONG THE ARC OF SAID CURVE, PASSING THROUGH A CENTRAL ANGLE OF 82°42'29" A DISTANCE OF 1097.41 FEET; THENCE SOUTH 05°19'16" EAST 19.70 FEET TO THE BEGINNING OF A CURVE, CONCAVE TO THE NORTHEAST, HAVING A RADIUS OF 848.57 FEET; THENCE ALONG THE ARC OF SAID CURVE, PASSING THROUGH A CENTRAL ANGLE OF 22°18'00" A DISTANCE OF 330.27 FEET; THENCE SOUTH 27°37'16" EAST 106.86 FEET; THENCE SOUTH 62°34'14" WEST 37.70 FEET; THENCE SOUTH 37°57'43" WEST 64.30 FEET; THENCE SOUTH 65°18'15" WEST 74.47 FEET; THENCE SOUTH 12°29'28" WEST 53.54 FEET; THENCE SOUTH 64°36'58" WEST 64.85 FEET; THENCE SOUTH 49°35'52" WEST 94.92 FEET; THENCE SOUTH 23°59'34" WEST 126.39 FEET; THENCE SOUTH 21°03'12" WEST 264.77 FEET; THENCE SOUTH 09°30'04" WEST 146.09 FEET TO SAID NORTH MARGIN OF 112TH STREET EAST; THENCE ALONG SAID MARGIN NORTH 88°31'34" WEST 610.67 FEET TO EAST LINE OF SAID SECTION 3; THENCE NORTH 00°13'37" EAST 5.09 FEET TO THE POINT OF BEGINNING.

TOGETHER WITH:

(Wetlands Parcel)

THAT PORTION OF THE SOUTHWEST QUARTER OF SECTION 2, TOWNSHIP 19 NORTH, RANGE 4 EAST, WILLAMETTE MERIDIAN, PIERCE COUNTY, WASHINGTON; DESCRIBED AS FOLLOWS:

COMMENCING AT A POINT ON THE WEST LINE OF SAID SECTION 2, SAID POINT BEARS NORTH 00°13'37" EAST 55.01 FEET FROM THE SOUTHWEST CORNER OF SAID SECTION 2 AND IS ALSO THE NORTH MARGIN OF 112TH STREET EAST (39TH AVENUE SE); THENCE ALONG SAID NORTH MARGIN SOUTH 88°31'34" EAST 610.67 FEET TO THE POINT OF BEGINNING; THENCE NORTH 09°30'04" WEST 146.09 FEET; THENCE NORTH 21°03'12" EAST 264.77 FEET; THENCE NORTH 23°59'34" EAST 126.39 FEET; THENCE NORTH 49°35'52" EAST 94.92 FEET; THENCE NORTH 64°36'58" EAST 64.85 FEET; THENCE NORTH 12°29'28" EAST 53.54 FEET; THENCE NORTH 65°18'15" EAST 74.47 FEET; THENCE NORTH 37°57'43" EAST 64.30 FEET; THENCE NORTH 62°34'14" EAST 37.70 FEET TO A POINT OF THE WESTERLY MARGIN OF WILDWOOD PARK DRIVE (SCHOOL ROAD EAST); THENCE SOUTH 27°37'16" EAST ALONG SAID WESTERLY MARGIN A DISTANCE OF 51.87 FEET TO THE BEGINNING OF A CURVE, CONCAVE TO THE SOUTHWEST, HAVING A RADIUS OF 920.34 FEET; THENCE ALONG THE ARC OF SAID CURVE, PASSING THROUGH A CENTRAL ANGLE OF 29°05'30" A DISTANCE OF 467.30 FEET; THENCE SOUTH 01°28'14" WEST 259.81 FEET TO THE SAID NORTH MARGIN OF 112TH STREET EAST; THENCE ALONG SAID NORTH MARGIN NORTH 88°31'34" WEST 470.95 FEET; THENCE SOUTH 10°42'07" WEST 5.07 FEET; THENCE NORTH 88°31'34" WEST 55.77 FEET TO THE POINT OF BEGINNING.



SUBJECT TO AND TOGETHER WITH ALL EASEMENTS OF RECORD.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	6/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

**Exhibit A**

Operation and Maintenance Manual

RANGE	TOWNSHIP	SECTION	QUARTER	016	7/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER



**Private Stormwater Facilities  
Operation & Maintenance Manual**

*PREPARED FOR:*

McGranahan Architects  
Contact: Mr. Andy Hartung  
2111 Pacific Avenue, Suite 100  
Tacoma, WA 98402

*PROJECT:*

Pierce College Puyallup  
Campus Parking Expansion – Lot A  
Puyallup, WA  
2200718.13

*PREPARED BY:*

Claire Hovde, PE  
Project Engineer

*REVIEWED BY:*

William J. Fierst, PE  
Principal

*DATE*

September 2023  
Revised January 2024

*Civil Engineers • Structural Engineers • Landscape Architects • Community Planners • Land Surveyors*

RANGE	TOWNSHIP	SECTION	QUARTER	016	8/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

**Private Stormwater Facilities  
Operation & Maintenance Manual**

*PREPARED FOR:*

McGranahan Architects  
Contact: Mr. Andy Hartung  
2111 Pacific Avenue, Suite 100 Tacoma,  
WA 98402

*PROJECT:*

Pierce College Puyallup  
Campus Parking Expansion – Lot A  
Puyallup, WA  
2200718.13

*PREPARED BY:*


Claire Hovde, PE  
Project Engineer

*REVIEWED BY:*

William J. Fierst, PE  
Principal

*DATE*

September 2023  
Revised January 2024



01/17/2024

I hereby state that this Private Stormwater Facilities Operation & Maintenance Manual for the Pierce College - Puyallup Campus Parking Expansion project has been prepared by me or under my supervision and meets the standard of care and expertise that is usual and customary in this community for professional engineers. I understand that City of Puyallup does not and will not assume liability for the sufficiency, suitability, or performance of drainage facilities prepared by me.



RANGE	TOWNSHIP	SECTION	QUARTER	016	9/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

***Table of Contents***

---

Section	Page
1.0 Introduction.....	1
2.0 Responsibility .....	1
3.0 Schedule.....	1
4.0 Cost .....	1
5.0 Vegetation Management Plan.....	1
6.0 Instructions for Person Maintaining Stormwater System .....	2
7.0 Conclusion .....	2



RANGE	TOWNSHIP	SECTION	QUARTER	016	10/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

**Appendices**

---

- Maintenance Checklists
- Annual Inspection Report



RANGE	TOWNSHIP	SECTION	QUARTER	016	11/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

**1.0 Introduction**

The Pierce College Puyallup Campus maintenance staff shall be responsible for maintaining properly functioning stormwater control facilities. This report presents a maintenance program that meets City of Puyallup maintenance requirements. The private stormwater facilities for this project include a system of catch basins and pipes to collect surface runoff and route it through a bioretention facility for stormwater treatment prior to routing to a detention pond.

It is vitally important that the proponent/owner maintain these facilities in a timely and conscientious manner to ensure the facilities function as designed. Siltation, debris, or lack of maintenance can reduce the capabilities of the conveyance system which can lead to localized flooding. If bioretention facilities are not maintained in accordance with the attached maintenance checklist, onsite stormwater can contribute to negative water quality to downstream waterbodies of the state.

**2.0 Responsibility**

The private stormwater facilities will be owned and maintained by Pierce College Puyallup Campus maintenance personnel.

Property Owner:

Pierce College Puyallup  
 1601 39<sup>th</sup> Avenue SE  
 Puyallup, WA 98374  
 (253) 840-8400

**3.0 Schedule**

Maintenance of the stormwater facilities shall follow the schedule as specified in the attached maintenance checklists. Additional maintenance may be required to respond to unusual storm events or reduced performance of the treatment system. A copy of the City of Puyallup-recommended maintenance schedule is attached and may be photocopied and used as inspection records. An annual inspection report must be submitted to the City of Puyallup in accordance with the Maintenance Agreement.

**4.0 Cost**

The following is an estimate of the average annual cost of maintenance for the stormwater control facilities within the scope of this project.

Vactor truck @ \$200/hour x 12 hours	\$2,400
Personnel @ \$25/hour x 12 hours	\$300
Dumping Fees @ \$50/ton x 12 tons	\$600
<u>Sweep Parking Lot Once Yearly</u>	<u>\$1,500</u>
<b>Total Estimated Annual Cost</b>	<b>\$4,800</b>

**5.0 Vegetation Management Plan**

The attached maintenance schedule provides guidance on vegetation control and management. Irrigation and other maintenance as necessary shall be provided to ensure that vegetation remains viable and that a hardy root structure forms in the first year. Vegetation planting shall be provided, as described in the construction documents.



RANGE	TOWNSHIP	SECTION	QUARTER	016	12/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## 6.0 Instructions for Person Maintaining Stormwater System

The attached Maintenance Checklists specify maintenance schedules for stormwater facilities onsite. Plan to complete a checklist for all system components per the following schedule:

1. Monthly from November through April.
2. Once in late summer (preferably September).
3. After major storm events.

Using photocopies of the attached pages, check off the problems that are noted each time the item is inspected. Document comments on problems found and the corrective action taken. The Inspection Checklist sheets should be kept on file for the City to inspect at all reasonable times and used to prepare the annual report required by City of Puyallup, due no later than January 30 for the preceding year's report.

## 7.0 Conclusion

This Operation and Maintenance Manual is developed for the operation of the Pierce College Puyallup Campus Parking Expansion – Lot A private stormwater systems. This Maintenance document has been prepared within the guidelines of City of Puyallup Construction Standards. If this plan is implemented, the owner can expect the stormwater system to function as designed.

AHBL, Inc.



Claire Hovde, PE  
Project Engineer

CFH/jms/lsk

September 2023  
Revised January 2024

Q:\2020\2200718\WORDPROC\Reports\2200718.13\20240117 Rpt (O&M) 2200718.13.docx

RANGE	TOWNSHIP	SECTION	QUARTER	016	13/ 52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## ***Maintenance Checklists***

---




RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	14/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Bioretention System

Bioretention facilities are engineered facilities that store and treat stormwater by filtering it through a specified soil profile. Water that enters the facility ponds in an earthen depression or other basin (e.g., concrete planter) before it infiltrates into the underlying bioretention soil. Stormwater that exceeds the surface storage capacity overflows to an adjacent drainage system. Treated water is either infiltrated into the underlying native soil or collected by an underdrain and discharged. An underdrain system can be comprised of perforated or slotted pipe, wrapped in an aggregate blanket.

Facility objects that are often associated with a bioretention unit include:

- Inlet
- Overflow
- Underdrains (optional)
- Signage
- Catch Basin
- Drywell



## Key Operations and Maintenance Considerations

- Protect the facility from external loads (e.g. trucks, riding mowers, other heavy equipment) to preserve the proper function of bioretention soils. Because the risk of compaction is higher when soils are saturated, any type of loading in the bioretention facility (including foot traffic) should be avoided during wet conditions. All maintenance activities must be performed in a manner to prevent compaction of the bioretention soil.
- Erosion control measures must be maintained in areas of concentrated flows (e.g., pipes inlets or narrow curb cuts). Inspect flow entrances, ponding area, and surface overflow areas periodically, and replace soil, plant material, and/or mulch layer in areas if erosion has occurred. Properly

RANGE	TOWNSHIP	SECTION	QUARTER	016	15/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

designed facilities with appropriate flow velocities should not have erosion problems except perhaps in extreme events. If erosion problems occur, the following should be reassessed:

- (1) flow volumes from contributing areas and bioretention cell sizing; (2) flow velocities and gradients within the cell; and (3) flow dissipation and erosion protection strategies in the pretreatment area and flow entrance. If sediment is deposited in the bioretention area, immediately determine the source within the contributing area, stabilize, and remove excess surface deposits.
- Establish and follow a maintenance schedule for visual inspection and remove sediment if the volume of the ponding area has been compromised.
- Corrective maintenance for excessive drawdown times may include clearing underdrain obstructions or tilling the bioretention soil media. Partial or complete replacement of bioretention soil media may be necessary.
- Regular maintenance of vegetation includes weeding and pruning. Plants require irrigation during the first 2 to 3 years of establishment and during extended dry periods. Replace all dead plants and, if specific plants have a high mortality rate, assess the cause and replace with appropriate species.
- The soil mix and plants are selected for optimum fertility, plant establishment, and growth. Nutrient and pesticide inputs should not be required and may degrade the pollutant processing capability of the bioretention area, as well as contribute pollutant loads to receiving waters. If in question, have soil analyzed for fertility.
- Replace mulch annually in bioretention facilities where heavy metal deposition is high (e.g., contributing areas that include gas stations, ports and roads with high traffic loads). In residential settings or other areas where metals or other pollutant loads are not anticipated to be high, replace or add mulch as needed (likely 3 to 5 years) to maintain a 2 to 3-inch depth.
- Soil mixes for bioretention facilities are designed to maintain long-term fertility and pollutant processing capability. Estimates from metal attenuation research suggest that metal accumulation should not present an environmental concern for at least 20 years in bioretention systems, but this will vary according to pollutant load. Replacing mulch media in bioretention facilities where heavy metal deposition is likely provides an additional level of protection for prolonged performance. If in question, have soil analyzed for fertility and pollutant levels.
- Presence of pests such as geese or rodents can generally be corrected by ensuring that drawdown time matches facility design function and plants are spaced at proper densities.
- If an underdrain is present, remove trash, debris, and sediment from the inlet orifice biannually.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	16/ 52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

- Irrigate or hand-water vegetation as needed to help plants establish in the first few years after installation and as needed after plants are established. The following schedule is recommended:
  - Provide watering weekly for two summers. On average, plants require 1-inch of water weekly to establish. Additional water may be necessary during excessive heat.
  - Provide summer watering every two to four weeks during the summer or as needed during prolonged dry periods.
  - Provided summer watering as needed after plants are established.

Refer to City of Puyallup Engineering and Construction Standards Section 600 for grass specifications and planting requirements.



RANGE	TOWNSHIP	SECTION	QUARTER	016	17/52
04E-	19N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Bioretention System			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
General	Pests	Signs of pest infestations (IPM protocol threshold(s) are exceeded), including rodent holes or mounds that disturb dispersion flow paths.	<p>Pests are not present or engaged in activities that present a significant public health risk or compromise to the intended design function of the facility. Pests that have exceeded acceptable thresholds have been addressed using appropriate IPM measures.</p> <p>Standing water that may allow mosquito breeding has been removed and cause of standing water has been addressed (see "Ponded Water").</p> <p>Pest-damaged vegetation has been removed.</p>
Facility Area	Trash and Debris	Trash and debris present in facility area.	Facility area is free of trash and debris.
	Pet Waste	Large volumes of feces from domestic pets are present.	<p>Pet waste removed.</p> <p>Pet waste station or additional signage installed, if appropriate.</p>
	Mulch	Mulch depth is less than 2 inches or the facility has bare spots without mulch cover.	Mulch has been restored to a depth of 2-3" and is appropriate to the location within the facility (e.g. compost mulch in the bottom and wood chips on side slopes).
Facility Bottom Area	Sediment	Sediment accumulated to extent that infiltration rate is reduced, water can be seen to be ponding, or surface storage capacity is significantly impacted.	<p>Source of sediment has been identified and controlled.</p> <p>Excess sediment has been removed, and damaged vegetation and mulch has been replaced.</p>
	Leaves	After fall leaf drop, leaves have accumulated in the facility in a manner to pose a risk of impeding water flow or clogging the outlet.	Leaves have been removed.
	Ponded Water	Water overflows during storms smaller than the design event, or ponded water remains in the basin more than 48 hours after the end of a storm.	Cause of excessive ponding has been identified by investigating: 1) potential that debris build-up is impeding infiltration; 2) condition of underdrain (if present); 3) potential that other water inputs are present (e.g. groundwater, illicit connections); 4) facility size is appropriate to contributing area; and 5) condition of bioretention soil media.

RANGE	TOWNSHIP	SECTION	QUARTER	016	18/ 52
04E-	19N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Bioretention System			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
			Cause of excessive ponding has been corrected. Engineer has been consulted where necessary.
Earthen Side Slopes and Berms	Erosion at Inlets/ Outlets	Erosion (gullies/ rills) greater than 2 inches deep around inlets, outlet, and alongside slopes.	For channels or cuts over 3 inches deep, temporary erosion control measures have been put into place until permanent repairs are made.  Source of erosion has been addressed/ eliminated and eroded areas repaired per design specifications, with additional stabilizing material (cobbles, vegetation, etc.) added as necessary.
	Erosion of Side Slopes	Erosion of sides causes slope to become a hazard.	Source of erosion has been addressed and side slopes repaired to design specifications. Slopes have stabilizing material where necessary.
	Settlement	Settlement greater than 3 inches (relative to undisturbed sections of berm).	Slopes and berm have been restored to design elevations/ heights.
	Berm Leaking	Downstream face of berm wet; seeps or leaks evident.	Any seeps or leaks have been plugged and berm material and compaction are per design specifications. Engineer has been consulted where necessary.
	Rodents in Berm	Any evidence of rodent holes or water piping in berm.	Rodents have been eradicated (see "Pests in Facility"). Holes have been filled and berm compacted (see "Berm Leaking").
Amended Soil	Soil Nutrients	Soil not providing plant nutrients.	Soil providing plant nutrients.
	Bare Spots	Bare spots on soil in bioretention area.	No bare spots. Bioretention area covered with vegetation or mulch mixed into the underlying soil.
	Compaction	Poor infiltration due to soil compaction in the bioretention area.	No soil compaction in the bioretention area.
Low Permeability Check Dams and Weirs	Sediment or Other Debris Blocking	Sediment, vegetation, or debris accumulated at or blocking (or having the potential to block) check dam, flow control weir or orifice.	No blockage present of check dam, flow control weir, or orifice. Any likely immediate sources of additional debris or sediment (additional dead plant material, erosion issue, etc. upstream) addressed or removed.
	Erosion or Undercutting	Erosion and/or undercutting present.	Eroded and/or undercut areas have been repaired and sources of issue addressed to prevent further erosion/undercutting at weir.
	Grade Board Not Level	Grade board or top of weir damaged or not level.	Grade board is undamaged (repaired or replaced) and level.

RANGE	TOWNSHIP	SECTION	QUARTER		19/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Bioretention System			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
Inlet	Erosion at Inlet	Concentrated flows are causing erosion at inlet.	A cover of rock or cobbles or other erosion protection measure (e.g., matting) is in place to protect the ground where concentrated water enters the facility (e.g., a pipe, curb cut or swale).
Splash Block Inlet	Water Misdirected from Inlet	Water is not being directed properly to the facility and away from the inlet structure.	Splash block(s) reconfigured/ repaired to direct water to facility and away from structure.
Curb Inlet/Outlet	Leaf Accumulation at Curb Cut	Accumulated leaves or other debris at curb cuts (inlets and outlets) can block water flow and proper function of the facility. Maintenance is particularly important in the fall.	Curb cuts and adjacent gutters are free of leaves and debris, and water can flow freely into (and out of) the facility.
Pipe Inlet/Outlet	Pipe is Damaged	Pipe is damaged.	Pipe repaired or replaced to design specifications.
	Pipe is Clogged	Pipe is clogged, completely or partially. Problem material may include leaves, debris, trash, roots, sediment, or other material.	Pipe is unclogged and free of any obstructions. Pipe functioning at design capacity.
	Access is Blocked	Vegetation is blocking access for inspection.	Area within 1 foot of inlets/outlets is clear of vegetation, and access pathways are clear and maintained where necessary.
Trash Rack	Trash and Debris	Trash or other debris is present on trash rack. Capacity may be reduced by buildup of trash or debris.	Trash rack is free of trash, leaves, debris, or other foreign material.
	Bar Screen Damage	Bar screen on trash rack is damaged or missing.	Bar screen has been repaired/ replaced to design specifications.
Overflow	Overflow Blocked	Overflow capacity is reduced by sediment or debris.	Overflow area is free of sediment and debris and capacity functions per design standards.
Underdrain Pipe	Reduced Capacity	Plant roots, sediment, or debris may reduce the capacity of the underdrain. Symptoms may include ponded water in facility bottom area.	Underdrain pipe is free of plant roots, sediment, and debris. Infiltration and pipe capacity functioning per design function.
Vegetation (continues on next page)	Plant Health	Plants not thriving across at least 80% of the entire design vegetated area within the BMP; overly dense vegetation requiring pruning.	Healthy water tolerant plants in bioretention area, plants thriving across at least 80% of the entire design vegetated area within the facility.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	20/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Bioretention System			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
	Diseased Plant Material	Diseased plants or plant material is present in the facility.	Diseased plants have been removed and disposed of in an approved location (off-site). Potential sources of and conditions exacerbating disease have been addressed (see Pacific Northwest Plant Disease Management Handbook). Vegetated areas replanted as necessary to maintain vegetative coverage per design.
	Vegetation Needs Pruning	Trees and shrubs need regular maintenance and/or corrective pruning.	Trees and shrubs pruned per routine maintenance schedule, appropriate to individual species and age of plants. All pruning of mature trees done under direct supervision of ISA certified arborist.
	Large Trees and Shrubs Interfering	Large trees and shrubs interfere with operation of the facility or access for maintenance.	Trees and shrubs have been pruned using most current ANSI A300 standards and ISA BMPs. Trees and shrubs removed if necessary for operation of facility per design function.
	Dead Vegetation	Standing dead vegetation is present (particularly in fall and spring).	Standing dead vegetation has been removed from site; gaps in vegetation have been replaced with new plantings where necessary, or appropriate erosion control measures put in place until vegetation replacement is feasible.
	Maintenance Needed Around Mature Trees	If conditions warrant maintenance work or planting of new vegetation around mature trees (within the dripline), appropriate care must be taken to avoid adverse impacts to the mature tree(s).	The most current ANSI A300 standards and ISA BMPs have been followed to the extent practicable (e.g., take care to minimize any damage to tree roots and avoid compaction of soil) when working around and under mature trees. New plantings under mature trees include mainly plants that come as bulbs, bare root or in 4-inch pots; new plants in no larger than 1-gallon containers.
	Stakes or Guys Present	Stakes or guys present in plantings installed for over 1 year.	Stakes or guys have been removed from new vegetation after 1 year since installation. Holes have been backfilled where necessary.
	Vehicular Sight Lines Impaired by Vegetation	Vegetation causes some visibility (line of sight) or driver safety issues.	Vegetation has been pruned to appropriate height and spread to maintain sight clearances. If continued (regular) pruning of a given plant have been necessary, plant(s) have been relocated to a more appropriate location and replaced with plant(s) of appropriate mature size.
	Emergent Vegetation Compromises Conveyance	Emergent vegetation compromises conveyance (may become too dense).	Emergent vegetation has been thinned and does not impede conveyance.

RANGE	TOWNSHIP	SECTION	QUARTER	016	21/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Bioretention System			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
	Noxious Weeds Present	Noxious weeds are present among the site vegetation. Remove, bag, and dispose of Class A & B noxious weeds immediately per WA law. Make reasonable attempts to remove and dispose of Class C noxious weeds. See <a href="http://www.nwcb.wa.gov/">http://www.nwcb.wa.gov/</a> . Follow Integrated Pest Management (IPM) protocols.	Noxious weeds are not present on site above thresholds established by WA law.

RANGE	TOWNSHIP	SECTION	QUARTER		22/52
04E-	19N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Catch Basin


A catch basin is an underground concrete structure typically fitted with a slotted grate to collect stormwater runoff and route it through underground pipes. Catch basins can also be used as a junction in a pipe system and may have a solid lid. There are two types.

A Type 1 catch basin is a rectangular box with approximate dimensions of 3'x2'x5'. Type 1 catch basins are utilized when the connected conveyance pipes are less than 18 inches in diameter and the depth from the gate to the bottom of the pipe is less than 5 feet.

A Type 2 catch basin, also commonly referred to as a storm manhole, is listed separately under "Manhole" in this book.

Catch basins typically provide a storage volume (sump) below the outlet pipe to allow sediments and debris to settle out of the stormwater runoff. Some catch basins are also fitted with a spill control device (inverted elbow on outlet pipe) intended to contain large quantities of grease or debris.

Catch basins are frequently associated with all stormwater facilities.



**Type 1**

RANGE	TOWNSHIP	SECTION	QUARTER	016	23/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

### Key Operations and Maintenance Considerations

- The most common tool for cleaning catch basins is an industrial vacuum truck with a tank and vacuum hose (e.g. Vactor® truck) to remove sediment and debris from the sump.
- A catch basin may be an enclosed space where harmful chemicals and vapors can accumulate. Therefore, if the inspection and maintenance requires entering a catch basin, it should be conducted by an individual trained and certified to work in hazardous confined spaces.

Catch Basin			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
General	Trash and Debris	Trash or debris which is located immediately in front of the catch basin opening or is blocking inletting capacity of the basin by more than 10%.	No trash or debris located immediately in front of catch basin or on grate opening.
		Trash or debris (in the basin) that exceeds 60 percent of the sump depth as measured from the bottom of basin to invert of the lowest pipe into or out of the basin, but in no case less than a minimum of six inches clearance from the debris surface to the invert of the lowest pipe.	No trash or debris in the catch basin.
		Trash or debris in any inlet or outlet pipe blocking more than 1/3 of its height.	Inlet and outlet pipes free of trash or debris.
		Dead animals or vegetation that could generate odors that could cause complaints or dangerous gases (e.g., methane).	No dead animals or vegetation present within the catch basin.
	Sediment	Sediment (in the basin) that exceeds 60 percent of the sump depth as measured from the bottom of basin to invert of the lowest pipe into or out of the basin, but in no case less than a minimum of 6 inches clearance from the sediment surface to the invert of the lowest pipe.	No sediment in the catch basin.
	Structure Damage to Frame and/or Top Slab	Top slab has holes larger than 2 square inches or cracks wider than 1/4 inch. (Intent is to make sure no material is running into basin.)	Top slab is free of holes and cracks.
		Frame not sitting flush on top slab, i.e., separation of more than 3/4 inch of the frame from the top slab. Frame not securely attached.	Frame is sitting flush on the riser rings or top slab and firmly attached.
	Fractures or Cracks in	Maintenance person judges that structure is unsound.	Basin replaced or repaired to design standards.

RANGE	TOWNSHIP	SECTION	QUARTER	016	24/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

	Basin Walls/ Bottom	Grout fillet has separated or cracked wider than 1/2 inch and longer than 1 foot at the joint of any inlet/outlet pipe or any evidence of soil particles entering catch basin through cracks.	Pipe is regouted and secure at basin wall.
	Settlement/ Misalignment	Catch basin has settled more than 1 inch or has rotated more than 2 inches out of alignment.	Basin replaced or repaired to design standards.
	Vegetation Inhibiting System	Vegetation growing across and blocking more than 10% of the basin opening.	No vegetation blocking opening to basin.
		Vegetation growing in inlet/outlet pipe joints that is more than six inches tall and less than six inches apart.	No vegetation or root growth present.
	Contaminants and Pollution	Any evidence of oil, gasoline, contaminants, or other pollutants. Sheen, obvious oil, or other contaminants present.  • Identify and remove source	No contaminants or pollutants present.
Catch Basin Cover	Cover Not in Place	Cover is missing or only partially in place. Any open catch basin requires maintenance.	Catch basin cover is closed.
	Locking Mechanism Not Working	Mechanism cannot be opened by one maintenance person with proper tools. Bolts into frame have less than 1/2 inch of thread. One or more bolts are missing.	Mechanism opens with proper tools. All bolts are seated and no bolts are missing. Cover is secure.
	Cover Difficult to Remove	One maintenance person cannot remove lid after applying normal lifting pressure (Intent is to keep cover from sealing off access to maintenance).	Cover can be removed by one maintenance person.
Metal Grates (If Applicable)	Grate Opening Unsafe	Grate with opening wider than 7/8 inch.	Grate opening meets design standards.
	Trash and Debris	Trash and debris that is blocking more than 20% of grate surface inletting capacity.	Grate free of trash and debris.
	Damaged or Missing	Grate missing or broken member(s) of the grate.	Grate is in place and meets design standards.
Oil/Debris Trap (If Applicable)	Dislodged	Oil or debris trap is misaligned with or dislodged from the outlet pipe.	Trap is connected to and aligned with outlet pipe.



RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	25/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Compost-Amended Soil

Naturally occurring (undisturbed) soil and vegetation provide important stormwater functions including: water infiltration; nutrient, sediment, and pollutant adsorption; sediment and pollutant biofiltration; water interflow storage and transmission; and pollutant decomposition.

Compaction from construction can reduce the soil's natural ability to provide these functions. Compost-amended soils are intended to replace these lost functions by establishing a minimum soil quality and depth in the post-development landscape.

Sufficient organic content is a key to soil quality. Soil organic matter can be attained through numerous amendments such as compost, composted woody material, biosolids, and forest product residuals. The full benefits of compost-amended soils are realized when desired soil media depths are maintained and soil compaction is minimized.

### Key Operations and Maintenance Considerations

- Replenish soil media as needed (as a result of erosion) and address compacted, poorly draining soils.
- Site uses should protect vegetation and avoid soil compaction. Care should be taken to prevent compaction of soils via vehicular loads and/or excessive foot traffic, especially during wet conditions.
- The table below provides the recommended maintenance frequencies, standards, and procedures for compost-amended soils. The level of routine maintenance required and the frequency of corrective maintenance actions may increase for facilities prone to erosion due to site conditions such as steep slopes or topography tending to concentrate flows.

RANGE	TOWNSHIP	SECTION	QUARTER	016	26/ 52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Compost-Amended Soil			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Soil Media	Soils Waterlogged or Not Infiltrating	Soils become waterlogged, or otherwise do not appear to be infiltrating.	Soils have been aerated or amended such that infiltration occurs and soils do not remain completely saturated, per design specifications.
	Erosion/Scouring	Areas of potential erosion are visible, such as gullies or scouring.	Any eroded areas have been repaired, and sources of erosion addressed to prevent further soil erosion.
Vegetation	Vegetation in Poor Health	Less than 75% of planted vegetation is healthy with a generally good appearance.	At least 75% of planted vegetation is healthy with generally good appearance. Any conditions found that were deleterious to plant health have been corrected where possible. Routine maintenance schedule has been updated as necessary to ensure continued plant health and satisfactory appearance.
	Poisonous Plants and Noxious Weeds	Any poisonous plants or nuisance vegetation which may constitute a hazard to maintenance personnel or the public.  Any evidence of noxious weeds as defined by State or local regulations.	No danger of poisonous vegetation where maintenance personnel or the public might normally be.  Eradication of Class A weeds as required by State law. Control of other listed weeds as directed by local policies.  Apply requirements of adopted IPM policy for the use of herbicides.
	Other Weeds Present	Other weeds (not listed on City/State noxious weed lists) are present on site.	Weeds have been removed per the routine maintenance schedule, following IPM protocols.

RANGE	TOWNSHIP	SECTION	QUARTER	016	27/ 52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER


## Control Structure/Flow Restrictor

Flow control structures and flow restrictors direct or restrict flow in or out of facility components. Outflow controls on detention facilities are a common example where flow control structures slowly release stormwater at a specific rate. The flow is regulated by a combination of orifices (holes with specifically sized diameters) and weirs (plates with rectangular or “V” shaped notch). Lack of maintenance of the control structure can result in the plugging of an orifice. If these flow controls are damaged, plugged, bypassed, or not working properly, the facility could overtop or release water too quickly.


Control structures have a history of maintenance-related problems and it is imperative to establish a good maintenance program for them to function properly. Sediment typically builds up inside the structure, which blocks or restricts flow to the outlet. To prevent this problem, routinely clean out these structures and conduct regular inspections to detect the need for non-routine cleanout.

Facility objects that are typically associated with a control structure/flow restrictor include:

- detention ponds
- media cartridge filters
- closed detention system
- conveyance stormwater pipe



RANGE	TOWNSHIP	SECTION	QUARTER	016	28/ 52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER



### Key Operations and Maintenance Considerations

- Conduct regular inspections of control structures to detect the need for non-routine cleanout, especially if construction or land-disturbing activities occur in the contributing drainage area.
- The most common tool for cleaning control structures/flow restrictors is a truck with a tank and vacuum hose (Vactor® truck) to remove sediment and debris from the sump.
- A control structure is an enclosed space where harmful chemicals and vapors can accumulate. Therefore, if the inspection and maintenance requires entering a control structure, it should be conducted by an individual trained and certified to work in hazardous confined spaces.

RANGE	TOWNSHIP	SECTION	QUARTER	016	29/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Control Structure/Flow Restrictor			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Structure	Trash and debris	Trash or debris of more than ½ cubic foot which is located immediately in front of the structure opening or is blocking capacity of the structure by more than 10%.	No Trash or debris blocking or potentially blocking entrance to structure.
		Trash or debris in the structure that exceeds 1/3 the depth from the bottom of basin to invert the lowest pipe into or out of the basin.	No trash or debris in the structure.
		Deposits of garbage exceeding 1 cubic foot in volume.	No condition present which would attract or support the breeding of insects or rodents.
	Sediment	Sediment exceeds 60% of depth from bottom of structure to invert of lowest pipe into or out of structure or bottom of FROP-T section or is within 6" of invert of lowest pipe into or out of structure or bottom of FROP-T section.	Sump of structure contains no sediment.
	Damage to frame and/or top slab	Top slab has holes larger than 2 square inches or cracks wider than ¼ inch.	Top slab is free of holes and cracks.
		Frame not sitting flush on top slab, separation of more than ¼ inch of the frame from the top slab.	Frame is sitting flush on top slab.
	Cracks in walls or bottom	Cracks wider than ½ inch and longer than 3 feet, any evidence of soil particles entering structure through cracks, or maintenance person judges that structure is unsound.	Structure is sealed and structurally sound.
		Cracks wider than ½" and longer than 1' at the joint of any inlet/outlet pipe or any evidence of soil particles entering structure through cracks.	No cracks more than 1/4 inch wide at the joint of inlet/outlet pipe.
	Settlement/ misalignment	Structure has settled more than 1 inch or has rotated more than 2 inches out of alignment.	Basin replaced or repaired to design standards.
	Damaged pipe joints	Cracks wider than ½" at joint of inlet/outlet pipes or any evidence of soil entering the structure at the joint of the inlet/outlet pipes.	No cracks more than ¼-inch wide at the joint of inlet/outlet pipes.
Contaminants and pollution	Any evidence of contaminants or pollution such as oil, gasoline, concrete slurries or paint.	Materials removed and disposed of according to applicable regulations. Source control BMPs implemented if applicable. No contaminants present other than a surface oil film.	
Ladder rungs missing or unsafe	Ladder is unsafe due to missing rungs, misalignment, rust, cracks, or sharp edges.	Ladder meets design standards and allows maintenance person safe access.	
FROP-T Section	Damage	T section is not securely attached to structure wall and outlet pipe structure should support at least 1,000 lbs of up or down pressure.	T section securely attached to wall and outlet pipe.
		Structure is not in upright position (allow up to 10% from plumb).	Structure in correct position.
		Connections to outlet pipe are not watertight or show signs of deteriorated grout.	Connections to outlet pipe are water tight; structure repaired or replaced and works as designed.
		Any holes—other than designed holes—in the structure.	Structure has no holes other than designed holes.
Shear Gate	Damaged or missing	Shear gate is missing.	Replace shear gate.
		Shear gate is not watertight.	Gate is watertight and works as designed.

RANGE	TOWNSHIP	SECTION	QUARTER		30/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

		Gate cannot be moved up and down by one maintenance person.	Gate moves up and down easily and is watertight.
		Chain/rod leading to gate is missing or damaged.	Chain is in place and works as designed.
Orifice Plate	Damaged or missing	Control device isn't working properly due to missing, out of place, bent orifice plate.	Plate is in place and works as designed.
	Obstructions	Any trash, debris, sediment, or vegetation blocking the plate.	Plate is free of all obstructions and works as designed.
Overflow Pipe	Obstructions	Any trash or debris blocking (or having the potential of blocking) the overflow pipe.	Pipe is free of all obstructions and works as designed.
	Deformed or damaged lip	Lip of overflow pipe is bent or deformed.	Overflow pipe does not allow overflow at an elevation lower than design
Inlet/Outlet Pipe	Damaged	Cracks wider than 1/8" at joint of the inlet/outlet pipes or any evidence of soil entering at the joints of the inlet/outlet pipes.	No cracks more than 1/4-inch wide at the joint of the inlet/outlet pipe.
Metal Grates (If Applicable)	Unsafe grate opening	Grate with opening wider than 7/8 inch.	Grate opening meets design standards.
	Trash and debris	Trash and debris that is blocking more than 20% of grate surface.	Grate free of trash and debris.
	Damaged or missing	Grate missing or broken member(s) of the grate.	Grate is in place and meets design standards.
Manhole Cover/Lid	Cover/lid not in place	Cover is missing or only partially in place. Open structure requires urgent maintenance.	Cover/lid protects opening to structure.
	Locking mechanism Not Working	Mechanism can't be opened by one maintenance person with proper tools. Bolts can't be seated. Cover does not work.	Mechanism opens with proper tools.
	Cover/lid difficult to Remove	One maintenance person cannot remove cover/lid after applying 80 lbs. of lift.	Cover/lid can be removed and reinstalled by one maintenance person.

RANGE	TOWNSHIP	SECTION	QUARTER	016	31/ 52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Conveyance Pipe

Storm sewer pipes convey stormwater. Inlet and outlet stormwater pipes convey stormwater in, through, and out of stormwater facilities.

Pipes are built from many materials. Pipes are cleaned to remove sediment or blockages when problems are identified. Stormwater pipes must be clear of obstructions and breaks to prevent localized flooding. All stormwater pipes should be in proper working order and free of the possible defects listed below.

### Key Operations and Maintenance Considerations

- The most common tool for cleaning stormwater conveyance pipes is a truck with a tank, vacuum hose, and a jet hose (Vactor® truck) to flush sediment and debris from the pipes.


Conveyance Pipe			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
General	Contaminants and Pollution	Any evidence of oil, gasoline, contaminants, or other pollutants. Sheen, obvious oil, or other contaminants present. <ul style="list-style-type: none"> <li>Identify and remove source.</li> </ul>	No contaminants or pollutants present.
	Obstructions, Including Roots	Root enters or deforms pipe, reducing flow.	Roots have been removed from pipe (using mechanical methods; don't put root-dissolving chemicals in storm sewer pipes). Vegetation over the line removed.
	Sediment and Debris	Sediment depth is greater than 20% of pipe diameter.	Pipe has been cleaned and is free of sediment/ debris. (Upstream debris traps installed where applicable.)
	Debris Barrier or Trash Rack Missing	Stormwater pipes > than 18 inches need debris barrier.	Debris barrier present on all stormwater pipes 18 inches and greater.
	Damage to protective coating or corrosion	Protective coating is damaged; rust or corrosion is weakening the structural integrity of any part of pipe.	Pipe repaired or replaced.
	Damaged	Any dent that decreases cross section area of pipe by more than 20% or determined to have weakened structural integrity of the pipe.	Pipe repaired or replaced.

RANGE	TOWNSHIP	SECTION	QUARTER	016	32/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

### Debris Barrier & Access Barrier (e.g. Trash Rack)

A debris barrier is a bar grate over the open end of a culvert or stormwater conveyance pipe. The intent of a debris barrier is to prevent large materials from entering a closed pipe system. Debris barriers are typically located on the outlet pipe from a detention pond to the control structure. If a debris barrier is not located on an outlet pipe of 18-inch diameter or greater, one should be installed to prevent plugging of the control structure and possible flooding.

An access barrier is installed on a pipe end that is large enough to allow entry. Their function is to prevent debris and unauthorized access into the storm conveyance pipe. Only qualified personnel should attempt to maintain or remove debris from the barrier when water is flowing through the conveyance pipe.





RANGE	TOWNSHIP	SECTION	QUARTER	016	33/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

### Key Operations and Maintenance Considerations

- The most common tool for cleaning debris and access barriers are hand tools such as a rake to remove collected debris.

Debris Barrier			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
General	Trash and Debris	Trash or debris that is plugging more than 20% of the openings in the barrier.	Barrier cleared to design flow capacity.
	Damaged/ Missing Bars	Bars are bent out of shape more than 3 inches.	Bars in place with no bends more than 3/4 inch.
		Bars are missing or entire barrier missing.	Bars in place according to design specifications.
		Bars are loose and rust is causing 50% deterioration to any part of barrier.	Barrier replaced or repaired to design specifications.
	Missing or Damaged Debris Barrier	Debris barrier missing or not attached to inlet/ outlet pipe.	Barrier is in place and firmly attached to pipe.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	34/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER


## Detention Pond

A stormwater detention pond is an open basin built by excavating below existing ground or by constructing above-ground berms (embankments). The detention pond temporarily stores stormwater runoff during rain events and slowly releases it through an outlet (control structure). Detention ponds are typically designed to completely drain within 24 hours after the completion of a storm event.

Facility objects that are typically associated with a detention pond include:

- access road or easement
- fence, gate, and water quality sign
- typical bioswale
- wet bioswale
- media filter cartridge
- control structure/flow restrictor
- energy dissipaters
- conveyance stormwater pipe

RANGE	TOWNSHIP	SECTION	QUARTER		35/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER



Example of a Manicured Detention Pond

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	36/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

### Key Operations and Maintenance Considerations

- Maintenance is of primary importance if detention ponds are to continue to function well.
- Sediment should be removed when the standards in the defect table are exceeded. Sediments must be disposed in accordance with current local health department requirements and the Minimum Functional Standards for Solid Waste Handling.
- Handle sediments removed during the maintenance operation in a manner consistent with the City's recommended street waste procedures.
- Maintenance of sediment forebays and attention to sediment accumulation within the pond is extremely important. Continually monitor sediment deposition in the basin. Owners, operators, and maintenance authorities should be aware that significant concentrations of metals (e.g., lead, zinc, and cadmium) as well as some organics such as pesticides, may be expected to accumulate at the bottom of these types of facilities. Regularly conduct testing sediment, especially near points of inflow, to determine the leaching potential and level of accumulation of potentially hazardous material before disposal.
- Slope areas that have become bare should be revegetated and eroded areas should be regraded prior to being revegetated.
- A common tool for cleaning detention ponds is a small bulldozer or excavator to remove built-up sediment and debris from the bottom of the pond during the dry season.

Refer to City of Puyallup Engineering and Construction Standards Section 600 for grass specifications and planting requirements.

RANGE	TOWNSHIP	SECTION	QUARTER		37/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Detention Pond			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Note: table spans multiple pages.			
General	Trash and Debris	Any trash and debris which exceed 1 cubic foot per 1,000 square feet. In general, there should be no visual evidence of dumping. If less than threshold all trash and debris will be removed as part of next scheduled maintenance.	Site is free of trash and debris.
	Poisonous Plants and Noxious Weeds	Any poisonous plants or nuisance vegetation which may constitute a hazard to maintenance personnel or the public. Any evidence of noxious weeds as defined by State or local regulations.	No danger of poisonous vegetation where maintenance personnel or the public might normally be.  Eradication of Class A weeds as required by State law. Control of other listed weeds as directed by local policies. Apply requirements of adopted IPM policy for the use of herbicides.
	Vegetation Growth and Hazard Trees	Vegetation growth does not allow maintenance access or interferes with maintenance activity (i.e., slope mowing, silt removal, vacuuming, or equipment movements). If trees are not interfering with access or maintenance, do not remove. Dead, diseased, or dying trees are identified. (Use a certified Arborist to determine health of tree or removal requirements.)	Vegetation does not hinder maintenance activities. Harvested vegetation should be recycled into mulch or other beneficial uses (e.g., alders for firewood).  Remove hazard trees.
	Contaminants and Pollution	Any evidence of oil, gasoline, contaminants, or other pollutants. (Coordinate removal/cleanup with local water quality response agency.)	No contaminants or pollutants present.
	Rodent Holes	Any evidence of rodent holes if facility is acting as a dam or berm, or any evidence of water piping through dam or berm via rodent holes.	Rodents destroyed and dam or berm repaired.
	Beaver Dams	Dam results in change or function of the facility.	Facility is returned to design function. (Coordinate trapping of beavers and removal of dams with appropriate permitting agencies.)
	Insects	When insects such as wasps and hornets interfere with maintenance activities.	Insects destroyed or removed from site. Apply insecticides in compliance with adopted IPM Plan.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	38/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Side Slopes of Pond	Erosion	Eroded damage over 2 inches deep where cause of damage is still present or where there is potential for continued erosion. Any erosion observed on a compacted berm embankment.	Slopes have been stabilized using appropriate erosion control measure(s); e.g., rock reinforcement, planting of grass, compaction. If erosion is occurring on compacted berms a licensed civil engineer should be consulted to resolve source of erosion.
Storage Area	Sediment	Accumulated sediment that exceeds 10% (typically 6"-12") of designed pond depth unless otherwise specified or affects inletting/outletting condition of facility.	Sediment cleaned out to designed pond shape and depth; pond reseeded if necessary to control erosion.
	Liner (If Applicable)	Liner is visible and has more than three 1/4-inch holes in it.	Liner repaired or replaced. Liner is fully covered.
Pond Berms (Dikes)	Settlements	Any part of berm which has settled 4 inches lower than the design elevation. If settlement is apparent, measure berm to determine amount of settlement. Settling can be an indication of more severe problems with the berm or outlet works. A licensed civil engineer should be consulted to determine the source of the settlement.	Dike is built back to the design elevation.
	Piping	Discernible water flow through pond berm. Ongoing erosion with potential for erosion to continue.  (Recommend Geotech engineer be called to inspect and evaluate condition and recommend repair of condition.	Piping eliminated. Erosion potential resolved.
	Tree Growth	Tree growth on berms over 4 feet in height may lead to piping through the berm which could lead to failure of the berm.	Trees removed. If root system is small (base less than 4"), root system may be left in place. Otherwise roots should be removed and berm restored. A licensed civil engineer should be consulted for proper berm/spillway restoration.
	Erosion	Eroded damage over 2 inches deep where cause of damage is still present or where there is potential for continued erosion. Any erosion observed on a compacted berm embankment.	Slopes have been stabilized using appropriate erosion control measure(s); rock reinforcement, planting of grass, compaction. If erosion is occurring on compacted berms a licensed civil engineer should be consulted to resolve source of erosion.

RANGE	TOWNSHIP	SECTION	QUARTER		39/
04E-	19 N-	03	4/4	016	52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Emergency Overflow/ Spillway	Tree Growth	Tree growth on emergency spillways creates blockage problems and may cause failure of the berm due to uncontrolled overtopping.	Trees removed. If root system is small (base less than 4"), root system may be left in place. Otherwise roots should be removed and berm restored. A licensed civil engineer should be consulted for proper berm/spillway restoration.
	Rock Missing	Only one layer of rock exists above native soil in area five square feet or larger, or any exposure of native soil at the top of flow path of spillway.	Rocks and pad depth are restored to design standards.


RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	40/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Energy Dissipater / Outfall Protection

An energy dissipater is installed on or near the inlet or outlet to a closed pipe system to prevent erosion at these locations. There are a variety of designs, including wire gabion baskets, rock splash pads, trenches, and specially designed pools or manholes. The rock splash pad is typically constructed of 4- to 12-inch diameter rocks a minimum of 12 inches thick and is often lined with filter fabric. The rock pad should extend above the top of the pipe a minimum of 1 foot.

Facility features that are typically associated with energy dissipaters include:

- detention ponds
- infiltration basin
- wetponds
- treatment wetlands



## Key Operations and Maintenance Considerations

- The most common tools for maintenance are hand tools such as rakes to redistribute rocks as necessary.
- Periodic removal of sediment or debris may be necessary.



RANGE	TOWNSHIP	SECTION	QUARTER	016	41/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Energy Dissipaters			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
External:			
Rock Pad	Missing or Moved Rock	Only one layer of rock exists above native soil in area five square feet or larger, or any exposure of native soil.	Rock pad has been replaced to design function.
	Erosion	Soil erosion in or adjacent to rock pad.	Rock pad has been replaced to design function.
	Sediment	Sediment on top of rock pad exceeds 10% of the surface.	Rock pad has been cleared of sediment.
	Poisonous Plants and Noxious Weeds	Any poisonous plants or nuisance vegetation which may constitute a hazard to maintenance personnel or the public. Any evidence of noxious weeds as defined by State or local regulations.	No danger of poisonous vegetation where maintenance personnel or the public might normally be. Eradication of Class A weeds as required by State law. Control of other listed weeds as directed by local policies. Apply requirements of adopted IPM policy for the use of herbicides.
	Other Weeds	Other weeds (not listed on State noxious weed lists) are present on the rock pad.	Weeds have been removed per the routine maintenance schedule, following IPM protocols.
Dispersion Trench	Pipe Plugged with Sediment	Accumulated sediment that exceeds 20% of the design depth.	Pipe is free of sediment and meets design specifications.
	Not Discharging Water Properly	Visual evidence of water discharging at concentrated points along trench (normal condition is a "sheet flow" of water along trench). Intent is to prevent erosion damage.	Trench has been repaired or modified such that it does not discharge at concentrated points and meets design function.
	Perforations Plugged	Over 1/2 of perforations in pipe are plugged with debris and sediment.	Perforated pipe has been cleaned or replaced and <25% of perforations are plugged.
	Water Flows Out Top of "Distributor" Catch Basin	Maintenance person observes or receives credible report of water flowing out during any storm less than the design storm or its causing or appears likely to cause damage.	Facility rebuilt per design specifications or redesigned to meet approved City standards.
	Receiving Area Over-Saturated	Water in receiving area is causing or has potential of causing landslide problems.	No danger of landslides.
Gabions	Damaged Mesh	Mesh of gabion broken, twisted or deformed so structure is weakened or rock may fall out.	Mesh is intact, no rock missing.
	Corrosion	Gabion mesh shows corrosion through more than 1/4 of its gage.	All gabion mesh capable of containing rock and retaining designed form.

RANGE	TOWNSHIP	SECTION	QUARTER	016	42/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Energy Dissipaters			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
	Collapsed or Deformed Baskets	Gabion basket shape deformed due to any cause.	All gabion baskets intact, structure stands as designed.
	Missing Rock	Any rock missing that could cause gabion to lose structural integrity.	No rock missing.
<b>Internal:</b>			
Manhole/ Chamber	Worn or Damaged Post, Baffles, Side of Chamber	Structure dissipating flow deteriorates to 1/2 of original size or any concentrated worn spot exceeding one square foot which would make structure unsound.	Structure replaced to design standards.


RANGE	TOWNSHIP	SECTION	QUARTER		43/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Facility Discharge Points (Outfall)

Stormwater facility discharge points may convey stormwater from the stormwater facility into open channels, ditches, ponds, streams, and wetlands. Stormwater facility discharge points need to be assessed to make sure stormwater is not causing any negative impacts to these drainage areas.

## Key Operations and Maintenance Considerations

- The most common tools are hand tools to remove debris or to redistribute outfall protection rock.



(Source: USDA - Natural Resources Conservation Service - Illinois)

RANGE	TOWNSHIP	SECTION	QUARTER		44/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Facility Discharge Point (Outfall)			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Monitoring	Contaminants in Discharge Water	Any evidence of oil, gasoline, contaminants, or other pollutants. Sheen, obvious oil, or other contaminants present.  • Identify and remove source.	Effluent discharge from facility is clear.
	Receiving Area Saturated	Water in receiving area is causing substrate to become saturated and unstable.	Receiving area is sound and not saturated.
	Ditch or Stream Banks Eroding (via Off Site Assessment)	Erosion, scouring, or headcuts in ditch or stream banks downstream of facility discharge point due to flow channelization or higher flows.	Ditch or stream banks are stable.
	Access	Vegetation is overgrown and there is no access to the outfall.	Vegetation is removed and/or path is cleared to access the outfall.
	Stains or Deposits	Stains or deposits present within the discharge area that are not natural occurring.	No stains or deposits exist and the source has been eliminated, unless the source is determined to be natural occurring.
	Stormwater Flow	Flow exists during the summer dry months when no flows should be present.	Source of the flows has been eliminated or source has been determined to be groundwater interflow.
	General	Missing or Moved Rock	Only one layer of rock exists above native soil in area five square feet or larger, or any exposure of native soil.
Erosion		Soil erosion in or adjacent to rock pad.	Rock pad replaced to design function.
Obstructions, Including Roots		Roots or debris enters pipe or deforms pipe, reducing flow.	Roots have been removed from pipe (using mechanical methods; do not put root-dissolving chemicals in storm sewer pipes). If necessary, vegetation over the line removed.
Pipe Rusted or Deteriorated		Any part of the pipe that is broken, crushed, or deformed more than 20% or any other failure to the piping.	Pipe repaired or replaced to design standards.

RANGE	TOWNSHIP	SECTION	QUARTER		45/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Fencing/Gates/Bollards/Water Quality Sign

Stormwater facilities such as detention ponds or treatment wetlands often have fences to protect them from damage and keep children away from ponds or hazardous areas. Some facilities are required to have informational signs telling the public that the site is a stormwater facility.

Fencing/Gates/Bollards/Water Quality Sign			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Fencing (Site)	Site erosion or holes under fence	Erosion or holes more than 4 inches high and 12-18 inches wide permitting access through an opening under a fence.	No access under the fence.
Fencing (Wood Posts, Boards, and Cross Members)	Missing or damaged parts	Missing or broken boards, post out of plumb by more than 6 inches or cross members broken	No gaps on fence due to missing or broken boards, post plumb to within 1½ inches, cross members sound.
	Weakened by rotting or insects	Any part showing structural deterioration due to rotting or insect damage	All parts of fence are structurally sound.
	Damaged or failed post foundation	Concrete or metal attachments deteriorated or unable to support posts.	Post foundation capable of supporting posts even in strong wind.
Fencing (Metal Posts, Rails, and Fabric)	Damaged parts	Post out of plumb more than 6 inches.	Post plumb to within 1½ inches.
		Top rails bent more than 6 inches.	Top rail free of bends greater than 1 inch.
		Any part of fence (including post, top rails, and fabric) more than 1 foot out of design alignment.	Fence is aligned and meets design standards.
		Missing or loose tension wire.	Tension wire in place and holding fabric.
	Deteriorated paint or protective coating	Part or parts that have a rusting or scaling condition that has affected structural adequacy.	Structurally adequate posts or parts with a uniform protective coating.
	Openings in fabric	Openings in fabric are such that an 8-inch diameter ball could fit through.	Fabric mesh openings within 50% of grid size.
Chain Link Fencing Gate	Damaged or missing members	Missing gate.	Gates in place.
		Broken or missing hinges such that gate cannot be easily opened and closed by a maintenance person.	Hinges intact and lubed. Gate is working freely.
		Gate is out of plumb more than 6 inches and more than 1 foot out of design alignment.	Gate is aligned and vertical.
		Missing stretcher bar, stretcher bands, and ties.	Stretcher bar, bands, and ties in place.
	Locking mechanism does not lock gate	Locking device missing, non-functioning or does not link to all parts.	Locking mechanism prevents opening of gate.
	Openings in fabric	Openings in fabric are such that an 8-inch diameter ball could fit through.	Fabric mesh openings within 50% of grid size.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	46/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Fencing/Gates/Bollards/Water Quality Sign			
Drainage System Feature	Potential Defect	Conditions When Maintenance Is Needed	Minimum Performance Standard
Bollards	Damaged or missing	Bollard broken, missing, does not fit into support hole or hinge broken or missing.	No access for motorized vehicles to get into facility.
	Does not lock	Locking assembly or lock missing or cannot be attached to lock bollard in place.	No access for motorized vehicles to get into facility.
Water Quality Sign	Sign is Damaged or Missing	Water quality sign is leaning more than 8 inches off vertical.	Sign reset to plumb.
		Water quality sign is missing or 20% of the surface is unreadable.	Sign replaced.

RANGE	TOWNSHIP	SECTION	QUARTER		47/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Vegetation

Many stormwater facilities use vegetation as part of the functional design. Vegetation must be maintained to contribute to the function of the facility and to prevent damage to structural elements of the facility (e.g. earthen berms). Another reason to maintain vegetation is aesthetics.

Vegetation maintenance can include trimming, plant replacement, weeding, and pest control. Vegetation maintenance in native vegetation retention areas carries specific requirements.

Objectives for vegetation management in stormwater facilities:

- Maintain healthy plant communities
- Reduce or eliminate sources of pollution related to vegetation care
- Cover bare soil areas with plants
- Control Class A and Class B noxious weeds; control unlisted invasive plants where needed to achieve management objectives
- Tolerance for natural appearance and weeds that do not interfere with facility functions

## Key Operations and Maintenance Considerations

- The vegetation management focus is establishing and maintaining healthy low-maintenance native plantings and sustaining the design function of vegetated filters such as biofiltration swales. This includes controlling invasive plants where appropriate, and planting cover on bare soils.
- Use plants appropriate to the facility type, as listed in the City of Puyallup's Engineering and Construction Standards Section 600.
- Consider the use of soil amendments such as compost before using fertilizer.
- Limit mulch use to covering bare soil while establishing plantings.
- When a chemical control method is chosen, carefully follow the manufacturer's label directions for use. When deciding on and using a chemical control, consider stormwater facilities and drainage systems as leading to water bodies and apply chemicals per the label directions for use over or near water.
- Allow a 5-foot buffer from mature established plantings to fence lines and access roads.
- Trees or shrubs that block access roads may be trimmed (or removed if within the access road) when access is required for maintenance by heavy equipment.
- Trees that pose a risk to stormwater structures due to root growth may be removed.

RANGE	TOWNSHIP	SECTION	QUARTER		48/52
04E-	19 N-	03	4/4	016	
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

## Use Only Appropriate Plants

Use plants that will thrive in the growing conditions of each facility. Growing conditions are affected by moisture, soil conditions, and light. Plants native to western Washington are preferred. Plant lists for biofiltration swales, bioretention systems, rain gardens, and other facility types are given in the City of Puyallup's Engineering and Construction Standards Section 600.

## Integrated Pest Management

Landscape management decisions for controlling unwanted vegetation, diseases, and pests in stormwater facilities should follow Integrated Pest Management principles.

An IPM program might consist of the following steps:

### Step 1: Correctly identify problem pests and understand their life cycle.

IPM starts with an understanding of the soil, water, natural resources, and human impacts on site. Identify and research the pest species, including basic physiology and best timing for control. Many pests are a problem during certain seasons or can only be treated in specific phases of the life cycle. Local pest identification help can be obtained from WSU Extension Master Gardeners or through online resources such as Washington State Noxious Weed Control Board and Washington Invasive Species Council.

### Step 2: Establish tolerance thresholds for pests.

Every landscape has a population of some pest insects, weeds, and diseases. Once the pest has been identified and studied, determine if low levels of the pest are tolerable. Small numbers of certain pests may not be harmful. If this is the case, simply continue to monitor the pest population.

In other cases, the pest may require control. Examples include a pest population that is rapidly increasing in numbers, or an invasive weed that requires control according to state law. Early detection, rapid response (EDRR) plays an important role in the control of pests that are known to be a severe problem in other regions but not yet occurring in ours. In this instance, the tolerance threshold is zero; a quick response to eliminate a future ongoing pest problem is the safest and least expensive control.

### Step 3: If pests exceed tolerance thresholds, choose a safe and effective control method.

IPM identifies physical, cultural, biological, and chemical control methods tailored specifically for the pest of concern and the site. Research the available options and choose a control method that is effective. Preferred control methods are economical, low risk to people, and mindful of environmental processes.



RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	49/ 52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Physical control works on a pest directly: digging, hand-pulling, mowing, tilling, trapping, etc.

Cultural control changes the pest's environment: landscape fabric, mulch, soil amendments, altering the irrigation method or duration, crop rotation, crop covers, etc.

Biological control uses natural enemies: beneficial insects, managed grazing, bird boxes and perches, etc.

Chemical control is the use of pesticides: insect bait stations, synthetic and organic foliar herbicides, microbial-based insecticides, oils, soaps, etc.

These control methods should be looked at as tools in a toolbox; IPM selects the right tools for the job at hand. Both short-term control and long-term management is best achieved by using more than one tool. Often, implementing cultural control methods reduces the amount of physical and chemical control needed.

#### Step 4: Monitor and evaluate.

Observe and record the results of the control treatment. Evaluate the effectiveness. If necessary, modify maintenance practices to support a healthy landscape and prevent recurrence of the pest.

IPM emphasizes that pest control is not a one-time proposition; the pest control process should be viewed as a cycle that rotates through planning, control, and evaluation. As pest issues change over time, the IPM plan adapts.

- Proper planning and management decisions begin the IPM process. All control methods are considered during the information-gathering and planning process. Often a combination of methods is best.
- Cultural methods of vegetation and pest control are preferred.
- Mechanical means of vegetation and pest control are next in line of preference and are utilized where appropriate.
- Biological methods of vegetation and pest control are considered before chemical means, where they are appropriate.
- Botanical and synthetic pesticides are used in an appropriate manner when other control methods are deemed ineffective or not cost-efficient.

RANGE	TOWNSHIP	SECTION	QUARTER		
04E-	19 N-	03	4/4	016	50/52
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

**Exhibit B**

Annual Inspection Report Example

RANGE	TOWNSHIP	SECTION	QUARTER	016	51/52
04E-	19 N-	03	4/4		
DOCUMENT NUMBER				SERIAL NUMBER	PAGE NUMBER

Docusign Envelope ID: C521D945-C743-4549-84F7-BE1227F00F6C

**Annual Inspection Report**  
 City of Puyallup - Stormwater BMP Facilities Inspection and Maintenance Log

Facility Name \_\_\_\_\_

Address \_\_\_\_\_

Begin Date \_\_\_\_\_ End Date \_\_\_\_\_

Date	BMP ID#	BMP Facility Description	Inspected by:	Cause for Inspection	Exceptions Noted	Comments and Actions Taken

**Instructions:**

Record all inspections and maintenance for all treatment BMPs on this form. Use additional log sheets and/or attach extended comments or documentation as necessary. Submit a copy of the completed log with the Annual Independent Inspectors' Report to the City, and start a new log at that time.

BMP ID# — Always use ID# from the Operation and Maintenance Manual.

Inspected by — Note all inspections and maintenance on this form, including the required independent annual inspection.

Cause for inspection — Note if the inspection is routine, pre-rainy-season, post-storm, annual, or in response to a noted problem or complaint.

Exceptions noted — Note any condition that requires correction or indicates a need for maintenance.

Comments and actions taken — Describe any maintenance done and need for follow-up.

Return Form to: Stormwater Engineer/City of Puyallup  
 333 South Meridian  
 Puyallup, WA 98371

