

ENGINEERING ANALYSIS FOR:
EAST TOWN CROSSING
APARTMENTS
PIONEER & SHAW
PUYALLUP, WA
BUILDING F



PIERUCCIONI E&C, LLC
CHON PIERUCCIONI, PE
3128 N. BENNETT ST.
TACOMA, WA 98407

REUSE OF DOCUMENTS
THIS DOCUMENT AND THE IDEAS AND DESIGN
INCORPORATED HEREIN ARE THE PROPERTY OF
PIERUCCIONI E&C, LLC AND ARE NOT TO BE REUSED
OR REPRODUCED IN WHOLE OR IN PART WITHOUT THE
WRITTEN AUTHORIZATION OF PIERUCCIONI E&C, LLC.

EAST TOWN CROSSING
BUILDING "F"
PIONEER & SHAW PUYALLUP WA

DESIGN CRITERIA

BUILDING CODE: 2018 INTERNATIONAL BUILDING CODE (IBC) AS AMENDED BY THE
LOCAL JURISDICTION.

VERTICAL LOADS

ROOF LIVE LOAD:

25 PSF (SNOW)

ROOF DEAD LOAD:

25 PSF

RESIDENTIAL FLOOR LIVE LOAD:

40 PSF (REDUCIBLE) : 60 PSF (FOR DECKS)

STAIRWAY LANDING AREAS:

150 PSF (INCLUDING $I_p=1.5$)

FLOOR DEAD LOAD:

30 PSF (INCLUDES 1 1/2" GYP TOPPING)

SNOW DESIGN DATA (ASCE 7-16)

WIND DESIGN DATA (ASCE 7-16)

FLAT SNOW LOAD: N/A

BASIC WIND SPEED (ASD) V= 85MPH

SNOW EXPOSURE FACTOR, $C_e=1.0$,

ULTIMATE WIND SPEED V= 110MPH

SNOW IMPORTANCE FACTOR, $I_s=1.0$,

RISK CATEGORY: II EXPOSURE: B

THERMAL FACTOR, $C_t=1.1$

IMPORTANCE FACTOR, $I_w= 1.0$

TOPOGRAPHIC FACTOR, $K_{zt}= 1.0$

SEISMIC DESIGN DATA (ASCE7-16)

SEISMIC RESPONSE SYSTEM: WOOD SHEARWALLS

EQUIVALENT LATERAL FORCE PROCEDURE (ASCE 7-16)

RISK CATEGORY: II

SEISMIC IMPORTANCE FACTOR, $I_e= 1.0$

MAPPED SPECTRAL RESPONSE ACCELERATION: $S_s=1.24$, $S_1=0.476$

DESIGN SPECTRAL RESPONSE ACCELERATION: $S_d=0.831$, $S_{d1}=0.476$

SITE CLASS: D

SEISMIC DESIGN CATEGORY: D

SEISMIC RESPONSE COEFFICIENT: $C_s= 0.091$

DESIGN BASE SHEAR: 98,140#

SOIL PROPERTIES:


BEARING CAPACITY: 2,000 PSF

LATERAL CAPACITY: 250 PSF/FT

REVISIONS



CITY REVIEW



City of Puyallup
Building
REVIEWED
FOR
COMPLIANCE

BSnowden

05/13/2024

3:04:58 PM



REVISIONS

ENGINEER: CP

CHECKED BY: CP

DATE: 2024.01.12

TITLE: STRUCTURAL
ANALYSIS

PROJECT #: ----

Calculations required to be provided by
the Permittee on site for all Inspections

2nd Floor Framing			
Member Name	Results (Max UTIL %)	Current Solution	Comments
Floor Joist 15'-2" and Under	Passed (101% M)	1 piece(s) 2 x 12 DF No.2 @ 16" OC	
Floor Joist 15'-2" - 17'-8"	Passed (102% M)	1 piece(s) 2 x 12 DF No.2 @ 12" OC	
Floor Joist 19'-4"	Passed (81% M)	2 piece(s) 2 x 12 DF No.2 @ 16" OC	
Floor Joist 20'-7" (with offset 3rd flr.)	Passed (75% M)	1 piece(s) 4 x 12 DF No.2 @ 16" OC	
Short Stair Stringers	Passed (68% R)	1 piece(s) 4 x 12 HF No.2	
Long Short Stair Stringers	Passed (98% ΔL)	1 piece(s) 3 1/2" x 12" 24F-V4 DF Glulam	
Top Landing Beam	Passed (98% R)	1 piece(s) 5 1/2" x 13 1/2" 24F-V4 DF Glulam	
10'-10" Deck Joist	Passed (71% R)	1 piece(s) 2 x 12 HF No.2 @ 16" OC	
Deck Cantilever Ledger 2'	Passed (47% R)	2 piece(s) 2 x 12 HF No.2	
Grid 2.6 (F-G.3) Flush Beam	Passed (96% R)	3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	
Grid 2.6 (G.9-H.8) Flush Beam	Passed (96% R)	3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	
Grid 2.4 (H.8-I.8) Door Header	Passed (46% R)	1 piece(s) 4 x 8 DF No.2	
Grid 2.4 (J.2-K.8) Door Header	Passed (73% M)	1 piece(s) 4 x 8 DF No.2	
Grid 5.5 (H-H.8) Door Header	Passed (77% R)	1 piece(s) 4 x 8 DF No.2	
Grid 5.5 (G.1-G.3) Flush Beam	Passed (63% R)	1 piece(s) 4 x 12 DF No.2	
Grid G.1 (5.2-5.3) Door Header	Passed (53% R)	1 piece(s) 4 x 8 DF No.2	
Grid 6 (G.1-G.3) Flush Beam	Passed (70% R)	1 piece(s) 4 x 12 DF No.2	
Grid 2.5 (D.4-D.6) Flush Beam	Passed (90% M)	1 piece(s) 4 x 12 DF No.2	
Grid 3.3 (D.8-E.1) Flush Beam	Passed (87% R)	1 piece(s) 4 x 12 DF No.2	
Grid 5.3 (D.5-E.2) Flush Beam	Passed (75% R)	2 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	
Grid 6 (D.3-D.6) Flush Beam	Passed (96% R)	1 piece(s) 4 x 12 DF No.2	
3rd Floor Framing			
Member Name	Results (Max UTIL %)	Current Solution	Comments
Floor Joist 15'-2" and Under	Passed (101% M)	1 piece(s) 2 x 12 DF No.2 @ 16" OC	
Floor Joist 15'-2" - 17'-8"	Passed (102% M)	1 piece(s) 2 x 12 DF No.2 @ 12" OC	
Floor Joist 19'-4"	Passed (81% M)	2 piece(s) 2 x 12 DF No.2 @ 16" OC	
Floor Joist 20'-7"	Passed (72% M)	1 piece(s) 4 x 12 DF No.2 @ 16" OC	
7'-6" Landing Joists	Passed (100% R)	1 piece(s) 2 x 12 HF No.2 @ 16" OC	
Top Landing Beam	Passed (99% ΔL)	1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam	
Short Stair Stringers	Passed (68% R)	1 piece(s) 4 x 12 HF No.2	
4' Mid Landing Joists	Passed (77% R)	1 piece(s) 2 x 12 HF No.2 @ 16" OC	
Mid Landing Beam Inner	Passed (79% ΔL)	1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam	
Mid Landing Beam Outer	Passed (102% ΔL)	1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam	
10'-10" Deck Joist	Passed (71% R)	1 piece(s) 2 x 12 HF No.2 @ 16" OC	
Deck Cantilever Ledger 2'	Passed (47% R)	2 piece(s) 2 x 12 HF No.2	
6' Window Header	Passed (17% M)	1 piece(s) 4 x 10 DF No.2	
Grid 2.6 (F-G.5) Flush Beam	Passed (97% ΔT)	3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	
Grid 2.6 (H-H.8) Flush Beam	Passed (64% R)	1 piece(s) 4 x 12 DF No.2	
Grid 2.4 (H.8-I.8) Door Header	Passed (46% R)	1 piece(s) 4 x 8 DF No.2	
Grid 2.4 (J.2-K.8) Door Header	Passed (73% M)	1 piece(s) 4 x 8 DF No.2	
Grid 5.5 (H-H.8) Door Header	Passed (34% R)	1 piece(s) 4 x 8 DF No.2	
Grid 5.5 (G.4-G.8) Door Header	Passed (89% M)	1 piece(s) 4 x 8 DF No.2	
Grid 5.5 (G.1-G.3) Flush Beam	Passed (32% R)	1 piece(s) 4 x 12 DF No.2	
Grid G.1 (5.2-5.3) Door Header	Passed (32% V)	1 piece(s) 4 x 8 DF No.2	
Grid 6 (G.1-G.3) Flush Beam	Passed (35% R)	1 piece(s) 4 x 12 DF No.2	
Grid 2.5 (D.4-D.6) Flush Beam	Passed (52% R)	1 piece(s) 4 x 12 DF No.2	
Grid 3.3 (D.8-E.1) Flush Beam	Passed (43% R)	1 piece(s) 4 x 12 DF No.2	
Grid 5.3 (D.5-E.2) Flush Beam	Passed (96% M)	1 piece(s) 4 x 12 DF No.2	
Grid 6 (D.3-D.6) Flush Beam	Passed (48% R)	1 piece(s) 4 x 12 DF No.2	

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC

ForteWEB v3.8

File Name: East Town Crossing Building F (Left Side) (2X12)


Roof Framing			
Member Name	Results (Max UTIL %)	Current Solution	Comments
Grid I Entry Roof Beam	Passed (91% R)	1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam	
Grid L 10' Deck Roof Beam	Passed (101% R)	1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam	
6' Window Header	Passed (90% R)	1 piece(s) 4 x 10 DF No.2	
Grid B 11' Deck Roof Beam	Passed (100% R)	1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam	
Deck Roof Cantilever Beam	Failed (61% R) Passed	1 piece(s) 5 1/2" x 10 1/2" 24F-V4 DF Glulam	An excessive uplift of -2576 lbs at support located at 4" failed this product.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Floor Joist 15'-2" and Under

1 piece(s) 2 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	735 @ 2 1/2"	2126 (3,50")	Passed (35%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	620 @ 1' 2 3/4"	2025	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2743 @ 7' 10 1/2"	2729	Passed (101%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.233 @ 7' 10 1/2"	0.511	Passed (L/790)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.408 @ 7' 10 1/2"	0.767	Passed (L/451)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 15' 9"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	315	420	735	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.50"	315	420	735	Blocking

Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6" o/c	
Bottom Edge (Lu)	15' 9" o/c	

Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 15' 9"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:29:36 PM UTC

ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3

File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Floor Joist 15'-2" - 17'-8"
1 piece(s) 2 x 12 DF No.2 @ 12" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	639 @ 2 1/2"	2126 (3,50")	Passed (30%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	553 @ 1' 2 3/4"	2025	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2783 @ 9' 1 1/2"	2729	Passed (102%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.320 @ 9' 1 1/2"	0.594	Passed (L/669)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.559 @ 9' 1 1/2"	0.892	Passed (L/383)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 18' 3 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	274	365	639	Blocking
2 - Stud wall - HF	5.50"	4.00"	1.50"	279	372	650	1 1/2" Rim Board

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' o/c	
Bottom Edge (Lu)	18' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 18' 5"	12"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Floor Joist 19'-4"
2 piece(s) 2 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	929 @ 2 1/2"	4253 (3,50")	Passed (22%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	815 @ 1' 2 3/4"	4050	Passed (20%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	4436 @ 9' 11 1/2"	5458	Passed (81%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.305 @ 9' 11 1/2"	0.650	Passed (L/768)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.533 @ 9' 11 1/2"	0.975	Passed (L/439)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 19' 11 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	398	531	929	Blocking
2 - Stud wall - HF	5.50"	4.00"	1.50"	405	540	945	1 1/2" Rim Board

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	9' 4" o/c	
Bottom Edge (Lu)	20' o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 20' 1"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Floor Joist 20'-7" (with offset 3rd flr.)

1 piece(s) 4 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2825 @ 21' 1 1/2"	4961 (3,50")	Passed (57%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1241 @ 20' 1 1/4"	4725	Passed (26%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	5279 @ 11' 1/8"	7004	Passed (75%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.355 @ 10' 9 15/16"	0.692	Passed (L/701)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.621 @ 10' 9 15/16"	1.038	Passed (L/401)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 21' 2 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	4.00"	1.50"	440	587	1028	1 1/2" Rim Board
2 - Stud wall - HF	3.50"	3.50"	1.99"	1211	1615	2825	Blocking

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	Continuous	
Bottom Edge (Lu)	Continuous	

Vertical Loads	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 21' 4"	16"	30.0	40.0	2nd floor load
2 - Point (lb)	20' 10 1/4"	N/A	798	1064	3rd Floor offset wall load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:29:36 PM UTC

ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3

File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Short Stair Stringers
1 piece(s) 4 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1450 @ 3"	2126 (1.50")	Passed (68%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1075 @ 1' 2 1/4"	3938	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2628 @ 3' 10 1/2"	5752	Passed (46%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.035 @ 3' 10 1/2"	0.181	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.046 @ 3' 10 1/2"	0.363	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 7' 3"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	385	1163	1547	See note ¹
2 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	385	1163	1547	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	7' 3" o/c	
Bottom Edge (Lu)	7' 3" o/c	

• Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS410	2.00"	N/A	8-10d	6-10d	
2 - Face Mount Hanger	LUS410	2.00"	N/A	8-10d	6-10d	

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	3" to 7' 6"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 7' 9" (Front)	2'	45.0	150.0	Default Load

• Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Long Short Stair Stringers
1 piece(s) 3 1/2" x 12" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3002 @ 2"	3189 (2.25")	Passed (94%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2576 @ 14' 1/2"	7420	Passed (35%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	11069 @ 7' 7 1/4"	16800	Passed (66%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.364 @ 7' 7 1/4"	0.372	Passed (L/490)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.486 @ 7' 7 1/4"	0.744	Passed (L/367)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 14' 10 1/2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 14' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Plate on concrete - HF	3.50"	2.25"	2.12"	761	2281	3042	1 1/4" Rim Board
2 - Hanger on 12" GLB beam	3.00"	Hanger ¹	1.50"	768	2306	3074	See note ¹

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	14' 11" o/c	
Bottom Edge (Lu)	14' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
2 - Face Mount Hanger	HHUS410	3.00"	N/A	30-10d	10-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	1 1/4" to 15' 1/2"	N/A	10.2	--	
1 - Uniform (PSF)	0 to 15' 3 1/2" (Front)	2'	45.0	150.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Weyerhaeuser Notes
Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library .
The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Top Landing Beam
1 piece(s) 5 1/2" x 13 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	11985 @ 11' 9"	12251 (5.50")	Passed (98%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	8786 @ 10' 6"	13118	Passed (67%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	31091 @ 6' 8 3/4"	33413	Passed (93%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.261 @ 6' 1"	0.285	Passed (L/525)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.346 @ 6' 1"	0.571	Passed (L/396)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 12' 1"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	4.69"	2563	7873	10437	Blocking
2 - Stud wall - HF	5.50"	5.50"	5.38"	2952	9033	11985	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	18.0	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	5' 6"	45.0	150.0	Default Load
2 - Point (lb)	5' 3 3/4" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1
3 - Point (lb)	1' 1/4" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1
4 - Point (lb)	6' 9 3/8" (Front)	N/A	768	2306	Linked from: Long Short Stair Stringers, Support 2
5 - Point (lb)	11' 7/8" (Front)	N/A	768	2306	Linked from: Long Short Stair Stringers, Support 2

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, 10'-10" Deck Joist
1 piece(s) 2 x 12 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1510 @ 2' 9 3/4"	2126 (3,50")	Passed (71%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	663 @ 3' 10 3/4"	1688	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-1477 @ 2' 9 3/4"	2577	Passed (57%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.059 @ 8' 10 11/16"	0.366	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.089 @ 8' 10 3/4"	0.549	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 13' 7 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- 480 lbs uplift at support located at 2". Strapping or other restraint may be required.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" HF beam	2.00"	Hanger ¹	1.50"	-127	114/-354	-480	See note ¹
2 - Stud wall - HF	3.50"	3.50"	2.49"	503	1007	1510	None
3 - Hanger on 11 1/4" HF beam	2.00"	Hanger ¹	1.50"	181	364	545	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	11' o/c	
Bottom Edge (Lu)	7' 11" o/c	

•Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d	
3 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d	

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 13' 11 1/2"	16"	30.0	60.0	Default Load

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)


Weyerhaeuser Notes
Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library .
The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Deck Cantilever Ledger 2'

2 piece(s) 2 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	855 @ 6"	1823 (1.50")	Passed (47%)	--	1.0 D + 1.0 L (Alt Spans)
Shear (lbs)	814 @ 2' 6 3/4"	3375	Passed (24%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-1738 @ 3' 9"	4482	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.017 @ 6' 1"	0.200	Passed (2L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.023 @ 6' 1"	0.233	Passed (2L/999+)	--	1.0 D + 1.0 L (Alt Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Overhang deflection criteria: LL (0.2") and TL (2L/240).
- Right cantilever length exceeds 1/3 member length or 1/2 back span length. Additional bracing should be considered.
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 5' 7"
 System : Floor
 Member Type : Flush Beam
 Building Use : Residential
 Building Code : IBC 2018
 Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" HF beam	6.00"	Hanger ¹	1.50"	277	893/-142	1170	See note ¹
2 - Stud wall - HF	6.00"	6.00"	2.52"	1048	2014	3062	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 7" o/c	
Bottom Edge (Lu)	5' 7" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28-2	2.00"	N/A	6-10d	3-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	6" to 6' 1"	N/A	8.6	--	
1 - Uniform (PSF)	0 to 6' 1" (Front)	7'	30.0	60.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
 ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
 File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 2.6 (F-G.3) Flush Beam
3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	11253 @ 11' 8 5/8"	11694 (5.50")	Passed (96%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	4295 @ 1' 4 3/4"	11222	Passed (38%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	13951 @ 5' 9 11/16"	24206	Passed (58%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.163 @ 5' 11 3/4"	0.285	Passed (L/840)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.290 @ 5' 11 3/4"	0.569	Passed (L/471)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 12' 5/8"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	2.74"	2558	3272	5830	Blocking
2 - Stud wall - HF	5.50"	5.50"	5.29"	4954	6299	11253	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 5/8"	N/A	17.2	--	
1 - Uniform (PSF)	0 to 3' 11 1/2" (Front)	15' 5 1/2"	30.0	40.0	Default Load
2 - Uniform (PSF)	3' 11 1/2" to 12' 5/8" (Front)	11' 2"	30.0	40.0	Default Load
3 - Point (lb)	11' 9 3/4" (Top)	N/A	2757	3508	Linked from: Grid 2.6 (F-G.5) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 2.6 (G.9-H.8) Flush Beam
3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	7145 @ 2"	7442 (3.50")	Passed (96%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	3420 @ 3' 8 1/2"	11222	Passed (30%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	4953 @ 2' 9 3/4"	24206	Passed (20%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.014 @ 2' 6 5/16"	0.115	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.025 @ 2' 6 5/16"	0.230	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 4' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	3.36"	3101	4043	7145	Blocking
2 - Stud wall - HF	3.50"	3.50"	2.90"	2680	3491	6171	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 11" o/c	
Bottom Edge (Lu)	4' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 11 1/4"	N/A	17.2	--	
1 - Uniform (PSF)	0 to 4' 11 1/4" (Front)	19' 11 1/2"	30.0	40.0	Default Load
2 - Point (lb)	4' 3/4" (Top)	N/A	1370	1796	Linked from: Grid 2.6 (H-H.8) Flush Beam, Support 2
3 - Point (lb)	1 3/4" (Top)	N/A	1370	1796	Linked from: Grid 2.6 (H-H.8) Flush Beam, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 2.4 (H.8-I.8) Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1523 @ 0	3281 (1.50")	Passed (46%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	873 @ 8 3/4"	3045	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1301 @ 1' 8 1/2"	2989	Passed (44%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.009 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.015 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	659	864	1523	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	659	864	1523	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	12' 7 3/4"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 2.4 (J.2-K.8) Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1969 @ 0	3281 (1.50")	Passed (60%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1319 @ 8 3/4"	3045	Passed (43%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2174 @ 2' 2 1/2"	2989	Passed (73%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.024 @ 2' 2 1/2"	0.147	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.043 @ 2' 2 1/2"	0.221	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	852	1117	1969	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	852	1117	1969	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 5" o/c	
Bottom Edge (Lu)	4' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 4' 5"	12' 7 3/4"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 5.5 (H-H.8) Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2522 @ 3' 5 1/4"	3281 (1.50")	Passed (77%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1200 @ 8 3/4"	3045	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1366 @ 1' 5 15/16"	2989	Passed (46%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.009 @ 1' 7 13/16"	0.115	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.017 @ 1' 7 13/16"	0.172	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5 1/4"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1088	1424	2512	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1094	1429	2522	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5 1/4"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5 1/4"	10' 3"	30.0	40.0	2nd Floor
2 - Uniform (PSF)	0 to 4 1/2"	10' 3"	30.0	40.0	3rd Floor
3 - Point (lb)	5 1/4"	N/A	484	632	Linked from: Grid 5.5 (H-H.8) Door Header, Support 1
4 - Point (lb)	3' 4 1/2"	N/A	484	632	Linked from: Grid 5.5 (H-H.8) Door Header, Support 2

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 5.5 (G.1-G.3) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3129 @ 2"	4961 (3,50")	Passed (63%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	659 @ 1' 2 3/4"	4725	Passed (14%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1410 @ 2' 1 5/8"	6091	Passed (23%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.003 @ 2' 1 5/8"	0.098	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.006 @ 2' 1 5/8"	0.197	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 3 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	2.21"	1366	1764	3129	Blocking
2 - Stud wall - HF	3,50"	3,50"	1.50"	678	876	1553	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 3" o/c	
Bottom Edge (Lu)	4' 3" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 3 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 3 1/4" (Front)	10' 3"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	688	888	Linked from: Grid 5.5 (G.1-G.3) Flush Beam, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid G.1 (5.2-5.3) Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1731 @ 2' 5"	3281 (1.50")	Passed (53%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	820 @ 8 3/4"	3045	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	941 @ 1' 1 3/4"	2989	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 1' 2 7/16"	0.081	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.004 @ 1' 2 7/16"	0.121	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 2' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	633	798	1431	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	764	966	1731	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	2' 5" o/c	
Bottom Edge (Lu)	2' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 2' 5"	N/A	6.4	--	
1 - Point (lb)	3/4"	N/A	269	337	Linked from: Grid G.1 (5.2-5.3) Door Header, Support 1
2 - Point (lb)	2' 4 1/4"	N/A	435	551	Linked from: Grid G.1 (5.2-5.3) Door Header, Support 2
3 - Point (lb)	1' 1 3/4"	N/A	678	876	Linked from: Grid 5.5 (G.1-G.3) Flush Beam, Support 2

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 6 (G.1-G.3) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3464 @ 2"	4961 (3,50")	Passed (70%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	716 @ 1' 2 3/4"	4725	Passed (15%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1535 @ 2' 1 3/8"	6091	Passed (25%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.004 @ 2' 1 3/8"	0.097	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.006 @ 2' 1 3/8"	0.195	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 2 3/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	2,44"	1509	1955	3464	Blocking
2 - Stud wall - HF	3,50"	3,50"	2,44"	1509	1955	3464	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 3" o/c	
Bottom Edge (Lu)	4' 3" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 2 3/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 2 3/4" (Front)	11' 5"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	764	989	Linked from: Grid 6 (G.1-G.3) Flush Beam, Support 1
3 - Point (lb)	4' 1" (Top)	N/A	764	989	Linked from: Grid 6 (G.1-G.3) Flush Beam, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 2.5 (D.4-D.6) Flush Beam

1 piece(s) 4 x 12 DF No.2

Overall Length: 5' 10 1/4"



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	6689 @ 5' 6 1/4"	7796 (5.50")	Passed (86%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	3613 @ 4' 5 1/2"	4725	Passed (76%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	5483 @ 3' 5 3/16"	6091	Passed (90%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.023 @ 3' 1/4"	0.130	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.041 @ 3' 1/4"	0.259	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 5' 10 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	4.59"	2818	3682	6500	Blocking
2 - Stud wall - HF	5.50"	5.50"	4.72"	2894	3795	6689	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 10" o/c	
Bottom Edge (Lu)	5' 10" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 5' 10 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 5' 10 1/4" (Front)	16' 2"	30.0	40.0	2nd Floor
2 - Uniform (PSF)	4' 8" to 5' 10 1/4" (Front)	16' 2"	30.0	40.0	3rd Floor
3 - Point (lb)	1 3/4" (Top)	N/A	1119	1462	Linked from: Grid 2.5 (D.4-D.6) Flush Beam, Support 1
4 - Point (lb)	4' 6 1/4" (Top)	N/A	1119	1462	Linked from: Grid 2.5 (D.4-D.6) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:29:36 PM UTC

ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3

File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 3.3 (D.8-E.1) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4302 @ 2"	4961 (3,50")	Passed (87%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1013 @ 1' 2 3/4"	4725	Passed (21%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2152 @ 2' 3 7/8"	6091	Passed (35%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.006 @ 2' 3 7/8"	0.108	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.011 @ 2' 3 7/8"	0.216	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 7 3/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	3.03"	1870	2432	4302	Blocking
2 - Stud wall - HF	3,50"	3,50"	3.03"	1870	2432	4302	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 8" o/c	
Bottom Edge (Lu)	4' 8" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 7 3/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 7 3/4" (Front)	13' 1"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	935	1216	Linked from: Grid 3.3 (D.8-E.1) Flush Beam, Support 1
3 - Point (lb)	4' 6" (Top)	N/A	935	1216	Linked from: Grid 3.3 (D.8-E.1) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 5.3 (D.5-E.2) Flush Beam
2 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	7659 @ 5 3/4"	10277 (7.25")	Passed (75%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	5338 @ 7' 8 1/4"	7481	Passed (71%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	9058 @ 5' 1 1/8"	16137	Passed (56%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.092 @ 4' 8 3/4"	0.207	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.164 @ 4' 8 3/4"	0.414	Passed (L/606)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 9' 2 3/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	7.25"	7.25"	5.40"	3337	4322	7659	Blocking
2 - Stud wall - HF	7.25"	7.25"	4.82"	2980	3858	6838	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	9' 3" o/c	
Bottom Edge (Lu)	9' 3" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 9' 2 3/4"	N/A	11.5	--	
1 - Uniform (PSF)	0 to 7' 10 1/4" (Front)	12'	30.0	40.0	Default Load
2 - Uniform (PSF)	7' 10 1/4" to 9' 1" (Front)	13' 4"	30.0	40.0	Default Load
3 - Point (lb)	4 1/4" (Top)	N/A	1446	1877	Linked from: Grid 5.3 (D.5-E.2) Flush Beam, Support 1
4 - Point (lb)	7' 9" (Top)	N/A	1446	1877	Linked from: Grid 5.3 (D.5-E.2) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing, Grid 6 (D.3-D.6) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4744 @ 2"	4961 (3.50")	Passed (96%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1191 @ 1' 2 3/4"	4725	Passed (25%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2546 @ 2' 5 5/8"	6091	Passed (42%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.008 @ 2' 5 5/8"	0.115	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.015 @ 2' 5 5/8"	0.230	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	3.35"	2062	2682	4744	Blocking
2 - Stud wall - HF	3.50"	3.50"	3.35"	2062	2682	4744	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 11" o/c	
Bottom Edge (Lu)	4' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 11 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 11 1/4" (Front)	13' 7"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	1031	1341	Linked from: Grid 6 (D.3-D.6) Flush Beam, Support 1
3 - Point (lb)	4' 9 3/4" (Back)	N/A	1031	1341	Linked from: Grid 6 (D.3-D.6) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Floor Joist 15'-2" and Under
1 piece(s) 2 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	735 @ 2 1/2"	2126 (3,50")	Passed (35%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	620 @ 1' 2 3/4"	2025	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2743 @ 7' 10 1/2"	2729	Passed (101%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.233 @ 7' 10 1/2"	0.511	Passed (L/790)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.408 @ 7' 10 1/2"	0.767	Passed (L/451)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 15' 9"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	315	420	735	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.50"	315	420	735	Blocking

• Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6" o/c	
Bottom Edge (Lu)	15' 9" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 15' 9"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Floor Joist 15'-2" - 17'-8"
1 piece(s) 2 x 12 DF No.2 @ 12" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	639 @ 2 1/2"	2126 (3,50")	Passed (30%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	553 @ 1' 2 3/4"	2025	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2783 @ 9' 1 1/2"	2729	Passed (102%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.320 @ 9' 1 1/2"	0.594	Passed (L/669)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.559 @ 9' 1 1/2"	0.892	Passed (L/383)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 18' 3 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	274	365	639	Blocking
2 - Stud wall - HF	5.50"	4.00"	1.50"	279	372	650	1 1/2" Rim Board

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' o/c	
Bottom Edge (Lu)	18' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 18' 5"	12"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Floor Joist 19'-4"
2 piece(s) 2 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	929 @ 2 1/2"	4253 (3,50")	Passed (22%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	815 @ 1' 2 3/4"	4050	Passed (20%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	4436 @ 9' 11 1/2"	5458	Passed (81%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.305 @ 9' 11 1/2"	0.650	Passed (L/768)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.533 @ 9' 11 1/2"	0.975	Passed (L/439)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 19' 11 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	398	531	929	Blocking
2 - Stud wall - HF	5.50"	4.00"	1.50"	405	540	945	1 1/2" Rim Board

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	9' 4" o/c	
Bottom Edge (Lu)	20' o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 20' 1"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Floor Joist 20'-7"
1 piece(s) 4 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	988 @ 21' 1 1/2"	4961 (3,50")	Passed (20%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	873 @ 1' 4 3/4"	4725	Passed (18%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	5023 @ 10' 9"	7004	Passed (72%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.335 @ 10' 9"	0.692	Passed (L/744)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.586 @ 10' 9"	1.038	Passed (L/425)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 21' 2 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	4.00"	1.50"	430	573	1003	1 1/2" Rim Board
2 - Stud wall - HF	3.50"	3.50"	1.50"	423	564	988	Blocking

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	21' 3" o/c	
Bottom Edge (Lu)	21' 3" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 21' 4"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, 7'-6" Landing Joists
1 piece(s) 2 x 12 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	975 @ 3"	975 (1.60")	Passed (100%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	731 @ 1' 2 1/4"	1688	Passed (43%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1828 @ 4'	2577	Passed (71%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.062 @ 4'	0.250	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.080 @ 4'	0.375	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 7' 6"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" LSL beam	3.00"	Hanger ¹	1.60"	240	800	1040	See note ¹
2 - Hanger on 11 1/4" LSL beam	3.00"	Hanger ¹	1.60"	240	800	1040	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 10" o/c	
Bottom Edge (Lu)	7' 6" o/c	

•Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	4-10d	
2 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	4-10d	

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 8'	16"	45.0	150.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Top Landing Beam
1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	9199 @ 4"	12251 (5.50")	Passed (75%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	6904 @ 1' 5 1/2"	11660	Passed (59%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	23175 @ 5' 4 3/8"	26400	Passed (88%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.282 @ 5' 11 15/16"	0.285	Passed (L/486)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.372 @ 5' 11 15/16"	0.571	Passed (L/368)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 12' 1"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	4.13"	2239	6960	9199	Blocking
2 - Stud wall - HF	5.50"	5.50"	3.43"	1851	5788	7639	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	16.0	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	5' 9"	45.0	150.0	Default Load
2 - Point (lb)	1' 1/4" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1
3 - Point (lb)	5' 3 3/4" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Short Stair Stringers
1 piece(s) 4 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1450 @ 3"	2126 (1.50")	Passed (68%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1075 @ 1' 2 1/4"	3938	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2628 @ 3' 10 1/2"	5752	Passed (46%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.035 @ 3' 10 1/2"	0.181	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.046 @ 3' 10 1/2"	0.363	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 7' 3"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	385	1163	1547	See note ¹
2 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	385	1163	1547	See note ¹

- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	7' 3" o/c	
Bottom Edge (Lu)	7' 3" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS410	2.00"	N/A	8-10d	6-10d	
2 - Face Mount Hanger	LUS410	2.00"	N/A	8-10d	6-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	3" to 7' 6"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 7' 9" (Front)	2'	45.0	150.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, 4' Mid Landing Joists
1 piece(s) 2 x 12 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	701 @ 2"	911 (1.50")	Passed (77%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	458 @ 1' 1 1/4"	1688	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	946 @ 2' 10 3/8"	2577	Passed (37%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.016 @ 2' 10 3/8"	0.180	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.021 @ 2' 10 3/8"	0.270	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 5' 4 3/4"
 System : Floor
 Member Type : Joist
 Building Use : Residential
 Building Code : IBC 2018
 Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" LSL beam	2.00"	Hanger ¹	1.50"	172	573	745	See note ¹
2 - Hanger on 11 1/4" LSL beam	2.00"	Hanger ¹	1.50"	172	573	745	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 5" o/c	
Bottom Edge (Lu)	5' 5" o/c	

• Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie							
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories	
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d		
2 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d		

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 5' 8 3/4"	16"	45.0	150.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
 ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
 File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Mid Landing Beam Inner
1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	6828 @ 11' 9"	12251 (5.50")	Passed (56%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	5286 @ 1' 5 1/2"	11660	Passed (45%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	18813 @ 6' 7/16"	26400	Passed (71%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.225 @ 6' 1/2"	0.285	Passed (L/609)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.300 @ 6' 1/2"	0.571	Passed (L/457)	--	1.0 D + 1.0 L (All Spans)

Member Length : 12' 1"
 System : Floor
 Member Type : Flush Beam
 Building Use : Residential
 Building Code : IBC 2018
 Design Methodology : ASD

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	3.06"	1704	5118	6823	Blocking
2 - Stud wall - HF	5.50"	5.50"	3.07"	1706	5122	6828	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	16.0	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	3' 1"	45.0	150.0	Default Load
2 - Point (lb)	1' 1/4" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1
3 - Point (lb)	5' 3 3/4" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1
4 - Point (lb)	6' 9 3/8" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1
5 - Point (lb)	11' 7/8" (Front)	N/A	385	1163	Linked from: Short Stair Stringers, Support 1

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
 ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
 File Name: East Town Crossing Building F (Left Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



3rd Floor Framing, Mid Landing Beam Outer
1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3687 @ 4"	7796 (5.50")	Passed (47%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2873 @ 1' 4"	6493	Passed (44%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	9941 @ 6' 1/2"	12863	Passed (77%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.291 @ 6' 1/2"	0.285	Passed (L/471)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.384 @ 6' 1/2"	0.571	Passed (L/357)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 12' 1"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	2.60"	892	2794	3687	Blocking
2 - Stud wall - HF	5.50"	5.50"	2.60"	892	2794	3687	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	8.9	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	3' 1"	45.0	150.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, 10'-10" Deck Joist
1 piece(s) 2 x 12 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1510 @ 2' 9 3/4"	2126 (3,50")	Passed (71%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	663 @ 3' 10 3/4"	1688	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-1477 @ 2' 9 3/4"	2577	Passed (57%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.059 @ 8' 10 11/16"	0.366	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.089 @ 8' 10 3/4"	0.549	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 13' 7 1/2"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- 480 lbs uplift at support located at 2". Strapping or other restraint may be required.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" HF beam	2.00"	Hanger ¹	1.50"	-127	114/-354	-480	See note ¹
2 - Stud wall - HF	3.50"	3.50"	2.49"	503	1007	1510	None
3 - Hanger on 11 1/4" HF beam	2.00"	Hanger ¹	1.50"	181	364	545	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	11' o/c	
Bottom Edge (Lu)	7' 11" o/c	

•Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d	
3 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d	

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 13' 11 1/2"	16"	30.0	60.0	Default Load

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



3rd Floor Framing, Deck Cantilever Ledger 2'
2 piece(s) 2 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	855 @ 6"	1823 (1.50")	Passed (47%)	--	1.0 D + 1.0 L (Alt Spans)
Shear (lbs)	814 @ 2' 6 3/4"	3375	Passed (24%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-1738 @ 3' 9"	4482	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.017 @ 6' 1"	0.200	Passed (2L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.023 @ 6' 1"	0.233	Passed (2L/999+)	--	1.0 D + 1.0 L (Alt Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Overhang deflection criteria: LL (0.2") and TL (2L/240).
- Right cantilever length exceeds 1/3 member length or 1/2 back span length. Additional bracing should be considered.
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 5' 7"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" HF beam	6.00"	Hanger ¹	1.50"	277	893/-142	1170	See note ¹
2 - Stud wall - HF	6.00"	6.00"	2.52"	1048	2014	3062	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 7" o/c	
Bottom Edge (Lu)	5' 7" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28-2	2.00"	N/A	6-10d	3-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	6" to 6' 1"	N/A	8.6	--	
1 - Uniform (PSF)	0 to 6' 1" (Front)	7'	30.0	60.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.eyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, 6' Window Header
1 piece(s) 4 x 10 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	478 @ 0	3281 (1.50")	Passed (15%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	341 @ 10 3/4"	3885	Passed (9%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	746 @ 3' 1 1/2"	4492	Passed (17%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 3' 1 1/2"	0.208	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.014 @ 3' 1 1/2"	0.313	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 6' 3"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	394	83	478	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	394	83	478	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 3" o/c	
Bottom Edge (Lu)	6' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 6' 3"	N/A	8.2	--	
1 - Uniform (PSF)	0 to 6' 3"	8"	15.0	40.0	Floor
2 - Uniform (PLF)	0 to 6' 3"	N/A	108.0	-	Wall

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 2.6 (F-G.5) Flush Beam
3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	7707 @ 4"	11694 (5.50")	Passed (66%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	5857 @ 1' 4 3/4"	11222	Passed (52%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	22526 @ 6' 9 1/2"	24206	Passed (93%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.381 @ 7' 2 3/4"	0.466	Passed (L/440)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.679 @ 7' 2 3/4"	0.698	Passed (L/247)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 14' 7 5/8"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	3.62"	3375	4332	7707	Blocking
2 - Stud wall - HF	5.50"	5.50"	2.95"	2757	3508	6266	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 11" o/c	
Bottom Edge (Lu)	14' 8" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 14' 7 5/8"	N/A	17.2	--	
1 - Uniform (PSF)	0 to 1' (Front)	19' 11 1/2"	30.0	40.0	Default Load
2 - Uniform (PSF)	1' to 6' 6 1/2" (Front)	15' 5 1/2"	30.0	40.0	Default Load
3 - Uniform (PSF)	6' 6 1/2" to 14' 7 5/8" (Front)	11' 2"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 2.6 (H-H.8) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3166 @ 2"	4961 (3,50")	Passed (64%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1436 @ 1' 2 3/4"	4725	Passed (30%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	3054 @ 2' 3"	6091	Passed (50%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.008 @ 2' 3"	0.104	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.014 @ 2' 3"	0.208	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 6"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	2,23"	1370	1796	3166	Blocking
2 - Stud wall - HF	3,50"	3,50"	2,23"	1370	1796	3166	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 6" o/c	
Bottom Edge (Lu)	4' 6" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 6"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 6" (Front)	19' 11 1/2"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 2.4 (H.8-I.8) Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1523 @ 0	3281 (1.50")	Passed (46%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	873 @ 8 3/4"	3045	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1301 @ 1' 8 1/2"	2989	Passed (44%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.009 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.015 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	659	864	1523	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	659	864	1523	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	12' 7 3/4"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 2.4 (J.2-K.8) Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1969 @ 0	3281 (1.50")	Passed (60%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1319 @ 8 3/4"	3045	Passed (43%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2174 @ 2' 2 1/2"	2989	Passed (73%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.024 @ 2' 2 1/2"	0.147	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.043 @ 2' 2 1/2"	0.221	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	852	1117	1969	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	852	1117	1969	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 5" o/c	
Bottom Edge (Lu)	4' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 4' 5"	12' 7 3/4"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 5.5 (H-H.8) Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1116 @ 0	3281 (1.50")	Passed (34%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	588 @ 8 3/4"	3045	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	860 @ 1' 6 1/2"	2989	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.005 @ 1' 6 1/2"	0.103	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.008 @ 1' 6 1/2"	0.154	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 1"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	484	632	1116	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	484	632	1116	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 1" o/c	
Bottom Edge (Lu)	3' 1" o/c	

Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 1"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 1"	10' 3"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 5.5 (G.4-G.8) Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1961 @ 0	3281 (1.50")	Passed (60%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1433 @ 8 3/4"	3045	Passed (47%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2655 @ 2' 8 1/2"	2989	Passed (89%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.045 @ 2' 8 1/2"	0.181	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.079 @ 2' 8 1/2"	0.271	Passed (L/824)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 5' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	850	1110	1961	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	850	1110	1961	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 5" o/c	
Bottom Edge (Lu)	5' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 5' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 5' 5"	10' 3"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 5.5 (G.1-G.3) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1576 @ 2"	4961 (3,50")	Passed (32%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	682 @ 1' 2 3/4"	4725	Passed (14%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1455 @ 2' 2"	6091	Passed (24%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.004 @ 2' 2"	0.100	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.006 @ 2' 2"	0.200	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,50"	688	888	1576	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,50"	688	888	1576	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 4" o/c	
Bottom Edge (Lu)	4' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 4" (Front)	10' 3"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid G.1 (5.2-5.3) Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	986 @ 2' 5"	3281 (1.50")	Passed (30%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	981 @ 1' 8 1/4"	3045	Passed (32%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	901 @ 1' 6"	2989	Passed (30%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 1' 2 7/8"	0.081	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.004 @ 1' 2 7/8"	0.121	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 2' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	269	337	606	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	435	551	986	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	2' 5" o/c	
Bottom Edge (Lu)	2' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 2' 5"	N/A	6.4	--	
1 - Point (lb)	1' 6"	N/A	688	888	Linked from: Grid 5.5 (G.1-G.3) Flush Beam, Support 2

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 6 (G.1-G.3) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1753 @ 2"	4961 (3,50")	Passed (35%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	759 @ 1' 2 3/4"	4725	Passed (16%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1618 @ 2' 2"	6091	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.004 @ 2' 2"	0.100	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.007 @ 2' 2"	0.200	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,50"	764	989	1753	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,50"	764	989	1753	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 4" o/c	
Bottom Edge (Lu)	4' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 4" (Front)	11' 5"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 2.5 (D.4-D.6) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2581 @ 2"	4961 (3,50")	Passed (52%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1177 @ 1' 2 3/4"	4725	Passed (25%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2502 @ 2' 3 1/8"	6091	Passed (41%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.007 @ 2' 3 1/8"	0.105	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.012 @ 2' 3 1/8"	0.209	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 6 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1.82"	1119	1462	2581	Blocking
2 - Stud wall - HF	3,50"	3,50"	1.82"	1119	1462	2581	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 6" o/c	
Bottom Edge (Lu)	4' 6" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 6 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 6 1/4" (Front)	16' 2"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 3.3 (D.8-E.1) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2151 @ 2"	4961 (3,50")	Passed (43%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1013 @ 1' 2 3/4"	4725	Passed (21%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2152 @ 2' 3 7/8"	6091	Passed (35%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.006 @ 2' 3 7/8"	0.108	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.011 @ 2' 3 7/8"	0.216	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 7 3/4"

System : Floor

Member Type : Flush Beam

Building Use : Residential

Building Code : IBC 2018

Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,52"	935	1216	2151	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,52"	935	1216	2151	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 8" o/c	
Bottom Edge (Lu)	4' 8" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 7 3/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 7 3/4" (Front)	13' 1"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:29:36 PM UTC

ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3

File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 5.3 (D.5-E.2) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3323 @ 2"	4961 (3,50")	Passed (67%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2260 @ 1' 2 3/4"	4725	Passed (48%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	5845 @ 3' 10 1/8"	6091	Passed (96%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.048 @ 3' 10 1/8"	0.184	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.086 @ 3' 10 1/8"	0.368	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 7' 8 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	2,34"	1446	1877	3323	Blocking
2 - Stud wall - HF	3,50"	3,50"	2,34"	1446	1877	3323	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	7' 8" o/c	
Bottom Edge (Lu)	7' 8" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 7' 8 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 7' 8 1/4" (Front)	12' 2 1/2"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

3rd Floor Framing, Grid 6 (D.3-D.6) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2372 @ 2"	4961 (3,50")	Passed (48%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1191 @ 1' 2 3/4"	4725	Passed (25%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2546 @ 2' 5 5/8"	6091	Passed (42%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.008 @ 2' 5 5/8"	0.115	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.015 @ 2' 5 5/8"	0.230	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1.67"	1031	1341	2372	Blocking
2 - Stud wall - HF	3,50"	3,50"	1.67"	1031	1341	2372	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 11" o/c	
Bottom Edge (Lu)	4' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 11 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 11 1/4" (Front)	13' 7"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Roof Framing, Grid I Entry Roof Beam
1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4533 @ 2"	4961 (3.50")	Passed (91%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	3633 @ 1' 2"	7466	Passed (49%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	12571 @ 5' 10 1/2"	14792	Passed (85%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.240 @ 5' 10 1/2"	0.571	Passed (L/571)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.486 @ 5' 10 1/2"	0.761	Passed (L/282)	--	1.0 D + 1.0 S (All Spans)

- Deflection criteria: LL (L/240) and TL (L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 11' 9"
System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD
Member Pitch : 0.25/12

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	3.50"	3.50"	3.20"	2293	2240	4533	Blocking
2 - Stud wall - HF	3.50"	3.50"	3.20"	2293	2240	4533	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	11' 9" o/c	
Bottom Edge (Lu)	11' 9" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 11' 9"	N/A	8.9	--	
1 - Uniform (PSF)	0 to 11' 9" (Front)	15' 3"	25.0	25.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Roof Framing, Grid L 10' Deck Roof Beam
1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4992 @ 10' 7 1/8"	4961 (3,50")	Passed (101%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	3893 @ 1' 4"	7466	Passed (52%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	12402 @ 5' 5 9/16"	14792	Passed (84%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.192 @ 5' 5 9/16"	0.513	Passed (L/643)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.387 @ 5' 5 9/16"	0.684	Passed (L/318)	--	1.0 D + 1.0 S (All Spans)

- Deflection criteria: LL (L/240) and TL (L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 10' 3 1/8".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 10' 9 1/8"
System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD
Member Pitch : 0.25/12

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	5.50"	5.50"	3.63"	2600	2550	5149	Blocking
2 - Stud wall - HF	3.50"	3.50"	3.52"	2520	2472	4992	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	10' 9" o/c	
Bottom Edge (Lu)	10' 9" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 10' 9 1/8"	N/A	8.9	--	
1 - Uniform (PSF)	0 to 10' 9 1/8" (Front)	18' 8"	25.0	25.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Roof Framing, 6' Window Header
1 piece(s) 4 x 10 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2956 @ 0	3281 (1.50")	Passed (90%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	2108 @ 10 3/4"	4468	Passed (47%)	1.15	1.0 D + 1.0 S (All Spans)
Moment (Ft-lbs)	4618 @ 3' 1 1/2"	5166	Passed (89%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.044 @ 3' 1 1/2"	0.208	Passed (L/999+)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.088 @ 3' 1 1/2"	0.313	Passed (L/853)	--	1.0 D + 1.0 S (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 6' 3"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1491	1465	2956	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1491	1465	2956	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 3" o/c	
Bottom Edge (Lu)	6' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 6' 3"	N/A	8.2	--	
1 - Uniform (PSF)	0 to 6' 3"	18' 9"	25.0	25.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

Roof Framing, Grid B 11' Deck Roof Beam
1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4622 @ 11' 4"	4622 (2.03")	Passed (100%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	3898 @ 10' 5 1/2"	7466	Passed (52%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	12904 @ 5' 9"	14792	Passed (87%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.236 @ 5' 9"	0.558	Passed (L/569)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.477 @ 5' 9"	0.745	Passed (L/281)	--	1.0 D + 1.0 S (All Spans)

Member Length : 11' 4"
 System : Roof
 Member Type : Drop Beam
 Building Use : Residential
 Building Code : IBC 2018
 Design Methodology : ASD
 Member Pitch : 0.25/12

- Deflection criteria: LL (L/240) and TL (L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	3.50"	3.50"	3.36"	2406	2354	4760	Blocking
2 - Hanger on 10 1/2" GLB beam	3.50"	Hanger ¹	2.03"	2456	2405	4861	See note ¹

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	11' 4" o/c	
Bottom Edge (Lu)	11' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
2 - Face Mount Hanger	Connector not found	N/A	N/A	N/A	N/A	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 11' 4"	N/A	8.9	--	
1 - Uniform (PSF)	0 to 11' 7 1/2" (Front)	16' 4 1/2"	25.0	25.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
 ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
 File Name: East Town Crossing Building F (Left Side) (2X12)

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



Roof Framing, Deck Roof Cantilever Beam
1 piece(s) 5 1/2" x 10 1/2" 24F-V4 DF Glulam

An excessive uplift of -2576 lbs at support located at 4" failed this product. Uplift resisted by ST6215 strap

Overall Length: 6' 5 1/2"



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	7528 @ 4' 2 3/4"	12254 (5.50")	Passed (61%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	4877 @ 5' 4"	11733	Passed (42%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	0 @ N/A	N/A	Passed (N/A)	--	N/A
Neg Moment (Ft-lbs)	-10162 @ 4' 2 3/4"	17918	Passed (57%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.041 @ 6' 5 1/2"	0.223	Passed (2L/999+)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.082 @ 6' 5 1/2"	0.297	Passed (2L/648)	--	1.0 D + 1.0 S (All Spans)

Member Length : 6' 5 1/2"
System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD
Member Pitch : 0.25/12

- Deflection criteria: LL (L/240) and TL (L/180).
- Overhang deflection criteria: LL (2L/240) and TL (2L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical negative moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 6' 1 1/2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	5.50"	5.50"	1.50"	-1290	-1286	-2576	None
2 - Stud wall - HF	5.50"	5.50"	3.38"	3837	3691	7528	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 6" o/c	
Bottom Edge (Lu)	6' 6" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 6' 5 1/2"	N/A	14.0	--	
1 - Point (lb)	6' 3 3/4" (Front)	N/A	2456	2405	Linked from: Grid A 14' Deck Roof Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:29:36 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Left Side) (2X12)

2nd Floor Framing			
Member Name	Results (Max UTIL %)	Current Solution	Comments
Floor Joist 15'-2" and Under	Passed (101% M)	1 piece(s) 2 x 12 DF No.2 @ 16" OC	
Floor Joist 15'-8"	Passed (81% M)	1 piece(s) 2 x 12 DF No.2 @ 12" OC	
8'-5" Landing Joists	Passed (90% R)	1 piece(s) 2 x 12 HF No.2 @ 12" OC	
Short Stair Stringers	Passed (72% R)	1 piece(s) 4 x 12 HF No.2	
Long Short Stair Stringers	Passed (98% R)	1 piece(s) 3 1/2" x 12" 24F-V4 DF Glulam	
Top Landing Beam	Passed (100% R)	1 piece(s) 5 1/2" x 13 1/2" 24F-V4 DF Glulam	
8'-10" Deck Joist	Passed (55% R)	1 piece(s) 2 x 12 HF No.2 @ 16" OC	
6' Window Header	Passed (79% M)	1 piece(s) 4 x 10 DF No.2	
Grid 12 (D.6-D.8) Flush Beam	Passed (57% R)	1 piece(s) 4 x 12 DF No.2	
Grid 10.9 (D.6-D.8) Flush Beam	Passed (56% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8.8 (D.5-D.7) Flush Beam	Passed (74% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8.8 (D.9-E) Bathroom Door Header	Passed (83% M)	1 piece(s) 4 x 8 DF No.2	
Grid 7.8 (D.4-D.5) Bedroom Door Header	Passed (74% R)	1 piece(s) 4 x 8 DF No.2	
Grid 7.8 (D.7-E) Flush Beam	Passed (63% R)	2 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	Squash Blocks Required
Grid 11.7 (F.9-G.1) Bedroom Door Header	Passed (60% R)	1 piece(s) 4 x 8 DF No.2	
Grid 11.3 (G.2-F.4) Flush Beam	Passed (70% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8.4 (F-F.3) Flush Beam	Passed (90% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8 (F.5-F.6) Bedroom Door Header	Passed (83% R)	1 piece(s) 4 x 8 DF No.2	
Main Landing Post	Passed (97% B/C)	1 piece(s) 6 x 10 DF No.2	
Grid 7.8D.6 Post	Passed (81% f_{cp})	1 piece(s) 4 x 6 DF No.2	
Grid A (7-7.8) Rim Beam	Passed (100% R)	1 piece(s) 3 1/2" x 11 7/8" 24F-V4 DF Glulam	
Grid 7 (A-C) Cantilever Beam	Failed (60% R) Passed	3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	An excessive uplift of -1956 lbs at support located at 9 1/2" failed this product.
Grid 7.8 (A-C) Cantilever Beam	Failed (73% R) Passed	3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	An excessive uplift of -1081 lbs at support located at 9 1/2" failed this product.
Grid 8.8 (A-B) Cantilever Beam	Passed (46% R)	1 piece(s) 4 x 12 HF No.2	

FORTEWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC

ForteWEB v3.8


File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing			
Member Name	Results (Max UTIL %)	Current Solution	Comments
Floor Joist 15'-8"	Passed (81% M)	1 piece(s) 2 x 12 DF No.2 @ 12" OC	
Floor Joist 15'-2" and Under	Passed (101% M)	1 piece(s) 2 x 12 DF No.2 @ 16" OC	
8'-5" Landing Joists	Passed (90% R)	1 piece(s) 2 x 12 HF No.2 @ 12" OC	
Short Stair Stringers	Passed (72% R)	1 piece(s) 4 x 12 HF No.2	
Top Landing Beam	Passed (84% ΔL)	1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam	
4' Mid Landing Joists	Passed (63% R)	1 piece(s) 2 x 8 HF No.2 @ 16" OC	
Mid Landing Inner Beam	Passed (72% ΔL)	1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam	
Mid Landing Outer Beam	Passed (83% ΔL)	1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam	
8'-10" Deck Joist	Passed (55% R)	1 piece(s) 2 x 12 HF No.2 @ 16" OC	
6' Window Header	Passed (79% M)	1 piece(s) 4 x 10 DF No.2	
Grid 12 (D.6-D8) Flush Beam	Passed (28% R)	1 piece(s) 4 x 12 DF No.2	
Grid 10.9 (D.6-D.8) Flush Beam	Passed (28% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8.8 (D.D-B.8) Flush Beam	Passed (34% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8.8 (D.8-D.9) Bathroom Door Header	Passed (33% R)	1 piece(s) 4 x 8 DF No.2	
Grid 7.8 (D.4-D.5) Bedroom Door Header	Passed (37% R)	1 piece(s) 4 x 8 DF No.2	
Grid 7.8 (D.7-E) Flush Beam	Passed (63% R)	2 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL	
Grid 11.7 (F.9-G.1) Bedroom Door Header	Passed (30% R)	1 piece(s) 4 x 8 DF No.2	
Grid 11.3 (G.2-G.4) Flush Beam	Passed (35% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8.4 (G-G.3) Flush Beam	Passed (64% R)	1 piece(s) 4 x 12 DF No.2	
Grid 8 (G.5-G.6) Bedroom Door Header	Passed (42% R)	1 piece(s) 4 x 8 DF No.2	
Roof Framing			
Member Name	Results (Max UTIL %)	Current Solution	Comments
Grid I.7 Entry Roof Beam	Passed (102% R)	1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam	
Grid A 7'-3" Deck Roof Beam	Passed (73% M+)	1 piece(s) 3 1/2" x 7 1/2" 24F-V4 DF Glulam	
Grid L 9' Deck Roof Beam	Passed (100% M+)	1 piece(s) 3 1/2" x 9" 24F-V4 DF Glulam	
6' Window Header	Passed (90% R)	1 piece(s) 4 x 10 DF No.2	

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Floor Joist 15'-2" and Under
1 piece(s) 2 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	736 @ 2 1/2"	2126 (3,50")	Passed (35%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	621 @ 1' 2 3/4"	2025	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2750 @ 7' 10 5/8"	2729	Passed (101%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.234 @ 7' 10 5/8"	0.512	Passed (L/787)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.410 @ 7' 10 5/8"	0.768	Passed (L/450)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 15' 9 1/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	315	421	736	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.50"	315	421	736	Blocking

• Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6" o/c	
Bottom Edge (Lu)	15' 9" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 15' 9 1/4"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Floor Joist 15'-8"
1 piece(s) 2 x 12 DF No.2 @ 12" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	569 @ 2 1/2"	2126 (3,50")	Passed (27%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	483 @ 1' 2 3/4"	2025	Passed (24%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2199 @ 8' 1 5/8"	2729	Passed (81%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.200 @ 8' 1 5/8"	0.528	Passed (L/953)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.349 @ 8' 1 5/8"	0.793	Passed (L/544)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 16' 3 1/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	244	325	569	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.50"	244	325	569	Blocking

• Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 7" o/c	
Bottom Edge (Lu)	16' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 16' 3 1/4"	12"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, 8'-5" Landing Joists
1 piece(s) 2 x 12 HF No.2 @ 12" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	821 @ 3"	911 (1.50")	Passed (90%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	638 @ 1' 2 1/4"	1688	Passed (38%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1727 @ 4' 5 1/2"	2577	Passed (67%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.073 @ 4' 5 1/2"	0.281	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.095 @ 4' 5 1/2"	0.421	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 8' 5"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" LSL beam	3.00"	Hanger ¹	1.50"	201	669	869	See note ¹
2 - Hanger on 11 1/4" LSL beam	3.00"	Hanger ¹	1.50"	201	669	869	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 4" o/c	
Bottom Edge (Lu)	8' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie							
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories	
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d		
2 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d		

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 8' 11"	12"	45.0	150.0	Default Load


Weyerhaeuser Notes
Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library .
The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Short Stair Stringers
1 piece(s) 4 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1521 @ 3"	2126 (1.50")	Passed (72%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1146 @ 1' 2 1/4"	3938	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2891 @ 4' 5/8"	5752	Passed (50%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.042 @ 4' 5/8"	0.190	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.056 @ 4' 5/8"	0.380	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 7' 7 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	403	1216	1618	See note ¹
2 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	403	1216	1618	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	7' 7" o/c	
Bottom Edge (Lu)	7' 7" o/c	

• Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS410	2.00"	N/A	8-16d	6-16d	
2 - Face Mount Hanger	LUS410	2.00"	N/A	8-16d	6-16d	

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	3" to 7' 10 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 8' 1 1/4" (Front)	2'	45.0	150.0	Default Load

• Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Long Short Stair Stringers
1 piece(s) 3 1/2" x 12" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3118 @ 2"	3189 (2.25")	Passed (98%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2693 @ 14' 7 1/2"	7420	Passed (36%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	11954 @ 7' 10 3/4"	16800	Passed (71%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.425 @ 7' 10 3/4"	0.515	Passed (L/437)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.567 @ 7' 10 3/4"	0.773	Passed (L/327)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 15' 5 1/2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 15' 6 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Plate on concrete - HF	3.50"	2.25"	2.20"	790	2369	3159	1 1/4" Rim Board
2 - Hanger on 12" GLB beam	3.00"	Hanger ¹	1.50"	797	2394	3191	See note ¹

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	15' 6" o/c	
Bottom Edge (Lu)	15' 6" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie						
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
2 - Face Mount Hanger	HHUS410	3.00"	N/A	30-10d	10-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	1 1/4" to 15' 7 1/2"	N/A	10.2	--	
1 - Uniform (PSF)	0 to 15' 10 1/2" (Front)	2'	45.0	150.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Top Landing Beam
1 piece(s) 5 1/2" x 13 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	12196 @ 11' 9"	12251 (5.50")	Passed (100%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	8941 @ 10' 6"	13118	Passed (68%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	31638 @ 6' 9"	33413	Passed (95%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.265 @ 6' 1"	0.285	Passed (L/516)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.352 @ 6' 1 1/16"	0.571	Passed (L/389)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 12' 1"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	4.76"	2604	7997	10601	Blocking
2 - Stud wall - HF	5.50"	5.50"	5.48"	3004	9192	12196	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	18.0	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	5' 6"	45.0	150.0	Default Load
2 - Point (lb)	5' 3 3/4" (Front)	N/A	403	1216	Linked from: Short Stair Stringers, Support 1
3 - Point (lb)	1' 1/4" (Front)	N/A	403	1216	Linked from: Short Stair Stringers, Support 1
4 - Point (lb)	6' 9 3/8" (Front)	N/A	797	2394	Linked from: Long Short Stair Stringers, Support 2
5 - Point (lb)	11' 7/8" (Front)	N/A	797	2394	Linked from: Long Short Stair Stringers, Support 2

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, 8'-10" Deck Joist
1 piece(s) 2 x 12 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1168 @ 9' 2 1/2"	2126 (3,50")	Passed (55%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	520 @ 8' 1 1/2"	1688	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-968 @ 9' 2 1/2"	2577	Passed (38%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.028 @ 4' 2 7/8"	0.301	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.042 @ 4' 2 3/4"	0.452	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 11' 11 3/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- 285 lbs uplift at support located at 11' 11 1/4". Strapping or other restraint may be required.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" HF beam	2.00"	Hanger ¹	1.50"	152	306	457	See note ¹
2 - Stud wall - HF	3.50"	3.50"	1.92"	389	779	1168	None
3 - Stud wall - HF	3.50"	3.50"	1.50"	-55	120/-230	64/-285	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' o/c	
Bottom Edge (Lu)	12' o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 12' 1 3/4"	16"	30.0	60.0	Default Load

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, 6' Window Header
1 piece(s) 4 x 10 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2272 @ 0	3281 (1.50")	Passed (69%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1621 @ 10 3/4"	3885	Passed (42%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	3550 @ 3' 1 1/2"	4492	Passed (79%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.031 @ 3' 1 1/2"	0.208	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.068 @ 3' 1 1/2"	0.313	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 6' 3"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1215	1057	2272	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1215	1057	2272	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 3" o/c	
Bottom Edge (Lu)	6' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 6' 3"	N/A	8.2	--	
1 - Uniform (PSF)	0 to 6' 3"	6' 7"	30.0	40.0	Floor
2 - Uniform (PLF)	0 to 6' 3"	N/A	108.0	-	Wall
3 - Uniform (PSF)	0 to 6' 3"	3'	25.0	25.0	Roof

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 12 (D.6-D.8) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2818 @ 2"	4961 (3,50")	Passed (57%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	529 @ 1' 2 3/4"	4725	Passed (11%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1162 @ 1' 11 5/8"	6091	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 1' 11 5/8"	0.090	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.004 @ 1' 11 5/8"	0.180	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,99"	1230	1588	2818	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,99"	1230	1588	2818	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 11" o/c	
Bottom Edge (Lu)	3' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 11 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 3' 11 1/4" (Front)	10' 1"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	615	794	Linked from: Grid 12 (B.6-B.8) Flush Beam, Support 1
3 - Point (lb)	3' 9 3/4" (Top)	N/A	615	794	Linked from: Grid 12 (B.6-B.8) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 10.9 (D.6-D.8) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2796 @ 2"	4961 (3.50")	Passed (56%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	525 @ 1' 2 3/4"	4725	Passed (11%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1153 @ 1' 11 5/8"	6091	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 1' 11 5/8"	0.090	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.004 @ 1' 11 5/8"	0.180	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.97"	1220	1576	2796	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.97"	1220	1576	2796	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 11" o/c	
Bottom Edge (Lu)	3' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 11 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 3' 11 1/4" (Front)	10'	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	610	788	Linked from: Grid 3.1 (B.6-B.8) Flush Beam, Support 1
3 - Point (lb)	3' 9 3/4" (Top)	N/A	610	788	Linked from: Grid 3.1 (B.6-B.8) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 8.8 (D.5-D.7) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3651 @ 4' 6 1/4"	4961 (3,50")	Passed (74%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1918 @ 3' 5 1/2"	4725	Passed (41%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	3277 @ 3' 2 7/16"	6091	Passed (54%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.009 @ 2' 5 1/4"	0.109	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.016 @ 2' 5 1/4"	0.218	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 8 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1.61"	993	1283	2275	Blocking
2 - Stud wall - HF	3,50"	3,50"	2.58"	1587	2064	3651	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 8" o/c	
Bottom Edge (Lu)	4' 8" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 8 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 8 1/4" (Front)	10'	30.0	40.0	2nd Floor
2 - Uniform (PSF)	3' 4 1/4" to 4' 8 1/4" (Front)	10'	30.0	40.0	3rd Floor
3 - Point (lb)	3' 2 1/2" (Top)	N/A	727	938	Linked from: Grid 5.2 (B.6-B.8) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 8.8 (D.9-E) Bathroom Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2637 @ 0	3281 (1.50")	Passed (80%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1911 @ 2' 8 1/4"	3045	Passed (63%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2472 @ 1' 10 1/2"	2989	Passed (83%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.016 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.029 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1138	1499	2637	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1050	1377	2426	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	10'	30.0	40.0	Default Load
2 - Uniform (PSF)	0 to 2' 2"	10'	30.0	40.0	Default Load
3 - Point (lb)	2' 2 3/4"	N/A	472	617	Linked from: Grid 5.2 (B.8-B.9) Bathroom Door Header, Support 1

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 7.8 (D.4-D.5) Bedroom Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2413 @ 0	3281 (1.50")	Passed (74%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	692 @ 8 3/4"	3045	Passed (23%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1031 @ 1' 8 1/2"	2989	Passed (34%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.007 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.012 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1046	1366	2413	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1046	1366	2413	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	10'	30.0	40.0	Default Load
2 - Point (lb)	3/4"	N/A	523	683	Linked from: Grid 6.2 (B.4-B.5) Bedroom Door Header, Support 1
3 - Point (lb)	3' 4 1/4"	N/A	523	683	Linked from: Grid 6.2 (B.4-B.5) Bedroom Door Header, Support 2

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 7.8 (D.7-E) Flush Beam
2 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3142 @ 8' 10"	4961 (3.50")	Passed (63%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2268 @ 1' 4 3/4"	7481	Passed (30%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	6426 @ 4' 7"	16137	Passed (40%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.067 @ 4' 7"	0.213	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.119 @ 4' 7"	0.425	Passed (L/854)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 8' 10 1/2"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	4.00"	2.24"	2852	3666	6519	1 1/2" Rim Board, Squash Blocks
2 - Stud wall - HF	3.50"	3.50"	2.22"	2752	3534	6285	Blocking, Squash Blocks

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Squash Blocks must match bearing length and are assumed to carry all loads applied directly above them, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	8' 11" o/c	
Bottom Edge (Lu)	8' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	1 1/2" to 9'	N/A	11.5	--	
1 - Uniform (PSF)	0 to 9' (Front)	10'	30.0	40.0	Default Load
2 - Point (lb)	8' 10 1/4" (Top)	N/A	1376	1767	Linked from: Grid 6.2 (B.7-C) Flush Beam, Support 2
3 - Point (lb)	2 3/4" (Top)	N/A	1426	1833	Linked from: Grid 6.2 (B.7-C) Flush Beam, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 11.7 (F.9-G.1) Bedroom Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1976 @ 0	3281 (1.50")	Passed (60%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	566 @ 8 3/4"	3045	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	844 @ 1' 8 1/2"	2989	Passed (28%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.006 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.010 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	860	1116	1976	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	860	1116	1976	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	8' 2"	30.0	40.0	Default Load
2 - Point (lb)	3/4"	N/A	430	558	Linked from: Grid 2.3 (D-D.1) Bedroom Door Header, Support 1
3 - Point (lb)	3' 4 1/4"	N/A	430	558	Linked from: Grid 2.3 (D-D.1) Bedroom Door Header, Support 2

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 11.3 (G.2-F.4) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3472 @ 2"	4961 (3,50")	Passed (70%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	756 @ 1' 2 3/4"	4725	Passed (16%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1612 @ 2' 2 1/8"	6091	Passed (26%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.004 @ 2' 2 1/8"	0.101	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.007 @ 2' 2 1/8"	0.201	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 4 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	2,45"	1512	1960	3472	Blocking
2 - Stud wall - HF	3,50"	3,50"	2,45"	1512	1960	3472	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 4" o/c	
Bottom Edge (Lu)	4' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 4 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 4 1/4" (Front)	11' 3"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	756	980	Linked from: Grid 2.7 (D.2-D.4) Flush Beam, Support 1
3 - Point (lb)	4' 2 3/4" (Top)	N/A	756	980	Linked from: Grid 2.7 (D.2-D.4) Flush Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 8.4 (F-F.3) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4468 @ 2"	4961 (3,50")	Passed (90%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1347 @ 4' 5 1/2"	4725	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2746 @ 2' 9 3/8"	6091	Passed (45%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.011 @ 2' 9 3/8"	0.131	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.020 @ 2' 9 3/8"	0.261	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 5' 4 3/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	3,15"	1946	2522	4468	Blocking
2 - Hanger on 11 1/4" LSL beam	3,50"	Hanger ¹	1,50"	1014	1318	2332	See note ¹

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 5" o/c	
Bottom Edge (Lu)	5' 5" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
2 - Face Mount Hanger	LUS414	2.00"	N/A	10-16d	6-16d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 5' 4 3/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 5' 8 1/4" (Front)	11' 4"	30.0	40.0	Default Load
2 - Point (lb)	1 3/4" (Top)	N/A	973	1261	Linked from: Grid 5.6 (D-D.3) Flush Beam, Support 1

- Side loads are assumed to not induce cross-grain tension.

Forteweb Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
Forteweb v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Grid 8 (F.5-F.6) Bedroom Door Header

1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2732 @ 0	3281 (1.50")	Passed (83%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	783 @ 8 3/4"	3045	Passed (26%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1167 @ 1' 8 1/2"	2989	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.008 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.014 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1184	1548	2732	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1184	1548	2732	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	11' 4"	30.0	40.0	Default Load
2 - Point (lb)	3/4"	N/A	592	774	Linked from: Grid 6 (D.5-D.6) Bedroom Door Header, Support 1
3 - Point (lb)	3' 4 1/4"	N/A	592	774	Linked from: Grid 6 (D.5-D.6) Bedroom Door Header, Support 2

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)


2nd Floor Framing, Main Landing Post

1 piece(s) 6 x 10 DF No.2

Wall Height: 9'

Member Height: 8' 7 1/2"

Tributary Width: 1' 4"



Drawing is Conceptual

Design Results	Actual	Allowed	Result	LDF	Load: Combination
Slenderness	11	50	Passed (22%)	--	--
Compression (lbs)	20238	30059	Passed (67%)	1.00	1.0 D + 1.0 L
Plate Bearing (lbs)	20238	21161	Passed (96%)	--	1.0 D + 1.0 L
Lateral Reaction (lbs)	79	--	--	1.60	1.0 D + 0.6 W
Lateral Shear (lbs)	65	9475	Passed (1%)	1.60	1.0 D + 0.6 W
Lateral Moment (ft-lbs)	171 @ mid-span	9642	Passed (2%)	1.60	1.0 D + 0.6 W
Total Deflection (in)	0.04 @ mid-span	0.86	Passed (L/2401)	--	1.0 D + 1.0 L
Bending/Compression	0.97	1	Passed (97%)	1.00	1.0 D + 1.0 L

- Lateral deflection criteria: Wind (L/120)
- Input axial load eccentricity for this design is 16.67% of applicable member side dimension.
- Applicable calculations are based on NDS.
- Bearing shall be on a metal plate or strap, or on other equivalently durable, rigid, homogeneous material with sufficient stiffness to distribute applied load.
- Special detailing and installation procedures are necessary for large wall construction.
- Lumber grading provisions must be extended over the length of the member per NDS 4.2.5.5.

Supports	Type	Material
Top	Dbl 2X	Hem Fir
Base	2X	Hem Fir

System : Wall
Member Type : Column
Building Code : IBC 2018
Design Methodology : ASD

Max Unbraced Length	Comments
1'	

Lateral Connections				
Supports	Connector	Type/Model	Quantity	Connector Nailing
Top	Nails	8d (0.113" x 2 1/2") (Toe)	2	N/A
Base	Nails	8d (0.113" x 2 1/2") (Toe)	2	N/A

- Nailed connection at the top of the member is assumed to be nailed through the bottom 2x plate prior to placement of the top 2x of the double top plate assembly.

Vertical Loads	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
1 - Point (lb)	N/A	3004	9192	Linked from: Top Landing Beam, Support 2
2 - Point (lb)	N/A	1975	6067	Linked from: Top Landing Beam, Support 1

Lateral Load	Location	Tributary Width	Wind (1.60)	Comments
1 - Uniform (PSF)	Full Length	1' 4"	22.9	

- ASCE/SEI 7 Sec. 30.4: Exposure Category (B), Mean Roof Height (33'), Topographic Factor (1.0), Wind Directionality Factor (0.85), Basic Wind Speed (110), Risk Category(II), Wind Zone (4), GCpi (+/- 0.18), Effective Wind Area determined using full member span and trib. width.
- IBC Table 1604.3, footnote f: Deflection checks are performed using 42% of this lateral wind load.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC

ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3

File Name: East Town Crossing Building F (Right Side) (2X12)

Page 25 / 58


2nd Floor Framing, Grid 7.8D.6 Post

1 piece(s) 4 x 6 DF No.2

Wall Height: 9'

Member Height: 8' 7 1/2"

Tributary Width: 0



Drawing is Conceptual

Design Results	Actual	Allowed	Result	LDF	Load: Combination
Slenderness	19	50	Passed (38%)	--	--
Compression (lbs)	6286	18757	Passed (34%)	1.00	1.0 D + 1.0 L
Plate Bearing (lbs)	6286	7796	Passed (81%)	--	1.0 D + 1.0 L
Lateral Reaction (lbs)	0	--	--	--	N/A
Lateral Shear (lbs)	0	N/A	Passed (N/A)	--	N/A
Lateral Moment (ft-lbs)	0 @ mid-span	N/A	Passed (N/A)	--	N/A
Total Deflection (in)	0.00 @ mid-span	N/A	Passed (N/A)	--	N/A
Bending/Compression	N/A	1	Passed (N/A)	--	N/A

- Lateral deflection criteria: Wind (L/180)
- Input axial load eccentricity for the design is zero
- Applicable calculations are based on NDS.
- Bearing shall be on a metal plate or strap, or on other equivalently durable, rigid, homogeneous material with sufficient stiffness to distribute applied load.

Supports	Type	Material
Top	Dbl 2X	Hem Fir
Base	2X	Hem Fir

System : Wall
Member Type : Column
Building Code : IBC 2018
Design Methodology : ASD

Max Unbraced Length	Comments
1'	

Lateral Connections

Supports	Connector	Type/Model	Quantity	Connector Nailing
Top	Nails	8d (0.113" x 2 1/2") (Toe)	2	N/A
Base	Nails	8d (0.113" x 2 1/2") (Toe)	2	N/A

- Nailed connection at the top of the member is assumed to be nailed through the bottom 2x plate prior to placement of the top 2x of the double top plate assembly.

Vertical Load	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
1 - Point (lb)	N/A	2752	3534	Linked from: Grid 6.2 (B.7-C) Flush Beam, Support 2

Lateral Load	Location	Tributary Width	Wind (1.60)	Comments
1 - Uniform (PSF)	Full Length	N/A	22.9	

- ASCE/SEI 7 Sec. 30.4: Exposure Category (B), Mean Roof Height (33'), Topographic Factor (1.0), Wind Directionality Factor (0.85), Basic Wind Speed (110), Risk Category(II), Wind Zone (4), GCpi (+/- 0.18), Effective Wind Area determined using full member span and trib. width.
- IBC Table 1604.3, footnote f: Deflection checks are performed using 42% of this lateral wind load.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	




10/31/2024 5:49:57 PM UTC

ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3

File Name: East Town Crossing Building F (Right Side) (2X12)

Page 26 / 58

2nd Floor Framing, Grid A (7-7.8) Rim Beam
1 piece(s) 3 1/2" x 11 7/8" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	5134 @ 3 1/2"	5134 (2.26")	Passed (100%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	4114 @ 1' 3 3/8"	8444	Passed (49%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	12782 @ 5' 3 1/4"	18920	Passed (68%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.098 @ 5' 3 1/4"	0.249	Passed (L/999+)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.260 @ 5' 3 1/4"	0.498	Passed (L/460)	--	1.0 D + 1.0 S (All Spans)

Member Length : 9' 11 1/2"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 9' 11 1/2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)				Accessories
	Total	Available	Required	Dead	Floor Live	Snow	Factored	
1 - Hanger on 11 7/8" GLB beam	3.50"	Hanger ¹	2.26"	3389	422	2042	5432	See note ¹
2 - Hanger on 11 7/8" GLB beam	3.50"	Hanger ¹	2.26"	3389	422	2042	5432	See note ¹

- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	10' o/c	
Bottom Edge (Lu)	10' o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	HHUS410	3.00"	N/A	30-10d	10-10d	
2 - Face Mount Hanger	HHUS410	3.00"	N/A	30-10d	10-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Snow (1.15)	Comments
0 - Self Weight (PLF)	3 1/2" to 10' 3"	N/A	10.1	--	--	
1 - Uniform (PSF)	0 to 10' 6 1/2" (Front)	1'	15.0	40.0	-	Level 2 Floor
2 - Uniform (PSF)	0 to 10' 6 1/2" (Front)	1'	15.0	40.0	-	Level 3 Floor
3 - Uniform (PLF)	0 to 10' 6 1/2" (Top)	N/A	216.0	-	-	Walls
4 - Uniform (PSF)	0 to 10' 6 1/2" (Front)	15' 6"	25.0	-	25.0	Roof

- Side loads are assumed to not induce cross-grain tension.

FortewEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
FortewEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Grid 7 (A-C) Cantilever Beam
3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL

An excessive uplift of -1956 lbs at support located at 9 1/2" failed this product. Uplift resisted by ST6215 strap



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	13979 @ 5' 6 1/2"	23389 (11.00")	Passed (60%)	--	1.0 D + 0.525 E + 0.75 L + 0.75 S (All Spans)
Shear (lbs)	6120 @ 6' 11 1/4"	12905	Passed (47%)	1.15	1.0 D + 0.75 L + 0.75 S (All Spans)
Moment (Ft-lbs)	-14621 @ 5' 6 1/2"	27837	Passed (53%)	1.15	1.0 D + 0.75 L + 0.75 S (All Spans)
Live Load Defl. (in)	0.051 @ 8'	0.200	Passed (2L/999+)	--	1.0 D + 0.75 L + 0.75 S (Alt Spans)
Total Load Defl. (in)	0.137 @ 8'	0.246	Passed (2L/430)	--	1.0 D + 0.75 L + 0.75 S (Alt Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Overhang deflection criteria: LL (0.2") and TL (2L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 8'
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)					Accessories
	Total	Available	Required	Dead	Floor Live	Snow	Seismic	Factored	
1 - Stud wall - HF	11.00"	11.00"	1.50"	-304	1261/-459	-994	1071/-1071	958/-1956	Blocking
2 - Stud wall - HF	11.00"	11.00"	6.57"	7949	2806	3036	3141/-3141	13979	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	8' o/c	
Bottom Edge (Lu)	8' o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Snow (1.15)	Seismic (1.60)	Comments
0 - Self Weight (PLF)	0 to 8'	N/A	17.2	--	--	--	
1 - Uniform (PSF)	0 to 8' (Front)	4' 11 3/4"	30.0	40.0	-	-	Level 2
2 - Uniform (PSF)	0 to 8' (Top)	4' 11 3/4"	30.0	40.0	-	-	Level 3
3 - Uniform (PLF)	0 to 8' (Top)	N/A	216.0	-	-	-	Wall
4 - Point (lb)	8' (Front)	N/A	-	-	-	2070	Seismic Strap
5 - Point (lb)	7' 10 1/4" (Front)	N/A	3389	422	2042	-	Linked from: Grid A (7-7.8) Rim Beam, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

2nd Floor Framing, Grid 7.8 (A-C) Cantilever Beam
3 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL

An excessive uplift of -1081 lbs at support located at 9 1/2" failed this product. Uplift resisted by ST6215 strap



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	16988 @ 6'	23389 (11.00")	Passed (73%)	--	1.0 D + 0.525 E + 0.75 L + 0.75 S (All Spans)
Shear (lbs)	6711 @ 7' 4 3/4"	12905	Passed (52%)	1.15	1.0 D + 0.75 L + 0.75 S (All Spans)
Moment (Ft-lbs)	-16302 @ 6'	27837	Passed (59%)	1.15	1.0 D + 0.75 L + 0.75 S (All Spans)
Live Load Defl. (in)	0.064 @ 8' 5 1/2"	0.200	Passed (2L/918)	--	1.0 D + 0.75 L + 0.75 S (Alt Spans)
Total Load Defl. (in)	0.155 @ 8' 5 1/2"	0.246	Passed (2L/382)	--	1.0 D + 0.75 L + 0.75 S (Alt Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Overhang deflection criteria: LL (0.2") and TL (2L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 8' 5 1/2"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)					Accessories
	Total	Available	Required	Dead	Floor Live	Snow	Seismic	Factored	
1 - Stud wall - HF	11.00"	11.00"	1.64"	620	2864/-677	-907	977/-977	3483/-1081	Blocking
2 - Stud wall - HF	11.00"	11.00"	7.99"	9151	5368	2949	3047/-3047	16988	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	8' 6" o/c	
Bottom Edge (Lu)	8' 6" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Snow (1.15)	Seismic (1.60)	Comments
0 - Self Weight (PLF)	0 to 8' 5 1/2"	N/A	17.2	--	--	--	
1 - Uniform (PSF)	0 to 8' 5 1/2" (Front)	4' 11 3/4"	30.0	40.0	-	-	Level 2
2 - Uniform (PSF)	0 to 8' 5 1/2" (Top)	4' 11 3/4"	30.0	40.0	-	-	Level 3
3 - Uniform (PLF)	0 to 8' 5 1/2" (Top)	N/A	216.0	-	-	-	Wall
4 - Uniform (PSF)	0 to 8' 5 1/2" (Front)	3' 8 1/2"	30.0	60.0	-	-	Level 2 Deck
5 - Uniform (PSF)	0 to 8' 5 1/2" (Front)	3' 8 1/2"	30.0	60.0	-	-	Level 3 Deck
6 - Point (lb)	8' 5 1/2" (Front)	N/A	-	-	-	2070	Seismic Strap
7 - Point (lb)	8' 3 3/4" (Back)	N/A	3389	422	2042	-	Linked from: Grid A (7-7.8) Rim Beam, Support 2

- Side loads are assumed to not induce cross-grain tension.

Forteweb Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
Forteweb v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



2nd Floor Framing, Grid 8.8 (A-B) Cantilever Beam
1 piece(s) 4 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3612 @ 2' 1/4"	7796 (5.50")	Passed (46%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1375 @ 1' 4 3/4"	3938	Passed (35%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-2127 @ 2' 1/4"	5752	Passed (37%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.008 @ 4' 3"	0.200	Passed (2L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.017 @ 4' 3"	0.223	Passed (2L/999+)	--	1.0 D + 1.0 L (Alt Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Overhang deflection criteria: LL (0.2") and TL (2L/240).
- Right cantilever length exceeds 1/3 member length or 1/2 back span length. Additional bracing should be considered.
- Allowed moment does not reflect the adjustment for the beam stability factor.
- 877 lbs uplift at support located at 4". Strapping or other restraint may be required.
- Applicable calculations are based on NDS.

Member Length : 4' 3"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	1.50"	-258	235/-618	-877	Blocking
2 - Stud wall - HF	5.50"	5.50"	2.55"	1889	1723	3612	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 3" o/c	
Bottom Edge (Lu)	4' 3" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 3"	N/A	10.0	--	
1 - Uniform (PLF)	0 to 4' 3" (Top)	N/A	216.0	-	Wall
2 - Uniform (PSF)	0 to 1' 11 1/4" (Front)	1' 8"	30.0	60.0	Level 2 Deck
3 - Uniform (PSF)	1' 11 1/4" to 4' 3" (Front)	5' 4"	30.0	60.0	Level 2 Deck
4 - Uniform (PSF)	0 to 4' 3" (Front)	1' 8"	30.0	60.0	Level 3 Deck

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Floor Joist 15'-8"
1 piece(s) 2 x 12 DF No.2 @ 12" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	569 @ 2 1/2"	2126 (3,50")	Passed (27%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	483 @ 1' 2 3/4"	2025	Passed (24%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2199 @ 8' 1 5/8"	2729	Passed (81%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.200 @ 8' 1 5/8"	0.528	Passed (L/953)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.349 @ 8' 1 5/8"	0.793	Passed (L/544)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 16' 3 1/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	244	325	569	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.50"	244	325	569	Blocking

• Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 7" o/c	
Bottom Edge (Lu)	16' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 16' 3 1/4"	12"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Floor Joist 15'-2" and Under
1 piece(s) 2 x 12 DF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	736 @ 2 1/2"	2126 (3,50")	Passed (35%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	621 @ 1' 2 3/4"	2025	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2750 @ 7' 10 5/8"	2729	Passed (101%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.234 @ 7' 10 5/8"	0.512	Passed (L/787)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.410 @ 7' 10 5/8"	0.768	Passed (L/450)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 15' 9 1/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.50"	315	421	736	Blocking
2 - Stud wall - HF	3.50"	3.50"	1.50"	315	421	736	Blocking

• Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6" o/c	
Bottom Edge (Lu)	15' 9" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 15' 9 1/4"	16"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, 8'-5" Landing Joists
1 piece(s) 2 x 12 HF No.2 @ 12" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	821 @ 3"	911 (1.50")	Passed (90%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	638 @ 1' 2 1/4"	1688	Passed (38%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1727 @ 4' 5 1/2"	2577	Passed (67%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.073 @ 4' 5 1/2"	0.281	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.095 @ 4' 5 1/2"	0.421	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 8' 5"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" LSL beam	3.00"	Hanger ¹	1.50"	201	669	869	See note ¹
2 - Hanger on 11 1/4" LSL beam	3.00"	Hanger ¹	1.50"	201	669	869	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 4" o/c	
Bottom Edge (Lu)	8' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie							
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories	
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d		
2 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d		

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 8' 11"	12"	45.0	150.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Short Stair Stringers
1 piece(s) 4 x 12 HF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1529 @ 3"	2126 (1.50")	Passed (72%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1154 @ 1' 2 1/4"	3938	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2923 @ 4' 7/8"	5752	Passed (51%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.043 @ 4' 7/8"	0.191	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.057 @ 4' 7/8"	0.382	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 7' 7 3/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	405	1222	1627	See note ¹
2 - Hanger on 11 1/4" GLB beam	3.00"	Hanger ¹	1.50"	405	1222	1627	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	7' 8" o/c	
Bottom Edge (Lu)	7' 8" o/c	

• Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS410	2.00"	N/A	8-16d	6-16d	
2 - Face Mount Hanger	LUS410	2.00"	N/A	8-16d	6-16d	

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	3" to 7' 10 3/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 8' 1 3/4" (Front)	2'	45.0	150.0	Default Load

• Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Top Landing Beam
1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	8041 @ 4"	12251 (5.50")	Passed (66%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	6022 @ 1' 5 1/2"	11660	Passed (52%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	20040 @ 5' 3 3/4"	26400	Passed (76%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.241 @ 5' 11 13/16"	0.285	Passed (L/569)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.319 @ 5' 11 3/4"	0.571	Passed (L/429)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 12' 1"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	3.61"	1975	6067	8041	Blocking
2 - Stud wall - HF	5.50"	5.50"	2.87"	1567	4836	6402	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	16.0	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	4' 8"	45.0	150.0	Default Load
2 - Point (lb)	1' 1/4" (Front)	N/A	405	1222	Linked from: Short Stair Stringers, Support 1
3 - Point (lb)	5' 3 3/4" (Front)	N/A	405	1222	Linked from: Short Stair Stringers, Support 1

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, 4' Mid Landing Joists
1 piece(s) 2 x 8 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	577 @ 2"	911 (1.50")	Passed (63%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	420 @ 9 1/4"	1088	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	640 @ 2' 4 5/8"	1284	Passed (50%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.028 @ 2' 4 5/8"	0.148	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.037 @ 2' 4 5/8"	0.222	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 4' 5 1/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 7 1/4" LSL beam	2.00"	Hanger ¹	1.50"	143	477	620	See note ¹
2 - Hanger on 7 1/4" LSL beam	2.00"	Hanger ¹	1.50"	143	477	620	See note ¹

• At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger

• ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 5" o/c	
Bottom Edge (Lu)	4' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie							
Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories	
1 - Face Mount Hanger	LU26	1.50"	N/A	6-10d	4-10dx1.5		
2 - Face Mount Hanger	LU26	1.50"	N/A	6-10d	4-10dx1.5		

• Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 4' 9 1/4"	16"	45.0	150.0	Default Load


Weyerhaeuser Notes
Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library .
The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Mid Landing Inner Beam
1 piece(s) 5 1/2" x 12" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	6299 @ 11' 9"	12251 (5.50")	Passed (51%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	4890 @ 1' 5 1/2"	11660	Passed (42%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	17407 @ 6' 7/16"	26400	Passed (66%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.207 @ 6' 1/2"	0.285	Passed (L/663)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.276 @ 6' 1/2"	0.571	Passed (L/496)	--	1.0 D + 1.0 L (All Spans)

Member Length : 12' 1"
 System : Floor
 Member Type : Flush Beam
 Building Use : Residential
 Building Code : IBC 2018
 Design Methodology : ASD

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	2.83"	1586	4707	6293	Blocking
2 - Stud wall - HF	5.50"	5.50"	2.83"	1587	4712	6299	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	16.0	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	2' 6"	45.0	150.0	Default Load
2 - Point (lb)	1' 1/4" (Front)	N/A	405	1222	Linked from: Short Stair Stringers, Support 1
3 - Point (lb)	5' 3 3/4" (Front)	N/A	405	1222	Linked from: Short Stair Stringers, Support 1
4 - Point (lb)	6' 9 3/8" (Front)	N/A	405	1222	Linked from: Short Stair Stringers, Support 1
5 - Point (lb)	11' 7/8" (Front)	N/A	405	1222	Linked from: Short Stair Stringers, Support 1

- Side loads are assumed to not induce cross-grain tension.

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
 ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
 File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



3rd Floor Framing, Mid Landing Outer Beam
1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2999 @ 4"	7796 (5.50")	Passed (38%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2337 @ 1' 4"	6493	Passed (36%)	1.00	1.0 D + 1.0 L (All Spans)
Pos Moment (Ft-lbs)	8088 @ 6' 1/2"	12863	Passed (63%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.236 @ 6' 1/2"	0.285	Passed (L/581)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.312 @ 6' 1/2"	0.571	Passed (L/439)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 12' 1"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	5.50"	2.12"	734	2266	2999	Blocking
2 - Stud wall - HF	5.50"	5.50"	2.12"	734	2266	2999	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' 1" o/c	
Bottom Edge (Lu)	12' 1" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 12' 1"	N/A	8.9	--	
1 - Uniform (PSF)	0 to 12' 1" (Front)	2' 6"	45.0	150.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, 8'-10" Deck Joist
1 piece(s) 2 x 12 HF No.2 @ 16" OC



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1168 @ 9' 2 1/2"	2126 (3,50")	Passed (55%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	520 @ 8' 1 1/2"	1688	Passed (31%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-968 @ 9' 2 1/2"	2577	Passed (38%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.028 @ 4' 2 7/8"	0.301	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
Total Load Defl. (in)	0.042 @ 4' 2 3/4"	0.452	Passed (L/999+)	--	1.0 D + 1.0 L (Alt Spans)
TJ-Pro™ Rating	N/A	N/A	N/A	--	N/A

Member Length : 11' 11 3/4"
System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- A 15% increase in the moment capacity has been added to account for repetitive member usage.
- 285 lbs uplift at support located at 11' 11 1/4". Strapping or other restraint may be required.
- Applicable calculations are based on NDS.
- No composite action between deck and joist was considered in analysis.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Hanger on 11 1/4" HF beam	2.00"	Hanger ¹	1.50"	152	306	457	See note ¹
2 - Stud wall - HF	3.50"	3.50"	1.92"	389	779	1168	None
3 - Stud wall - HF	3.50"	3.50"	1.50"	-55	120/-230	64/-285	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	12' o/c	
Bottom Edge (Lu)	12' o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
1 - Face Mount Hanger	LUS28	1.75"	N/A	6-10dx1.5	3-10d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Load	Location (Side)	Spacing	Dead (0.90)	Floor Live (1.00)	Comments
1 - Uniform (PSF)	0 to 12' 1 3/4"	16"	30.0	60.0	Default Load

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Weyerhaeuser Notes


Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



3rd Floor Framing, 6' Window Header
1 piece(s) 4 x 10 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2272 @ 0	3281 (1.50")	Passed (69%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1621 @ 10 3/4"	3885	Passed (42%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	3550 @ 3' 1 1/2"	4492	Passed (79%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.031 @ 3' 1 1/2"	0.208	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.068 @ 3' 1 1/2"	0.313	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 6' 3"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1215	1057	2272	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1215	1057	2272	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 3" o/c	
Bottom Edge (Lu)	6' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 6' 3"	N/A	8.2	--	
1 - Uniform (PSF)	0 to 6' 3"	6' 7"	30.0	40.0	Floor
2 - Uniform (PLF)	0 to 6' 3"	N/A	108.0	-	Wall
3 - Uniform (PSF)	0 to 6' 3"	3'	25.0	25.0	Roof

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 12 (D.6-D8) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1409 @ 2"	4961 (3,50")	Passed (28%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	529 @ 1' 2 3/4"	4725	Passed (11%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1162 @ 1' 11 5/8"	6091	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 1' 11 5/8"	0.090	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.004 @ 1' 11 5/8"	0.180	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,50"	615	794	1409	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,50"	615	794	1409	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 11" o/c	
Bottom Edge (Lu)	3' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 11 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 3' 11 1/4" (Front)	10' 1"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 10.9 (D.6-D.8) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1398 @ 2"	4961 (3,50")	Passed (28%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	525 @ 1' 2 3/4"	4725	Passed (11%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1153 @ 1' 11 5/8"	6091	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.002 @ 1' 11 5/8"	0.090	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.004 @ 1' 11 5/8"	0.180	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 11 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,50"	610	788	1398	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,50"	610	788	1398	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 11" o/c	
Bottom Edge (Lu)	3' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 11 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 3' 11 1/4" (Front)	10'	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 8.8 (D.D-B.8) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1664 @ 2"	4961 (3,50")	Passed (34%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	791 @ 1' 2 3/4"	4725	Passed (17%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1683 @ 2' 4 1/8"	6091	Passed (28%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.005 @ 2' 4 1/8"	0.109	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.009 @ 2' 4 1/8"	0.218	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 8 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,50"	727	938	1664	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,50"	727	938	1664	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 8" o/c	
Bottom Edge (Lu)	4' 8" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 8 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 8 1/4" (Front)	10'	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 8.8 (D.8-D.9) Bathroom Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1089 @ 0	3281 (1.50")	Passed (33%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	574 @ 8 3/4"	3045	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	839 @ 1' 6 1/2"	2989	Passed (28%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.005 @ 1' 6 1/2"	0.103	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.008 @ 1' 6 1/2"	0.154	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 1"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	472	617	1089	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	472	617	1089	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 1" o/c	
Bottom Edge (Lu)	3' 1" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 1"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 1"	10'	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 7.8 (D.4-D.5) Bedroom Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1207 @ 0	3281 (1.50")	Passed (37%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	692 @ 8 3/4"	3045	Passed (23%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1031 @ 1' 8 1/2"	2989	Passed (34%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.007 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.012 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	523	683	1207	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	523	683	1207	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	10'	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 7.8 (D.7-E) Flush Beam
2 piece(s) 1 3/4" x 11 1/4" 2.0E Microllam® LVL



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3142 @ 8' 10"	4961 (3.50")	Passed (63%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2268 @ 1' 4 3/4"	7481	Passed (30%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	6426 @ 4' 7"	16137	Passed (40%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.067 @ 4' 7"	0.213	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.119 @ 4' 7"	0.425	Passed (L/854)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.

Member Length : 8' 10 1/2"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	5.50"	4.00"	2.24"	1426	1833	3260	1 1/2" Rim Board
2 - Stud wall - HF	3.50"	3.50"	2.22"	1376	1767	3142	Blocking

- Rim Board is assumed to carry all loads applied directly above it, bypassing the member being designed.
- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	8' 11" o/c	
Bottom Edge (Lu)	8' 11" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	1 1/2" to 9'	N/A	11.5	--	
1 - Uniform (PSF)	0 to 9' (Front)	10'	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 11.7 (F.9-G.1) Bedroom Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	988 @ 0	3281 (1.50")	Passed (30%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	566 @ 8 3/4"	3045	Passed (19%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	844 @ 1' 8 1/2"	2989	Passed (28%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.006 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.010 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	430	558	988	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	430	558	988	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	8' 2"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator


ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 11.3 (G.2-G.4) Flush Beam

1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1736 @ 2"	4961 (3,50")	Passed (35%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	756 @ 1' 2 3/4"	4725	Passed (16%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1612 @ 2' 2 1/8"	6091	Passed (26%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.004 @ 2' 2 1/8"	0.101	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.007 @ 2' 2 1/8"	0.201	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 4' 4 1/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3,50"	3,50"	1,50"	756	980	1736	Blocking
2 - Stud wall - HF	3,50"	3,50"	1,50"	756	980	1736	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	4' 4" o/c	
Bottom Edge (Lu)	4' 4" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 4' 4 1/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 4' 4 1/4" (Front)	11' 3"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 8.4 (G-G.3) Flush Beam
1 piece(s) 4 x 12 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2100 @ 5' 4 3/4"	3281 (1.50")	Passed (64%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1347 @ 4' 5 1/2"	4725	Passed (29%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	2746 @ 2' 9 3/8"	6091	Passed (45%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.011 @ 2' 9 3/8"	0.131	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.020 @ 2' 9 3/8"	0.261	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/480) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 5' 4 3/4"
System : Floor
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Stud wall - HF	3.50"	3.50"	1.58"	973	1261	2234	Blocking
2 - Hanger on 11 1/4" LSL beam	3.50"	Hanger ¹	1.50"	1014	1318	2332	See note ¹

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.
- At hanger supports, the Total Bearing dimension is equal to the width of the material that is supporting the hanger
- ¹ See Connector grid below for additional information and/or requirements.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	5' 5" o/c	
Bottom Edge (Lu)	5' 5" o/c	

- Maximum allowable bracing intervals based on applied load.

Connector: Simpson Strong-Tie

Support	Model	Seat Length	Top Fasteners	Face Fasteners	Member Fasteners	Accessories
2 - Face Mount Hanger	LUS414	2.00"	N/A	10-16d	6-16d	

- Refer to manufacturer notes and instructions for proper installation and use of all connectors.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 5' 4 3/4"	N/A	10.0	--	
1 - Uniform (PSF)	0 to 5' 8 1/4" (Front)	11' 4"	30.0	40.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

3rd Floor Framing, Grid 8 (G.5-G.6) Bedroom Door Header
1 piece(s) 4 x 8 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	1366 @ 0	3281 (1.50")	Passed (42%)	--	1.0 D + 1.0 L (All Spans)
Shear (lbs)	783 @ 8 3/4"	3045	Passed (26%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1167 @ 1' 8 1/2"	2989	Passed (39%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.008 @ 1' 8 1/2"	0.114	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.014 @ 1' 8 1/2"	0.171	Passed (L/999+)	--	1.0 D + 1.0 L (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 3' 5"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Floor Live	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	592	774	1366	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	592	774	1366	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	3' 5" o/c	
Bottom Edge (Lu)	3' 5" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Floor Live (1.00)	Comments
0 - Self Weight (PLF)	0 to 3' 5"	N/A	6.4	--	
1 - Uniform (PSF)	0 to 3' 5"	11' 4"	30.0	40.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Roof Framing, Grid I.7 Entry Roof Beam
1 piece(s) 3 1/2" x 10 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	5084 @ 2"	4961 (3.50")	Passed (102%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	4075 @ 1' 2"	7466	Passed (55%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	14099 @ 5' 10 1/2"	14792	Passed (95%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.269 @ 5' 10 1/2"	0.571	Passed (L/509)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.545 @ 5' 10 1/2"	0.761	Passed (L/252)	--	1.0 D + 1.0 S (All Spans)

Member Length : 11' 9"
System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD
Member Pitch : 0.25/12

- Deflection criteria: LL (L/240) and TL (L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 11' 5".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	3.50"	3.50"	3.59"	2569	2515	5084	Blocking
2 - Stud wall - HF	3.50"	3.50"	3.59"	2569	2515	5084	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	9' 10" o/c	
Bottom Edge (Lu)	11' 9" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 11' 9"	N/A	8.9	--	
1 - Uniform (PSF)	0 to 11' 9" (Front)	17' 1 1/2"	25.0	25.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Roof Framing, Grid A 7'-3" Deck Roof Beam
1 piece(s) 3 1/2" x 7 1/2" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	3077 @ 7' 10"	4961 (3,50")	Passed (62%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	2357 @ 1' 1"	5333	Passed (44%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	5525 @ 4' 1"	7547	Passed (73%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.125 @ 4' 1"	0.375	Passed (L/719)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.253 @ 4' 1"	0.500	Passed (L/356)	--	1.0 D + 1.0 S (All Spans)

- Deflection criteria: LL (L/240) and TL (L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 7' 6".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Member Length : 8'
System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD
Member Pitch : 0.25/12

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	5.50"	5.50"	2.26"	1618	1591	3208	Blocking
2 - Stud wall - HF	3.50"	3.50"	2.17"	1552	1526	3077	Blocking

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	8' o/c	
Bottom Edge (Lu)	8' o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 8'	N/A	6.4	--	
1 - Uniform (PSF)	0 to 8' (Front)	15' 7"	25.0	25.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Roof Framing, Grid L 9' Deck Roof Beam
1 piece(s) 3 1/2" x 9" 24F-V4 DF Glulam



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	4850 @ 9' 7 1/2"	4961 (3.50")	Passed (98%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	3801 @ 1' 2 1/2"	6400	Passed (59%)	1.15	1.0 D + 1.0 S (All Spans)
Pos Moment (Ft-lbs)	10877 @ 4' 11 3/4"	10868	Passed (100%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.219 @ 4' 11 3/4"	0.465	Passed (L/509)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.442 @ 4' 11 3/4"	0.620	Passed (L/252)	--	1.0 D + 1.0 S (All Spans)

Member Length : 9' 9 1/2"
System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD
Member Pitch : 0.25/12

- Deflection criteria: LL (L/240) and TL (L/180).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Critical positive moment adjusted by a volume/size factor of 1.00 that was calculated using length L = 9' 3 1/2".
- The effects of positive or negative camber have not been accounted for when calculating deflection.
- The specified glulam is assumed to have its strong laminations at the bottom of the beam. Install with proper side up as indicated by the manufacturer.
- Applicable calculations are based on NDS.

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Stud wall - HF	5.50"	5.50"	3.54"	2529	2490	5018	Blocking
2 - Stud wall - HF	3.50"	3.50"	3.42"	2444	2406	4850	None

- Blocking Panels are assumed to carry no loads applied directly above them and the full load is applied to the member being designed.

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6" o/c	
Bottom Edge (Lu)	9' 10" o/c	

- Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location (Side)	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 9' 9 1/2"	N/A	7.7	--	
1 - Uniform (PSF)	0 to 9' 9 1/2" (Front)	20'	25.0	25.0	Default Load

- Side loads are assumed to not induce cross-grain tension.

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.


The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

Roof Framing, 6' Window Header
1 piece(s) 4 x 10 DF No.2



Drawing is Conceptual. All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal (typ.).

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2956 @ 0	3281 (1.50")	Passed (90%)	--	1.0 D + 1.0 S (All Spans)
Shear (lbs)	2108 @ 10 3/4"	4468	Passed (47%)	1.15	1.0 D + 1.0 S (All Spans)
Moment (Ft-lbs)	4618 @ 3' 1 1/2"	5166	Passed (89%)	1.15	1.0 D + 1.0 S (All Spans)
Live Load Defl. (in)	0.044 @ 3' 1 1/2"	0.208	Passed (L/999+)	--	1.0 D + 1.0 S (All Spans)
Total Load Defl. (in)	0.088 @ 3' 1 1/2"	0.313	Passed (L/853)	--	1.0 D + 1.0 S (All Spans)

- Deflection criteria: LL (L/360) and TL (L/240).
- Allowed moment does not reflect the adjustment for the beam stability factor.
- Applicable calculations are based on NDS.

Member Length : 6' 3"
System : Wall
Member Type : Header
Building Use : Residential
Building Code : IBC 2018
Design Methodology : ASD

Supports	Bearing Length			Loads to Supports (lbs)			Accessories
	Total	Available	Required	Dead	Snow	Factored	
1 - Trimmer - HF	1.50"	1.50"	1.50"	1491	1465	2956	None
2 - Trimmer - HF	1.50"	1.50"	1.50"	1491	1465	2956	None

Lateral Bracing	Bracing Intervals	Comments
Top Edge (Lu)	6' 3" o/c	
Bottom Edge (Lu)	6' 3" o/c	

•Maximum allowable bracing intervals based on applied load.

Vertical Loads	Location	Tributary Width	Dead (0.90)	Snow (1.15)	Comments
0 - Self Weight (PLF)	0 to 6' 3"	N/A	8.2	--	
1 - Uniform (PSF)	0 to 6' 3"	18' 9"	25.0	25.0	Default Load

Weyerhaeuser Notes

Weyerhaeuser warrants that the sizing of its products will be in accordance with Weyerhaeuser product design criteria and published design values. Weyerhaeuser expressly disclaims any other warranties related to the software. Use of this software is not intended to circumvent the need for a design professional as determined by the authority having jurisdiction. The designer of record, builder or framer is responsible to assure that this calculation is compatible with the overall project. Accessories (Rim Board, Blocking Panels and Squash Blocks) are not designed by this software. Products manufactured at Weyerhaeuser facilities are third-party certified to sustainable forestry standards. Weyerhaeuser Engineered Lumber Products have been evaluated by ICC-ES under evaluation reports ESR-1153 and ESR-1387 and/or tested in accordance with applicable ASTM standards. For current code evaluation reports, Weyerhaeuser product literature and installation details refer to www.weyerhaeuser.com/woodproducts/document-library.

The product application, input design loads, dimensions and support information have been provided by ForteWEB Software Operator

ForteWEB Software Operator	Job Notes
Chon Pieruccioni Pieruccioni Engineering (206) 949-7866 cpieru@hotmail.com	



10/31/2024 5:49:57 PM UTC
ForteWEB v3.8, Engine: V8.4.1.24, Data: V8.1.6.3
File Name: East Town Crossing Building F (Right Side) (2X12)

GEOMETRY

Footing Length (X-dir)	3.50	ft	
Footing Width (Z-dir)	3.50	ft	
Footing Thickness	8.0	in	OK
Soil Cover	0.00	ft	
Column Length (X-dir)	6.0	in	
Column Width (Z-dir)	6.0	in	
Offset (X-dir)	0.00	in	OK
Offset (Z-dir)	0.00	in	OK
Base Plate (L x W)	6.0 x 6.0	in	

SOIL PRESSURES (D+L)

Gross Allow. Soil Pressure	2.0	ksf	
Soil Pressure at Corner 1	1.6	ksf	
Soil Pressure at Corner 2	1.6	ksf	
Soil Pressure at Corner 3	1.6	ksf	
Soil Pressure at Corner 4	1.6	ksf	
Bearing Pressure Ratio	0.80		OK
Ftg. Area in Contact with Soil	100.0	%	
X-eccentricity / Ftg. Length	0.00		OK
Z-eccentricity / Ftg. Width	0.00		OK

APPLIED LOADS

	Dead	Live	RLive	Snow	Wind	Seismic	
Axial Force P	5.2	13.7	0.0	0.0	0.0	0.0	kip
Moment about X Mx ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Moment about Z Mz ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Shear Force Vx	0.0	0.0	0.0	0.0	0.0	0.0	kip
Shear Force Vz	0.0	0.0	0.0	0.0	0.0	0.0	kip

OVERTURNING CALCULATIONS (Comb: 0.6D+0.6W)

- Overturning about X-X

- Moment Mx = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ k-ft

- Shear Force Vz = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ kip

Arm = $0.00 + 8.0 / 12 = 0.67$ ft

Moment = $0.0 * 0.67 = 0.0$ k-ft

- Passive Force = 0.0 kip

Arm = 0.27 ft

Moment = 0.0 k-ft

- Overturning moment X-X = $0.0 + 0.0 = 0.0$ k-ft

- Resisting about X-X

- Footing weight = $0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.7 * 1.75 = 1.3$ k-ft

- Pedestal weight = $0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0$ kip

Arm = $W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75$ ft

Moment = $0.0 * 1.75 = 0.0$ k-ft

- Soil cover = $0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.0 * 1.75 = 0.0$ k-ft

- Buoyancy = $0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.3 * 1.75 = -0.5$ k-ft

- Axial force P = $0.6 * 5.2 + 0.6 * 0.0 = 3.1$ kip

Arm = $W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75$ ft

Moment = $3.1 * 1.75 = 5.5$ k-ft

- Resisting moment X-X = $1.3 + 0.0 + 0.0 + 5.5 + -0.5 = 6.2$ k-ft

- Overturning safety factor X-X = $\frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{6.2}{0.0} = 62.11 > 1.50$ OK

- Overturning about Z-Z

$$\text{- Moment } M_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about Z-Z

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.7 * 1.75 = 1.3 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.3 * 1.75 = -0.5 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 5.2 + 0.6 * 0.0 = 3.1 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 3.1 * 1.75 = 5.5 \text{ k-ft}$$

$$\text{- Resisting moment Z-Z} = 1.3 + 0.0 + 0.0 + 5.5 + -0.5 = 6.2 \text{ k-ft}$$

$$\text{- Overturning safety factor Z-Z} = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{6.2}{0.0} = 62.11 > 1.50 \text{ OK}$$

SOIL BEARING PRESSURES (Comb: D+L)

$$\text{Overturning moment X-X} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment X-X} = 2.1 + 0.0 + 0.0 + -0.9 + 33.0 = 34.3 \text{ k-ft}$$

$$\text{Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment Z-Z} = 2.1 + 0.0 + 0.0 + -0.9 + 33.0 = 34.3 \text{ k-ft}$$

$$\text{Resisting force} = \text{Footing} + \text{Pedestal} + \text{Soil} - \text{Buoyancy} + P = 1.2 + 0.0 + 0.0 - 0.5 + 18.9 = 19.6 \text{ kip}$$

X-coordinate of resultant from maximum bearing corner:

$$X_p = \frac{Z\text{-Resisting moment} - Z\text{-Overturning moment}}{\text{Resisting force}} = \frac{34.3 - 0.0}{19.6} = 1.75 \text{ ft}$$

Z-coordinate of resultant from maximum bearing corner:

$$Z_p = \frac{X\text{-Resisting moment} - X\text{-Overturning moment}}{\text{Resisting force}} = \frac{34.3 - 0.0}{19.6} = 1.75 \text{ ft}$$

$$X\text{-ecc} = \text{Length} / 2 - X_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$Z\text{-ecc} = \text{Width} / 2 - Z_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$\text{Area} = \text{Width} * \text{Length} = 3.50 * 3.50 = 12.3 \text{ ft}^2$$

$$S_x = \text{Length} * \text{Width}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$

$$S_z = \text{Width} * \text{Length}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$



- Footing is in full bearing. Soil pressures are as follows:

$$P1 = P * (1/A + Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 19.6 * (1 / 12.3 + 0.00 / 7.1 + 0.00 / 7.1) = 1.60 \text{ ksf}$$

$$P2 = P * (1/A - Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 19.6 * (1 / 12.3 - 0.00 / 7.1 + 0.00 / 7.1) = 1.60 \text{ ksf}$$

$$P3 = P * (1/A - Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 19.6 * (1 / 12.3 - 0.00 / 7.1 - 0.00 / 7.1) = 1.60 \text{ ksf}$$

$$P4 = P * (1/A + Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 19.6 * (1 / 12.3 + 0.00 / 7.1 - 0.00 / 7.1) = 1.60 \text{ ksf}$$



SLIDING CALCULATIONS (Comb: 0.6D+0.6W)

Internal friction angle = 28.0 deg

Passive coefficient $k_p = 4.33$ (per Coulomb)Pressure at mid-depth = $k_p \cdot \text{Density} \cdot (\text{Cover} + \text{Thick} / 2) = 4.33 \cdot 110 \cdot (0.00 + 8.0 / 12 / 2) = 0.16$ ksfX-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Width} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4$ kipZ-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Length} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4$ kipFriction force = $\text{Resisting force} \cdot \text{Friction coeff.} = \text{Max}(0, 3.5 \cdot 0.35) = 1.2$ kip

Use 100% of Passive + 100% of Friction for sliding resistance

$$\text{- Sliding safety factor X-X} = \frac{\text{X-Passive force} + \text{Friction}}{\text{X-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.2}{0.0} = 16.12 > 1.50 \quad \text{OK}$$

$$\text{- Sliding safety factor Z-Z} = \frac{\text{Z-Passive force} + \text{Friction}}{\text{Z-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.2}{0.0} = 16.12 > 1.50 \quad \text{OK}$$

UPLIFT CALCULATIONS (Comb: 0.6D+0.6W)

$$\text{- Uplift safety factor} = \frac{\text{Pedestal} + \text{Footing} + \text{Cover} - \text{Buoyancy}}{\text{Uplift load}} = \frac{0.0 + 0.7 + 0.0 - 0.3}{0.0} = 99.99 > 1.00 \quad \text{OK}$$

ONE-WAY SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

Concrete $f'_c = 2.5$ ksiSteel $f_y = 40.0$ ksi

Soil density = 110 pcf



d Top X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 2.0 - 0.8 / 2 = 5.6$ ind Top Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 2.0 - 0.8 - 0.8 / 2 = 4.9$ ind Bot X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 3.0 - 0.5 / 2 = 4.8$ ind Bot Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 3.0 - 0.5 - 0.5 / 2 = 4.3$ in $\phi V_{cx} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Width} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.8 / 1000 = 15.0$ kip

ACI Eq. (22.5.5.1)

 $\phi V_{cz} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Length} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.3 / 1000 = 13.4$ kip

- Shear forces calculated as the volume of the bearing pressures under the effective areas:

One-way shear V_{ux} (- Side) = 9.0 kip < 15.0 kip OKOne-way shear V_{ux} (+ Side) = 9.0 kip < 15.0 kip OKOne-way shear V_{uz} (- Side) = 9.0 kip < 13.4 kip OKOne-way shear V_{uz} (+ Side) = 9.0 kip < 13.4 kip OK



FLEXURE CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Plain } \phi M_{nx} = 5 * \phi * \sqrt{f_c} * L * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

ACI Eq. (14.5.2.1a)

$$\text{Plain } \phi M_{nz} = 5 * \phi * \sqrt{f_c} * W * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

- Top Bars

No Top Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Top

- Top moments calculated as the overburden minus the bearing pressures times the lever arm:

$$\text{Top moment -Mux (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Mux (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

- Bottom Bars

$$\text{Use 5 \#4 Z-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.3) = 0.0056$$

$$q = 0.0056 * 40 / 2.5 = 0.090$$

$$\text{Use 5 \#4 X-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.8) = 0.0050$$

$$q = 0.0050 * 40 / 2.5 = 0.080$$

$$\beta = L / W = 3.50 / 3.50 = 1.00 \quad \gamma_s = 2 * \beta / (\beta + 1) = 2 * 1.00 / (1.00 + 1) = 1.00$$

ACI 13.3.3.3

$$\text{Bending strength } \phi M_n = \phi * b * d^2 * f_c * q * (1 - 0.59 * q)$$

ACI 22.2.2

$$\phi M_{nx} = 0.90 * 3.50 * 12 * 4.3^2 * 2.5 * 0.090 * (1 - 0.59 * 0.090) = 12.1 \text{ k-ft}$$

$$\phi M_{nz} = 0.90 * 3.50 * 12 * 4.8^2 * 2.5 * 0.080 / 1.00 * (1 - 0.59 * 0.080 / 1.00) = 13.6 \text{ k-ft}$$

- Bottom moments calculated as the bearing minus the overburden pressures times the lever arm:

$$\text{Bottom moment Mux (- Side)} = 9.0 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.75$$

$$\text{Bottom moment Mux (+ Side)} = 9.1 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.75$$

$$\text{Bottom moment Muz (- Side)} = 9.0 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.67$$

$$\text{Bottom moment Muz (+ Side)} = 9.1 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.67$$

$$X\text{-As min} = 0.0018 * \text{Width} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$Z\text{-As min} = 0.0018 * \text{Length} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$X\text{-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$Z\text{-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$X\text{-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight } X\text{-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$X\text{-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.67) = 12.0 \text{ in}$$

$$\text{Hooked } X\text{-Ldh} = \text{Max} (8 db, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$X\text{-Ldh} = \text{Max} (8 db, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.67) = 6.0 \text{ in}$$

$$-X \text{ Ld provided} = (\text{Length} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$+X \text{ Ld provided} = (\text{Length} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

4 of 7

$$Z\text{-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight } Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.67) = 12.0 \text{ in}$$

$$\text{Hooked } Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.75) = 6.0 \text{ in}$$



$$-Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$+Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$X\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$

ACI 7.7.2.3

$$Z\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$



LOAD TRANSFER CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Area } A1 = \text{col } L * \text{col } W = 6.0 * 6.0 = 36.0 \text{ in}^2$$

$$Sx = \text{col } W * \text{col } L^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$Sz = \text{col } L * \text{col } W^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$\text{Bearing } Pbu = P / A1 + Mz / Sx + Mx / Sz = 28.1 / 36.0 + 0.0 * 12 / 36.0 + 0.0 * 12 / 36.0 = 0.8 \text{ ksi}$$

$$\text{Min edge} = \text{Min} (L / 2 - X\text{-offset} - \text{col } L / 2, W / 2 - Z\text{-offset} - \text{col } W / 2)$$

$$\text{Min edge} = \text{Min} (3.50 * 12 / 2 - 0.0 - 6.0 / 2, 3.50 * 12 / 2 - 0.0 - 6.0 / 2) = 18.0 \text{ in}$$

$$\text{Area } A2 = \text{Min} [L * W, (\text{col } L + 2 * \text{Min edge}) * (\text{col } W + 2 * \text{Min edge})]$$

ACI R22.8.3.2

$$A2 = \text{Min} [3.50 * 12 * 3.5 * 12, (6.0 + 2 * 18.0) * (6.0 + 2 * 18.0)] = 1764.0 \text{ in}^2$$

$$\text{Footing } \phi Pnc = \phi * 0.85 * f_c * \text{Min} [2, \sqrt{A2 / A1}] = 0.65 * 0.85 * 2.5 * \text{Min} [2, \sqrt{(1764.0 / 36.0)}] = 2.8 \text{ ksi}$$

$$\text{Footing } \phi Pns = \phi * As * Fy / A1 = 0.0 \text{ ksi}$$

ACI 22.8.3.2

$$\text{Footing bearing } \phi Pn = \phi Pnc + \phi Pns = 2.8 + 0.0 = 2.8 \text{ ksi} > 0.8 \text{ psi OK}$$

Hooked $L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * \text{db} * \text{ratio})$

ACI 25.4.3

$$L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * 60.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.75 * 0.14) = 6.0 \text{ in}$$

Ld provided = Dowel length = $3.00 * 12 = 36.0 \text{ in} > 24.3 \text{ in OK}$

Ldh provided = Footing thickness - Cover = $8.00 - 3.0 = 5.0 \text{ in} < 6.0 \text{ in NG}$

PUNCHING SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5Lr)

$$\text{X-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asx} = 20$$

$$\text{Z-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asz} = 20$$

$$\text{as} = \text{asx} + \text{asz} = 20 + 20 = 40 \quad \text{Col type} = \text{Interior} \quad \beta = L / W = 6.0 / 6.0 = 1.00$$

ACI 22.6.5.2

$$\text{Perimeter } b_o = \text{asx} / 10 * (L + d/2 + \text{X-Edge}) + \text{asx} / 10 * (W + d/2 + \text{Z-Edge})$$

ACI 22.6.4.2

$$b_o = 20 / 10 * (6.0 + 4.5 / 2 + 2.3) + 20 / 10 * (6.0 + 4.5 / 2 + 2.3) = 42.0 \text{ in}$$

$$\text{Area } A_{bo} = (L + d/2 + \text{X-Edge}) * (W + d/2 + \text{Z-Edge}) = (6.0 + 4.5 / 2 + 2.3) * (6.0 + 4.5 / 2 + 2.3) = 110.3 \text{ in}^2$$

$$\phi V_c = \phi * \text{Min} (2 + 4 / \beta, \text{as} * d / b_o + 2, 4) * \sqrt{f_c}$$

ACI 22.6.5.2

$$\phi V_c = 0.75 * \text{Min} (2 + 4 / 1.00, 40 * 4.5 / 42.0 + 2, 4) * \sqrt{2500} = 150.0 \text{ psi}$$

Punching force $F = P + \text{Overburden} * A_{bo} - \text{Bearing}$

$$F = 28.1 + 0.07 * 110.3 / 144 - 1.8 = 26.3 \text{ kip}$$

$$b1 = L + d/2 + \text{X-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in} \quad b2 = W + d/2 + \text{Z-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in}$$

$$\gamma_{vx} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b2/b1}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.4.2.2)

$$\gamma_{vz} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b1/b2}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.2.3.2)

$$X2z = b1/2 = 10.5/2 = 5.3 \text{ in} \quad X2x = b2/2 = 10.5/2 = 5.3 \text{ in}$$

$$J_{cz} = b1 * d^3 / 6 + b1^3 * d / 6 + b1^2 * b2 * d / 2$$

ACI R8.4.4.2.3

$$J_{cz} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$J_{cx} = b2 * d^3 / 6 + b2^3 * d / 6 + b2^2 * b1 * d / 2$$

ACI R8.4.4.2.3


$$J_{cx} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$\text{Stress due to } P = F / (b_o * d) * 1000 = 26.3 / (42.0 * 4.5) * 1000 = 139.4 \text{ psi}$$

$$\text{Stress due to } M_x = \gamma_{vx} * X\text{-OTM} * X2x / J_{cx} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$

$$\text{Stress due to } M_z = \gamma_{vz} * Z\text{-OTM} * X2z / J_{cz} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$


$$\text{Punching stress} = P\text{-stress} + M_x\text{-stress} + M_z\text{-stress} = 139.4 + 0.0 + 0.0 = 139.4 \text{ psi} < 150.0 \text{ psi OK}$$




DESIGN CODES

Concrete Design ACI 318-14

Load Combinations ASCE 7-10/16



ELEVATION



PLAN

GEOMETRY

Footing Length (X-dir)	3.50	ft	
Footing Width (Z-dir)	3.50	ft	
Footing Thickness	8.0	in	OK
Soil Cover	0.00	ft	
Column Length (X-dir)	6.0	in	
Column Width (Z-dir)	6.0	in	
Offset (X-dir)	0.00	in	OK
Offset (Z-dir)	0.00	in	OK
Base Plate (L x W)	6.0 x 6.0	in	

SOIL PRESSURES (D+L)

Gross Allow. Soil Pressure	2.0	ksf	
Soil Pressure at Corner 1	1.9	ksf	
Soil Pressure at Corner 2	1.9	ksf	
Soil Pressure at Corner 3	1.9	ksf	
Soil Pressure at Corner 4	1.9	ksf	
Bearing Pressure Ratio	0.93		OK
Ftg. Area in Contact with Soil	100.0	%	
X-eccentricity / Ftg. Length	0.00		OK
Z-eccentricity / Ftg. Width	0.00		OK

APPLIED LOADS

	Dead	Live	RLive	Snow	Wind	Seismic	
Axial Force P	6.0	16.0	0.0	0.0	0.0	0.0	kip
Moment about X Mx ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Moment about Z Mz ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Shear Force Vx	0.0	0.0	0.0	0.0	0.0	0.0	kip
Shear Force Vz	0.0	0.0	0.0	0.0	0.0	0.0	kip

OVERTURNING CALCULATIONS (Comb: 0.6D+0.6W)

- Overturning about X-X

- Moment Mx = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ k-ft

- Shear Force Vz = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ kip

Arm = $0.00 + 8.0 / 12 = 0.67$ ft

Moment = $0.0 * 0.67 = 0.0$ k-ft

- Passive Force = 0.0 kip

Arm = 0.27 ft

Moment = 0.0 k-ft

- Overturning moment X-X = $0.0 + 0.0 = 0.0$ k-ft

- Resisting about X-X

- Footing weight = $0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.7 * 1.75 = 1.3$ k-ft

- Pedestal weight = $0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0$ kip

Arm = $W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75$ ft

Moment = $0.0 * 1.75 = 0.0$ k-ft

- Soil cover = $0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.0 * 1.75 = 0.0$ k-ft

- Buoyancy = $0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.3 * 1.75 = -0.5$ k-ft

- Axial force P = $0.6 * 6.0 + 0.6 * 0.0 = 3.6$ kip

Arm = $W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75$ ft

Moment = $3.6 * 1.75 = 6.3$ k-ft

- Resisting moment X-X = $1.3 + 0.0 + 0.0 + 6.3 + -0.5 = 7.1$ k-ft

- Overturning safety factor X-X = $\frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{7.1}{0.0} = 70.51 > 1.50$ OK

- Overturning about Z-Z

$$\text{- Moment } M_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment } Z-Z = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about Z-Z

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.7 * 1.75 = 1.3 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.3 * 1.75 = -0.5 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 6.0 + 0.6 * 0.0 = 3.6 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 3.6 * 1.75 = 6.3 \text{ k-ft}$$

$$\text{- Resisting moment } Z-Z = 1.3 + 0.0 + 0.0 + 6.3 + -0.5 = 7.1 \text{ k-ft}$$

$$\text{- Overturning safety factor } Z-Z = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{7.1}{0.0} = 70.51 > 1.50 \text{ OK}$$

SOIL BEARING PRESSURES (Comb: D+L)

$$\text{Overturning moment } X-X = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment } X-X = 2.1 + 0.0 + 0.0 + -0.9 + 38.5 = 39.8 \text{ k-ft}$$

$$\text{Overturning moment } Z-Z = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment } Z-Z = 2.1 + 0.0 + 0.0 + -0.9 + 38.5 = 39.8 \text{ k-ft}$$

$$\text{Resisting force} = \text{Footing} + \text{Pedestal} + \text{Soil} - \text{Buoyancy} + P = 1.2 + 0.0 + 0.0 - 0.5 + 22.0 = 22.7 \text{ kip}$$

X-coordinate of resultant from maximum bearing corner:

$$X_p = \frac{Z\text{-Resisting moment} - Z\text{-Overturning moment}}{\text{Resisting force}} = \frac{39.8 - 0.0}{22.7} = 1.75 \text{ ft}$$

Z-coordinate of resultant from maximum bearing corner:

$$Z_p = \frac{X\text{-Resisting moment} - X\text{-Overturning moment}}{\text{Resisting force}} = \frac{39.8 - 0.0}{22.7} = 1.75 \text{ ft}$$

$$X\text{-ecc} = \text{Length} / 2 - X_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$Z\text{-ecc} = \text{Width} / 2 - Z_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$\text{Area} = \text{Width} * \text{Length} = 3.50 * 3.50 = 12.3 \text{ ft}^2$$

$$S_x = \text{Length} * \text{Width}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$

$$S_z = \text{Width} * \text{Length}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$



- Footing is in full bearing. Soil pressures are as follows:

$$P1 = P * (1/A + Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 22.7 * (1 / 12.3 + 0.00 / 7.1 + 0.00 / 7.1) = 1.85 \text{ ksf}$$

$$P2 = P * (1/A - Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 22.7 * (1 / 12.3 - 0.00 / 7.1 + 0.00 / 7.1) = 1.85 \text{ ksf}$$

$$P3 = P * (1/A - Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 22.7 * (1 / 12.3 - 0.00 / 7.1 - 0.00 / 7.1) = 1.85 \text{ ksf}$$

$$P4 = P * (1/A + Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 22.7 * (1 / 12.3 + 0.00 / 7.1 - 0.00 / 7.1) = 1.85 \text{ ksf}$$



SLIDING CALCULATIONS (Comb: 0.6D+0.6W)

Internal friction angle = 28.0 deg

Passive coefficient $k_p = 4.33$ (per Coulomb)Pressure at mid-depth = $k_p \cdot \text{Density} \cdot (\text{Cover} + \text{Thick} / 2) = 4.33 \cdot 110 \cdot (0.00 + 8.0 / 12 / 2) = 0.16 \text{ ksf}$ X-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Width} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4 \text{ kip}$ Z-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Length} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4 \text{ kip}$ Friction force = $\text{Resisting force} \cdot \text{Friction coeff.} = \text{Max}(0, 4.0 \cdot 0.35) = 1.4 \text{ kip}$

Use 100% of Passive + 100% of Friction for sliding resistance

$$\text{- Sliding safety factor X-X} = \frac{\text{X-Passive force} + \text{Friction}}{\text{X-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.4}{0.0} = 17.80 > 1.50 \text{ OK}$$

$$\text{- Sliding safety factor Z-Z} = \frac{\text{Z-Passive force} + \text{Friction}}{\text{Z-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.4}{0.0} = 17.80 > 1.50 \text{ OK}$$

UPLIFT CALCULATIONS (Comb: 0.6D+0.6W)

$$\text{- Uplift safety factor} = \frac{\text{Pedestal} + \text{Footing} + \text{Cover} - \text{Buoyancy}}{\text{Uplift load}} = \frac{0.0 + 0.7 + 0.0 - 0.3}{0.0} = 99.99 > 1.00 \text{ OK}$$

ONE-WAY SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

Concrete $f'_c = 2.5 \text{ ksi}$ Steel $f_y = 40.0 \text{ ksi}$

Soil density = 110 pcf



d Top X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 2.0 - 0.8 / 2 = 5.6 \text{ in}$ d Top Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 2.0 - 0.8 - 0.8 / 2 = 4.9 \text{ in}$ d Bot X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 3.0 - 0.5 / 2 = 4.8 \text{ in}$ d Bot Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 3.0 - 0.5 - 0.5 / 2 = 4.3 \text{ in}$ $\phi V_{cx} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Width} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.8 / 1000 = 15.0 \text{ kip}$

ACI Eq. (22.5.5.1)

 $\phi V_{cz} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Length} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.3 / 1000 = 13.4 \text{ kip}$

- Shear forces calculated as the volume of the bearing pressures under the effective areas:

One-way shear V_{ux} (- Side) = 10.6 kip < 15.0 kip OKOne-way shear V_{ux} (+ Side) = 10.5 kip < 15.0 kip OKOne-way shear V_{uz} (- Side) = 10.6 kip < 13.4 kip OKOne-way shear V_{uz} (+ Side) = 10.5 kip < 13.4 kip OK



FLEXURE CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Plain } \phi M_{nx} = 5 * \phi * \sqrt{f_c} * L * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

ACI Eq. (14.5.2.1a)

$$\text{Plain } \phi M_{nz} = 5 * \phi * \sqrt{f_c} * W * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

- Top Bars

No Top Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Top

- Top moments calculated as the overburden minus the bearing pressures times the lever arm:

$$\text{Top moment -Mux (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Mux (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

- Bottom Bars

$$\text{Use 5 \#4 Z-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.3) = 0.0056$$

$$q = 0.0056 * 40 / 2.5 = 0.090$$

$$\text{Use 5 \#4 X-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.8) = 0.0050$$

$$q = 0.0050 * 40 / 2.5 = 0.080$$

$$\beta = L / W = 3.50 / 3.50 = 1.00 \quad \gamma_s = 2 * \beta / (\beta + 1) = 2 * 1.00 / (1.00 + 1) = 1.00$$

ACI 13.3.3.3

$$\text{Bending strength } \phi M_n = \phi * b * d^2 * f_c * q * (1 - 0.59 * q)$$

ACI 22.2.2

$$\phi M_{nx} = 0.90 * 3.50 * 12 * 4.3^2 * 2.5 * 0.090 * (1 - 0.59 * 0.090) = 12.1 \text{ k-ft}$$

$$\phi M_{nz} = 0.90 * 3.50 * 12 * 4.8^2 * 2.5 * 0.080 / 1.00 * (1 - 0.59 * 0.080 / 1.00) = 13.6 \text{ k-ft}$$

- Bottom moments calculated as the bearing minus the overburden pressures times the lever arm:

$$\text{Bottom moment Mux (- Side)} = 10.6 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.87$$

$$\text{Bottom moment Mux (+ Side)} = 10.6 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.88$$

$$\text{Bottom moment Muz (- Side)} = 10.6 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.78$$

$$\text{Bottom moment Muz (+ Side)} = 10.6 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.78$$

$$\text{X-As min} = 0.0018 * \text{Width} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$\text{Z-As min} = 0.0018 * \text{Length} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$\text{X-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$\text{Z-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$\text{X-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight X-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$\text{X-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.78) = 12.0 \text{ in}$$

$$\text{Hooked X-Ldh} = \text{Max} (8 db, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$\text{X-Ldh} = \text{Max} (8 db, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.78) = 6.0 \text{ in}$$

$$\text{-X Ld provided} = (\text{Length} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$\text{+X Ld provided} = (\text{Length} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK} \quad 4 \text{ of } 7$$

$$Z\text{-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight } Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.78) = 12.0 \text{ in}$$

$$\text{Hooked } Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.88) = 6.0 \text{ in}$$



$$-Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$+Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$X\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$

ACI 7.7.2.3

$$Z\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$



LOAD TRANSFER CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Area } A1 = \text{col } L * \text{col } W = 6.0 * 6.0 = 36.0 \text{ in}^2$$

$$Sx = \text{col } W * \text{col } L^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$Sz = \text{col } L * \text{col } W^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$\text{Bearing } Pbu = P / A1 + Mz / Sx + Mx / Sz = 32.8 / 36.0 + 0.0 * 12 / 36.0 + 0.0 * 12 / 36.0 = 0.9 \text{ ksi}$$

$$\text{Min edge} = \text{Min} (L / 2 - X\text{-offset} - \text{col } L / 2, W / 2 - Z\text{-offset} - \text{col } W / 2)$$

$$\text{Min edge} = \text{Min} (3.50 * 12 / 2 - 0.0 - 6.0 / 2, 3.50 * 12 / 2 - 0.0 - 6.0 / 2) = 18.0 \text{ in}$$

$$\text{Area } A2 = \text{Min} [L * W, (\text{col } L + 2 * \text{Min edge}) * (\text{col } W + 2 * \text{Min edge})]$$

ACI R22.8.3.2

$$A2 = \text{Min} [3.50 * 12 * 3.5 * 12, (6.0 + 2 * 18.0) * (6.0 + 2 * 18.0)] = 1764.0 \text{ in}^2$$

$$\text{Footing } \phi Pnc = \phi * 0.85 * f_c * \text{Min} [2, \sqrt{A2 / A1}] = 0.65 * 0.85 * 2.5 * \text{Min} [2, \sqrt{(1764.0 / 36.0)}] = 2.8 \text{ ksi}$$

$$\text{Footing } \phi Pns = \phi * As * Fy / A1 = 0.0 \text{ ksi}$$

ACI 22.8.3.2

$$\text{Footing bearing } \phi Pn = \phi Pnc + \phi Pns = 2.8 + 0.0 = 2.8 \text{ ksi} > 0.9 \text{ psi OK}$$

Hooked $L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * \text{db} * \text{ratio})$

ACI 25.4.3

$$L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * 60.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.75 * 0.16) = 6.0 \text{ in}$$

Ld provided = Dowel length = $3.00 * 12 = 36.0 \text{ in} > 28.3 \text{ in OK}$

Ldh provided = Footing thickness - Cover = $8.00 - 3.0 = 5.0 \text{ in} < 6.0 \text{ in NG}$

PUNCHING SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5Lr)

$$\text{X-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asx} = 20$$

$$\text{Z-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asz} = 20$$

$$\text{as} = \text{asx} + \text{asz} = 20 + 20 = 40 \quad \text{Col type} = \text{Interior} \quad \beta = L / W = 6.0 / 6.0 = 1.00$$

ACI 22.6.5.2

$$\text{Perimeter } b_o = \text{asx} / 10 * (L + d/2 + \text{X-Edge}) + \text{asz} / 10 * (W + d/2 + \text{Z-Edge})$$

ACI 22.6.4.2

$$b_o = 20 / 10 * (6.0 + 4.5 / 2 + 2.3) + 20 / 10 * (6.0 + 4.5 / 2 + 2.3) = 42.0 \text{ in}$$

$$\text{Area } A_{bo} = (L + d/2 + \text{X-Edge}) * (W + d/2 + \text{Z-Edge}) = (6.0 + 4.5 / 2 + 2.3) * (6.0 + 4.5 / 2 + 2.3) = 110.3 \text{ in}^2$$

$$\phi V_c = \phi * \text{Min} (2 + 4 / \beta, \text{as} * d / b_o + 2, 4) * \sqrt{f_c}$$

ACI 22.6.5.2

$$\phi V_c = 0.75 * \text{Min} (2 + 4 / 1.00, 40 * 4.5 / 42.0 + 2, 4) * \sqrt{2500} = 150.0 \text{ psi}$$

Punching force $F = P + \text{Overburden} * A_{bo} - \text{Bearing}$

$$F = 32.8 + 0.07 * 110.3 / 144 - 2.1 = 30.8 \text{ kip}$$

$$b1 = L + d/2 + \text{X-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in} \quad b2 = W + d/2 + \text{Z-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in}$$

$$\gamma_{vx} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b2/b1}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.4.2.2)

$$\gamma_{vz} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b1/b2}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.2.3.2)

$$X2z = b1/2 = 10.5/2 = 5.3 \text{ in} \quad X2x = b2/2 = 10.5/2 = 5.3 \text{ in}$$

$$J_{cz} = b1 * d^3 / 6 + b1^3 * d / 6 + b1^2 * b2 * d / 2$$

ACI R8.4.4.2.3

$$J_{cz} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$J_{cx} = b2 * d^3 / 6 + b2^3 * d / 6 + b2^2 * b1 * d / 2$$

ACI R8.4.4.2.3


$$J_{cx} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$\text{Stress due to } P = F / (b_o * d) * 1000 = 30.8 / (42.0 * 4.5) * 1000 = 162.7 \text{ psi}$$

$$\text{Stress due to } M_x = \gamma_{vx} * X\text{-OTM} * X2x / J_{cx} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$

$$\text{Stress due to } M_z = \gamma_{vz} * Z\text{-OTM} * X2z / J_{cz} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$


$$\text{Punching stress} = P\text{-stress} + M_x\text{-stress} + M_z\text{-stress} = 162.7 + 0.0 + 0.0 = 162.7 \text{ psi} > 150.0 \text{ psi NG}$$




DESIGN CODES

Concrete Design ACI 318-14

Load Combinations ASCE 7-10/16



ELEVATION



PLAN

GEOMETRY

Footing Length (X-dir)	3.50	ft	
Footing Width (Z-dir)	3.50	ft	
Footing Thickness	8.0	in	OK
Soil Cover	0.00	ft	
Column Length (X-dir)	6.0	in	
Column Width (Z-dir)	6.0	in	
Offset (X-dir)	0.00	in	OK
Offset (Z-dir)	0.00	in	OK
Base Plate (L x W)	6.0 x 6.0	in	

SOIL PRESSURES (D+L)

Gross Allow. Soil Pressure	2.0	ksf	
Soil Pressure at Corner 1	1.8	ksf	
Soil Pressure at Corner 2	1.8	ksf	
Soil Pressure at Corner 3	1.8	ksf	
Soil Pressure at Corner 4	1.8	ksf	
Bearing Pressure Ratio	0.90		OK
Ftg. Area in Contact with Soil	100.0	%	
X-eccentricity / Ftg. Length	0.00		OK
Z-eccentricity / Ftg. Width	0.00		OK

APPLIED LOADS

	Dead	Live	RLive	Snow	Wind	Seismic	
Axial Force P	6.0	15.3	0.0	0.0	0.0	0.0	kip
Moment about X Mx ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Moment about Z Mz ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Shear Force Vx	0.0	0.0	0.0	0.0	0.0	0.0	kip
Shear Force Vz	0.0	0.0	0.0	0.0	0.0	0.0	kip

OVERTURNING CALCULATIONS (Comb: 0.6D+0.6W)

- Overturning about X-X

- Moment Mx = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ k-ft

- Shear Force Vz = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ kip

Arm = $0.00 + 8.0 / 12 = 0.67$ ft

Moment = $0.0 * 0.67 = 0.0$ k-ft

- Passive Force = 0.0 kip

Arm = 0.27 ft

Moment = 0.0 k-ft

- Overturning moment X-X = $0.0 + 0.0 = 0.0$ k-ft

- Resisting about X-X

- Footing weight = $0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.7 * 1.75 = 1.3$ k-ft

- Pedestal weight = $0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0$ kip

Arm = $W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75$ ft

Moment = $0.0 * 1.75 = 0.0$ k-ft

- Soil cover = $0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.0 * 1.75 = 0.0$ k-ft

- Buoyancy = $0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3$ kip

Arm = $W / 2 = 3.50 / 2 = 1.75$ ft

Moment = $0.3 * 1.75 = -0.5$ k-ft

- Axial force P = $0.6 * 6.0 + 0.6 * 0.0 = 3.6$ kip

Arm = $W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75$ ft

Moment = $3.6 * 1.75 = 6.3$ k-ft

- Resisting moment X-X = $1.3 + 0.0 + 0.0 + 6.3 + -0.5 = 7.1$ k-ft

- Overturning safety factor X-X = $\frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{7.1}{0.0} = 70.51 > 1.50$ OK

- Overturning about Z-Z

$$\text{- Moment } M_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about Z-Z

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.7 * 1.75 = 1.3 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.3 * 1.75 = -0.5 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 6.0 + 0.6 * 0.0 = 3.6 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 3.6 * 1.75 = 6.3 \text{ k-ft}$$

$$\text{- Resisting moment Z-Z} = 1.3 + 0.0 + 0.0 + 6.3 + -0.5 = 7.1 \text{ k-ft}$$

$$\text{- Overturning safety factor Z-Z} = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{7.1}{0.0} = 70.51 > 1.50 \text{ OK}$$

SOIL BEARING PRESSURES (Comb: D+L)

$$\text{Overturning moment X-X} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment X-X} = 2.1 + 0.0 + 0.0 + -0.9 + 37.3 = 38.5 \text{ k-ft}$$

$$\text{Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment Z-Z} = 2.1 + 0.0 + 0.0 + -0.9 + 37.3 = 38.5 \text{ k-ft}$$

$$\text{Resisting force} = \text{Footing} + \text{Pedestal} + \text{Soil} - \text{Buoyancy} + P = 1.2 + 0.0 + 0.0 - 0.5 + 21.3 = 22.0 \text{ kip}$$

X-coordinate of resultant from maximum bearing corner:

$$X_p = \frac{Z\text{-Resisting moment} - Z\text{-Overturning moment}}{\text{Resisting force}} = \frac{38.5 - 0.0}{22.0} = 1.75 \text{ ft}$$

Z-coordinate of resultant from maximum bearing corner:

$$Z_p = \frac{X\text{-Resisting moment} - X\text{-Overturning moment}}{\text{Resisting force}} = \frac{38.5 - 0.0}{22.0} = 1.75 \text{ ft}$$

$$X\text{-ecc} = \text{Length} / 2 - X_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$Z\text{-ecc} = \text{Width} / 2 - Z_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$\text{Area} = \text{Width} * \text{Length} = 3.50 * 3.50 = 12.3 \text{ ft}^2$$

$$S_x = \text{Length} * \text{Width}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$

$$S_z = \text{Width} * \text{Length}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$



- Footing is in full bearing. Soil pressures are as follows:

$$P1 = P * (1/A + Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 22.0 * (1 / 12.3 + 0.00 / 7.1 + 0.00 / 7.1) = 1.80 \text{ ksf}$$

$$P2 = P * (1/A - Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 22.0 * (1 / 12.3 - 0.00 / 7.1 + 0.00 / 7.1) = 1.80 \text{ ksf}$$

$$P3 = P * (1/A - Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 22.0 * (1 / 12.3 - 0.00 / 7.1 - 0.00 / 7.1) = 1.80 \text{ ksf}$$

$$P4 = P * (1/A + Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 22.0 * (1 / 12.3 + 0.00 / 7.1 - 0.00 / 7.1) = 1.80 \text{ ksf}$$



SLIDING CALCULATIONS (Comb: 0.6D+0.6W)

Internal friction angle = 28.0 deg

Passive coefficient $k_p = 4.33$ (per Coulomb)Pressure at mid-depth = $k_p \cdot \text{Density} \cdot (\text{Cover} + \text{Thick} / 2) = 4.33 \cdot 110 \cdot (0.00 + 8.0 / 12 / 2) = 0.16$ ksfX-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Width} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4$ kipZ-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Length} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4$ kipFriction force = $\text{Resisting force} \cdot \text{Friction coeff.} = \text{Max}(0, 4.0 \cdot 0.35) = 1.4$ kip

Use 100% of Passive + 100% of Friction for sliding resistance

$$\text{- Sliding safety factor X-X} = \frac{\text{X-Passive force} + \text{Friction}}{\text{X-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.4}{0.0} = 17.80 > 1.50 \text{ OK}$$

$$\text{- Sliding safety factor Z-Z} = \frac{\text{Z-Passive force} + \text{Friction}}{\text{Z-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.4}{0.0} = 17.80 > 1.50 \text{ OK}$$

UPLIFT CALCULATIONS (Comb: 0.6D+0.6W)

$$\text{- Uplift safety factor} = \frac{\text{Pedestal} + \text{Footing} + \text{Cover} - \text{Buoyancy}}{\text{Uplift load}} = \frac{0.0 + 0.7 + 0.0 - 0.3}{0.0} = 99.99 > 1.00 \text{ OK}$$

ONE-WAY SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

Concrete $f'_c = 2.5$ ksiSteel $f_y = 40.0$ ksi

Soil density = 110 pcf



d Top X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 2.0 - 0.8 / 2 = 5.6$ ind Top Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 2.0 - 0.8 - 0.8 / 2 = 4.9$ ind Bot X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 3.0 - 0.5 / 2 = 4.8$ ind Bot Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 3.0 - 0.5 - 0.5 / 2 = 4.3$ in $\phi V_{cx} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Width} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.8 / 1000 = 15.0$ kip

ACI Eq. (22.5.5.1)

 $\phi V_{cz} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Length} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.3 / 1000 = 13.4$ kip

- Shear forces calculated as the volume of the bearing pressures under the effective areas:

One-way shear V_{ux} (- Side) = 10.2 kip < 15.0 kip OKOne-way shear V_{ux} (+ Side) = 10.2 kip < 15.0 kip OKOne-way shear V_{uz} (- Side) = 10.2 kip < 13.4 kip OKOne-way shear V_{uz} (+ Side) = 10.2 kip < 13.4 kip OK



FLEXURE CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Plain } \phi M_{nx} = 5 * \phi * \sqrt{f_c} * L * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

ACI Eq. (14.5.2.1a)

$$\text{Plain } \phi M_{nz} = 5 * \phi * \sqrt{f_c} * W * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

- Top Bars

No Top Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Top

- Top moments calculated as the overburden minus the bearing pressures times the lever arm:

$$\text{Top moment -Mux (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Mux (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

- Bottom Bars

$$\text{Use 5 \#4 Z-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.3) = 0.0056$$

$$q = 0.0056 * 40 / 2.5 = 0.090$$

$$\text{Use 5 \#4 X-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.8) = 0.0050$$

$$q = 0.0050 * 40 / 2.5 = 0.080$$

$$\beta = L / W = 3.50 / 3.50 = 1.00 \quad \gamma_s = 2 * \beta / (\beta + 1) = 2 * 1.00 / (1.00 + 1) = 1.00$$

ACI 13.3.3.3

$$\text{Bending strength } \phi M_n = \phi * b * d^2 * f_c * q * (1 - 0.59 * q)$$

ACI 22.2.2

$$\phi M_{nx} = 0.90 * 3.50 * 12 * 4.3^2 * 2.5 * 0.090 * (1 - 0.59 * 0.090) = 12.1 \text{ k-ft}$$

$$\phi M_{nz} = 0.90 * 3.50 * 12 * 4.8^2 * 2.5 * 0.080 / 1.00 * (1 - 0.59 * 0.080 / 1.00) = 13.6 \text{ k-ft}$$

- Bottom moments calculated as the bearing minus the overburden pressures times the lever arm:

$$\text{Bottom moment Mux (- Side)} = 10.2 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.84$$

$$\text{Bottom moment Mux (+ Side)} = 10.2 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.85$$

$$\text{Bottom moment Muz (- Side)} = 10.2 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.75$$

$$\text{Bottom moment Muz (+ Side)} = 10.2 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.75$$

$$\text{X-As min} = 0.0018 * \text{Width} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$\text{Z-As min} = 0.0018 * \text{Length} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$\text{X-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$\text{Z-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$\text{X-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight X-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$\text{X-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.75) = 12.0 \text{ in}$$

$$\text{Hooked X-Ldh} = \text{Max} (8 db, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$\text{X-Ldh} = \text{Max} (8 db, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.75) = 6.0 \text{ in}$$

$$\text{-X Ld provided} = (\text{Length} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$\text{+X Ld provided} = (\text{Length} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK} \quad 4 \text{ of } 7$$

$$Z\text{-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight } Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.75) = 12.0 \text{ in}$$

$$\text{Hooked } Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.85) = 6.0 \text{ in}$$



$$-Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$+Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$X\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$

ACI 7.7.2.3

$$Z\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$



LOAD TRANSFER CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Area } A1 = \text{col } L * \text{col } W = 6.0 * 6.0 = 36.0 \text{ in}^2$$

$$Sx = \text{col } W * \text{col } L^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$Sz = \text{col } L * \text{col } W^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$\text{Bearing } Pbu = P / A1 + Mz / Sx + Mx / Sz = 31.7 / 36.0 + 0.0 * 12 / 36.0 + 0.0 * 12 / 36.0 = 0.9 \text{ ksi}$$

$$\text{Min edge} = \text{Min} (L / 2 - X\text{-offset} - \text{col } L / 2, W / 2 - Z\text{-offset} - \text{col } W / 2)$$

$$\text{Min edge} = \text{Min} (3.50 * 12 / 2 - 0.0 - 6.0 / 2, 3.50 * 12 / 2 - 0.0 - 6.0 / 2) = 18.0 \text{ in}$$

$$\text{Area } A2 = \text{Min} [L * W, (\text{col } L + 2 * \text{Min edge}) * (\text{col } W + 2 * \text{Min edge})]$$

ACI R22.8.3.2

$$A2 = \text{Min} [3.50 * 12 * 3.5 * 12, (6.0 + 2 * 18.0) * (6.0 + 2 * 18.0)] = 1764.0 \text{ in}^2$$

$$\text{Footing } \phi Pnc = \phi * 0.85 * f_c * \text{Min} [2, \sqrt{A2 / A1}] = 0.65 * 0.85 * 2.5 * \text{Min} [2, \sqrt{(1764.0 / 36.0)}] = 2.8 \text{ ksi}$$

$$\text{Footing } \phi Pns = \phi * As * Fy / A1 = 0.0 \text{ ksi}$$

ACI 22.8.3.2

$$\text{Footing bearing } \phi Pn = \phi Pnc + \phi Pns = 2.8 + 0.0 = 2.8 \text{ ksi} > 0.9 \text{ psi OK}$$

Hooked $L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * \text{db} * \text{ratio})$

ACI 25.4.3

$$L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * 60.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.75 * 0.15) = 6.0 \text{ in}$$

Ld provided = Dowel length = $3.00 * 12 = 36.0 \text{ in} > 27.4 \text{ in OK}$

Ldh provided = Footing thickness - Cover = $8.00 - 3.0 = 5.0 \text{ in} < 6.0 \text{ in NG}$

PUNCHING SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5Lr)

$$\text{X-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asx} = 20$$

$$\text{Z-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asz} = 20$$

$$\text{as} = \text{asx} + \text{asz} = 20 + 20 = 40 \quad \text{Col type} = \text{Interior} \quad \beta = L / W = 6.0 / 6.0 = 1.00$$

ACI 22.6.5.2

$$\text{Perimeter } b_o = \text{asx} / 10 * (L + d/2 + \text{X-Edge}) + \text{asz} / 10 * (W + d/2 + \text{Z-Edge})$$

ACI 22.6.4.2

$$b_o = 20 / 10 * (6.0 + 4.5 / 2 + 2.3) + 20 / 10 * (6.0 + 4.5 / 2 + 2.3) = 42.0 \text{ in}$$

$$\text{Area } A_{bo} = (L + d/2 + \text{X-Edge}) * (W + d/2 + \text{Z-Edge}) = (6.0 + 4.5 / 2 + 2.3) * (6.0 + 4.5 / 2 + 2.3) = 110.3 \text{ in}^2$$

$$\phi V_c = \phi * \text{Min} (2 + 4 / \beta, \text{as} * d / b_o + 2, 4) * \sqrt{f_c}$$

ACI 22.6.5.2

$$\phi V_c = 0.75 * \text{Min} (2 + 4 / 1.00, 40 * 4.5 / 42.0 + 2, 4) * \sqrt{2500} = 150.0 \text{ psi}$$

Punching force $F = P + \text{Overburden} * A_{bo} - \text{Bearing}$

$$F = 31.7 + 0.07 * 110.3 / 144 - 2.0 = 29.7 \text{ kip}$$

$$b1 = L + d/2 + \text{X-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in} \quad b2 = W + d/2 + \text{Z-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in}$$

$$\gamma_{vx} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b2/b1}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.4.2.2)

$$\gamma_{vz} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b1/b2}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.2.3.2)

$$X2z = b1/2 = 10.5/2 = 5.3 \text{ in} \quad X2x = b2/2 = 10.5/2 = 5.3 \text{ in}$$

$$J_{cz} = b1 * d^3 / 6 + b1^3 * d / 6 + b1^2 * b2 * d / 2$$

ACI R8.4.4.2.3

$$J_{cz} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$J_{cx} = b2 * d^3 / 6 + b2^3 * d / 6 + b2^2 * b1 * d / 2$$

ACI R8.4.4.2.3


$$J_{cx} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$\text{Stress due to } P = F / (b_o * d) * 1000 = 29.7 / (42.0 * 4.5) * 1000 = 157.1 \text{ psi}$$

$$\text{Stress due to } M_x = \gamma_{vx} * X\text{-OTM} * X2x / J_{cx} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$

$$\text{Stress due to } M_z = \gamma_{vz} * Z\text{-OTM} * X2z / J_{cz} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$


$$\text{Punching stress} = P\text{-stress} + M_x\text{-stress} + M_z\text{-stress} = 157.1 + 0.0 + 0.0 = 157.1 \text{ psi} > 150.0 \text{ psi NG}$$




DESIGN CODES

Concrete Design ACI 318-14

Load Combinations ASCE 7-10/16



ELEVATION



PLAN

GEOMETRY

Footing Length (X-dir)	3.50	ft	
Footing Width (Z-dir)	3.50	ft	
Footing Thickness	8.0	in	OK
Soil Cover	0.00	ft	
Column Length (X-dir)	6.0	in	
Column Width (Z-dir)	6.0	in	
Offset (X-dir)	0.00	in	OK
Offset (Z-dir)	0.00	in	OK
Base Plate (L x W)	6.0 x 6.0	in	

SOIL PRESSURES (D+L)

Gross Allow. Soil Pressure	2.0	ksf	
Soil Pressure at Corner 1	1.5	ksf	
Soil Pressure at Corner 2	1.5	ksf	
Soil Pressure at Corner 3	1.5	ksf	
Soil Pressure at Corner 4	1.5	ksf	
Bearing Pressure Ratio	0.77		OK
Ftg. Area in Contact with Soil	100.0	%	
X-eccentricity / Ftg. Length	0.00		OK
Z-eccentricity / Ftg. Width	0.00		OK

APPLIED LOADS

	Dead	Live	RLive	Snow	Wind	Seismic	
Axial Force P	5.2	12.9	0.0	0.0	0.0	0.0	kip
Moment about X Mx ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Moment about Z Mz ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Shear Force Vx	0.0	0.0	0.0	0.0	0.0	0.0	kip
Shear Force Vz	0.0	0.0	0.0	0.0	0.0	0.0	kip

OVERTURNING CALCULATIONS (Comb: 0.6D+0.6W)

- Overturning about X-X

- Moment Mx = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ k-ft

- Shear Force Vz = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ kip

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

- Passive Force = 0.0 kip

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

- Overturning moment X-X = $0.0 + 0.0 = 0.0$ k-ft

- Resisting about X-X

- Footing weight = $0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7$ kip

$$\text{Arm} = W / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.7 * 1.75 = 1.3 \text{ k-ft}$$

- Pedestal weight = $0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0$ kip

$$\text{Arm} = W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

- Soil cover = $0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0$ kip

$$\text{Arm} = W / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

- Buoyancy = $0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3$ kip

$$\text{Arm} = W / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.3 * 1.75 = -0.5 \text{ k-ft}$$

- Axial force P = $0.6 * 5.2 + 0.6 * 0.0 = 3.1$ kip

$$\text{Arm} = W / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 3.1 * 1.75 = 5.5 \text{ k-ft}$$

- Resisting moment X-X = $1.3 + 0.0 + 0.0 + 5.5 + -0.5 = 6.2$ k-ft

- Overturning safety factor X-X = $\frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{6.2}{0.0} = 62.11 > 1.50$ OK

- Overturning about Z-Z

$$\text{- Moment } M_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment } Z-Z = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about Z-Z

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 3.50 * 3.50 * 8.0 / 12 * 0.15 = 0.7 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.7 * 1.75 = 1.3 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (3.50 * 3.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.75 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 3.50 * 3.50 * 62 * (0.67) = -0.3 \text{ kip}$$

$$\text{Arm} = L / 2 = 3.50 / 2 = 1.75 \text{ ft}$$

$$\text{Moment} = 0.3 * 1.75 = -0.5 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 5.2 + 0.6 * 0.0 = 3.1 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 3.50 / 2 - 0.0 / 12 = 1.75 \text{ ft}$$

$$\text{Moment} = 3.1 * 1.75 = 5.5 \text{ k-ft}$$

$$\text{- Resisting moment } Z-Z = 1.3 + 0.0 + 0.0 + 5.5 + -0.5 = 6.2 \text{ k-ft}$$

$$\text{- Overturning safety factor } Z-Z = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{6.2}{0.0} = 62.11 > 1.50 \text{ OK}$$

SOIL BEARING PRESSURES (Comb: D+L)

$$\text{Overturning moment } X-X = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment } X-X = 2.1 + 0.0 + 0.0 + -0.9 + 31.7 = 32.9 \text{ k-ft}$$

$$\text{Overturning moment } Z-Z = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment } Z-Z = 2.1 + 0.0 + 0.0 + -0.9 + 31.7 = 32.9 \text{ k-ft}$$

$$\text{Resisting force} = \text{Footing} + \text{Pedestal} + \text{Soil} - \text{Buoyancy} + P = 1.2 + 0.0 + 0.0 - 0.5 + 18.1 = 18.8 \text{ kip}$$

X-coordinate of resultant from maximum bearing corner:

$$X_p = \frac{Z\text{-Resisting moment} - Z\text{-Overturning moment}}{\text{Resisting force}} = \frac{32.9 - 0.0}{18.8} = 1.75 \text{ ft}$$

Z-coordinate of resultant from maximum bearing corner:

$$Z_p = \frac{X\text{-Resisting moment} - X\text{-Overturning moment}}{\text{Resisting force}} = \frac{32.9 - 0.0}{18.8} = 1.75 \text{ ft}$$

$$X\text{-ecc} = \text{Length} / 2 - X_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$Z\text{-ecc} = \text{Width} / 2 - Z_p = 3.50 / 2 - 1.75 = 0.00 \text{ ft}$$

$$\text{Area} = \text{Width} * \text{Length} = 3.50 * 3.50 = 12.3 \text{ ft}^2$$

$$S_x = \text{Length} * \text{Width}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$

$$S_z = \text{Width} * \text{Length}^2 / 6 = 3.50 * 3.50^2 / 6 = 7.1 \text{ ft}^3$$



- Footing is in full bearing. Soil pressures are as follows:

$$P1 = P * (1/A + Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 18.8 * (1 / 12.3 + 0.00 / 7.1 + 0.00 / 7.1) = 1.54 \text{ ksf}$$

$$P2 = P * (1/A - Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 18.8 * (1 / 12.3 - 0.00 / 7.1 + 0.00 / 7.1) = 1.54 \text{ ksf}$$

$$P3 = P * (1/A - Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 18.8 * (1 / 12.3 - 0.00 / 7.1 - 0.00 / 7.1) = 1.54 \text{ ksf}$$

$$P4 = P * (1/A + Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 18.8 * (1 / 12.3 + 0.00 / 7.1 - 0.00 / 7.1) = 1.54 \text{ ksf}$$



SLIDING CALCULATIONS (Comb: 0.6D+0.6W)

Internal friction angle = 28.0 deg

Passive coefficient $k_p = 4.33$ (per Coulomb)Pressure at mid-depth = $k_p \cdot \text{Density} \cdot (\text{Cover} + \text{Thick} / 2) = 4.33 \cdot 110 \cdot (0.00 + 8.0 / 12 / 2) = 0.16$ ksfX-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Width} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4$ kipZ-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Length} = 0.16 \cdot 8.0 / 12 \cdot 3.50 = 0.4$ kipFriction force = $\text{Resisting force} \cdot \text{Friction coeff.} = \text{Max}(0, 3.5 \cdot 0.35) = 1.2$ kip

Use 100% of Passive + 100% of Friction for sliding resistance

$$\text{- Sliding safety factor X-X} = \frac{\text{X-Passive force} + \text{Friction}}{\text{X-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.2}{0.0} = 16.12 > 1.50 \quad \text{OK}$$

$$\text{- Sliding safety factor Z-Z} = \frac{\text{Z-Passive force} + \text{Friction}}{\text{Z-Horizontal load}} = \frac{1.00 \cdot 0.4 + 1.00 \cdot 1.2}{0.0} = 16.12 > 1.50 \quad \text{OK}$$

UPLIFT CALCULATIONS (Comb: 0.6D+0.6W)

$$\text{- Uplift safety factor} = \frac{\text{Pedestal} + \text{Footing} + \text{Cover} - \text{Buoyancy}}{\text{Uplift load}} = \frac{0.0 + 0.7 + 0.0 - 0.3}{0.0} = 99.99 > 1.00 \quad \text{OK}$$

ONE-WAY SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

Concrete $f'_c = 2.5$ ksiSteel $f_y = 40.0$ ksi

Soil density = 110 pcf



d Top X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 2.0 - 0.8 / 2 = 5.6$ ind Top Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 2.0 - 0.8 - 0.8 / 2 = 4.9$ ind Bot X-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} / 2 = 8.0 - 3.0 - 0.5 / 2 = 4.8$ ind Bot Z-dir = $\text{Thick} - \text{Cover} - \text{X-diameter} - \text{Z-diameter} / 2 = 8.0 - 3.0 - 0.5 - 0.5 / 2 = 4.3$ in $\phi V_{cx} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Width} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.8 / 1000 = 15.0$ kip

ACI Eq. (22.5.5.1)

 $\phi V_{cz} = 2 \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Length} \cdot d / 1000 = 2 \cdot 0.75 \cdot \sqrt{(2500)} \cdot 3.5 \cdot 12 \cdot 4.3 / 1000 = 13.4$ kip

- Shear forces calculated as the volume of the bearing pressures under the effective areas:

One-way shear V_{ux} (- Side) = 8.7 kip < 15.0 kip OKOne-way shear V_{ux} (+ Side) = 8.6 kip < 15.0 kip OKOne-way shear V_{uz} (- Side) = 8.7 kip < 13.4 kip OKOne-way shear V_{uz} (+ Side) = 8.6 kip < 13.4 kip OK



FLEXURE CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Plain } \phi M_{nx} = 5 * \phi * \sqrt{f_c} * L * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

ACI Eq. (14.5.2.1a)

$$\text{Plain } \phi M_{nz} = 5 * \phi * \sqrt{f_c} * W * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 3.50 * 8.0^2 / 6 / 1000 = 1.5 \text{ k-ft}$$

- Top Bars

No Top Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Top

- Top moments calculated as the overburden minus the bearing pressures times the lever arm:

$$\text{Top moment -Mux (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Mux (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (- Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

$$\text{Top moment -Muz (+ Side)} = 0.0 \text{ k-ft} < 5.6 \text{ k-ft OK}$$

- Bottom Bars

$$\text{Use 5 \#4 Z-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.3) = 0.0056$$

$$q = 0.0056 * 40 / 2.5 = 0.090$$

$$\text{Use 5 \#4 X-Bars } \rho = A_s / b d = 1.0 / (3.50 * 12 * 4.8) = 0.0050$$

$$q = 0.0050 * 40 / 2.5 = 0.080$$

$$\beta = L / W = 3.50 / 3.50 = 1.00 \quad \gamma_s = 2 * \beta / (\beta + 1) = 2 * 1.00 / (1.00 + 1) = 1.00$$

ACI 13.3.3.3

$$\text{Bending strength } \phi M_n = \phi * b * d^2 * f_c * q * (1 - 0.59 * q)$$

ACI 22.2.2

$$\phi M_{nx} = 0.90 * 3.50 * 12 * 4.3^2 * 2.5 * 0.090 * (1 - 0.59 * 0.090) = 12.1 \text{ k-ft}$$

$$\phi M_{nz} = 0.90 * 3.50 * 12 * 4.8^2 * 2.5 * 0.080 / 1.00 * (1 - 0.59 * 0.080 / 1.00) = 13.6 \text{ k-ft}$$

- Bottom moments calculated as the bearing minus the overburden pressures times the lever arm:

$$\text{Bottom moment Mux (- Side)} = 8.7 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.72$$

$$\text{Bottom moment Mux (+ Side)} = 8.7 \text{ k-ft} < 12.1 \text{ k-ft OK} \quad \text{ratio} = 0.72$$

$$\text{Bottom moment Muz (- Side)} = 8.7 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.64$$

$$\text{Bottom moment Muz (+ Side)} = 8.7 \text{ k-ft} < 13.6 \text{ k-ft OK} \quad \text{ratio} = 0.64$$

$$\text{X-As min} = 0.0018 * \text{Width} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$\text{Z-As min} = 0.0018 * \text{Length} * \text{Thick} = 0.0018 * 3.50 * 12 * 8.0 = 0.6 \text{ in}^2 < 1.0 \text{ in}^2 \text{ OK}$$

ACI 8.6.1.1

$$\text{X-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$\text{Z-As max for 0.005 tension strain} = 3.20 \text{ in}^2 > 1.00 \text{ in}^2 \text{ OK}$$

ACI 21.2.2

$$\text{X-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight X-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$\text{X-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.64) = 12.0 \text{ in}$$

$$\text{Hooked X-Ldh} = \text{Max} (8 db, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$\text{X-Ldh} = \text{Max} (8 db, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.64) = 6.0 \text{ in}$$

$$\text{-X Ld provided} = (\text{Length} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$\text{+X Ld provided} = (\text{Length} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK} \quad 4 \text{ of } 7$$

$$Z\text{-Cover factor} = \text{Min} (2.5, (\text{Cover} + db / 2, \text{Spacing} / 2) / db) = \text{Min} (2.5, (3.0 + 0.50 / 2, 9.0 / 2) / 0.50) = 2.5$$

$$\text{Straight } Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * f_y / (f_c)^{1/2} * \text{Grade} * \text{Size} * \text{Casting} / \text{Cover} * db * \text{ratio})$$

ACI Eq. (25.4.2.3a)

$$Z\text{-Ld} = \text{Max} (12.0, 3 / 40 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.8 * 1.0 / 2.5 * 0.50 * 0.64) = 12.0 \text{ in}$$

$$\text{Hooked } Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * db * \text{ratio}) =$$

ACI 25.4.3

$$Z\text{-Ldh} = \text{Max} (8 \text{ db}, 6, 0.02 * 40.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.50 * 0.72) = 6.0 \text{ in}$$



$$-Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 + \text{Offset} - \text{Cover} = 3.50 * 12 / 2 + 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$+Z \text{ Ld provided} = (\text{Width} - \text{Col}) / 2 - \text{Offset} - \text{Cover} = 3.50 * 12 / 2 - 0.0 - 6.0 / 2 - 2.5 = 15.5 \text{ in} > 12.0 \text{ in OK}$$

$$X\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$

ACI 7.7.2.3

$$Z\text{-bar spacing} = 9.0 \text{ in} < \text{Min} (3 * t, 18.0) = 18.0 \text{ in OK}$$



LOAD TRANSFER CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Area } A1 = \text{col } L * \text{col } W = 6.0 * 6.0 = 36.0 \text{ in}^2$$

$$Sx = \text{col } W * \text{col } L^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$Sz = \text{col } L * \text{col } W^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$\text{Bearing } Pbu = P / A1 + Mz / Sx + Mx / Sz = 26.9 / 36.0 + 0.0 * 12 / 36.0 + 0.0 * 12 / 36.0 = 0.7 \text{ ksi}$$

$$\text{Min edge} = \text{Min} (L / 2 - X\text{-offset} - \text{col } L / 2, W / 2 - Z\text{-offset} - \text{col } W / 2)$$

$$\text{Min edge} = \text{Min} (3.50 * 12 / 2 - 0.0 - 6.0 / 2, 3.50 * 12 / 2 - 0.0 - 6.0 / 2) = 18.0 \text{ in}$$

$$\text{Area } A2 = \text{Min} [L * W, (\text{col } L + 2 * \text{Min edge}) * (\text{col } W + 2 * \text{Min edge})]$$

ACI R22.8.3.2

$$A2 = \text{Min} [3.50 * 12 * 3.5 * 12, (6.0 + 2 * 18.0) * (6.0 + 2 * 18.0)] = 1764.0 \text{ in}^2$$

$$\text{Footing } \phi Pnc = \phi * 0.85 * f_c * \text{Min} [2, \sqrt{A2 / A1}] = 0.65 * 0.85 * 2.5 * \text{Min} [2, \sqrt{(1764.0 / 36.0)}] = 2.8 \text{ ksi}$$

$$\text{Footing } \phi Pns = \phi * As * Fy / A1 = 0.0 \text{ ksi}$$

ACI 22.8.3.2

$$\text{Footing bearing } \phi Pn = \phi Pnc + \phi Pns = 2.8 + 0.0 = 2.8 \text{ ksi} > 0.7 \text{ psi OK}$$

Hooked $L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * \text{db} * \text{ratio})$

ACI 25.4.3

$$L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * 60.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.75 * 0.13) = 6.0 \text{ in}$$

Ld provided = Dowel length = $3.00 * 12 = 36.0 \text{ in} > 23.2 \text{ in OK}$

Ldh provided = Footing thickness - Cover = $8.00 - 3.0 = 5.0 \text{ in} < 6.0 \text{ in NG}$

PUNCHING SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5Lr)

$$\text{X-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asx} = 20$$

$$\text{Z-Edge} = d/2 = 4.5 / 2 = 2.3 \text{ in} \quad \text{asz} = 20$$

$$\text{as} = \text{asx} + \text{asz} = 20 + 20 = 40 \quad \text{Col type} = \text{Interior} \quad \beta = L / W = 6.0 / 6.0 = 1.00$$

ACI 22.6.5.2

$$\text{Perimeter } b_o = \text{asx} / 10 * (L + d/2 + \text{X-Edge}) + \text{asz} / 10 * (W + d/2 + \text{Z-Edge})$$

ACI 22.6.4.2

$$b_o = 20 / 10 * (6.0 + 4.5 / 2 + 2.3) + 20 / 10 * (6.0 + 4.5 / 2 + 2.3) = 42.0 \text{ in}$$

$$\text{Area } A_{bo} = (L + d/2 + \text{X-Edge}) * (W + d/2 + \text{Z-Edge}) = (6.0 + 4.5 / 2 + 2.3) * (6.0 + 4.5 / 2 + 2.3) = 110.3 \text{ in}^2$$

$$\phi V_c = \phi * \text{Min} (2 + 4 / \beta, \text{as} * d / b_o + 2, 4) * \sqrt{f_c}$$

ACI 22.6.5.2

$$\phi V_c = 0.75 * \text{Min} (2 + 4 / 1.00, 40 * 4.5 / 42.0 + 2, 4) * \sqrt{2500} = 150.0 \text{ psi}$$

Punching force $F = P + \text{Overburden} * A_{bo} - \text{Bearing}$

$$F = 26.9 + 0.07 * 110.3 / 144 - 1.7 = 25.2 \text{ kip}$$

$$b1 = L + d/2 + \text{X-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in} \quad b2 = W + d/2 + \text{Z-Edge} = 6.0 + 4.5 / 2 + 2.3 = 10.5 \text{ in}$$

$$\gamma_{vx} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b2/b1}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.4.2.2)

$$\gamma_{vz} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{b1/b2}} = 1 - \frac{1}{1 + (2/3) \sqrt{10.5/10.5}} = 0.40$$

ACI Eq. (8.4.2.3.2)

$$X2z = b1/2 = 10.5/2 = 5.3 \text{ in} \quad X2x = b2/2 = 10.5/2 = 5.3 \text{ in}$$

$$J_{cz} = b1 * d^3 / 6 + b1^3 * d / 6 + b1^2 * b2 * d / 2$$

ACI R8.4.4.2.3

$$J_{cz} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$J_{cx} = b2 * d^3 / 6 + b2^3 * d / 6 + b2^2 * b1 * d / 2$$

ACI R8.4.4.2.3


$$J_{cx} = 10.5 * 4.5^3 / 6 + 10.5^3 * 4.5 / 6 + 10.5^2 * 10.5 * 4.5 / 2 = 3632 \text{ in}^4$$

$$\text{Stress due to } P = F / (b_o * d) * 1000 = 25.2 / (42.0 * 4.5) * 1000 = 133.3 \text{ psi}$$

$$\text{Stress due to } M_x = \gamma_{vx} * X\text{-OTM} * X2x / J_{cx} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$

$$\text{Stress due to } M_z = \gamma_{vz} * Z\text{-OTM} * X2z / J_{cz} = 0.40 * 0.0 * 12 * 5.3 / 3632 * 1000 = 0.0 \text{ psi}$$


$$\text{Punching stress} = P\text{-stress} + M_x\text{-stress} + M_z\text{-stress} = 133.3 + 0.0 + 0.0 = 133.3 \text{ psi} < 150.0 \text{ psi OK}$$




DESIGN CODES

Concrete Design ACI 318-14

Load Combinations ASCE 7-10/16



ELEVATION



PLAN

GEOMETRY

Footing Length (X-dir)	2.00	ft	
Footing Width (Z-dir)	2.60	ft	
Footing Thickness	8.0	in	OK
Soil Cover	0.00	ft	
Column Length (X-dir)	6.0	in	
Column Width (Z-dir)	6.0	in	
Offset (X-dir)	0.00	in	OK
Offset (Z-dir)	0.00	in	OK
Base Plate (L x W)	6.0 x 6.0	in	

SOIL PRESSURES (D+L)

Gross Allow. Soil Pressure	2.0	ksf	
Soil Pressure at Corner 1	2.0	ksf	
Soil Pressure at Corner 2	2.0	ksf	
Soil Pressure at Corner 3	2.0	ksf	
Soil Pressure at Corner 4	2.0	ksf	
Bearing Pressure Ratio	0.99		OK
Ftg. Area in Contact with Soil	100.0	%	
X-eccentricity / Ftg. Length	0.00		OK
Z-eccentricity / Ftg. Width	0.00		OK

APPLIED LOADS

	Dead	Live	RLive	Snow	Wind	Seismic	
Axial Force P	4.5	5.5	0.0	0.0	0.0	0.0	kip
Moment about X Mx ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Moment about Z Mz ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Shear Force Vx	0.0	0.0	0.0	0.0	0.0	0.0	kip
Shear Force Vz	0.0	0.0	0.0	0.0	0.0	0.0	kip

OVERTURNING CALCULATIONS (Comb: 0.6D+0.6W)

- Overturning about X-X

- Moment Mx = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ k-ft

- Shear Force Vz = $0.6 * 0.0 + 0.6 * 0.0 = 0.0$ kip

Arm = $0.00 + 8.0 / 12 = 0.67$ ft

Moment = $0.0 * 0.67 = 0.0$ k-ft

- Passive Force = 0.0 kip

Arm = 0.27 ft

Moment = 0.0 k-ft

- Overturning moment X-X = $0.0 + 0.0 = 0.0$ k-ft

- Resisting about X-X

- Footing weight = $0.6 * W * L * Thick * Density = 0.6 * 2.60 * 2.00 * 8.0 / 12 * 0.15 = 0.3$ kip

Arm = $W / 2 = 2.60 / 2 = 1.30$ ft

Moment = $0.3 * 1.30 = 0.4$ k-ft

- Pedestal weight = $0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0$ kip

Arm = $W / 2 - Offset = 2.60 / 2 - 0.0 / 12 = 1.30$ ft

Moment = $0.0 * 1.30 = 0.0$ k-ft

- Soil cover = $0.6 * W * L * SC * Density = 0.6 * (2.60 * 2.00 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0$ kip

Arm = $W / 2 = 2.60 / 2 = 1.30$ ft

Moment = $0.0 * 1.30 = 0.0$ k-ft

- Buoyancy = $0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 2.60 * 2.00 * 62 * (0.67) = -0.1$ kip

Arm = $W / 2 = 2.60 / 2 = 1.30$ ft

Moment = $0.1 * 1.30 = -0.2$ k-ft

- Axial force P = $0.6 * 4.5 + 0.6 * 0.0 = 2.7$ kip

Arm = $W / 2 - Offset = 2.60 / 2 - 0.0 / 12 = 1.30$ ft

Moment = $2.7 * 1.30 = 3.5$ k-ft

- Resisting moment X-X = $0.4 + 0.0 + 0.0 + 3.5 + -0.2 = 3.7$ k-ft

- Overturning safety factor X-X = $\frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{3.7}{0.0} = 37.47 > 1.50$ OK

- Overturning about Z-Z

$$\text{- Moment } M_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about Z-Z

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 2.60 * 2.00 * 8.0 / 12 * 0.15 = 0.3 \text{ kip}$$

$$\text{Arm} = L / 2 = 2.00 / 2 = 1.00 \text{ ft}$$

$$\text{Moment} = 0.3 * 1.00 = 0.3 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 2.00 / 2 - 0.0 / 12 = 1.00 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.00 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (2.60 * 2.00 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 = 2.00 / 2 = 1.00 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.00 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 2.60 * 2.00 * 62 * (0.67) = -0.1 \text{ kip}$$

$$\text{Arm} = L / 2 = 2.00 / 2 = 1.00 \text{ ft}$$

$$\text{Moment} = 0.1 * 1.00 = -0.1 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 4.5 + 0.6 * 0.0 = 2.7 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 2.00 / 2 - 0.0 / 12 = 1.00 \text{ ft}$$

$$\text{Moment} = 2.7 * 1.00 = 2.7 \text{ k-ft}$$

$$\text{- Resisting moment Z-Z} = 0.3 + 0.0 + 0.0 + 2.7 + -0.1 = 2.9 \text{ k-ft}$$

$$\text{- Overturning safety factor Z-Z} = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{2.9}{0.0} = 28.82 > 1.50 \text{ OK}$$

SOIL BEARING PRESSURES (Comb: D+L)

$$\text{Overturning moment X-X} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment X-X} = 0.7 + 0.0 + 0.0 + -0.3 + 13.0 = 13.4 \text{ k-ft}$$

$$\text{Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment Z-Z} = 0.5 + 0.0 + 0.0 + -0.2 + 10.0 = 10.3 \text{ k-ft}$$

$$\text{Resisting force} = \text{Footing} + \text{Pedestal} + \text{Soil} - \text{Buoyancy} + P = 0.5 + 0.0 + 0.0 - 0.2 + 10.0 = 10.3 \text{ kip}$$

X-coordinate of resultant from maximum bearing corner:

$$X_p = \frac{Z\text{-Resisting moment} - Z\text{-Overturning moment}}{\text{Resisting force}} = \frac{10.3 - 0.0}{10.3} = 1.00 \text{ ft}$$

Z-coordinate of resultant from maximum bearing corner:

$$Z_p = \frac{X\text{-Resisting moment} - X\text{-Overturning moment}}{\text{Resisting force}} = \frac{13.4 - 0.0}{10.3} = 1.30 \text{ ft}$$

$$X\text{-ecc} = \text{Length} / 2 - X_p = 2.00 / 2 - 1.00 = 0.00 \text{ ft}$$

$$Z\text{-ecc} = \text{Width} / 2 - Z_p = 2.60 / 2 - 1.30 = 0.00 \text{ ft}$$

$$\text{Area} = \text{Width} * \text{Length} = 2.60 * 2.00 = 5.2 \text{ ft}^2$$

$$S_x = \text{Length} * \text{Width}^2 / 6 = 2.00 * 2.60^2 / 6 = 2.3 \text{ ft}^3$$

$$S_z = \text{Width} * \text{Length}^2 / 6 = 2.60 * 2.00^2 / 6 = 1.7 \text{ ft}^3$$



- Footing is in full bearing. Soil pressures are as follows:

$$P1 = P * (1/A + Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 10.3 * (1/5.2 + 0.00 / 2.3 + 0.00 / 1.7) = 1.98 \text{ ksf}$$

$$P2 = P * (1/A - Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 10.3 * (1/5.2 - 0.00 / 2.3 + 0.00 / 1.7) = 1.98 \text{ ksf}$$

$$P3 = P * (1/A - Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 10.3 * (1/5.2 - 0.00 / 2.3 - 0.00 / 1.7) = 1.98 \text{ ksf}$$

$$P4 = P * (1/A + Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 10.3 * (1/5.2 + 0.00 / 2.3 - 0.00 / 1.7) = 1.98 \text{ ksf}$$



SLIDING CALCULATIONS (Comb: 0.6D+0.6W)

Internal friction angle = 28.0 deg

Passive coefficient $k_p = 4.33$ (per Coulomb)Pressure at mid-depth = $k_p \cdot \text{Density} \cdot (\text{Cover} + \text{Thick} / 2) = 4.33 \cdot 110 \cdot (0.00 + 8.0 / 12 / 2) = 0.16$ ksfX-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Width} = 0.16 \cdot 8.0 / 12 \cdot 2.60 = 0.3$ kipZ-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Length} = 0.16 \cdot 8.0 / 12 \cdot 2.00 = 0.2$ kipFriction force = $\text{Resisting force} \cdot \text{Friction coeff.} = \text{Max}(0, 2.9 \cdot 0.35) = 1.0$ kip

Use 100% of Passive + 100% of Friction for sliding resistance

$$\text{- Sliding safety factor X-X} = \frac{\text{X-Passive force} + \text{Friction}}{\text{X-Horizontal load}} = \frac{1.00 \cdot 0.3 + 1.00 \cdot 1.0}{0.0} = 12.84 > 1.50 \quad \text{OK}$$

$$\text{- Sliding safety factor Z-Z} = \frac{\text{Z-Passive force} + \text{Friction}}{\text{Z-Horizontal load}} = \frac{1.00 \cdot 0.2 + 1.00 \cdot 1.0}{0.0} = 12.20 > 1.50 \quad \text{OK}$$

UPLIFT CALCULATIONS (Comb: 0.6D+0.6W)

$$\text{- Uplift safety factor} = \frac{\text{Pedestal} + \text{Footing} + \text{Cover} - \text{Buoyancy}}{\text{Uplift load}} = \frac{0.0 + 0.3 + 0.0 - 0.1}{0.0} = 99.99 > 1.00 \quad \text{OK}$$

ONE-WAY SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

Concrete $f'_c = 2.5$ ksiSteel $f_y = 40.0$ ksi

Soil density = 110 pcf

Use Plain Concrete Shear Strength

$$\phi V_{cx} = \frac{4}{3} \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Width} \cdot t / 1000 = \frac{4}{3} \cdot 0.60 \cdot \sqrt{2500} \cdot 2.6 \cdot 12 \cdot 8.0 / 1000 = 10.0 \text{ kip}$$

ACI 14.5.5.1

$$\phi V_{cz} = \frac{4}{3} \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Length} \cdot t / 1000 = \frac{4}{3} \cdot 0.60 \cdot \sqrt{2500} \cdot 2.0 \cdot 12 \cdot 8.0 / 1000 = 7.7 \text{ kip}$$



- Shear forces calculated as the volume of the bearing pressures under the effective areas:

$$\text{One-way shear } V_{ux} \text{ (- Side)} = 0.6 \text{ kip} < 10.0 \text{ kip} \quad \text{OK}$$

$$\text{One-way shear } V_{ux} \text{ (+ Side)} = 0.6 \text{ kip} < 10.0 \text{ kip} \quad \text{OK}$$

$$\text{One-way shear } V_{uz} \text{ (- Side)} = 2.1 \text{ kip} < 7.7 \text{ kip} \quad \text{OK}$$

$$\text{One-way shear } V_{uz} \text{ (+ Side)} = 2.1 \text{ kip} < 7.7 \text{ kip} \quad \text{OK}$$



FLEXURE CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Plain } \phi M_{nx} = 5 * \phi * \sqrt{f_c} * L * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 2.00 * 8.0^2 / 6 / 1000 = 0.9 \text{ k-ft}$$

ACI Eq. (14.5.2.1a)

$$\text{Plain } \phi M_{nz} = 5 * \phi * \sqrt{f_c} * W * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 2.60 * 8.0^2 / 6 / 1000 = 1.1 \text{ k-ft}$$

- Top Bars

No Top Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Top

- Top moments calculated as the overburden minus the bearing pressures times the lever arm:

$$\text{Top moment -Mux (- Side)} = 0.0 \text{ k-ft} < 3.2 \text{ k-ft OK}$$

$$\text{Top moment -Mux (+ Side)} = 0.0 \text{ k-ft} < 3.2 \text{ k-ft OK}$$

$$\text{Top moment -Muz (- Side)} = 0.0 \text{ k-ft} < 4.2 \text{ k-ft OK}$$

$$\text{Top moment -Muz (+ Side)} = 0.0 \text{ k-ft} < 4.2 \text{ k-ft OK}$$

- Bottom Bars

No Bottom Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Bottom



- Bottom moments calculated as the bearing minus the overburden pressures times the lever arm:

$$\text{Bottom moment Mux (- Side)} = 3.0 \text{ k-ft} < 3.2 \text{ k-ft OK} \quad \text{ratio} = 0.94$$

$$\text{Bottom moment Mux (+ Side)} = 3.0 \text{ k-ft} < 3.2 \text{ k-ft OK} \quad \text{ratio} = 0.94$$

$$\text{Bottom moment Muz (- Side)} = 2.0 \text{ k-ft} < 4.2 \text{ k-ft OK} \quad \text{ratio} = 0.48$$

$$\text{Bottom moment Muz (+ Side)} = 2.0 \text{ k-ft} < 4.2 \text{ k-ft OK} \quad \text{ratio} = 0.48$$



LOAD TRANSFER CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Area } A1 = \text{col } L * \text{col } W = 6.0 * 6.0 = 36.0 \text{ in}^2$$

$$Sx = \text{col } W * \text{col } L^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$Sz = \text{col } L * \text{col } W^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$\text{Bearing } Pbu = P / A1 + Mz / Sx + Mx / Sz = 14.2 / 36.0 + 0.0 * 12 / 36.0 + 0.0 * 12 / 36.0 = 0.4 \text{ ksi}$$

$$\text{Min edge} = \text{Min} (L / 2 - X\text{-offset} - \text{col } L / 2, W / 2 - Z\text{-offset} - \text{col } W / 2)$$

$$\text{Min edge} = \text{Min} (2.00 * 12 / 2 - 0.0 - 6.0 / 2, 2.60 * 12 / 2 - 0.0 - 6.0 / 2) = 9.0 \text{ in}$$

$$\text{Area } A2 = \text{Min} [L * W, (\text{col } L + 2 * \text{Min edge}) * (\text{col } W + 2 * \text{Min edge})]$$

ACI R22.8.3.2

$$A2 = \text{Min} [2.00 * 12 * 2.6 * 12, (6.0 + 2 * 9.0) * (6.0 + 2 * 9.0)] = 576.0 \text{ in}^2$$

$$\text{Footing } \phi Pnc = \phi * 0.85 * f'c * \text{Min} [2, \sqrt{(A2 / A1)}] = 0.65 * 0.85 * 2.5 * \text{Min} [2, \sqrt{(576.0 / 36.0)}] = 2.8 \text{ ksi}$$

$$\text{Footing } \phi Pns = \phi * As * Fy / A1 = 0.0 \text{ ksi}$$

ACI 22.8.3.2

$$\text{Footing bearing } \phi Pn = \phi Pnc + \phi Pns = 2.8 + 0.0 = 2.8 \text{ ksi} > 0.4 \text{ psi OK}$$

Hooked $L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * \text{db} * \text{ratio})$

ACI 25.4.3

$$L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * 60.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.75 * 0.07) = 6.0 \text{ in}$$

Ld provided = Dowel length = $3.00 * 12 = 36.0 \text{ in} > 12.3 \text{ in OK}$

Ldh provided = Footing thickness - Cover = $8.00 - 3.0 = 5.0 \text{ in} < 6.0 \text{ in NG}$

PUNCHING SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5Lr)

$$X\text{-Edge} = \text{Length} / 2 - \text{Offset} - \text{Col} / 2 = 2.00 * 12 / 2 - 0.0 - 6.0 / 2 = 9.0 \text{ in} \quad \alpha_{sx} = 10$$

$$Z\text{-Edge} = \text{Width} / 2 - \text{Offset} - \text{Col} / 2 = 2.60 * 12 / 2 - 0.0 - 6.0 / 2 = 12.6 \text{ in} \quad \alpha_{sz} = 10$$

$$\alpha_s = \alpha_{sx} + \alpha_{sz} = 10 + 10 = 20 \quad \text{Col type} = \text{Corner} \quad \beta = L / W = 6.0 / 6.0 = 1.00$$

ACI 22.6.5.2

$$\text{Perimeter } b_o = \alpha_{sz} / 10 * (L + d / 2 + X\text{-Edge}) + \alpha_{sx} / 10 * (W + d / 2 + Z\text{-Edge})$$

ACI 22.6.4.2

$$b_o = 10 / 10 * (6.0 + 8.0 / 2 + 9.0) + 10 / 10 * (6.0 + 8.0 / 2 + 12.6) = 41.6 \text{ in}$$

$$\text{Area } A_{bo} = (L + d / 2 + X\text{-Edge}) * (W + d / 2 + Z\text{-Edge}) = (6.0 + 8.0 / 2 + 9.0) * (6.0 + 8.0 / 2 + 12.6) = 429.4 \text{ in}^2$$

Use Plain Concrete Shear Strength

$$\phi V_c = \phi * \text{Min} (1 + 2 / \beta, 2) * 4/3 * \sqrt{f_c}$$

ACI 14.5.5.1

$$\phi V_c = 0.60 * \text{Min} (1 + 2 / 1.00, 2) * 4/3 * \sqrt{2500} = 80.0 \text{ psi}$$

Punching force $F = P + \text{Overburden} * A_{bo} - \text{Bearing}$

$$F = 14.2 + 0.07 * 429.4 / 144 - 3.8 = 10.6 \text{ kip}$$

$$b_1 = L + d / 2 + X\text{-Edge} = 6.0 + 8.0 / 2 + 9.0 = 19.0 \text{ in} \quad b_2 = W + d / 2 + Z\text{-Edge} = 6.0 + 8.0 / 2 + 12.6 = 22.6 \text{ in}$$

$$\gamma_{vx} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{(b_2 / b_1)}} = 1 - \frac{1}{1 + (2/3) \sqrt{(22.6 / 19.0)}} = 0.42$$

ACI Eq. (8.4.4.2.2)

$$\gamma_{vz} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{(b_1 / b_2)}} = 1 - \frac{1}{1 + (2/3) \sqrt{(19.0 / 22.6)}} = 0.38$$

ACI Eq. (8.4.2.3.2)

$$X_{2z} = b_1^2 / 2 / (b_1 + b_2) = 19.0^2 / 2 / (19.0 + 22.6) = 4.3 \text{ in} \quad X_{2x} = b_2^2 / 2 / (b_2 + b_1) = 6.1 \text{ in}$$

$$J_{cz} = b_1 * d^3 / 12 + b_1^3 * d / 12 + b_1 * d * (b_1 / 2 - X_{2z})^2 + b_2 * d * X_{2z}^2$$

ACI R8.4.4.2.3

$$J_{cz} = 19.0 * 8.0^3 / 12 + 19.0^3 * 8.0 / 12 + 19.0 * 8.0 * (19.0 / 2 - 4.3)^2 + 22.6 * 8.0 * 4.3^2 = 12836 \text{ in}^4$$

$$J_{cx} = b_2 * d^3 / 12 + b_2^3 * d / 12 + b_2 * d * (b_2 / 2 - X_{2x})^2 + b_1 * d * X_{2x}^2$$

ACI R8.4.4.2.3


$$J_{cx} = 22.6 * 8.0^3 / 12 + 22.6^3 * 8.0 / 12 + 22.6 * 8.0 * (22.6 / 2 - 6.1)^2 + 19.0 * 8.0 * 6.1^2 = 19204 \text{ in}^4$$

$$\text{Stress due to } P = F / (b_o * d) * 1000 = 10.6 / (41.6 * 8.0) * 1000 = 31.8 \text{ psi}$$

$$\text{Stress due to } M_x = \gamma_{vx} * X\text{-OTM} * X_{2x} / J_{cx} = 0.42 * 0.0 * 12 * 6.1 / 19204 * 1000 = 0.0 \text{ psi}$$

$$\text{Stress due to } M_z = \gamma_{vz} * Z\text{-OTM} * X_{2z} / J_{cz} = 0.42 * 0.0 * 12 * 4.3 / 12836 * 1000 = 0.0 \text{ psi}$$


$$\text{Punching stress} = P\text{-stress} + M_x\text{-stress} + M_z\text{-stress} = 31.8 + 0.0 + 0.0 = 31.8 \text{ psi} < 80.0 \text{ psi OK}$$




DESIGN CODES

Concrete Design ACI 318-14

Load Combinations ASCE 7-10/16



ELEVATION



PLAN

GEOMETRY				SOIL PRESSURES (D+L)			
Footing Length (X-dir)	1.50	ft		Gross Allow. Soil Pressure	2.0	ksf	
Footing Width (Z-dir)	2.60	ft		Soil Pressure at Corner 1	2.0	ksf	
Footing Thickness	8.0	in	OK	Soil Pressure at Corner 2	2.0	ksf	
Soil Cover	0.00	ft		Soil Pressure at Corner 3	2.0	ksf	
Column Length (X-dir)	6.0	in		Soil Pressure at Corner 4	2.0	ksf	
Column Width (Z-dir)	6.0	in		Bearing Pressure Ratio	0.99	OK	
Offset (X-dir)	0.00	in	OK	Ftg. Area in Contact with Soil	100.0	%	
Offset (Z-dir)	0.00	in	OK	X-eccentricity / Ftg. Length	0.00	OK	
Base Plate (L x W)	6.0 x 6.0	in		Z-eccentricity / Ftg. Width	0.00	OK	

APPLIED LOADS

	Dead	Live	RLive	Snow	Wind	Seismic	
Axial Force P	3.0	4.5	0.0	0.0	0.0	0.0	kip
Moment about X Mx ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Moment about Z Mz ..	0.0	0.0	0.0	0.0	0.0	0.0	k-ft
Shear Force Vx	0.0	0.0	0.0	0.0	0.0	0.0	kip
Shear Force Vz	0.0	0.0	0.0	0.0	0.0	0.0	kip

OVERTURNING CALCULATIONS (Comb: 0.6D+0.6W)

- Overturning about X-X

$$\text{- Moment } M_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment } X-X = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about X-X

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 2.60 * 1.50 * 8.0 / 12 * 0.15 = 0.2 \text{ kip}$$

$$\text{Arm} = W / 2 = 2.60 / 2 = 1.30 \text{ ft}$$

$$\text{Moment} = 0.2 * 1.30 = 0.3 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = W / 2 - Offset = 2.60 / 2 - 0.0 / 12 = 1.30 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.30 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (2.60 * 1.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = W / 2 = 2.60 / 2 = 1.30 \text{ ft}$$

$$\text{Moment} = 0.0 * 1.30 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 2.60 * 1.50 * 62 * (0.67) = -0.1 \text{ kip}$$

$$\text{Arm} = W / 2 = 2.60 / 2 = 1.30 \text{ ft}$$

$$\text{Moment} = 0.1 * 1.30 = -0.1 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 3.0 + 0.6 * 0.0 = 1.8 \text{ kip}$$

$$\text{Arm} = W / 2 - Offset = 2.60 / 2 - 0.0 / 12 = 1.30 \text{ ft}$$

$$\text{Moment} = 1.8 * 1.30 = 2.3 \text{ k-ft}$$

$$\text{- Resisting moment } X-X = 0.3 + 0.0 + 0.0 + 2.3 + -0.1 = 2.5 \text{ k-ft}$$

$$\text{- Overturning safety factor } X-X = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{2.5}{0.0} = 25.18 > 1.50 \text{ OK}$$

- Overturning about Z-Z

$$\text{- Moment } M_z = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ k-ft}$$

$$\text{- Shear Force } V_x = 0.6 * 0.0 + 0.6 * 0.0 = 0.0 \text{ kip}$$

$$\text{Arm} = 0.00 + 8.0 / 12 = 0.67 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.67 = 0.0 \text{ k-ft}$$

$$\text{- Passive Force} = 0.0 \text{ kip}$$

$$\text{Arm} = 0.27 \text{ ft}$$

$$\text{Moment} = 0.0 \text{ k-ft}$$

$$\text{- Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

- Resisting about Z-Z

$$\text{- Footing weight} = 0.6 * W * L * Thick * Density = 0.6 * 2.60 * 1.50 * 8.0 / 12 * 0.15 = 0.2 \text{ kip}$$

$$\text{Arm} = L / 2 = 1.50 / 2 = 0.75 \text{ ft}$$

$$\text{Moment} = 0.2 * 0.75 = 0.2 \text{ k-ft}$$

$$\text{- Pedestal weight} = 0.6 * W * L * H * Density = 0.6 * 6.0 / 12 * 6.0 / 12 * 0.0 * 0.15 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 1.50 / 2 - 0.0 / 12 = 0.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.75 = 0.0 \text{ k-ft}$$

$$\text{- Soil cover} = 0.6 * W * L * SC * Density = 0.6 * (2.60 * 1.50 - 6.0 / 12 * 6.0 / 12) * 0.0 * 110 = 0.0 \text{ kip}$$

$$\text{Arm} = L / 2 = 1.50 / 2 = 0.75 \text{ ft}$$

$$\text{Moment} = 0.0 * 0.75 = 0.0 \text{ k-ft}$$

$$\text{- Buoyancy} = 0.6 * W * L * \gamma * (SC + Thick - WT) = 0.6 * 2.60 * 1.50 * 62 * (0.67) = -0.1 \text{ kip}$$

$$\text{Arm} = L / 2 = 1.50 / 2 = 0.75 \text{ ft}$$

$$\text{Moment} = 0.1 * 0.75 = -0.1 \text{ k-ft}$$

$$\text{- Axial force } P = 0.6 * 3.0 + 0.6 * 0.0 = 1.8 \text{ kip}$$

$$\text{Arm} = L / 2 - Offset = 1.50 / 2 - 0.0 / 12 = 0.75 \text{ ft}$$

$$\text{Moment} = 1.8 * 0.75 = 1.4 \text{ k-ft}$$

$$\text{- Resisting moment Z-Z} = 0.2 + 0.0 + 0.0 + 1.4 + -0.1 = 1.5 \text{ k-ft}$$

$$\text{- Overturning safety factor Z-Z} = \frac{\text{Resisting moment}}{\text{Overturning moment}} = \frac{1.5}{0.0} = 14.52 > 1.50 \text{ OK}$$

SOIL BEARING PRESSURES (Comb: D+L)

$$\text{Overturning moment X-X} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment X-X} = 0.5 + 0.0 + 0.0 + -0.2 + 9.8 = 10.0 \text{ k-ft}$$

$$\text{Overturning moment Z-Z} = 0.0 + 0.0 = 0.0 \text{ k-ft}$$

$$\text{Resisting moment Z-Z} = 0.3 + 0.0 + 0.0 + -0.1 + 5.6 = 5.8 \text{ k-ft}$$

$$\text{Resisting force} = \text{Footing} + \text{Pedestal} + \text{Soil} - \text{Buoyancy} + P = 0.4 + 0.0 + 0.0 - 0.2 + 7.5 = 7.7 \text{ kip}$$

X-coordinate of resultant from maximum bearing corner:

$$X_p = \frac{Z\text{-Resisting moment} - Z\text{-Overturning moment}}{\text{Resisting force}} = \frac{5.8 - 0.0}{7.7} = 0.75 \text{ ft}$$

Z-coordinate of resultant from maximum bearing corner:

$$Z_p = \frac{X\text{-Resisting moment} - X\text{-Overturning moment}}{\text{Resisting force}} = \frac{10.0 - 0.0}{7.7} = 1.30 \text{ ft}$$

$$X\text{-ecc} = \text{Length} / 2 - X_p = 1.50 / 2 - 0.75 = 0.00 \text{ ft}$$

$$Z\text{-ecc} = \text{Width} / 2 - Z_p = 2.60 / 2 - 1.30 = 0.00 \text{ ft}$$

$$\text{Area} = \text{Width} * \text{Length} = 2.60 * 1.50 = 3.9 \text{ ft}^2$$

$$S_x = \text{Length} * \text{Width}^2 / 6 = 1.50 * 2.60^2 / 6 = 1.7 \text{ ft}^3$$

$$S_z = \text{Width} * \text{Length}^2 / 6 = 2.60 * 1.50^2 / 6 = 1.0 \text{ ft}^3$$



- Footing is in full bearing. Soil pressures are as follows:

$$P1 = P * (1/A + Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 7.7 * (1 / 3.9 + 0.00 / 1.7 + 0.00 / 1.0) = 1.98 \text{ ksf}$$

$$P2 = P * (1/A - Z\text{-ecc} / S_x + X\text{-ecc} / S_z) = 7.7 * (1 / 3.9 - 0.00 / 1.7 + 0.00 / 1.0) = 1.98 \text{ ksf}$$

$$P3 = P * (1/A - Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 7.7 * (1 / 3.9 - 0.00 / 1.7 - 0.00 / 1.0) = 1.98 \text{ ksf}$$

$$P4 = P * (1/A + Z\text{-ecc} / S_x - X\text{-ecc} / S_z) = 7.7 * (1 / 3.9 + 0.00 / 1.7 - 0.00 / 1.0) = 1.98 \text{ ksf}$$



SLIDING CALCULATIONS (Comb: 0.6D+0.6W)

Internal friction angle = 28.0 deg

Passive coefficient $k_p = 4.33$ (per Coulomb)Pressure at mid-depth = $k_p \cdot \text{Density} \cdot (\text{Cover} + \text{Thick} / 2) = 4.33 \cdot 110 \cdot (0.00 + 8.0 / 12 / 2) = 0.16$ ksfX-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Width} = 0.16 \cdot 8.0 / 12 \cdot 2.60 = 0.3$ kipZ-Passive force = $\text{Pressure} \cdot \text{Thick} \cdot \text{Length} = 0.16 \cdot 8.0 / 12 \cdot 1.50 = 0.2$ kipFriction force = $\text{Resisting force} \cdot \text{Friction coeff.} = \text{Max}(0, 1.9 \cdot 0.35) = 0.7$ kip

Use 100% of Passive + 100% of Friction for sliding resistance

$$\text{- Sliding safety factor X-X} = \frac{\text{X-Passive force} + \text{Friction}}{\text{X-Horizontal load}} = \frac{1.00 \cdot 0.3 + 1.00 \cdot 0.7}{0.0} = 9.53 > 1.50 \text{ OK}$$

$$\text{- Sliding safety factor Z-Z} = \frac{\text{Z-Passive force} + \text{Friction}}{\text{Z-Horizontal load}} = \frac{1.00 \cdot 0.2 + 1.00 \cdot 0.7}{0.0} = 8.36 > 1.50 \text{ OK}$$

UPLIFT CALCULATIONS (Comb: 0.6D+0.6W)

$$\text{- Uplift safety factor} = \frac{\text{Pedestal} + \text{Footing} + \text{Cover} - \text{Buoyancy}}{\text{Uplift load}} = \frac{0.0 + 0.2 + 0.0 - 0.1}{0.0} = 99.99 > 1.00 \text{ OK}$$

ONE-WAY SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

Concrete $f'_c = 2.5$ ksiSteel $f_y = 40.0$ ksi

Soil density = 110 pcf

Use Plain Concrete Shear Strength

$$\phi V_{cx} = \frac{4}{3} \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Width} \cdot t / 1000 = \frac{4}{3} \cdot 0.60 \cdot \sqrt{(2500)} \cdot 2.6 \cdot 12 \cdot 8.0 / 1000 = 10.0 \text{ kip}$$

ACI 14.5.5.1

$$\phi V_{cz} = \frac{4}{3} \cdot \phi \cdot \sqrt{f'_c} \cdot \text{Length} \cdot t / 1000 = \frac{4}{3} \cdot 0.60 \cdot \sqrt{(2500)} \cdot 1.5 \cdot 12 \cdot 8.0 / 1000 = 5.8 \text{ kip}$$



- Shear forces calculated as the volume of the bearing pressures under the effective areas:

$$\text{One-way shear } V_{ux} \text{ (- Side)} = 0.0 \text{ kip} < 10.0 \text{ kip OK}$$

$$\text{One-way shear } V_{ux} \text{ (+ Side)} = 0.0 \text{ kip} < 10.0 \text{ kip OK}$$

$$\text{One-way shear } V_{uz} \text{ (- Side)} = 1.6 \text{ kip} < 5.8 \text{ kip OK}$$

$$\text{One-way shear } V_{uz} \text{ (+ Side)} = 1.6 \text{ kip} < 5.8 \text{ kip OK}$$



FLEXURE CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Plain } \phi M_{nx} = 5 * \phi * \sqrt{f_c} * L * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 1.50 * 8.0^2 / 6 / 1000 = 0.6 \text{ k-ft}$$

ACI Eq. (14.5.2.1a)

$$\text{Plain } \phi M_{nz} = 5 * \phi * \sqrt{f_c} * W * \text{Thick}^2 / 6 = 5 * 0.60 * \sqrt{(2500)} * 2.60 * 8.0^2 / 6 / 1000 = 1.1 \text{ k-ft}$$

- Top Bars

No Top Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Top

- Top moments calculated as the overburden minus the bearing pressures times the lever arm:

$$\text{Top moment -Mux (- Side)} = 0.0 \text{ k-ft} < 2.4 \text{ k-ft OK}$$

$$\text{Top moment -Mux (+ Side)} = 0.0 \text{ k-ft} < 2.4 \text{ k-ft OK}$$

$$\text{Top moment -Muz (- Side)} = 0.0 \text{ k-ft} < 4.2 \text{ k-ft OK}$$

$$\text{Top moment -Muz (+ Side)} = 0.0 \text{ k-ft} < 4.2 \text{ k-ft OK}$$

- Bottom Bars

No Bottom Reinforcement Provided at the Footing

Use Plain Concrete Flexural Strength at Bottom



- Bottom moments calculated as the bearing minus the overburden pressures times the lever arm:

$$\text{Bottom moment Mux (- Side)} = 2.3 \text{ k-ft} < 2.4 \text{ k-ft OK} \quad \text{ratio} = 0.96$$

$$\text{Bottom moment Mux (+ Side)} = 2.3 \text{ k-ft} < 2.4 \text{ k-ft OK} \quad \text{ratio} = 0.96$$

$$\text{Bottom moment Muz (- Side)} = 0.9 \text{ k-ft} < 4.2 \text{ k-ft OK} \quad \text{ratio} = 0.22$$

$$\text{Bottom moment Muz (+ Side)} = 0.9 \text{ k-ft} < 4.2 \text{ k-ft OK} \quad \text{ratio} = 0.22$$



LOAD TRANSFER CALCULATIONS (Comb: 1.2D+1.6L+0.5S)

$$\text{Area } A1 = \text{col } L * \text{col } W = 6.0 * 6.0 = 36.0 \text{ in}^2$$

$$Sx = \text{col } W * \text{col } L^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$Sz = \text{col } L * \text{col } W^2 / 6 = 6.0 * 6.0^2 / 6 = 36.0 \text{ in}^3$$

$$\text{Bearing } Pbu = P / A1 + Mz / Sx + Mx / Sz = 10.8 / 36.0 + 0.0 * 12 / 36.0 + 0.0 * 12 / 36.0 = 0.3 \text{ ksi}$$

$$\text{Min edge} = \text{Min} (L / 2 - X\text{-offset} - \text{col } L / 2, W / 2 - Z\text{-offset} - \text{col } W / 2)$$

$$\text{Min edge} = \text{Min} (1.50 * 12 / 2 - 0.0 - 6.0 / 2, 2.60 * 12 / 2 - 0.0 - 6.0 / 2) = 6.0 \text{ in}$$

$$\text{Area } A2 = \text{Min} [L * W, (\text{col } L + 2 * \text{Min edge}) * (\text{col } W + 2 * \text{Min edge})]$$

ACI R22.8.3.2

$$A2 = \text{Min} [1.50 * 12 * 2.6 * 12, (6.0 + 2 * 6.0) * (6.0 + 2 * 6.0)] = 324.0 \text{ in}^2$$

$$\text{Footing } \phi Pnc = \phi * 0.85 * f'c * \text{Min} [2, \sqrt{(A2 / A1)}] = 0.65 * 0.85 * 2.5 * \text{Min} [2, \sqrt{(324.0 / 36.0)}] = 2.8 \text{ ksi}$$

$$\text{Footing } \phi Pns = \phi * As * Fy / A1 = 0.0 \text{ ksi}$$

ACI 22.8.3.2

$$\text{Footing bearing } \phi Pn = \phi Pnc + \phi Pns = 2.8 + 0.0 = 2.8 \text{ ksi} > 0.3 \text{ psi OK}$$

Hooked $L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * f_y / (f_c)^{1/2} * \text{Confining} * \text{Location} * \text{Concrete} * \text{db} * \text{ratio})$

ACI 25.4.3

$$L_{dh} = \text{Max} (8 \text{ db}, 6, 0.02 * 60.0 * 1000 / (2500)^{1/2} * 1.0 * 0.7 * 0.0 * 0.75 * 0.05) = 6.0 \text{ in}$$

Ld provided = Dowel length = $3.00 * 12 = 36.0 \text{ in} > 12.0 \text{ in OK}$

Ldh provided = Footing thickness - Cover = $8.00 - 3.0 = 5.0 \text{ in} < 6.0 \text{ in NG}$

PUNCHING SHEAR CALCULATIONS (Comb: 1.2D+1.6L+0.5Lr)

$$\text{X-Edge} = \text{Length} / 2 - \text{Offset} - \text{Col} / 2 = 1.50 * 12 / 2 - 0.0 - 6.0 / 2 = 6.0 \text{ in} \quad \alpha_{sx} = 10$$

$$\text{Z-Edge} = \text{Width} / 2 - \text{Offset} - \text{Col} / 2 = 2.60 * 12 / 2 - 0.0 - 6.0 / 2 = 12.6 \text{ in} \quad \alpha_{sz} = 10$$

$$\alpha_s = \alpha_{sx} + \alpha_{sz} = 10 + 10 = 20 \quad \text{Col type} = \text{Corner} \quad \beta = L / W = 6.0 / 6.0 = 1.00$$

ACI 22.6.5.2

$$\text{Perimeter } b_o = \alpha_{sz} / 10 * (L + d / 2 + \text{X-Edge}) + \alpha_{sx} / 10 * (W + d / 2 + \text{Z-Edge})$$

ACI 22.6.4.2

$$b_o = 10 / 10 * (6.0 + 8.0 / 2 + 6.0) + 10 / 10 * (6.0 + 8.0 / 2 + 12.6) = 38.6 \text{ in}$$

$$\text{Area } A_{bo} = (L + d / 2 + \text{X-Edge}) * (W + d / 2 + \text{Z-Edge}) = (6.0 + 8.0 / 2 + 6.0) * (6.0 + 8.0 / 2 + 12.6) = 361.6 \text{ in}^2$$

Use Plain Concrete Shear Strength

$$\phi V_c = \phi * \text{Min} (1 + 2 / \beta, 2) * 4/3 * \sqrt{f_c}$$

ACI 14.5.5.1

$$\phi V_c = 0.60 * \text{Min} (1 + 2 / 1.00, 2) * 4/3 * \sqrt{2500} = 80.0 \text{ psi}$$

Punching force $F = P + \text{Overburden} * A_{bo} - \text{Bearing}$

$$F = 10.8 + 0.07 * 361.6 / 144 - 3.9 = 7.1 \text{ kip}$$

$$b_1 = L + d / 2 + \text{X-Edge} = 6.0 + 8.0 / 2 + 6.0 = 16.0 \text{ in} \quad b_2 = W + d / 2 + \text{Z-Edge} = 6.0 + 8.0 / 2 + 12.6 = 22.6 \text{ in}$$

$$\gamma_{vx} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{(b_2 / b_1)}} = 1 - \frac{1}{1 + (2/3) \sqrt{(22.6 / 16.0)}} = 0.44$$

ACI Eq. (8.4.4.2.2)

$$\gamma_{vz} \text{ factor} = 1 - \frac{1}{1 + (2/3) \sqrt{(b_1 / b_2)}} = 1 - \frac{1}{1 + (2/3) \sqrt{(16.0 / 22.6)}} = 0.36$$

ACI Eq. (8.4.2.3.2)

$$X_{2z} = b_1^2 / 2 / (b_1 + b_2) = 16.0^2 / 2 / (16.0 + 22.6) = 3.3 \text{ in} \quad X_{2x} = b_2^2 / 2 / (b_2 + b_1) = 6.6 \text{ in}$$

$$J_{cz} = b_1 * d^3 / 12 + b_1^3 * d / 12 + b_1 * d * (b_1 / 2 - X_{2z})^2 + b_2 * d * X_{2z}^2$$

ACI R8.4.4.2.3

$$J_{cz} = 16.0 * 8.0^3 / 12 + 16.0^3 * 8.0 / 12 + 16.0 * 8.0 * (16.0 / 2 - 3.3)^2 + 22.6 * 8.0 * 3.3^2 = 8210 \text{ in}^4$$

$$J_{cx} = b_2 * d^3 / 12 + b_2^3 * d / 12 + b_2 * d * (b_2 / 2 - X_{2x})^2 + b_1 * d * X_{2x}^2$$

ACI R8.4.4.2.3


$$J_{cx} = 22.6 * 8.0^3 / 12 + 22.6^3 * 8.0 / 12 + 22.6 * 8.0 * (22.6 / 2 - 6.6)^2 + 16.0 * 8.0 * 6.6^2 = 18229 \text{ in}^4$$

$$\text{Stress due to } P = F / (b_o * d) * 1000 = 7.1 / (38.6 * 8.0) * 1000 = 23.0 \text{ psi}$$

$$\text{Stress due to } M_x = \gamma_{vx} * X\text{-OTM} * X_{2x} / J_{cx} = 0.44 * 0.0 * 12 * 6.6 / 18229 * 1000 = 0.0 \text{ psi}$$

$$\text{Stress due to } M_z = \gamma_{vz} * Z\text{-OTM} * X_{2z} / J_{cz} = 0.44 * 0.0 * 12 * 3.3 / 8210 * 1000 = 0.0 \text{ psi}$$


$$\text{Punching stress} = P\text{-stress} + M_x\text{-stress} + M_z\text{-stress} = 23.0 + 0.0 + 0.0 = 23.0 \text{ psi} < 80.0 \text{ psi OK}$$




DESIGN CODES

Concrete Design ACI 318-14

Load Combinations ASCE 7-10/16



ELEVATION



PLAN

10/26/2024

C. PIERUCCIONI, PE

ETC-BUILDING F

LATERAL ANALYSIS

1

WIND $V_{ASD} = 85 \text{ mph}$ $V_{ULT} = 110 \text{ mph}$ Ex. B $K_{zt} = 1.0$ $S_{LOPE} = 0.34$
 $K = 36$ $R = 1.06$

$$Z_{ONE A} = 12.9 \text{ psf} \times 1.06 = \cancel{13.7 \text{ psf}} \quad 16.0 \text{ psf}$$

$$Z_{ONE B} = 8.8 \text{ psf} \times 1.06 = 9.3 \text{ psf}$$

$$Z_{ONE C} = 10.2 \text{ psf} \times 1.06 = \cancel{10.8 \text{ psf}} \quad 16.0 \text{ psf}$$

$$Z_{ONE D} = 7.0 \text{ psf} \times 1.06 = \cancel{7.4 \text{ psf}} \quad 8.0 \text{ psf}$$

SEISMIC $S_{DS} = 0.831$ $R = 6.5$ $I_c = 1.0$

$$C_s = (0.831 / (6.5 \times 1.0)) / 1.4 = 0.091$$

$$W_{\text{ROOF}} = (35 \text{ psf} \times 10,100 \text{ sf}) = 353,500 \text{ \#} \quad h = 9'$$

$$W_{\text{LEVEL 3}} = (40 \text{ psf} \times 8,910 \text{ sf}) = 356,400 \text{ \#} \quad h = 9'$$

$$W_{\text{LEVEL 2}} = (40 \text{ psf} \times 9,214 \text{ sf}) = 368,560 \text{ \#} \quad h = 9'$$

$$W_{\text{TOTAL}} = 1,078,460 \text{ \#}$$

$$\begin{aligned} h &= 29' \\ h &= 20' \\ h &= 10' \end{aligned}$$

$$V_s = (1,078,460 \text{ \#} \times 0.091) = 98,140 \text{ \#}$$

$$F_{\text{ROOF}} = \left[\frac{(353,500 \text{ \#} \times 29')}{(353,500 \text{ \#} \times 29') + (356,400 \text{ \#} \times 20') + (368,560 \text{ \#} \times 10')} \right] \times 98,140 = 47,892 \text{ \#}$$

$$F_{\text{LEVEL 3}} = \left[\frac{(356,400 \text{ \#} \times 20')}{(353,500 \text{ \#} \times 29') + (356,400 \text{ \#} \times 20') + (368,560 \text{ \#} \times 10')} \right] \times 98,140 \text{ \#} = 33,209 \text{ \#}$$

$$F_{\text{LEVEL 2}} = \left[\frac{(368,560 \text{ \#} \times 10')}{(353,500 \text{ \#} \times 29') + (356,400 \text{ \#} \times 20') + (368,560 \text{ \#} \times 10')} \right] \times 98,140 \text{ \#} = 17,039 \text{ \#}$$

GRID 1/2

$$F_{3W} = (16 \text{ PSF} \times 208 \text{ SF}) + (9.3 \text{ PSF} \times 170 \text{ SF}) + (8 \text{ PSF} \times 75 \text{ SF}) = 5,044 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (1.536 \text{ SF} / 10,100 \text{ SF}) = 7,283 \text{ \#}$$

$$F_{2W} = 5,044 \text{ \#} + (16 \text{ PSF} \times 237 \text{ SF}) = 8,836 \text{ \#}$$

$$F_{2E} = 7,283 \text{ \#} + 33,209 \text{ \#} \times (1.370 \text{ SF} / 8,910 \text{ SF}) = 12,390 \text{ \#}$$

$$F_{1W} = 8,836 \text{ \#} + (16 \text{ PSF} \times 240 \text{ SF}) = 12,676 \text{ \#}$$

$$F_{1E} = 12,390 \text{ \#} + 17,039 \text{ \#} \times (1.370 \text{ SF} / 9,214 \text{ SF}) = 14,923 \text{ \#}$$

GRID 4/5

$$F_{3W} = (16 \text{ PSF} \times 447 \text{ SF}) + (8 \text{ PSF} \times 33 \text{ SF}) = 7,416 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (2.835 \text{ SF} / 10,100 \text{ SF}) = 13,443 \text{ \#}$$

$$F_{2W} = 7,416 \text{ \#} + (16 \text{ PSF} \times 411 \text{ SF}) = 14,472 \text{ \#}$$

$$F_{2E} = 13,443 \text{ \#} + 33,209 \text{ \#} \times (2.417 \text{ SF} / 8,910 \text{ SF}) = 22,451 \text{ \#}$$

$$F_{1W} = 14,472 \text{ \#} + (16 \text{ PSF} \times 443 \text{ SF}) = 21,560 \text{ \#}$$

$$F_{1E} = 22,451 \text{ \#} + 17,039 \text{ \#} \times (2.574 \text{ SF} / 9,214 \text{ SF}) = 27,211 \text{ \#}$$

GRID 7

$$F_{3W} = (16 \text{ PSF} \times 464 \text{ SF}) = 7,424 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (2.047 \text{ SF} / 10,100 \text{ SF}) = 9,706 \text{ \#}$$

$$F_{2W} = 7,424 \text{ \#} + (16 \text{ PSF} \times 355 \text{ SF}) = 13,104 \text{ \#}$$

$$F_{2E} = 9,706 \text{ \#} + 33,209 \text{ \#} \times (1.942 \text{ SF} / 8,910 \text{ SF}) = 16,945 \text{ \#}$$

$$F_{1W} = 13,104 \text{ \#} + (16 \text{ PSF} \times 357 \text{ SF}) = 18,816 \text{ \#}$$

$$F_{1E} = 16,945 \text{ \#} + 17,039 \text{ \#} \times (1.942 \text{ SF} / 9,214 \text{ SF}) = 20,536 \text{ \#}$$

GRID 9/10

$$F_{3W} = (16 \text{ PSF} \times 291 \text{ SF}) = 4,656 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (2,107 \text{ SF} / 10,100 \text{ SF}) = 9,991 \text{ \#}$$

$$F_{2W} = 4,656 \text{ \#} + (16 \text{ PSF} \times 321 \text{ SF}) = 9,792 \text{ \#}$$

$$F_{2E} = 9,991 \text{ \#} + 33,209 \text{ \#} \times (1,755 \text{ SF} / 8,910 \text{ SF}) = 16,532 \text{ \#}$$

$$F_{1W} = 9,792 \text{ \#} + (16 \text{ PSF} \times 323 \text{ SF}) = 14,960 \text{ \#}$$

$$F_{1E} = 16,532 \text{ \#} + 17,039 \text{ \#} \times (1,903 \text{ SF} / 9,214 \text{ SF}) = 20,051 \text{ \#}$$

GRID 13

$$F_{3W} = (16 \text{ PSF} \times 159 \text{ SF}) + (9.3 \text{ PSF} \times 114 \text{ SF}) + (8 \text{ PSF} \times 55 \text{ SF}) = 3,644 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (1,579 \text{ SF} / 10,100 \text{ SF}) = 7,487 \text{ \#}$$

$$F_{2W} = 3,644 \text{ \#} + (16 \text{ PSF} \times 174 \text{ SF}) = 6,428 \text{ \#}$$

$$F_{2E} = 7,487 \text{ \#} + 33,209 \text{ \#} \times (1,425 \text{ SF} / 8,910 \text{ SF}) = 12,798 \text{ \#}$$

$$F_{1W} = 6,428 \text{ \#} + (16 \text{ PSF} \times 177 \text{ SF}) = 9,260 \text{ \#}$$

$$F_{1E} = 12,798 \text{ \#} + 17,039 \text{ \#} \times (1,425 \text{ SF} / 9,214 \text{ SF}) = 15,434 \text{ \#}$$

GRID A-C

$$F_{3w} = (16 \text{ psf} \times 1615 \text{ sf}) + (9.3 \text{ psf} \times 132 \text{ sf}) + (8 \text{ psf} \times 33 \text{ sf}) = 4,116 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (2,399 \text{ sf} / 10,100 \text{ sf}) = 11,376 \text{ \#}$$

$$F_{2w} = 4,116 \text{ \#} + (16 \text{ psf} \times 186 \text{ sf}) = 7,092 \text{ \#}$$

$$F_{2E} = 11,376 \text{ \#} + 33,209 \text{ \#} \times (2,048 \text{ sf} / 8,910 \text{ sf}) = 19,009 \text{ \#}$$

$$F_{1w} = 7,092 \text{ \#} + (16 \text{ psf} \times 174 \text{ sf}) = 9,876 \text{ \#}$$

$$F_{1E} = 19,009 \text{ \#} + 17,039 \text{ \#} \times (2,048 \text{ sf} / 9,214 \text{ sf}) = 22,796 \text{ \#}$$

GRID F

$$F_{3w} = (16 \text{ psf} \times 274 \text{ sf}) = 4,384 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (5,091 \text{ sf} / 10,100 \text{ sf}) = 24,140 \text{ \#}$$

$$F_{2w} = 4,384 \text{ \#} + (16 \text{ psf} \times 323 \text{ sf}) = 9,552 \text{ \#}$$

$$F_{2E} = 24,140 \text{ \#} + 33,209 \text{ \#} \times (4,761 \text{ sf} / 8,910 \text{ sf}) = 41,885 \text{ \#}$$

$$F_{1w} = 9,552 \text{ \#} + (16 \text{ psf} \times 317 \text{ sf}) = 14,624 \text{ \#}$$

$$F_{1E} = 41,885 \text{ \#} + 17,039 \text{ \#} \times (5,003 \text{ sf} / 9,214 \text{ sf}) = 51,137 \text{ \#}$$

GRID K-M

$$F_{3w} = (16 \text{ psf} \times 280 \text{ sf}) + (9.3 \text{ psf} \times 65 \text{ sf}) = 5,085 \text{ \#}$$

$$F_{3E} = 47,892 \text{ \#} \times (2,610 \text{ sf} / 10,100 \text{ sf}) = 12,376 \text{ \#}$$

$$F_{2w} = 5,085 \text{ \#} + (16 \text{ psf} \times 213 \text{ sf}) = 8,493 \text{ \#}$$

$$F_{2E} = 12,376 \text{ \#} + 33,209 \text{ \#} \times (2,101 \text{ sf} / 8,910 \text{ sf}) = 20,207 \text{ \#}$$

$$F_{1w} = 8,493 \text{ \#} + (16 \text{ psf} \times 210 \text{ sf}) = 11,853 \text{ \#}$$

$$F_{1E} = 20,207 \text{ \#} + 17,039 \text{ \#} \times (2,163 \text{ sf} / 9,214 \text{ sf}) = 24,207 \text{ \#}$$

GR105 112 (21'-10" FTAO)

$$(LEVEL 3) FE = 7,283\# \times (21.83' / 63.67') = 2,497\#$$

$$VE = 342\text{PIF}$$


$$\text{USE } \triangle W2 \quad VEA_{allow} = 353\text{PIF}$$

HOLD DOWNS

$$TE = 1,025\# \times 1.25 - \frac{1}{2}(30\text{PSF} \times 2' \times 10.92') - \frac{1}{2}(12\text{PSF} \times 4.5' \times 10.92') = 713\#$$

USE MST37 w/ 2 STUOPS

$$TE_{allow} = 2,140\# \times 1.4 / 1.6 = 4,873\#$$



$$(LEVEL 2) FE = 12,390\# \times (21.83' / 63.67') = 4,248\#$$

$$VE = 581\text{PIF}$$

$$\text{USE } \triangle W4 \quad VEA_{allow} = 595\text{PIF}$$

HOLD DOWNS

$$TE = 1,744\# \times 1.25 + 713\# - \frac{1}{2}(30\text{PSF} \times 7.9' \times 10.92') - \frac{1}{2}(12\text{PSF} \times 9' \times 10.92') = 1,009\#$$

USE MST37 w/ 2 STUOPS

$$TE_{allow} = 2,140\# \times 1.4 / 1.6 = 4,873\#$$

$$(LEVEL 1) FE = 14,923\# \times (21.83' / 63.67') = 5,116\#$$

$$VE = 700\text{PIF}$$

$$\text{USE } \triangle W8 \quad VEA_{allow} = 770\text{PIF}$$

HOLD DOWNS

$$TE = 2,101\# \times 1.25 + 1,009\# - \frac{1}{2}(30\text{PSF} \times 7.9' \times 10.92') - \frac{1}{2}(12\text{PSF} \times 9' \times 10.92') = 1,752\#$$

USE HDU2-SDS2.5 w/ 2 STUOPS

$$TE_{allow} = 2,215\# \times 1.4 / 1.6 = 4,938\#$$

GRID 2 (12'-6" FTAO)

$$(LEVEL 3) FE = 7.283^{\#} \times (12.5' / 63.67') = 1430^{\#}$$


$$VE = 172 \text{ PIF}$$

$$\text{USE } \nabla W1 \quad V_{EALLOW} = 242 \text{ PIF}$$

HOLD DOWNS

$$TE = 1,030^{\#} \times 1.25 - \frac{1}{2}(25 \text{ PSF} \times 2' \times 6.25') - \frac{1}{2}(12 \text{ PSF} \times 4.5' \times 6.25') = 963^{\#}$$

$$\text{USE } \nabla W1 \text{ (2 STOPS)} \quad T_{EALLOW} = 2,140^{\#} \times 1.4 / 1.6 = 1,873^{\#}$$



$$(LEVEL 2) FE = 12,390^{\#} \times (12.5' / 63.67') = 2,432^{\#}$$

$$VE = 292 \text{ PIF}$$

$$\text{USE } \nabla W2 \quad V_{EALLOW} = 353 \text{ PIF}$$

HOLD DOWNS

$$TE = 1,751^{\#} \times 1.25 + 963^{\#} - \frac{1}{2}(30 \text{ PSF} \times 7' \times 6.25') - \frac{1}{2}(12 \text{ PSF} \times 9' \times 6.25') = 2,158^{\#}$$

$$\text{USE } \nabla W2 \text{ (2 STOPS)} \quad T_{EALLOW} = 3,425^{\#} \times 1.4 / 1.6 = 2,997^{\#}$$

$$(LEVEL 1) FE = 14,923^{\#} \times (12.5' / 63.67') = 2,930^{\#}$$

$$VE = 352 \text{ PIF}$$

$$\text{USE } \nabla W2 \quad V_{EALLOW} = 353 \text{ PIF}$$

HOLD DOWNS

$$TE = 2,110^{\#} \times 1.25 + 2,158^{\#} - \frac{1}{2}(30 \text{ PSF} \times 7' \times 6.25') - \frac{1}{2}(12 \text{ PSF} \times 9' \times 6.25') = 3,802^{\#}$$

$$\text{USE } \nabla W2 \text{ (2 STOPS)} \quad T_{EALLOW} = 5,920^{\#} \times 1.4 / 1.6 = 5,093^{\#}$$

GRID 1 (18'-9" FTAO)

$$(LEVEL 3) FE = 7,783\# \times (18.75' / 63.67') = 2,145\#$$


$$VE = 197\text{PIF}$$

$$\text{USE } \nabla W1 \quad VEA_{LOW} = 242\text{PIF}$$

HOLD DOWNS

$$TE = 1,030\# \times 1.75 - 1/2(25\text{PSF} \times 2' \times 9.33') - 1/2(12\text{PSF} \times 4.5' \times 9.33') = 800\#$$

$$\boxed{\text{USE MS37 W/2 STUDS}} \quad TE_{LOW} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$



$$(LEVEL 2) FE = 12,390\# \times (18.75' / 63.67') = 3,649\#$$

$$VE = 318\text{PIF}$$

$$\text{USE } \nabla W2 \quad VEA_{LOW} = 353\text{PIF}$$

HOLD DOWNS

$$TE = 1,752\# \times 1.75 + 800\# - 1/2(30\text{PSF} \times 8.8' \times 9.33') - 1/2(12\text{PSF} \times 9' \times 9.33') = 1,245\#$$

$$\boxed{\text{USE MS37 W/2 STUDS}} \quad TE_{LOW} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$

$$(LEVEL 1) FE = 14,973\# \times (18.75' / 63.67') = 4,395\#$$

$$VE = 394\text{PIF}$$

$$\text{USE } \nabla W3 \quad VEA_{LOW} = 456\text{PIF}$$

HOLD DOWNS

$$TE = 2,110\# \times 1.25 + 1,245\# - 1/2(30\text{PSF} \times 8.8' \times 9.33') - 1/2(12\text{PSF} \times 9' \times 9.33') = 2,138\#$$

$$\boxed{\text{USE HD04-SDS7.5 W/2 STUDS}} \quad TE_{LOW} = 3,295\# \times 1.4 / 1.6 = 2,874\#$$

GRID 2 (1047' FTAO)

$$(LEVEL 3) FE = 7,283 \# \times (10.58' / 63.67') = 1,210 \#$$


$$VE = 764 \text{ PIF}$$

$$USE \boxed{W2} \quad V_{EALLOW} = 353 \text{ PIF}$$

HOLD DOWNS

$$TE = 1,029 \# \times 1.75 - 1/2 (75 \text{ PIF} \times 2' \times 5.29') - 1/2 (125 \text{ PIF} \times 4.5' \times 5.29') = 1,011 \#$$

$$\boxed{USE \text{ MST37 w/ 7 STUFS}} \quad T_{EALLOW} = 2,140 \# \times 1.4 / 1.6 = 1,873 \#$$



$$(LEVEL 2) FE = 12,390 \# \times (10.58' / 63.67') = 2,059 \#$$

$$VE = 450 \text{ PIF}$$

$$USE \boxed{W3} \quad V_{EALLOW} = 450 \text{ PIF}$$

HOLD DOWNS

$$TE = 1,752 \# \times 1.25 + 1,011 \# - 1/2 (30 \text{ PIF} \times 7.3' \times 5.29') - 1/2 (125 \text{ PIF} \times 9' \times 5.29') = 2,336 \#$$

$$\boxed{USE \text{ MST48 w/ 2 STUFS}} \quad T_{EALLOW} = 3,425 \# \times 1.4 / 1.6 = 2,997 \#$$

$$(LEVEL 1) FE = 14,923 \# \times (10.58' / 63.67') = 2,480 \#$$

$$VE = 541 \text{ PIF}$$

$$USE \boxed{W4} \quad V_{EALLOW} = 595 \text{ PIF}$$

HOLD DOWNS

$$TE = 2,110 \# \times 1.75 + 2,336 \# - 1/2 (30 \text{ PIF} \times 7.3' \times 5.29') - 1/2 (125 \text{ PIF} \times 9' \times 5.29') = 4,109 \#$$


$$\boxed{USE \text{ HD08-50S25 w/ 7 STUFS}} \quad T_{EALLOW} = 5,220 \# \times 1.4 / 1.6 = 5,093 \#$$

GRID 4/5 (LEVEL 3) $F_E = 13,443^\#$

2 SEGMENTS

 $L = 25'-8"$ $h = 9'$

$$V_E = 13,443^\# / 55.33' = 243 \text{ PIF}$$

 $L = 29'-9"$ $LT = 55'-4"$ USE  $V_{EALLOW} = 353 \text{ PIF}$ HOLD DOWNS

$$T_E = 243 \text{ PIF} \times 9' \times 1.25 - \frac{1}{2} (25 \text{ PIF} \times 2' \times 12.93') - \frac{1}{2} (12 \text{ PIF} \times 4.5' \times 12.93') = 2,066^\#$$

USE 4ST48 W/2 STOPS


$$T_{EALLOW} = 3,425^\# \times 1.4 / 1.6 = 2,997^\#$$

GRID 4/5 (LEVEL 2) $F_E = 22,451^\#$

2 SEGMENTS

 $L = 55'-4"$ $h = 9'$

$$V_E = 22,451^\# / 55.33' = 406 \text{ PIF}$$

USE  $V_{EALLOW} = 456 \text{ PIF}$ HOLD DOWNS

$$T_E = 406 \text{ PIF} \times 9' \times 1.25 + 2,066^\# - \frac{1}{2} (30 \text{ PIF} \times 7.6' \times 12.93') - \frac{1}{2} (12 \text{ PIF} \times 9' \times 12.93') = 4,478^\#$$

USE 4ST60 W/2 STOPS


$$T_{EALLOW} = 5,405^\# \times 1.4 / 1.6 = 4,729^\#$$

GRID 4/5 (LEVEL 1) $F_E = 27,211^\#$

2 SEGMENTS

 $L = 55'-4"$ $h = 9'$

$$V_E = 27,211^\# / 55.33' = 492 \text{ PIF}$$

USE  $V_{EALLOW} = 595 \text{ PIF}$ HOLD DOWNS

$$T_E = 492 \text{ PIF} \times 9' \times 1.25 + 4,478^\# - \frac{1}{2} (30 \text{ PIF} \times 7.6' \times 12.93') - \frac{1}{2} (20 \text{ PIF} \times 9' \times 12.93') = 7,955^\#$$


USE 4DU14-30S25 W/3 STOPS

$$T_{EALLOW} = 9,260^\# \times 1.4 / 1.6 = 8,103^\#$$

GRID 7 (LEVEL 3) FE = 9,706#

2 SEGMENTS L = 28'-5" h = 9'
L = 29'-9"
LT = 56'-2"

$$VE = 9,706\# / 56.16' = 173\text{ PLF}$$

USE  VEA110W = 242 PLFHOLD DOWNS


$$TE = 173\text{ PLF} \times 9' \times 1.25 - 1/2(25\text{ PLF} \times 1' \times 14.21') - 1/2(8\text{ PLF} \times 9.5' \times 14.21') = 1,510\#$$

$$\boxed{\text{USE (2) HDU2-SDS2.5 W/2STOPS}} \quad TE_{110W} = 2,215\# \times 1.4 / 1.6 = 1,939\#$$

GRID 7 (LEVEL 2) FE = 16,945#

2 SEGMENTS LT = 56'-2" h = 9'

$$VE = 16,945\# / 56.16' = 302\text{ PLF}$$

USE  VEA110W = 353 PLFHOLD DOWNS


$$TE = 302\text{ PLF} \times 9' \times 1.25 + 1,510\# - 1/2(30\text{ PLF} \times 6.95' \times 14.21') - 1/2(8\text{ PLF} \times 9' \times 14.21') = 2,911\#$$

$$\boxed{\text{USE (2) HDU5-SDS2.5 W/2STOPS}} \quad TE_{110W} = 4,340\# \times 1.4 / 1.6 = 3,793\#$$

GRID 7 (LEVEL 1) FE = 20,536#

2 SEGMENTS LT = 56'-2" h = 9'

$$VE = 20,536\# / 56.16' = 366\text{ PLF}$$

USE  VEA110W = 456 PLFHOLD DOWNS


$$TE = 366\text{ PLF} \times 9' \times 1.25 + 2,911\# - 1/2(30\text{ PLF} \times 6.95' \times 14.21') - 1/2(8\text{ PLF} \times 9' \times 14.21') = 5,032\#$$

$$\boxed{\text{USE (1) HDU8-SDS2.5 W/2STOPS}} \quad TE_{110W} = 5,820\# \times 1.4 / 1.6 = 5,093\#$$

GRID 9/10 (LEVEL 3) FE=9,991#

2 SEGMENTS L=29'-4" h=9'
L=29'-4"
LT=58'-8"

$$VE = 9,991\# / 58.67' = 170\text{PIF}$$

USE  VEAICOL=242PIFHOLD DOWNS


$$TE = 170\text{PIF} \times 9 \times 1.25 - 1/2(25\text{PIF} \times 2 \times 14.67') - 1/2(120\text{PIF} \times 4.5 \times 14.67') = 1,153\#$$

USE MST37 w/2STOPS

GRID 9/10 (LEVEL 2) FE=16,532#

2 SEGMENTS L=58'-8" h=9'

$$VE = 16,532\# / 58.67' = 282\text{PIF}$$

USE  VEAICOL=353PIFHOLD DOWNS


$$TE = 282\text{PIF} \times 9 \times 1.25 + 1,153\# - 1/2(30\text{PIF} \times 4 \times 14.67') - 1/2(120\text{PIF} \times 9 \times 14.67') = 2,651\#$$

USE MST43 w/2STOPS TEAICOL=3,425# $1/4/1.6 = 2,997\#$

GRID 9/10 (LEVEL 1) FE=20,051#

2 SEGMENTS L=58'-8" h=9'

$$VE = 20,051\# / 58.67' = 342\text{PIF}$$

USE  VEAICOL=353PIFHOLD DOWNS

$$TE = 342\text{PIF} \times 9 \times 1.25 + 2,651\# - 1/2(30\text{PIF} \times 4 \times 14.67') - 1/2(120\text{PIF} \times 9 \times 14.67') = 4,323\#$$

USE MST48-SDS7.5 w/2STOPS TEAICOL=5,820# $1/4/1.6 = 5,093\#$

GRID B (11'9" FTAO)

(LEVEL 3) $FE = 7,487\# \times (11.75' / 63.58') = 1,384\#$


$VE = 353 \text{ pif}$

USE W3 $VE_{allow} = 456 \text{ pif}$

HOLD DOWNS

$TE = 1,060\# \times 1.25 - 1/2(250\# \times 2' \times 5.88') - 1/2(200\# \times 4.5' \times 5.88') = 1,019\#$

USE MST37 W / 2 STOPS $TE_{allow} = 2,140\# \times 1.4 / 1.6 = 1,873\#$



(LEVEL 2) $FE = 12,798\# \times (11.75' / 63.58') = 23,65\#$

$VE = 601 \text{ pif}$

USE W8 $VE_{allow} = 770 \text{ pif}$

HOLD DOWNS

$TE = 1,811\# \times 1.25 + 1,019\# - 1/2(300\# \times 7' \times 5.88') - 1/2(200\# \times 9' \times 5.88') = 2,348\#$

USE MST48 W / 2 STOPS $TE_{allow} = 3,425\# \times 1.4 / 1.6 = 2,997\#$

(LEVEL 1) $FE = 15,434\# \times (11.75' / 63.58') = 2,852\#$

$VE = 728 \text{ pif}$

USE W8 $VE_{allow} = 770 \text{ pif}$

HOLD DOWNS

$TE = 7,185\# \times 1.25 + 2,348\# - 1/2(300\# \times 7' \times 5.88') - 1/2(200\# \times 9' \times 5.88') = 4,144\#$

USE HDOB-SDS25 W / 2 STOPS $TE_{allow} = 5,820\# \times 1.4 / 1.6 = 5,093\#$

GRID 13 (11'-7" FTAD)

$$(LEVEL 3) FE = 7,487\# \times (11.58' / 63.58') = 1,364\#$$

$$VE = 177\text{PIR}$$

$$\text{USE } \boxed{W1} \quad VEA_{LOW} = 242\text{PIR}$$

HOLD DOWNS

$$TE = 1,060\# \times 1.25 - 1/2(25\text{PIR} \times 2' \times 5.79') - 1/2(120\text{PIR} \times 4.5' \times 5.79') = 1,024\#$$

$$\boxed{\text{USE MST37 W/ 2 STUFS}} \quad TE_{ALLOW} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$

$$(LEVEL 2) FE = 17,798\# \times (11.58' / 63.58') = 2,331\#$$

$$VE = 302\text{PIR}$$

$$\text{USE } \boxed{W2} \quad VEA_{LOW} = 353\text{PIR}$$

HOLD DOWNS

$$TE = 1,812\# \times 1.25 + 1,024\# - 1/2(30\text{PIR} \times 7.5' \times 5.79') - 1/2(120\text{PIR} \times 9' \times 5.79') = 2,325\#$$

$$\boxed{\text{USE MST48 W/ 2 STUFS}} \quad TE_{ALLOW} = 3,425\# \times 1.4 / 1.6 = 2,997\#$$

$$(LEVEL 1) FE = 15,434\# \times (11.58' / 63.58') = 2,811\#$$

$$VE = 364\text{PIR}$$

$$\text{USE } \boxed{W3} \quad VEA_{LOW} = 450\text{PIR}$$

HOLD DOWNS

$$TE = 2,185\# \times 1.25 + 2,325\# - 1/2(30\text{PIR} \times 7.5' \times 5.79') - 1/2(120\text{PIR} \times 9' \times 5.79') = 4,092\#$$

$$\boxed{\text{USE HDUB-SDS 25 W/ 2 STUFS}} \quad TE_{ALLOW} = 5,920\# \times 1.4 / 1.6 = 5,093\#$$

GRID 13 (2'-1" FRAO)

$$(LEVEL 3) \quad FE = 7,487\# \times (22.08' / 63.58') = 2,600\#$$


$$VE = 212\text{ PLF}$$

$$\text{USE } \boxed{W1} \quad VEA_{allow} = 2412\text{ PLF}$$

HOLD DOWNS

$$TE = 6060\# \times 1.25 - 1/2(750\# \times 2' \times 11.04') - 1/2(12\text{ PSF} \times 4.5' \times 11.04') = 751\#$$

$$\boxed{\text{USE } 4\text{ ST } 37 \text{ w/ 2 STUDS}} \quad TE_{allow} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$



$$(LEVEL 2) \quad FE = 12,798\# \times (22.08' / 63.58') = 4,444\#$$

$$VE = 362\text{ PLF}$$

$$\text{USE } \boxed{W3} \quad VEA_{allow} = 456\text{ PLF}$$

HOLD DOWNS

$$TE = 1,811\# \times 1.25 + 751\# - 1/2(30\text{ PSF} \times 5.1' \times 11.04') - 1/2(12\text{ PSF} \times 9' \times 11.04') = 1,574\#$$

$$\boxed{\text{USE } 4\text{ ST } 37 \text{ w/ 2 STUDS}} \quad TE_{allow} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$

$$(LEVEL 1) \quad FE = 15,434\# \times (22.08' / 63.58') = 5,360\#$$

$$VE = 437\text{ PLF}$$

$$\text{USE } \boxed{W3} \quad VEA_{allow} = 456\text{ PLF}$$

HOLD DOWNS

$$TE = 2,187\# \times 1.25 + 1,574\# - 1/2(30\text{ PSF} \times 5.1' \times 11.04') - 1/2(12\text{ PSF} \times 9' \times 11.04') = 2,865\#$$

$$\boxed{\text{USE } HDU 4-S952.5 \text{ w/ 2 STUDS}} \quad TE_{allow} = 3,285\# \times 1.4 / 1.6 = 2,874\#$$

GRID B (8'-2" FT40)

$$(LEVEL 3) \quad FE = 7,487\# \times (18.16' / 63.58') = 2,138\#$$


$$VE = 353\text{PIF}$$

$$\text{USE } \triangle W3 \quad VE_{allow} = 950\text{PIF}$$

HOLD DOWNS

$$TE = 1,060\# \times 1.25 - \frac{1}{2}(30\text{PSF} \times 2' \times 9.09') - \frac{1}{2}(12\text{PSF} \times 4.5' \times 9.09') = 853\#$$

$$\boxed{\text{USE MST37 w/ 2 STUDS}} \quad TE_{allow} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$



$$(LEVEL 2) \quad FE = 12,798\# \times (18.16' / 63.58') = 3,655\#$$

$$VE = 604\text{PIF}$$

$$\text{USE } \triangle W8 \quad VE_{allow} = 770\text{PIF}$$

HOLD DOWNS

$$TE = 1,911\# \times 1.25 + 853\# - \frac{1}{2}(30\text{PSF} \times 5.9' \times 9.09') - \frac{1}{2}(12\text{PSF} \times 9' \times 9.09') = 1,823\#$$

$$\boxed{\text{USE MST37 w/ 2 STUDS}} \quad TE_{allow} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$

$$(LEVEL 1) \quad FE = 15,434\# \times (18.16' / 63.58') = 4,408\#$$

$$VE = 728\text{PIF}$$

$$\text{USE } \triangle W8 \quad VE_{allow} = 770\text{PIF}$$

HOLD DOWNS

$$TE = 2,125\# \times 1.25 + 1,823\# - \frac{1}{2}(30\text{PSF} \times 5.9' \times 9.09') - \frac{1}{2}(12\text{PSF} \times 9' \times 9.09') = 3,260\#$$

$$\boxed{\text{USE HD05-SPS7.5 w/ 2 STUDS}} \quad TE_{allow} = 4,340\# \times 1.4 / 1.6 = 3,898\#$$

GRIOB (14'-7" FTAO)

$$(LEVEL 3) FE = 11,376 \# \times (14.58' / 93.67') = 1,771 \#$$


$$VE = 199 \text{ PLF}$$

$$USE \boxed{W1} \quad VE_{ALLOW} = 242 \text{ PLF}$$

HOLD DOWNS

$$TE = 1,093 \# \times 1.25 - 1/2 (25 \text{ PLF} \times 16.5' \times 7.29') - 1/2 (12 \text{ PLF} \times 4.5' \times 7.29') = -344 \#$$

SO NO HD'S REQ'D



$$(LEVEL 2) FE = 19,009 \# \times (14.58' / 93.67') = 2,959 \#$$

$$VE = 332 \text{ PLF}$$

$$USE \boxed{W2} \quad VE_{ALLOW} = 353 \text{ PLF}$$

HOLD DOWNS

$$TE = 1,827 \# \times 1.25 - 344 \# - 1/2 (12 \text{ PLF} \times 9' \times 7.29') = 1,546 \#$$

$$\boxed{USE \text{ A3637 W/2 STUOPS}} \quad TE_{ALLOW} = 2,140 \# \times 1.4 / 1.6 = 1,873 \#$$

$$(LEVEL 1) FE = 22,796 \# \times (14.58' / 93.67') = 3,548 \#$$

$$VE = 398 \text{ PLF}$$

$$USE \boxed{W3} \quad VE_{ALLOW} = 456 \text{ PLF}$$

HOLD DOWNS

$$TE = 3,120 \# \times 1.25 + 1,546 \# - 1/2 (20 \text{ PLF} \times 9' \times 7.29') = 3,890 \#$$

$$\boxed{USE \text{ HDUB-SDS2.5 W/2 STUOPS}} \quad TE_{ALLOW} = 5,820 \# \times 1.4 / 1.6 = 5,093 \#$$

GRID C (25'6" FT 40)


(LEVEL 3) $FE = 11,376\# \times (25.5'/93.67') = 3,096\#$

$VE = 208\text{PIF}$

USE W1 $VE_{ALLOW} = 242\text{PIF}$

HOLD DOWNS

$TE = 1,093\# \times 1.75 - 1/2(250\# \times 16.9' \times 12.75') - 1/2(120\# \times 4.5' \times 12.75') = -1,671\#$
 SO NO HD'S REQ'D



(LEVEL 2) $FE = 19,009\# \times (25.5'/93.67') = 5,175\#$

$VE = 348\text{PIF}$

USE W2 $VE_{ALLOW} = 353\text{PIF}$

HOLD DOWNS

$TE = 1,826\# \times 1.75 - 1,671\# - 1/2(170\# \times 9' \times 12.75') = -77\#$
 SO NO HD'S REQ'D

(LEVEL 1) $FE = 22,796\# \times (25.5'/93.67') = 6,206\#$

$VE = 418\text{PIF}$

USE W3 $VE_{ALLOW} = 456\text{PIF}$

HOLD DOWNS

$TE = 2,190\# \times 1.75 - 77\# - 1/2(120\# \times 9' \times 12.75') = 1,972\#$

USE HDOU4-SDS25 W/2 STOPS $TE_{ALLOW} = 3,285\# \times 1.4/1.6 = 2,879\#$

GRID A (0'-7" FTAO)

(LEVEL 3) $F_{E2} = 11,376\# \times (10.58' / 93.67') = 1,285\#$


$V_E = 281\text{PIK}$

USE $\nabla W2$ $V_{EALLOW} = 353\text{PIK}$

HOLD DOWNS

$T_E = 1,098\# \times 1.25 - 1/2 (17\text{PSF} \times 17.4' \times 5.29') - 1/2 (17\text{PSF} \times 4.5' \times 5.29') = 79\#$

USE $MST37W / 2 \text{ STOPS}$ $T_{EALLOW} = 2,140\# \times 1.4 / 1.6 = 1,973\#$



(LEVEL 2) $F_{E2} = 19,009\# \times (10.58' / 93.67') = 2,147\#$

$V_E = 469\text{PIK}$

USE $\nabla W4$ $V_{EALLOW} = 595\text{PIK}$

HOLD DOWNS

$T_E = 1,826\# \times 1.25 + 79\# - 1/2 (17\text{PSF} \times 9' \times 5.29') = 2,076\#$

USE $MST40W / 2 \text{ STOPS}$ $T_{EALLOW} = 3,425\# \times 1.4 / 1.6 = 2,997\#$

GRID A (21'-1" FTAO)

(LEVEL 1) $F_{E2} = 22,796\# \times (21.08' / 93.67') = 5,130\#$

$V_E = 589\text{PIK}$

USE $\nabla W4$ $V_{EALLOW} = 595\text{PIK}$


HOLD DOWNS

STACKED $T_E = 2,188\# \times 1.25 + 2,076\# - 1/2 (17\text{PSF} \times 9' \times 5.29') = 4,525\#$

USE $HDO8-SDS2.5W / 2 \text{ STOPS}$ $T_{EALLOW} = 5,820\# \times 1.4 / 1.6 = 5,093\#$

UNSTACKED $T_E = 2,188\# \times 1.25 - 1/2 (17\text{PSF} \times 9' \times 5.29') = 2,449\#$

USE $HDO4-SDS2.5W / 2 \text{ STOPS}$ $T_{EALLOW} = 3,285\# \times 1.4 / 1.6 = 2,874\#$



GRIDA (10'-6" FTAD)

$$(LEVEL 3) FE = 11,376\# \times (10.5' / 93.67') = 1,275\#$$

$$VE = 283 \text{ PLF}$$


$$USE \text{ W12 } V_{EALLOW} = 353 \text{ PLF}$$

HOLD DOWNS

$$TE = 1,093\# \times 1.25 - 1/2(750\text{ LF} \times 17.6' \times 5.25') - 1/2(12\text{ PLF} \times 4.5' \times 5.25') = 70\#$$

USE MST37 w/ 2 STUFS

$$T_{EALLOW} = 2,140\# \times 1.4 / 1.6 = 1,873\#$$



$$(LEVEL 2) FE = 19,009\# \times (10.5' / 93.67') = 2,131\#$$

$$VE = 474 \text{ PLF}$$

$$USE \text{ W14 } V_{EALLOW} = 595 \text{ PLF}$$

HOLD DOWNS

$$TE = 1,827\# \times 1.25 + 70\# - 1/2(12\text{ PLF} \times 9' \times 5.25') = 2,070\#$$


USE MSTC48B3 w/ 2 STUFS

$$T_{EALLOW} = 3,900\# \times 0.85 \times 1.4 / 1.6 = 2,900\#$$

GRID B (20'-9" FTAD)

(LEVEL 3) $FE = 11,376\# \times (20.75' / 93.67') = 2,520\#$


$VE = 337\text{PIF}$

USE  $VE_{allow} = 353\text{PIF}$

HOLD DOWNS


$TE = 1,093\# \times 1.25 - 1/2(25\text{PSF} \times 13.6' \times 10.38') - 1/2(12\text{PSF} \times 4.5' \times 10.38') = -678\#$

USE



(LEVEL 2) $FE = 19,009\# \times (20.75' / 93.67') = 4,211\#$

$VE = 564\text{PIF}$

USE  $VE_{allow} = 595\text{PIF}$

HOLD DOWNS


$TE = 1,826\# \times 1.25 - 678\# - 1/2(12\text{PSF} \times 9' \times 10.38') = 1,044\#$

USE M537. W12 STUDS $TE_{allow} = 2,140\# \times 1.1 / 1.6 = 1,473\#$

(LEVEL 1)

$FE = 22,796\# \times (20.75' / 93.67') = 5,050\#$


$VE = 538\text{PIF}$

USE  $VE_{allow} = 595\text{PIF}$

HOLD DOWNS

$TE = 2,190\# \times 1.25 + 1,044\# - 1/2(12\text{PSF} \times 9' \times 10.38') = 3,221\#$

USE HDO5-SDS25 W12 STUDS $TE_{allow} = 4,340\# \times 1.1 / 1.6 = 3,798\#$



GRIDA (11.9" FTAO)

$$(LEVEL 3) FE = 11,376 \# \times (11.75' / 93.67') = 1,427 \#$$


$$VE = 250 \text{ P.I.F.}$$

$$\text{USE } \triangle W2 \quad VE_{allow} = 353 \text{ P.I.F.}$$

HOLD DOWNS

$$TE = 1,098 \# \times 1.25 - 1/2 (250 \text{ P.F.} \times 16.5' \times 5.88') - 1/2 (173 \text{ P.F.} \times 4.5' \times 5.88') = 1 \#$$

$$\text{USE MST 37 W/ 2 STUDS}$$



$$(LEVEL 2) FE = 19,009 \# \times (11.75' / 93.67') = 2,384 \#$$

$$VE = 418 \text{ P.I.F.}$$

$$\text{USE } \triangle W3 \quad VE_{allow} = 456 \text{ P.I.F.}$$

HOLD DOWNS

$$TE = 1,834 \# \times 1.25 + 1 \# - 1/2 (12 \text{ P.F.} \times 9' \times 5.88') = 1,976 \#$$

$$\text{USE MST 48 W/ 2 STUDS} \quad TE_{allow} = 3,425 \# \times 1.0 / 1.6 = 2,141 \#$$

$$(LEVEL 1) FE = 22,796 \# \times (11.75' / 93.67') = 2,860 \#$$

$$VE = 502 \text{ P.I.F.}$$

$$\text{USE } \triangle W4 \quad VE_{allow} = 595 \text{ P.I.F.}$$


HOLD DOWNS

$$TE = 2,200 \# \times 1.25 + 1,976 \# - 1/2 (12 \text{ P.F.} \times 9' \times 5.88') = 4,408 \#$$

$$\text{USE HDUB-SDS 2.5 W/ 2 STUDS} \quad TE_{allow} = 5,920 \# \times 1.0 / 1.6 = 3,700 \#$$

GRID (LEVEL 3) $FE = 24,140\#$ 6 SEGMENTS $L = 30'-4"$ $h = 9'$

$$V_E = 24,140\# / 117.25' = 206\text{PIF}$$

USE  $V_{E\text{allow}} = 242\text{PIF}$

HOLD DOWNS

$$L = 14'-3"$$

$$L = 24'-8"$$

$$L = 13'-10"$$

$$L = 15'-7"$$

$$L = 18'-7"$$

$$L_T = 117'-3"$$

$$L = 30'-4" \quad TE = 206\text{PIF} \times 9' \times 1.25 - 1/2(25\text{PSF} \times 8.9' \times 15.16') - 1/2(8\text{PSF} \times 4.5' \times 15.16') = 358\#$$

USE H002-S0525 W/2STUDS $TE_{\text{allow}} = 2,215^2 \times 1.6 / 1.6 = 1,938\#$

$$L = 14'-3" \quad TE = 206\text{PIF} \times 9' \times 1.25 - 1/2(25\text{PSF} \times 26' \times 7.13') - 1/2(12\text{PSF} \times 4.5' \times 15.16') = -409\#$$

SO NO HD'S REQ'D

$$L = 24'-8" \quad TE = 206\text{PIF} \times 9' \times 1.25 - 1/2(25\text{PSF} \times 14.8' \times 12.33') - 1/2(8\text{PSF} \times 4.5' \times 12.33') = -956\#$$

SO NO HD'S REQ'D

$$L = 13'-10" \quad TE = 206\text{PIF} \times 9' \times 1.25 - 1/2(25\text{PSF} \times 15.3' \times 6.92') - 1/2(8\text{PSF} \times 4.5' \times 6.92') = 870\#$$

USE H002-S0525 W/2STUDS $TE_{\text{allow}} = 2,215^2 \times 1.6 / 1.6 = 1,938\#$

$$L = 15'-7" \quad TE = 206\text{PIF} \times 9' \times 1.25 - 1/2(25\text{PSF} \times 28' \times 7.8') - 1/2(12\text{PSF} \times 4.5' \times 7.8') = -623\#$$

SO NO HD'S REQ'D

$$L = 18'-7" \quad TE = 206\text{PIF} \times 9' \times 1.25 - 1/2(25\text{PSF} \times 17.4' \times 9.29') - 1/2(8\text{PSF} \times 4.5' \times 9.29') = 130\#$$

USE H002-S0525 W/2STUDS $TE_{\text{allow}} = 2,215^2 \times 1.4 / 1.6 = 1,938\#$