

Farenhyt

IFP-2000/RPS-2000 Calculations
Version 11.03.09

Global Project Values:

Project Name: WASF PAVILION ELEV MOD

Project ID: KL5758

Prepared By: WSFP

Date: 3/18/2025

Standby Hours: 24

Alarm Mins: 5

Derating Factor: 1.2

Voltage Drop Warning

Threshold % : 10

Panel ID: IFP-2000/RPS-2000

Location: ELECTRICAL ROOM

Model: IFP-2000 Add. Fire Alarm Control Panel

Volts: 24 VDC

Max NAC Current: 3.0 Amps

Max Panel Current: 9.0 Amps

Part.#	Description	Qty	Current Draw		Wire AWG & Type	Ohms Per 1000 Ft.	Length(ft) One-Way	Actual Ohms	Volts @ EOL	%Drop
			Standby	Alarm						
2000	IFP/RPS-2000 Panel	1	0.290	0.530	MA					
SD500-AIM	Addr. Input Module	20	0.011	0.011						
SD500-MIM	Mini-Input Module		0.000	0.000						
SD500-ARM	Addr. Relay Module	3	0.002	0.002						
SD500-PS	Addr. Pull Station	1	0.001	0.001						
SD500-ANM	Addr. Notification Mod.		0.000	0.000						
SD500-LED	Addr. LED Module		0.000	0.000						
SD500-SDM	Addr. Smoke Det. Mod.		0.000	0.000						
SD505-AIS	Addr. Ion Smoke Det.		0.000	0.000						
SD505-APS	Addr. Photo Smoke Det.	4	0.002	0.002						
SD505-AHS	Addr. Heat Detector	71	0.039	0.039						
SD505-DUCT	Addr. Duct Detector		0.000	0.000						
SD505-DUCTR	Addr. Duct w/Relay		0.000	0.000						
SD505-6IB	Addr. Det. Iso. Base		0.000	0.000						
SD505-6RB	Addr. Det. Relay Base		0.000	0.000						
SD505-6SB	Addr. Det. Sounder Base		0.000	0.000						
SD500-LIM	Line Isolator Module		0.000	0.000						
5815XL	SLC Expander		0.000	0.000						
RA-2000	LCD Remote Annunc	1	0.025	0.050						
5824	Serial/Parallel Module		0.000	0.000						
5496	Power Expander		0.000	0.000						
RPS-1000	Power Expander		0.000	0.000						
5865-4	LED Annunciator (4G)		0.000	0.000						
5865-3	LED Annunciator (3G)		0.000	0.000						
5880	LED Driver Module		0.000	0.000						
5883	Relay Module		0.000	0.000						
IFP-RPT-UTP	Copper Wire Repeater		0.000	0.000						
IFP-RPT-FO	Fiber Optic Repeater		0.000	0.000						
PGM-I/O #1	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #2	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #3	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #4	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #5	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #6	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #7	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
PGM-I/O #8	Notification Appl Circuit		0.000	0.000	#12 Solid	1.59		0.00	20.40	0.00%
Total Standby Current (Amps)			0.369	0.634	Total Alarm Current (Amps)					
Standby Time In Hours			24	0.083	Alarm Time In Minutes / 60 (5 Mins)					
Total Standby AH Required			8.867	0.053	Total Alarm AH Required					
Total Combined AH Required			8.92							
Multiply By The Derating Factor			1.20							
Minimum Battery AmpHours Required			10.70							

Command Shortcuts

Configure Circuits

Print Page