

### SITE SPECIFICATIONS

SITE DATA: ASSESSORS/TAX PARCEL NUMBER(S): 2105200150 PARCEL/SITE SIZE: 80.436 SF / 1.85 ACRES SECTION/TOWNSHIP/RANGE: 26/20/04 DEVELOPMENT JURISDICTION: CITY OF PUYALLUP SITE ADDRESS: 2401 INTER AVE SE PUYALLUP, WA 98372 ZONING: LIMITED MANUFACTURING DENSITY: X PRESENT USE: LIMITED MANUFACTURING SENSITIVE AREAS: NO WETLANDS: UNDER CURRENT REVIEW FLOOD PLAIN HAZARD AREAS: NO EROSION HAZARD AREAS: NO LANDSLIDE HAZARD AREAS: NO COAL MINE HAZARD AREAS: NO SEISMIC HAZARD AREAS: NO CREEKS/STREAMS: NO LAKES: NO STEEP SLOPES(10% OR GREATER): NO VOLCANIC: NO WILDLIFE HABITAT: NO SHORELINE CLASSIFICATION: NO NORTH: LIMITED MANUFACTURING SOUTH: LIMITED MANUFACTURING EAST: LIMITED MANUFACTURING WEST: LIMITED MANUFACTURING

#### VERIFICATION NOTE

ALL EXISTING UTILITIES IN THE CONSTRUCTION AREA SHALL BE IDENTIFIED AND VERIFIED FOR DEPTH AND LOCATION PRIOR TO ANY CONSTRUCTION ACTIVITIES SO TO IDENTIFY ANY POTENTIAL CONFLICTS WITH PROPOSED CONSTRICTION. CONTACT PROJECT ENGINEER IMMEDIATELY IF ANY CONFLICTS ARE IDENTIFIED.

PRIOR TO ANY CONSTRUCTION ACTIVITIES, VERIFY EXISTING TOPOGRAPHY IS CONSISTENT WITH WHAT IS SHOWN ON PLANS AND IF THERE ARE ANY POTENTIAL CONFLICTS WITH PROPOSED CONSTRUCTION ACTIVITIES. CONTACT PROJECT ENGINEER IMMEDIATELY IF ANY CONFLICTS ARE IDENTIFIED.

#### FIRE SPRINKLER NOTE

FIRE LINE SHALL BE SIZED BY A LICENSED FIRE PROTECTION ENGINEER. A SEPARATE, DETAILED PLAN SHALL BE APPROVED BY THE FIRE MARSHALL AND INSTALLED BY A WASHINGTON CERTIFIED LEVEL "U" CONTRACTOR IN ACCORDANCE WITH WAC 212-80-010. A POST INDICATOR VALVE SHALL BE INSTALLED ON THE SPRINKLER LINE TO ISOLATE THE FIRE SYSTEM FROM THE WATER SYSTEM WHEN REQUIRED.

#### FILL SPECIFICATIONS

FILL MATERIAL SHALL NOT CONTAIN PETROLEUM PRODUCTS, OR SUBSTANCES WHICH ARE HAZARDOUS, DANGEROUS, TOXIC, OR WHICH OTHERWISE VIOLATE ANY STATE, FEDERAL. OR LOCAL LAW, ORDINANCE, CODE, REGULATION, RULE, ORDER, OR STANDARD.

#### **TOPOGRAPHIC NOTE**

THE EXISTING CULTURAL AND TOPOGRAPHICAL DATA SHOWN ON THESE DRAWINGS HAS BEEN PREPARED, IN PART, BASED UPON INFORMATION FURNISHED BY OTHERS. WHILE THIS INFORMATION IS BELIEVED TO BE RELIABLE, MCINNIS ENGINEERING CANNOT ENSURE ACCURACY AND THUS IS NOT RESPONSIBLE FOR THE ACCURACY OF THAT INFORMATION OR FOR ANY ERRORS OR OMISSIONS WHICH MAY HAVE BEEN INCORPORATED INTO THESE DRAWINGS AS A RESULT.

#### PROJECT BENCHMARK

#### **ELEVATION: 60.21 FEET**

DESCRIPTION: SOUTHWEST DEED CORNER BEING A REBAR WITH PLASTIC CAP STAMPED "APEX LS 41278/45792" AT SURFACE

## SECONDARY PROJECT BENCHMARK

ELEVATION:61.41 FEET

DESCRIPTION:

SOUTHEAST DEED CORNER BEING A REBAR WITH PLASTIC CAP STAMPED "APEX LS 41278/45792" AT SURFACE

#### **METHODOLOGY:**

THIS SURVEY WAS PERFORMED VIA CONVENTIONAL AND RADIAL TRAVERSE METHODS WITH A TOPCON PS103 3" SECOND TOTAL STATION AND A GEOMAX ZOOM 95 3" SECOND TOTAL STATION TOGETHER WITH RTK NETWORK/ROVER TECHNIQUES UTILIZING TOPCON GR-3 RECEIVER AND CARLSON GRx7 RECIEVER AND MEET OR EXCEED ACCURACY REQUIREMENTS CONTAINED IN WAC 332.130.090



#### LEGAL DESCRIPTION

PER BOUNDARY LINE RESOLUTION PURSUANT TO RCW 58.04.007 AND QUIT CLAIM RECORDED UNDER PIERCE COUNTY AFN 201705310130

LOT 8, ACKERSON'S 2ND ADDITION TO PUYALLUP, ACCORDING TO PLAT RECORDED IN BOOK 80F PLATS, AT PAGE 25, PIERCE COUNTY, WASHINGTON; SITUATE IN THE CITY OF PUYALLUP, COUNTY OF PIERCE, STATE OF WASHINGTON.

EXCEPT THAT OF LOT 8, ACKERSON'S 2ND ADDITION TO PUYALLUP, ACCORDING TO PLAT RECORDED IN BOOK 80F PLATS, AT PAGE 25, PIERCE COUNTY, WASHINGTON LAYING EASTERLY OF THE FOLLOWING DESCRIBED IINE

BEGINNING AT THE SOUTHEAST CORNER OF SAID LOT 8 THENCE NORTH 0° 18' 18" EAST ALONG THE EAST LINE OF LOT 8 A DISTANCE OF 146.28 FEET TO THE INTERSECTION OF THE CYCLONE FENCE AS IT EXISTS AS OF FEBRUARY 17, 2017;

THENCE NORTH 0° 43' 59" WEST ALONG THE EXISTING CYCLONE FENCE A DISTANCE OF 202.91 FEET TO A POINT 5.00 FEET SOUTHERLY OF THE SOUTH FACE OF THE METAL BUILDING AS IT EXISTS AS OF FEBRUARY 17, 2017; THENCE NORTH 89° 46' 41" WEST PARALLEL WITH THE EXISTING METAL BUILDING A DISTANCE OF 4.65 FEET TO A PONT 5 FEET FROM THE WESTERLY FACE OF THE EXITING METAL BUILDING;

THENCE NORTH 0° 01' 42" EAST PARALLEL WITH THE WESTERLY FACE OF THE EXISTING METAL BUILDING A DISTANCE OF 56.50 FEET TO A POINT ON THE NORTHERLY LINE OF SAID LOT 8, SAID POINT LAYS SOUTH 89° 59' 48" WEST AND 7.85 FEET DISTANT FROM THE NORTHEAST CORNER OF SAID LOT 8; AREA OF EXCEPTION BEING 753 SQUARE FEET MORE OR LESS. CONTAINING 80436 SQUARE FEET (1.85 ACRES) MORE OR LESS.

# **2401 INTER COVER SHEET**

A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA

## SHEET INDEX

SHEET NUMBER	SHEET NAME	DESCRIPTION
1	C-1	COVER SHEET
2	C-2	SITE PLAN AND HORIZONTAL CONTROL
3	C-3	TESC PLAN
4	C-4	TESC NOTES AND DETAILS
5	C-5	GRADING PLAN
6	C-6	FRONTAGE IMPROVEMENT PLAN
7	C-7	STREET LIGHTING PLAN
8-11	C8-C12	NOTES AND DETAILS

## **EXISTING LEGEND**

×t+.+	EXISTING SURFACE SPOT ELEVATION		BUILDING		
	EXISTING STORM DRAIN CATCH BASIN		FLOW LINE CURB		PROPERT
S	SANITARY SEWER MANHOLE		EXTRUDED CURB	— — —	SETBACK
$\blacksquare$	EXISTING WATER METER		STANDARD CURB		
$\bowtie$	EXISTING WATER VALVE		EDGE OF CONCRETE		PROPOSE
Q	EXISTING FIRE HYDRANT		EDGE OF GRAVEL		PROPOSE
	EXISTING IRRIGATION CONTROL VALVE	SS(REC)	EXISTING SANITARY SEWER LINE RECORD POSITION		
Ρ	EXISTING POWER METER	SD	EXISTING STORMDRAIN LINE		PROPOSE
J.	EXISTING UTILITY POLE	W	EXISTING WATER LINE		
$\boxtimes$	EXISTING UTILITY JUNCTION BOX	T	EXISTING SUBTERRANEAN TELECOMMUNICATIONS LINE		PROPOSE
T ×	EXISTING SIGN AS NOTED	OHU	EXISTING OVERHEAD UTILITY LINE		PROPOSE
			EXISTING CHAINLINK FENCE AS NOTED		
P		\\\/I	WETLAND MARGIN	SD	STORM DI
C)			EDGE EXISTING ASPHALT PAVING	x	PROPOSE
- ų			EXISTING CONCRETE SURFACE		
(481)			EXISTING ASPHALT SURFACE		CATCH BA
(481)				58	PROPOSE
тор			EXISTING GRAVEL SURFACE		
тое —	EXISTING TOE OF SLOPE		BUILDING HATCH		



ngin

cinni

U U

[T]

Z

5

ш

Ш

S

**VE** 

Ó

C

NTER

40

N

# NOTE: THIS APPROVAL IS VOID AFTER 180 DAYS FROM APPROVAL

THE CITY WILL NOT BE RESPONSIBLE FOR ERRORS AND/OR OMISSIONS ON THESE PLANS. FIELD CONDITIONS MAY DICTATE CHANGES TO THESE PLANS AS DETERMINED BY THE

DEVELOPMENT ENGINEERING MANAGER.

**OWNER/CLIENT:** 

2401 INTER INC BOX P.O.252 PUYALLUP, WA 98371 (253) 841-1388 MIKE@EJPOULTRY.COM

**CIVIL ENGINEER** MCINNIS ENGINEERING 202 E 34TH ST **TACOMA, WA 98404** CONTACT: WILL MCINNIS OFFICE: 253-414-1992

**SURVEYOR** 

MCINNIS ENGINEERING 202 E 34TH ST TACOMA, WA 98404 CONTACT: LARRY WALKER OFFICE: 253-414-1992

#### **PROJECT SPECIFICATIONS** PARCEL NO: 2105200150 ADDRESS: 2401 INTER AVE SE PUYALLUP, WA 98372 ZONING: LIMITED MANUFACTURING PARCEL SIZE: 1.85 AC PROPOSED LOT USE: LM NO. OF DWELLING UNITS: 0 DOMESTIC WATER SOURCE: PUBLIC SEWAGE DISPOSAL SYSTEM: PUBLIC EXISTING PARKING TOTAL: 0 **PROPOSED PARKING TOTAL: 3**

# **BASIS OF BEARINGS**

HELD BEARING OF SOUTH 89° 59 57 " EAST ALONG THE CENTER LINE OF INTER AVENUE AS SHOWN ON RECORD OF SURVEY FOR BOUNDARY LINE RESOLUTION UNDER PIERCE COUNTY AUDITOR'S FILE NUMBER 201705315001

# **VERTICAL DATUM**

NAVD 88.

THE BENCHMARKS SHOWN HEREON WERE DERIVED BY GPS 15 MINUTE OBSERVATIONS CONSTRAINING TO THE WSRN (WASHINGTON STATE REFERENCE NETWORK) AND EMPLOYING THE 2012a GEOID MODEL

# HORIZONTAL DATUM

ASSUMED

## SURVEYORS NOTES:

- NO DEED CORNERS WERE SET THIS SURVEY THIS SURVEY DOES NOT PURPORT TO SHOW ALL OR ANY EASEMENTS OF RECORD. THIS SURVEY WAS PERFORMED WITHOUT THE BENEFIT OF
- TITLE REPORT. THE PURPOSE OF THIS SURVEY IS TO SHOW CURRENT CONDITIONS OF SITE FOR DESIGN PURPOSES
- THIS SURVEY SHOWN HEREON IS A CONGLOMERATION OF DATA OBSERVED BY THIS SURVEYOR FROM TWO DIFFERENT COMPANIES. ALL WORK SHOWN HEREON WAS PERFORMED BY THIS SURVEYOR. DATA SHOWN HEREON NORTH OF THE SOUTHERLY BANK OF THE NORTHERLY DEPICTED EAST/WEST DRAINAGE SWALE WAS OBSERVED IN 2024 UNDER MCINNIS ENGINEERING. ALL DATA SOUTHERLY OF SAID SOUTHERLY DRAINAGE SWALE BANK WAS OBSERVED IN 2019 UNDER ABBEY ROAD GROUP. SAID ABBEY ROAD GROUP DATA MAY NOT REFLECT CURRENT CONDITIONS.
- DATES OF SURVEY: MAY 07, 2019 AND DECEMBER 13TH AND 20TH, 2024. CONTOUR INTERVAL SHOWN HEREON IS AT A 1' INTERVAL THE SUBSURFACE UTILITIES OF POWER, NATURAL GAS, AND TELECOMMUNICATIONS WERE DEMARCATED BY 811 ONE CALL SERVICE IN
- APRIL OF 2019 AND FIELD LOCATED BY ABBEY ROAD GROUP IN MAY OF 2019. ABBEY ROAD GROUP DOES NOT WARRANT NOR CERTIFY THE ACCURACY OR COMPLETENESS OF SAID UTILITIES. NO UTILITY LOCATES WERE REQUESTED FOR THE 2024 TOPOGRAPHIC SURVEY AREA. THERE MAY EXIST UTILITIES NOT SHOWN HEREON.
- THIS SURVEY DOES NOT RESOLVE ANY POSSIBLE UNWRITTEN RIGHTS DUE TO ADVERSE POSSESSION OR OTHER OCCUPATIONAL INDICATORS SUCH AS FENCES. 8. INVESTIGATION OF SUBSURFACE UTILITIES AS CONTRACTED BETWEEN
- ABBEY ROAD GROUP AND CLIENT WAS LIMITED TO 811 ONE CALL LOCATES. THERE MAY BE OTHER UTILITIES NOT DEPICTED. IF CONSTRUCTION IS TAKE PLACE WITHIN THE DEPICTED TOPOGRAPHY, ONE MUST BE CAUTIOUS AND MAY HAVE TO PERFORM ADDITIONAL RESEARCH
- FOR RECORD LOCATIONS OF UTILITIES IN THE AREA. 9. SEWER LATERALS AS DEPICTED WERE DERIVED THROUGH 811 UTILITY MARKING AND ABBEY ROAD GROUP DOES NOT WARRANT NOR CERTIFY
- THE ACCURACY OR COMPLETENESS OF SAID UTILITIES. 10. FOR A COMPLETE BOUNDARY BREAKDOWN, PLEASE REFERENCE RECORD OF SURVEY FOR BOUNDARY LINE RESOLUTION UNDER PIERCE COUNTY AUDITOR'S FILE NUMBER 201705315001

# CUT AND FILL

FILL: 0 CY CUT: 10,857CY

PLEASE NOTE THAT CUT AND FILL NUMBERS ARE ESTIMATES AND MAY NOT REFLECT THE FINAL IMPORT/EXPORT.

> CALL BEFORE YOU DIG 1-800-424-5555 OR 811





C1

**PROPOSED LEGEND** 

PERTY LINE

OSED CONCRETE

OSED ASPHALT

OSED INFILTRATION TRENCH

OSED INFILTRATION TRENCH

OSED INFILTRATION TRENCH M DRAIN

OSED FENCE

H BASIN

OSED CONTOUR LINES





# **2401 INTER TESC PLAN**

## A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA

## **TESC INSPECTION NOTES:**

- INSPECT ALL INLET PROTECTION ON CATCH BASINS. CLEAN OR REPLACE IF FULL OF SEDIMENT /DEBRIS AND
- REPAIR/REPLACE AS NEEDED IF DAMAGED TO MAINTAIN PROTECTION. INSPECT ALL PERMANENT AND TEMPORARY STABILIZED SLOPES. REPAIR ANY DAMAGED SECTIONS AND RE-VEGETATE AS NEEDED TO ENSURE THE ESTABLISHMENT OF VEGETATION AND THAT NO EROSION OF THE SLOPES OCCUR. INSPECT ALL FILTER FABRIC FENCING FOR SIGNS OF EROSION, DAMAGE OR FAILURES. REPAIR AND/OR REPLACE AS NEEDED. SEE FILTER FABRIC NOTES. SEDIMENT BUILD-UP ALONG FENCE SHALL BE REMOVED WHEN REACHES 1/3 THE FENCE HEIGHT. IF EROSION IS OCCURRING, CONTRACTOR SHALL INSTALL ADDITIONAL EROSION
- CONTROL MEASURES AS NEEDED TO PREVENT EROSION. ANY FILL/CUT SLOPES SHALL BE INSPECTED FOR EROSION. IF SIGNS OF EROSION ARE PRESENT, INSTALL APPROPRIATE BMPS AS NEEDED TO STOP EROSION AND STABILIZE SLOPES.
- TESC LEAD RESPONSIBLE FOR NOTIFYING ENGINEER IF ADDITIONAL MEASURES ARE WARRANTED.

### **PERMANENT STABILIZATION NOTES:**

- 1. ALL EXPOSED SOILS AND SLOPES SHALL BE SEEDED OR OTHERWISE STABILIZED IMMEDIATELY AFTER CONSTRUCTION AND GRADING ACTIVITIES HAVE BEEN COMPLETED.
- 2. SILT FENCE, IF DEEMED APPROPRIATE, SHALL REMAIN FOR A MINIMUM OF 30 DAYS AFTER THE FINAL STABILIZATION OF
- THE SLOPES HAS OCCURRED. 3. ALL TEMPORARY EROSION CONTROL BMP'S SHALL BE REMOVED 30 DAYS AFTER FINAL STABILIZATION HAS OCCURRED
- AS DIRECTED BY CITY OR COUNTY INSPECTOR. 4. CONTRACTOR SHALL REFER TO THE CONSTRUCTION SWPP FOR APPLICABLE BMPS.

#### **CONSTRUCTION ENTRANCE NOTES:**

- MATERIAL SHALL BE 4" TO 8" QUARRY SPALLS ( 4 TO 6 INCH FOR RESIDENTIAL SINGLE FAMILY LOTS) AND MAY BE
- TOP-DRESSED WITH 1 TO 3 INCH ROCK. 2. THE ROCK PAD SHALL BE AT LEAST 12" THICK AND 100' LONG (REDUCED TO 20 FEET FOR SITES LESS THAN 1 ACRE OF DISTURBED SOIL) WIDTH SHALL BE FULL WIDTH OF INGRESS AND EGRESS AREA. SMALLER PADS MAY BE APPROVED FOR
- SINGLE-FAMILY RESIDENTIAL AND COMMERCIAL SITES . ADDITIONAL ROCK SHALL BE ADDED PERIODICALLY TO MAINTAIN FUNCTION OF THE PAD. 4. IF THE PAD DOES NOT ADEQUATELY REMOVE MUD FROM THE VEHICLE WHEELS, THE WHEELS SHALL BE HOSED OFF
- BEFORE THE VEHICLE ENTERS A PAVED STREET. THE WASHING SHALL BE DONE ON AN AREA COVERED WITH CRUSHED ROCK AND WASH WATER SHALL DRAIN TO A SEDIMENT RETENTION FACILITY OR THROUGH A SILT FENCE.

- N00° 43' 59"W 202.91

Remove ESC details from this page and adhere to the city details on Sheet



CONSTRUCTION ENTRANCE SCALE:NTS

## FILTER FABRIC FENCE NOTES:

- SUPPORT POST, WITH A MINIMUM 6-INCH OVERLAP. AND SECURELY FASTENED AT BOTH ENDS TO POSTS. POSTS SHALL BE SPACED A MAXIMUM OF OFEET APART AND DRIVEN SECURELY INTO THE GROUND (MINIMUM OF 30 INCHES).
- A TRENCH SHALL BE EXCAVATED APPROXIMATELY 8 INCHES WIDE AND 12 INCHES DEEP ALONG THE LINE OF POSTS AND UPSLOPE FROM THE BARRIER. THIS TRENCH SHALL BE BACKFILLED WITH WASHED GRAVEL.
- WHEN STANDARD STRENGTH FILTER FABRIC IS USED, A WIRE MESH SUPPORT FENCE SHALL BE FASTENED SECURELY TO THE UPSLOPE SIDE OF THE POSTS USING HEAVY-DUTY WIRE STAPLES AT LEAST 1 INCH LONG, TIE WIRES OR HOG RINGS. THE WIRE SHALL EXTEND INTO THE TRENCH A MINIMUM OF A INCHES AND SHALL NOT EXTEND MORE THAN 24 INCHES ABOVE THE ORIGINAL GROUND SURFACE.
- THE STANDARD STRENGTH FILTER FABRIC SHALL BE STAPLED OR WIRED TO THE FENCE, AND 20 INCHES OF THE FABRIC SHALL BE EXTENDED INTO THE TRENCH. THE FABRIC SHALL NOT EXTEND MORE THAN 24 INCHES ABOVE THE ORIGINAL GROUND SURFACE. FILTER FABRIC SHALL NOT BE STAPLED TO EXISTING TREES.
- WHEN EXTRA-STRENGTH FILTER FABRIC AND CLOSER POST SPACING IS USED, THE WIRE MESH SUPPORT FENCE MAY BE ELIMINATED. IN SUCH A CASE, THE FILTER FABRIC IS STAPLED OR WIRED DIRECTLY TO THE POSTS WITH ALL OTHER PROVISIONS OF ABOVE NOTES APPLYING. FILTER FABRIC FENCES SHALL NOT BE REMOVED BEFORE THE UPSLOPE AREA HAS BEEN PERMANENTLY STABILIZED.
- FILTER FABRIC FENCES SHALL BE INSPECTED IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. ANY REQUIRED REPAIRS SHALL BE MADE IMMEDIATELY.
- SILT FENCES WILL BE INSTALLED PARALLEL TO ANY SLOPE CONTOURS. CONTRIBUTING LENGTH TO FENCE WILL NOT BE GREATER THAN 100 FEET
- DO NOT INSTALL BELOW AN OUTLET PIPE OR WEIR. 12.
- INSTALL DOWNSLOPE OF EXPOSED AREAS.







6"

SECTION



# **CONTRACTOR NOTES:**

TRIFO



13.

14.

SCALE: 1" = 30' FOR 22" X 34" SHEET LINE IS 1" AT

FULL SCALE





### **AMENDED SOILS NOTES:**

• SOIL AMENDMENTS ARE REQUIRED FOR ALL DISTURBED AREAS IN ACCORDANCE WITH CS 01.02.0A AND DEPTH OF THE 2019 SURFACE WATER MANAGEMENT MANUAL

AMENDED SOILS SHALL BE A MINIMUM OF 8" (NON-COMPACTED) WITH SUBSOILS SCARIFIED AT LEAST 4" WITH INCORPORATION OF THE UPPER MATERIAL TO AVOID STRATIFIED LAYERS, WHERE FEASIBLE. QUALITY OF COMPOST AND OTHER MATERIALS USED TO MEET THE ORGANIC CONTENT REQUIREMENTS ARE AS FOLLOWS:

a. THE ORGANIC CONTENT FOR "PRE-APPROVED" AMENDMENT RATES CAN BE MET ONLY USING COMPOST THAT MEETS THE

DEFINITION OF "COMPOSTED MATERIALS" IN WAC 173-350-220. THE WAC IS AVAILABLE ONLINE AT: HTTP://WWW.ECY.WA.GOV/PROGRAMS/SWFA/FACILITIES/350.HTML THE COMPOST MUST ALSO HAVE AN ORGANIC MATTER CONTENT OF 35% TO 65%, AND A CARBON TO NITROGEN RATIO BELOW 25:1. THE CARBON TO NITROGEN RATIO MAY BE AS HIGH AS 35: 1 FOR PLANTINGS COMPOSED ENTIRELY OF PLANTS NATIVE TO THE PUGET SOUND LOWLANDS REGION CALCULATED AMENDMENT RATES MAY BE MET THROUGH USE OF COMPOSTED MATERIALS AS DEFINED ABOVE; OR OTHER ORGANIC MATERIALS AMENDED TO MEET THE CARBON TO NITROGEN RATIO REQUIREMENTS, AND MEETING THE CONTAMINANT STANDARDS OF GRADE A COMPOST.

 USE ONE OF THE FOLLOWING OPTIONS TO MEET THE POST CONSTRUCTION SOIL QUALITY AND DEPTH REQUIREMENTS. USE THE MOST RECENT VERSION OF "GUIDELINES FOR RESOURCES FOR IMPLEMENTING SOIL QUALITY AND DEPTH BMP T5.13" TO MEET THE REQUIREMENTS OF THIS BMP. THIS GUIDANCE CAN BE FOUND ONLINE AT: WWW.SOILSFORSALMON.ORG

a. LEAVE NATIVE VEGETATION AND SOIL UNDISTURBED, AND PROTECT FROM COMPACTION DURING CONSTRUCTION b. AMEND EXISTING SITE TOPSOIL OR SUBSOIL EITHER AT DEFAULT "PRE-APPROVED" RATES, OR AT CUSTOM CALCULATED RA TES BASED ON SPECIFIC TESTS OF THE SOIL AND AMENDMENT

c. STOCKPILE EXISTING TOPSOIL DURING GRADING, AND REPLACE IT PRIOR TO PLANTING. STOCKPILED TOPSOIL MUST ALSO BE AMENDED IF NEEDED TO MEET THE ORGANIC MATTER OR DEPTH REQUIREMENTS, EITHER AT A DEFAULT "PRE-APPROVED" RATE OR AT A CUSTOM CALCULATED RATE.

IMPORT TOPSOIL MIX OF SUFFICIENT ORGANIC CONTENT AND DEPTH TO MEET THE REQUIREMENTS. MORE THAN ONE METHOD MAY BE USED ON DIFFERENT PORTIONS OF THE SAME SITE. SOIL THAT ALREADY MEETS THE DEPTH AND ORGANIC MATTER QUALITY STANDARDS, AND IS NOT COMPACTED, DOES NOT NEED TO BE AMENDED. AMENDED SOILS SHALL BE MAINTAINED AS FOLLOWS:

a. SOIL QUALITY AND DEPTH SHOULD BE ESTABLISHED TOWARD THE END OF CONSTRUCTION AND ONCE ESTABLISHED, SHOULD BE PROTECTED FROM COMPACTION. SUCH AS FROM LARGE MACHINERY USE. AND FROM EROSION. SOIL SHOULD BE PLANTED AND MULCHED AFTER INSTALLATION.

c. PLANT DEBRIS OR ITS EQUIVALENT SHOULD BE LEFT ON THE SOIL SURFACE TO REPLENISH ORGANIC MA TIER.

IT SHOULD BE POSSIBLE TO REDUCE USE OF IRRIGATION, FERTILIZERS, HERBICIDES AND PESTICIDES. THESE ACTIVITIES SHOULD BE ADJUSTED WHERE POSSIBLE, RATHER THAN CONTINUING TO IMPLEMENT FORMERLY ESTABLISHED PRACTICES.

• SEE PROJECT CONSTRUCTION SWPPP FOR ADDITIONAL INFORMATION OR SECTION 2.2.1.4 OF CHAPTER 2 OF VOLUME 6 OF THE 2021 SURFACE WATER MANAGEMENT MANUAL

#### MULCHING NOTES:

1. MULCH MATERIALS USED SHALL BE STRAW OR HAY, AND SHALL BE APPLIED AT THE RATE OF 75-100 POUNDS PER 1000 SQ. FT. (APPX 2" THICK).

2. MULCH SHALL BE APPLIED IN ALL AREAS WITH EXPOSED SLOPES GREATER THAN 2: 1 3. MULCHING SHALL BE USED IMMEDIATELY AFTER SEEDING OR IN AREAS WHICH CANNOT BE SEEDED BECAUSE OF THE SFASON

4. ALL AREAS NEEDING MULCH SHALL BE COVERED BY NOVEMBER 1

1. INLET PROTECTION SHALL BE INSTALLED IN ALL NEWLY CONSTRUCTED CATCH BASINS AND ALONG ALL IMPACTED FRONTAGE AND OFFSITE AREAS PER THE REQUIREMENTS OF THE CITY INSPECTOR PER DETAIL 3 ON THIS SHEET. 2. CONSTRUCTION FENCE CAN BE UTILIZED IN PLACE OF FILTER FABRIC FENCE ONLY IN AREAS WHERE THE GRADES DO NOT ALLOW THE POTENTIAL FOR ANY STORMWATER TO LEAVE THE SITE.

ALL DEMOLISHED MATERIALS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF AT A CITY APPROVED LOCATION AND IN A MANNER CONSISTENT WITH CURRENT REGULATIONS AND REQUIREMENTS. ALL AREAS THAT WILL BE UNWORKED FOR MORE THAN SEVEN (7) DAYS DURING THE DRY SEASON OR TWO (2) DAYS DURING THE WET SEASON, SHALL BE COVERED WITH STRAW, WOOD FIBER MULCH, COMPOST, PLASTIC SHEETING, OR

OTHER EQUIVALENT PER CURRENT CITY OR COUNTY STANDARDS. SEE SEEDING NOTES AND MULCHING NOTES ON THIS SHFFT 5. CONTRACTOR SHALL DESIGNATE A WASHINGTON DEPT OF ECOLOGY CERTIFIED EROSION CONTROL LEAD PERSON, AND

SHALL COMPLY WITH THE CONSTRUCTION STORMWATER POLLUTION PREVENTION PLAN (SWPPP) PREPARED FOR THE PROJECT AT ANY TIME DURING CONSTRUCTION IT IS DETERMINED BY THE CITY OR COUNTY THAT MUD AND DEBRIS ARE BEING

TRACKED ONTO PUBLIC STREETS WITH INSUFFICIENT CLEANUP, ALL WORK SHALL CEASE ON THE PROJECT UNTIL THIS CONDITION IS CORRECTED. THE CONTRACTOR AND/OR THE OWNER SHALL IMMEDIATELY TAKE ALL STEPS NECESSARY TO PREVENT FUTURE TRACKING OF MUD AND DEBRIS INTO THE PUBLIC ROW, WHICH MAY INCLUDE THE INSTALLATION OF A WHEEL WASH FACILITY ON-SITE. 7. SEDIMENT LADEN RUNOFF SHALL NOT BE ALLOWED TO DISCHARGE BEYOND THE LIMITS OF THE IMPROVEMENTS.

ADDITIONAL MEASURES SHALL BE INSTALLED AS NEEDED. SAND BAGS SHALL BE SECURELY PLACED AROUND INSTALLED CATCH BASINS WITH INLET PROTECTION AS FIELD AND

WEATHER CONDITIONS WARRANT SO TO PROTECT ALL DISPERSION AND INFILTRATION TRENCHES SEDIMENT LADEN RUNOFF 9. TREES WITHIN WORKING LIMITS TO BE SAVED, SHALL BE MARKED AS SUCH ON SITE AND PROTECTION FENCE PLACED AROUND EACH TREE.

#### **SEEDING NOTES:**

1. THE FOLLOWING SEED MIXTURE SHALL BE AS BELOW AND SHALL BE APPLIED AT THE RATE RECOMMENDED BY THE SUPPLIER.

### TABLE D.3.2.B TEMPORARY EROSION CONTROL SEED MIX

	% WEIGHT	% PURITY	% GERMINATION
CHEWINGS OR RED FESCUE FESTUCA RUBRA VAR. COMMUTATA OR FESTUCA RUBRA	40	98	90
ANNUAL OR PERENNIAL RYE	40	98	90
REDTOP OR COLONIAL BENTGRASS AGROSTIS ALBA OR AGROSTIS TENUIS	10	92	85
WHITE DUTCH CLOVER TRIFOLIUM REPENS	10	98	90

2. SEED BEDS PLANTED BETWEEN MAY 1 AND OCTOBER 31 WILL REQUIRE IRRIGATION AND OTHER MAINTENANCE AS NECESSARY TO FOSTER AND PROTECT THE ROOT STRUCTURE. FOR SEED BEDS PLANTED BETWEEN OCTOBER 31 AND APRIL 30, ARMORING OF THE SEED BED WILL BE NECESSARY. {E.G., GEOTEXTILES, JUTE MAT, CLEAR PLASTIC COVERING), BEFORE SEEDING, INSTALL NEEDED SURFACE RUNOFF CONTROL MEASURES SUCH AS GRADIENT TERRACES,

INTERCEPTOR DIKES, SWALES, LEVEL SPREADERS AND SEDIMENT BASINS.

5. THE SEEDBED SHALL BE FIRM WITH A FAIRLY FINE SURFACE, FOLLOWING SURFACE ROUGHENING. PERFORM ALL OPERATIONS ACROSS OR AT RIGHT ANGLES TO THE SLOPE.

6. FERTILIZERS ARE TO BE USED ACCORDING TO SUPPLIER'S RECOMMENDATIONS. AMOUNTS USED SHOULD BE MINIMIZED, ESPECIALLY ADJACENT TO WATER BODIES AND WETLANDS.



File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240Plotted By: ----

CALL BEFORE YOU DIG 1-800-424-5555 OR 811

sengineering.com 253.414.1992 mcinnis Η Z H 5 **G** ШМ 83 83

Шΰ

AV WA

ШС

**Ľ** 

Ľ

Ш

Ζ

Ω

 $\mathbf{O}$ 



DESIGNED

DRAWN

01/24/25

DATE

V. MCINNIS

W. MCINNIS

JOB NO.

SHEET

SCALE

1"=30'

CHECKED

J. MCINNIS

APPROVED

J. MCINNIS

24-166

C3 OF C12

C3



a ALL LIMITS OF CLEARING AND AREAS OF VEGETATION PRESERVATION AS PRESCRIBED ON THE PLANS SHALL BE CLEARLY FLAGGED IN THE FIELD AND OBSERVED DURING CONSTRUCTION.

2. ALL REQUIRED SEDIMENTATION AND EROSION CONTROL FACILITIES MUST BE CONSTRUCTED AND IN OPERATION PRIOR TO ANY LAND CLEARING AND/OR OTHER CONSTRUCTION TO ENSURE THAT SEDIMENT LADEN WATER DOES NOT ENTER THE NATURAL DRAINAGE SYSTEM. THE CONTRACTOR SHALL SCHEDULE AN INSPECTION OF THE EROSION CONTROL FACILITIES PRIOR TO ANY LAND CLEARING AND/OR CONSTRUCTION. ALL EROSION AND SEDIMENT FACILITIES SHALL BE MAINTAINED IN A SATISFACTORY CONDITION AS DETERMINED BY THE CITY, UNTIL SUCH TIME THAT CLEARING AND/OR CONSTRUCTION IS COMPLETED AND THE POTENTIAL FOR ON-SITE EROSION HAS PASSED. THE IMPLEMENTATION, MAINTENANCE, REPLACEMENT, AND ADDITIONS TO THE EROSION AND SEDIMENTATION CONTROL SYSTEMS SHALL BE THE RESPONSIBILITY OF THE PERMITEE.

3. THE EROSION AND SEDIMENTATION CONTROL SYSTEM FACILITIES DEPICTED ON THESE PLANS ARE INTENDED TO BE MINIMUM REQUIREMENTS TO MEET ANTICIPATED SITE CONDITIONS, AS CONSTRUCTION PROGRESSES AND UNEXPECTED OR SEASONAL CONDITIONS DICTATE, FACILITIES WILL BE NECESSARY TO ENSURE COMPLETE SILTATION CONTROL ON THE SITE, DURING THE COURSE OF CONSTRUCTION, IT ISHALL BE THE OBLIGATION AND RESPONSIBILITY OF THE PERMITEE TO ADDRESS ANY NEW CONDITIONS THAT MAY B CREATED BY HIS ACTIVITIES AND TO PROVIDE ADDITIONAL FACILITIES, OVER AND ABOVE THE MINIMUM REQUIREMENTS, AS MAY BE NEEDED TO PROTECT ADJACENT PROPERTIES, SENSITIVE AREAS, NATURAL WATER COURSES, AND/OR STORM DRAINAGE SYSTEMS

4. APPROVAL OF THESE PLANS IS FOR GRADING, TEMPORARY DRAINAGE, EROSION AND SEDIMENTATION CONTROL ONLY. IT DOES NOT CONSTITUTE AN APPROVAL OF PERMANENT STORM DRAINAGE DESIGN, SIZE OR LOCATION OF PIPES, RESTRICTORS, CHANNELS, OR RETENTION FACILITIES.

5. ANY DISTURBED AREA WHICH HAS BEEN STRIPPED OF VEGETATION AND WHERE NO FURTHER WORK IS ANTICIPATED FOR A PERIOD OF 30 DAYS OR MORE, MUST BE IMMEDIATELY STABILIZED WITH MULCHING, GRASS PLANTING, OR OTHER APPROVED EROSION CONTROL TREATMENT APPLICABLE TO THE TIME OF YEAR IN QUESTION, GRASS SEEDING ALONE WILL BE ACCEPTABLE ONLY DURING THE MONTHS OF APRIL THROUGH SEPTEMBER INCLUSVE. SEEDING MAY PROCEED OUTSIDE THE SPECIFIED TIME PERIOD WHENEVER IT IS IN THE INTEREST OF THE PERMITEE BUT MUST BE AUGMENTED WITH MULCHING, NETTING, OR OTHER TREATMENT APPROVED BY TH CITY.

6. IN CASE EROSION OR SEDIMENTATION OCCURS TO ADJACENT PROPERTIES, ALL CONSTRUCTION WORK WITHIN THE DEVELOPMENT THAT WILL FURTHER AGGRAVATE THE SITUATION MUST CEASE, AND THE OWNER/CONTRACTOR WILL IMMEDIATELY COMMENCE RESTORATION METHODS. RESTORATION ACTIVITY WILL CONTINUE UNTIL SUCH TIME AS THE AFFECTED PROPERTY OWNER IS SATISFIED

7. NO TEMPORARY OR PERMANENT STOCKPILING OF MATERIALS OR EQUIPMENT SHALL OCCUR WITHIN CRITICAL AREAS OR ASSOCIATED BUFFERS, OR THE CRITICAL ROOT ZONE FOR VEGETATION PROPOSED FOR RETENTION.



GRADING, EROSION, AND SEDIMENTATION CONTROL NOTES SCALE:NTS

#### SEDIMENTATION NOTE

AT ANY TIME DURING CONSTRUCTION IT IS DETERMINED BY THE CITY THAT MUD AND DEBRIS ARE BEING TRACKED ONTO PUBLIC STREETS WITH INSUFFICIENT CLEANUP, ALL WORK SHALL CEASE ON THE PROJECT UNTIL THIS CONDITION IS CORRECTED. THE CONTRACTOR AND/OR THE OWNER SHALL IMMEDIATELY TAKE ALL STEPS NECESSARY TO PREVENT FUTURE TRACKING OF MUD AND DEBRIS INTO THE PUBLIC ROW. WHICH MAY INCLUDE THE INSTALLATION OF A WHEEL WASH FACILITY ON-SITE.

SEDIMENT LADEN RUNOFF SHALL NOT BE ALLOWED TO DISCHARGE BEYOND THE CONSTRUCTION LIMITS IN ACCORDANCE WITH CITY REGULATIONS.

### CONSTRUCTION SEQUENCE

- HOLD A PRECONSTRUCTION MEETING WITH THE CITY AND
- OBTAIN REQUIRED PERMITS. ESTABLISH CLEARING AND GRADING LIMITS. CONSTRUCT TEMPORARY CONSTRUCTION ENTRANCE. CONSTRUCT PERIMETER DITCHES, SILT FENCES, AND OTHER EROSION CONTROL DEVICES AS SHOWN. CONSTRUCT PROTECTION DEVICES FOR CRITICAL AREAS AND SIGNIFICANT TREES PROPOSED FOR RETENTION. SCHEDULE AN EROSION INSPECTION WITH THE CITY. CONSTRUCT STORM DRAINAGE RETENTION/DETENTION (CONTROL AND STORAGE) FACILITIES. PROVIDE EMERGENCY OVERFLOW AS APPLICABLE.

- ALL DITCHES AND SWALES AS SHOWN SHALL BE PROVIDED TO DIRECT ALL SURFACE WATER TO THE RETENTION/DETENTION AND SEDIMENTATION POND AS CLEARING AND GRADING PROGRESSES. NO UNCONTROLLED SURFACE WATER SHALL BE ALLOWED TO LEAVE THE SITE OR BE DISCHARGED TO A CRITICAL AREA AT ANY TIME DURING THE GRADING OPERATIONS.
- CLEARLY STATE AT WHAT POINT GRADING ACTIVITIES CAN BEGIN, USUALLY ONLY AFTER ALL DRAINAGE AND EROSION CONTROL MEASURES ARE IN PLACE.
- IDENTIFY EROSION CONTROL MEASURES WHICH REQUIRE REGULAR MAINTENANCE.

# **2401 INTER TESC NOTES AND DETAILS**

A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA

-GEOTEXTILE

FABRIC

GLASS

REINFORCED

POLYPROPYLENE,

2.0 MM OPENING

CATCH BASIN INSERT

GRADING, EROSION, AND SEDIMENTATION CONTROL NOTES 05.02.01



OVERFLOW (TO BYPASS PFAK STORM SCREEN IS FIBER-VOLUMES) SEDIMENT ACCUMULATION-NOTE: CLEAN / REMOVE AND REPLACE WHEN FILLED TO 1/3 OF AVAILABLE STORAGE CB INSERT TO BE OF GOOD QUALITY AND CLEANABLE LEAVE IN GOOD CONDITION FOR BUILDERS DETAIL CBI-1 **CATCH BASIN INSERT FOR TRASH & DEBRIS** 

- THE MEETING.
- SEWER SERVICE.
- THE "CITY STANDARDS").

- ECOLOGY AT (360)407-6300.

- SURVEY CORNERS.

#### **APPROVED**

com

ering.

ngin

## CITY OF PUYALLUP

DEVELOPMENT ENGINEERING

NOTE: THIS APPROVAL IS VOID AFTER 180 DAYS FROM APPROVAL

THE CITY WILL NOT BE RESPONSIBLE FOR ERRORS

AND/OR OMISSIONS ON THESE PLANS. FIELD CONDITIONS MAY DICTATE CHANGES TO THESE PLANS AS DETERMINED BY THE

DEVELOPMENT ENGINEERING MANAGER.



#### **GENERAL NOTES**

1. ALL WORK IN CITY RIGHT-OF-WAY REQUIRES A PERMIT FROM THE CITY OF PUYALLUP PRIOR TO ANY WORK COMMENCING, THE GENERAL CONTRACTOR SHALL ARRANGE FOR A PRECONSTRUCTION MEETING AT THE DEVELOPMENT SERVICES CENTER TO BE ATTENDED BY ALL CONTRACTORS THAT WILL PERFORM WORK SHOWN ON THE ENGINEERING PLANS, REPRESENTATIVES FROM ALL APPLICABLE UTILITY COMPANIES, THE PROJECT OWNER AND APPROPRIATE CITY STAFF REPRESENTATIVES OF INVOLVED UTILITIES AND THE CITY OF PUYALLUP. CONTACT THE ENGINEERING SERVICES TO SCHEDULE THE MEETING (253-841-5568). THE CONTRACTOR IS RESPONSIBLE TO HAVE THEIR OWN SET OF PLANS AT

2. AFTER COMPLETION OF ALL ITEMS SHOWN ON THESE PLANS AND BEFORE ACCEPTANCE OF THE PROJECT, THE CONTRACTOR SHALL OBTAIN A "PUNCH LIST" PREPARED BY THE CITY'S INSPECTOR DETAILING REMAINING ITEMS OF WORK TO BE COMPLETED. ALL ITEMS OF WORK SHOWN ON THESE PLANS SHALL BE COMPLETED TO THE SATISFACTION OF THE CITY PRIOR TO ACCEPTANCE OF THE WATER SYSTEM AND PROVISION OF SANITARY

3. ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION (HEREINAFTER REFERRED TO AS THE "STANDARD SPECIFICATIONS"), WASHINGTON STATE DEPARTMENT OF TRANSPORTATION AND AMERICAN PUBLIC WORKS ASSOCIATION, WASHINGTON STATE CHAPTER, LATEST EDITION, UNLESS SUPERSEDED OR AMENDED BY THE CITY OF PUYALLUP CITY STANDARDS FOR PUBLIC WORKS ENGINEERING AND CONSTRUCTION (HEREINAFTER REFERRED TO AS

4. A COPY OF THESE APPROVED PLANS AND APPLICABLE CITY DEVELOPER SPECIFICATIONS AND DETAILS SHALL BE ON SITE DURING CONSTRUCTION.

5. ANY REVISIONS MADE TO THESE PLANS MUST BE REVIEWED AND APPROVED BY THE DEVELOPER'S ENGINEER AND THE CITY PRIOR TO ANY IMPLEMENTATION IN THE FIELD. THE CITY SHALL NOT BE RESPONSIBLE FOR ANY ERRORS AND/OR OMISSIONS ON THESE PLANS. 6. THE CONTRACTOR SHALL HAVE ALL UTILITIES VERIFIED ON THE GROUND PRIOR TO ANY CONSTRUCTION. CALL (811) AT LEAST TWO WORKING DAYS IN ADVANCE. THE OWNER AND HIS/HER ENGINEER SHALL BE CONTACTED IMMEDIATELY IF A CONFLICT EXISTS. 7. ANY STRUCTURE AND/OR OBSTRUCTION THAT REQUIRES REMOVAL OR RELOCATION' RELATING TO THIS PROJECT SHALL BE DONE SO AT THE DEVELOPER'S EXPENSE.

8. LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE TRUE ELEVATIONS AND LOCATIONS OF HIDDEN UTILITIES. ALL VISIBLE ITEMS SHALL BE THE ENGINEER'S RESPONSIBILITY. 9. THE CONTRACTOR SHALL INSTALL, REPLACE, OR RELOCATE ALL SIGNS, AS SHOWN ON THE

PLANS OR AS AFFECTED BY CONSTRUCTION, PER CITY STANDARD DETAILS. 10. POWER, STREET LIGHT, CABLE, AND TELEPHONE LINES SHALL BE IN A TRENCH LOCATED WITHIN A 10-FOOT UTILITY EASEMENT ADJACENT TO PUBLIC RIGHT-OF-WAY. RIGHT-OF-WAY CROSSINGS SHALL HAVE A MINIMUM HORIZONTAL SEPARATION FROM

OTHER UTILITIES (SEWER, WATER, STORM) OF 5 FEET. 11. ALL CONSTRUCTION SURVEYING FOR EXTENSIONS OF PUBLIC FACILITIES SHALL BE DONE UNDER THE DIRECTION OF A WASHINGTON STATE LICENSED LAND SURVEYOR OR A WASHINGTON STATE LICENSED PROFESSIONAL CIVIL ENGINEER.

12. DURING CONSTRUCTION, ALL PUBLIC STREETS ADJACENT TO THIS PROJECT SHALL BE KEPT CLEAN OF ALL MATERIAL DEPOSITS RESULTING FROM ON-SITE CONSTRUCTION, AND EXISTING STRUCTURES SHALL BE PROTECTED AS DIRECTED BY THE CITY. CERTIFIED RECORD DRAWINGS ARE REQUIRED PRIOR TO PROJECT ACCEPTANCE. 14. A NPDES STORMWATER GENERAL PERMIT MAY BE REQUIRED BY THE DEPARTMENT OF ECOLOGY FOR THIS PROJECT. FOR INFORMATION CONTACT THE DEPARTMENT OF

15. ANY DISTURBANCE OR DAMAGE TO CRITICAL AREAS AND ASSOCIATED BUFFERS, OR SIGNIFICANT TREES FOR PRESERVATION AND PROTECTION SHALL BE MITIGATED IN ACCORDANCE WITH A MITIGATION PLAN REVIEWED AND APPROVED BY THE CITY%%146S PLANNING DIVISION. PREPARATION AND IMPLEMENTATION OF THE MITIGATION PLAN SHALL BE AT THE DEVELOPER'S EXPENSE.

16. NO SURVEY MONUMENT SHALL BE REMOVED OR DESTROYED (THE PHYSICAL DISTURBANCE OR COVERING OF A MONUMENT SUCH THAT THE SURVEY POINT IS NO LONGER VISABLE OR READILY ACCESSIBLE) BEFORE A PERMIT IS OBTAINED FROM THE DEPARTMENT OF NATURAL RESOURCES (DNR).WAC 332-120-030(2) STATES "IT SHALL BE THE RESPONSIBILITY OF <THOSE> PERFORMING CONSTRUCTION WORK OR OTHER ACTIVITY (INCLUDING ROAD AND STREET RESURFACING PROJECTS TO ADEQUATELY SEARCH THE RECORDS AND THE PHYSICAL AREA OF THE PROPOSED CONSTRUCTION WORK OR OTHER ACTIVITY FOR THE PURPOSE OF LOCATING AND REFERENCING ANY KNOWN OR EXISTING SURVEY MONUMENTS" CONSTRUCTION SHALL NOT COMMENCE UNTIL WAC OUTLINED IN CHAPTER 332-120 IS COMPLIED WITH. SURVEY MONUMENTS SUBJECT TO WAC 332-120-030(2) INCLUDE LOCAL CONTROL POINTS AND LAND BOUNDARY

17. EXPOSED SOILS WITH AN AREA GREATER THAN 5,000 SQUARE FEET THAT ARE SCHEDULED TO REMAIN UNWORKED FOR MORE THAN 24 HOURS AND EXPOSED AREAS OF LESS THAN 5,000 SQUARE FEET THAT WILL REMAIN UNWORKED FOR MORE THAN SEVEN (7) DAYS SHALL BE STABILIZED IMMEDIATELY.

> CALL BEFORE YOU DIG 1-800-424-5555 OR 811

File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PldMB@ER -124/25ESC NOTES & DETARS and the second sec





File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PldMater - 128/25RONTAGE PLANttad=2:









# **2401 INTER** NOTES AND DETAILS

A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA



DAYLIGHT CULVERT OPEN DITCH 3 SCALE:NTS





8

File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PldNedeR - 1029/2612 NOTES & DET All Sydwg-



# **2401 INTER** NOTES AND DETAILS

A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA

#### **APPROVED**

CITY OF PUYALLUP DEVELOPMENT ENGINEERING

#### DATE

MANAGER.

NOTE: THIS APPROVAL IS VOID AFTER 180 DAYS FROM APPROVAL

THE CITY WILL NOT BE

RESPONSIBLE FOR ERRORS AND/OR OMISSIONS ON THESE PLANS. FIELD CONDITIONS MAY DICTATE CHANGES TO THESE PLANS AS DETERMINED BY THE DEVELOPMENT ENGINEERING

ALL WORK IN CITY RIGHT-OF-WAY REQUIRES A PERMIT FROM THE CITY OF PUYALLUP. PRIOR TO ANY WORK COMMENCING, THE GENERAL CONTRACTOR SHALL ARRANGE FOR A PRECONSTRUCTION MEETING AT THE DEVELOPMENT SERVICES CENTER TO BE ATTENDED BY ALL CONTRACTORS THAT WILL PERFORM WORK SHOWN ON THE ENGINEERING PLANS, REPRESENTATIVES FROM ALL APPLICABLE UTILITY COMPANIES, THE PROJECT OWNER AND APPROPRIATE CITY STAFF. CONTACT ENGINEERING SERVICES TO SCHEDULE THE MEETING (253) 841-5568. THE CONTRACTOR IS RESPONSIBLE TO HAVE THEIR OWN APPROVED SET OF PLANS AT THE MEETING.

STORMWATER NOTES

2. AFTER COMPLETION OF ALL ITEMS SHOWN ON THESE PLANS AND BEFORE ACCEPTANCE OF THE PROJECT, THE CONTRACTOR SHALL OBTAIN A "PUNCH LIST" PREPARED BY THE CITY'S INSPECTOR DETAILING REMAINING ITEMS OF WORK TO BE COMPLETED. ALL ITEMS OF WORK SHOWN ON THESE PLANS SHALL BE COMPLETED TO THE SATISFACTION OF THE CITY PRIOR TO ACCEPTANCE OF THE WATER SYSTEM AND PROVISION OF SANITARY SEWER SERVICE.

3. ALL MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION (HEREINAFTER REFERRED TO AS THE "STANDARD SPECIFICATIONS"), WASHINGTON STATE DEPARTMENT OF TRANSPORTATION AND AMERICAN PUBLIC WORKS ASSOCIATION, WASHINGTON STATE CHAPTER, LATEST EDITION, UNLESS SUPERSEDED OR AMENDED BY THE CITY OF PUYALLUP CITY STANDARDS FOR PUBLIC WORKS ENGINEERING AND CONSTRUCTION (HEREINAFTER REFERRED TO AS THE "CITY STANDARDS").

4. A COPY OF THESE APPROVED PLANS AND APPLICABLE CITY DEVELOPER SPECIFICATIONS AND DETAILS SHALL BE ON SITE DURING CONSTRUCTION.

5. ANY REVISIONS MADE TO THESE PLANS MUST BE REVIEWED AND APPROVED BY THE DEVELOPER'S ENGINEER AND THE ENGINEERING SERVICES STAFF PRIOR TO ANY IMPLEMENTATION IN THE FIELD. THE CITY SHALL NOT BE RESPONSIBLE FOR ANY ERRORS AND/OR OMISSIONS ON THESE PLANS.

6. THE CONTRACTOR SHALL HAVE ALL UTILITIES VERIFIED ON THE GROUND PRIOR TO ANY CONSTRUCTION. CALL (811) AT LEAST TWO WORKING DAYS IN ADVANCE. THE OWNER AND HIS/HER ENGINEER SHALL BE CONTACTED IMMEDIATELY IF A CONFLICT EXISTS.

7. ANY STRUCTURE AND/OR OBSTRUCTION WHICH REQUIRE REMOVAL OR RELOCATION RELATING TO THIS PROJECT, SHALL BE DONE SO AT THE DEVELOPER'S EXPENSE.

8. DURING CONSTRUCTION, ALL EXISTING AND NEWLY INSTALLED DRAINAGE STRUCTURES SHALL BE PROTECTED FROM SEDIMENTS.

9. ALL STORM MANHOLES SHALL CONFORM TO CITY STANDARD DETAIL NO. 02.01.01. FLOW CONTROL MANHOLE/OIL WATER SEPARATOR SHALL CONFORM TO CITY STANDARD DETAIL NO. 02.01.06 AND 02.01.07.

10. MANHOLE RING AND COVER SHALL CONFORM TO CITY STANDARD DETAIL 06.01.02 AND 06.01.03. THE COVER SHALL BE MARKED WITH "STORM" OR "DRAIN" IN 2-INCH RAISED LETTERS. MINIMUM WEIGHT OF THE FRAME SHALL BE 210 POUNDS. MINIMUM WEIGHT OF THE COVER SHALL BE 150 POUNDS.

11. CATCH BASINS TYPE I SHALL CONFORM TO CITY STANDARD DETAIL NO.02.01.02 AND 02.01.03 AND SHALL BE USED ONLY FOR DEPTHS LESS THAN 5 FEET FROM TOP OF THE GRATE TO THE INVERT OF THE STORM PIPE.

12. CATCH BASINS TYPE II SHALL CONFORM TO CITY STANDARD DETAIL NO.02.01.04 AND SHALL BE USED FOR DEPTHS GREATER THAN 5 FEET FROM TOP OF THE GRATE TO THE INVERT OF THE STORM PIPE.

13. CAST IRON OR DUCTILE IRON FRAME AND GRATE SHALL CONFORM TO CITY STANDARD DETAIL NO.02.01.05. GRATE SHALL BE MARKED WITH "DRAINS TO STREAM". SOLID CATCH BASIN LIDS (SQUARE UNLESS NOTED AS (ROUND) SHALL CONFORM TO WSDOT STANDARD PLAN B-2 (OLYMPIC FOUNDRY NO. SM60 OR EQUAL). VANED GRATES SHALL CONFORM TO WSDOT STANDARD PLAN B-2A (OLYMPIC FOUNDRY NO. SM60V OR EQUAL).

14. STORMWATER PIPE SHALL BE ONLY PVC, CONCRETE OR DUCTILE IRON PIPE.

a. THE USE OF ANY OTHER TYPE SHALL BE REVIEWED AND APPROVED BY THE ENGINEERING SERVICES STAFF PRIOR TO INSTALLATION.

b. PVC PIPE SHALL BE PER ASTM D3034, SDR 35 FOR PIPE SIZE 15-INCH AND SMALLER AND F679 FOR PIPE SIZES 18 TO 27 INCH. MINIMUM COVER ON PVC PIPE SHALL BE 3.0 FEET.

CONCRETE PIPE SHALL CONFORM TO THE WSDOT STANDARD SPECIFICATIONS FOR CONCRETE UNDERDRAIN PIPE. MINIMUM COVER ON CONCRETE PIPE SHALL NOT LESS THAN 3.0 FEET.

d. DUCTILE IRON PIPE SHALL BE CLASS 50, CONFORMING TO AWWA C151. MINIMUM COVER ON DUCTILE IRON PIPE SHALL BE 1.0 FOOT.

e. POLYPROPYLENE PIPE (PP) SHALL BE DUAL WALLED, HAVE A SMOOTH INTERIOR AND EXTERIOR CORRUGATIONS AND MEET WSDOT 9-05.24(1). 12-INCH THROUGH 30"-INCH PIPE SHALL MEET OR EXCEED ASTM F2736 AND AASHTO M330, TYPE S, OR TYPE D. 36-INCH THROUGH 60-INCH PIPE SHALL MEET OR EXCEED ASTM F2881 AND AASHTO M330, TYPE S, OR TYPE D. TESTING SHALL BE PER ASTM F1417. MINIMUM COVER OVER POLYPROPYLENE PIPE SHALL BE 3-FEET.

15. TRENCHING, BEDDING, AND BACKFILL FOR PIPE SHALL CONFORM TO CITY STANDARD DETAIL NO. 06.01.01.

16. STORM PIPE SHALL BE A MINIMUM OF 10 FEET AWAY FROM BUILDING FOUNDATIONS AND/OR ROOF LINES.

17. ALL STORM DRAIN MAINS SHALL BE VIDEO INSPECTED BY THE CITY OF PUYALLUP COLLECTIONS DIVISION PRIOR TO FINAL ACCEPTANCE BY THE CITY.

18. AFTER ALL OTHER UTILITIES ARE INSTALLED AND PRIOR TO ASPHALT WORK, ALL STORM PIPE SHALL PASS A LOW PRESSURE AIR TEST IN ACCORDANCE WITH SECTION 7-04.3(4)D OF THE STANDARD SPECIFICATIONS. PRODUCTS USED TO SEAL THE INSIDE OF THE PIPE ARE NOT TO BE USED TO OBTAIN THE AIR TEST.

19. ALL STORM DRAIN MAINS SHALL BE MANDRELLED.

20. ALL TEMPORARY SEDIMENTATION AND EROSION CONTROL MEASURES, AND PROTECTIVE MEASURES FOR CRITICAL AREAS AND SIGNIFICANT TREES SHALL BE INSTALLED PRIOR TO INITIATING ANY CONSTRUCTION ACTIVITIES.

<b>MGIDNIS</b> ENGINEERING
2401 INTER 2401 INTER AND DETAILS 2401 INTER AVE SE PUYALLUP, WA 98372
ATTENDE WARDEN TO THE TOTAL OF WARDEN TO THE TOTAL ENGINEER OF WARDEN TO THE TOTAL OF WARDEN TO THE TOTAL OF TOTAL
DESCRIPTION INITIAL RELEASE
HEAD       SCALE         MO       15         DESIGNED       SCALE         W. MCINNIS       N.T.S.         DRAWN       CHECKED         W. MCINNIS       J. MCINNIS         DATE       APPROVED         01/24/25       J. MCINNIS         JOB NO.       24-166

#### CALL BEFORE YOU DIG 1-800-424-5555 OR 811

File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PldNedeR - 1029/2612 NOTES & DET All Sydwg-

C9



File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PloNet@R 1/2#/2612 NOTES & DET + 240PloNet@R 1/2#/2612 NOTES & DET

![](_page_10_Figure_0.jpeg)

![](_page_10_Figure_2.jpeg)

# **2401 INTER** NOTES AND DETAILS

A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA

### **APPROVED**

.com

ering.

5

#### CITY OF PUYALLUP DEVELOPMENT ENGINEERING

#### DATE

NOTE: THIS APPROVAL IS VOID AFTER 180 DAYS FROM APPROVAL

#### DATE THE CITY WILL NOT BE

RESPONSIBLE FOR ERRORS AND/OR OMISSIONS ON THESE PLANS. FIELD CONDITIONS MAY DICTATE

CHANGES TO THESE PLANS AS DETERMINED BY THE

DEVELOPMENT ENGINEERING MANAGER.

Έ						ç	Tacol		
				ENGINEERING					
	2401 INTER NOTES AND DETAILS					2401 INTER AVE SE PUYALLUP, WA 98372			
			E of AND	W. WAS 37399 ISTEV	Martin	Contraction of the second	1124	25	
	DESCRIPTION	INITIAL RELEASE							
	DESI WNN DESI W. M DRAV W. M DATE 01/2 <sup>2</sup> JOI	AUDICAL 2017	D IIS IIS D. <b>24</b>		SC. I CHI J. M APF J. M	ALE N.T.S ECKI ICIN ICIN	S. ED NIS VED NIS		
G 1	 	24-166 SHEET C11 ○F C12							

	_				_
DE. TO CUT AND COUPLE ADDITIONAL IY. THE SITE DESIGN ENGINEER IS NILS. THE BASE STONE DEPTH MAY	INTER	AA, WA	DRAWN: HAK	CHECKED: RWD	CONSTRUCTION. IT IS THE
	2401	TACON	DATE: 9/21/22	PROJECT #: \$309928	L REVIEW THIS DRAWING PRIOR TO (
"ADS N-12 BOTTOM MANIFOLD 1 36" ABOVE CHAMPER BASE			WOTEN PLANDED TO MC 3500 SVSTEM	DESCRIPTION	PRESENTATIVE. THE SITE DESIGN ENGINEER SHAL
1.35" ABOVE CHAMBER BASE ITES)				E DRWN CHKD	DTHER PROJECT REF
M OUTLET FLOW 6.0 CFS I BY ENGINEER / PROVIDED BY OTHERS)			PC/0	CH.COM	TE DESIGN ENGINEER OR
DS N-12 TOP CONNECTION RT 26.36" ABOVE CHAMBER BASE NOTES) ADS 45° N12 BEND	¢	Tech	System	WWW.STORMTE	HE DIRECTION OF THE S
SED STRUCTURE W/ELEVATED BYPASS MANIFOLD M INLET FLOW 13.5 CFS I BY ENGINEER / PROVIDED BY OTHERS)		Storm	Chamber (	888-892-2694	IDED TO ADS UNDER T
TIAL CUT END CAP, PART# MC3500IEPP24BC OR MC3500IEPP24BW ALL MC-3500 24" BOTTOM CONNECTIONS AND ISOLATOR PLUS ROWS	AN BLVD	43026	40'		ORMATION PROV
" ADS N-12 TOP MANIFOLD 26.36" ABOVE CHAMBER BASE JTES / TYP 2 PLACES) /INIMUM 17.5' OF ADSPLUS175 WOVEN GEOTEXTILE	4640 TRUEM	HILLIARD, OF	20'		ARED BASED ON INFO
EDDING STONE AND UNDERNEATH CHAMBER FEET OUR PROTECTION AT ALL CHAMBER INLET ROWS		Ŝ	0-		IIS DRAWING HAS BEEN PREP

### CALL BEFORE YOU DI 1-800-424-5555 OR 8<sup>4</sup>

File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PloNtoter - 240PloNto

![](_page_11_Figure_0.jpeg)

![](_page_11_Figure_1.jpeg)

STORMTECH DETAIL 6 OF 6 SCALE:NTS

2

PARTS LIST 20 - ENDCAPS (INCLUDING ISOLATOR ROW) 200 - MC-3500 CHAMBERS (INCLUDING ISOLATOR ROW) 1 - INSPECTION PORT 8 - OUTLET MANIFOLD 4 - 6" HDPE UNDERDRAIN

# **2401 INTER** NOTES AND DETAILS

A PORTION OF THE SW 1/4 OF SECTION 26, TOWNSHIP 20 N, RANGE 4 E, W.M. PIERCE COUNTY, WA

![](_page_11_Figure_6.jpeg)

4 CONTECH FILTER SCALE:NTS

#### SOIL AMENDMENT NOTES

SOIL RETENTION. RETAIN IN A UNDISTURBED STATE, THE DUFF LAYER AND NATIVE TOPSOIL TO THE MAXIMUM EXTENT PRACTICABLE. IN ANY AREAS REQUIRING GRADING REMOVE AND STOCKPILE THE DUFF LAYER AND TOPSOIL ON SITE IN A DESIGNATED, CONTROLLED AREA, NOT ADJACENT TO PUBLIC RESOURCES AND CRITICAL AREAS, TO BE REAPPLIED TO OTHER PORTIONS OF THE SITE WHERE FEASIBLE.

SOIL QUALITY. ALL AREAS SUBJECT TO CLEARING AND GRADING THAT HAVE NOT BEEN COVERED BY IMPERVIOUS SURFACE, INCORPORATED INTO A DRAINAGE FACILITY OR ENGINEERED AS STRUCTURAL FILL OR SLOPE SHALL, AT PROJECT COMPLETION, DEMONSTRATE THE FOLLOWING:

- A. THE TOPSOIL LAYER WITH A MINIMUM ORGANIC MATTER CONTENT OF 10% DRY WEIGHT IN PLANTING BEDS, AND 5% ORGANIC MATTER CONTENT IN TURF AREAS, AND A PH FROM 6.0 TO 8.0 OR MATCHING THE PH OF THE UNDISTURBED SOIL. THE TOPSOIL LAYER SHALL HAVE A MINIMUM DEPTH OF EIGHT INCHES EXCEPT WHERE TREE ROOTS LIMIT THE DEPTH OF INCORPORATION OF AMENDMENTS NEEDED TO MEET THE CRITERIA. SUBSOILS BELOW THE TOPSOIL LAYER SHOULD BE SCARIFIED AT LEAST 4 INCHES WITH SOME INCORPORATION OF THE UPPER MATERIAL TO AVOID STRATIFIED LAYERS, WHERE FEASIBLE.
  B. MULCH PLANTING BEDS WITH 2 INCHES OF ORGANIC MATERIAL.
- C. USE COMPOST AND OTHER MATERIALS THAT MEET THESE ORGANIC CONTENT REQUIREMENTS:
- THE ORGANIC CONTENT FOR "PRE-APPROVED" AMENDMENT RATES CAN BE MET ONLY USING COMPOST MEETING THE COMPOST SPECIFICATION FOR BMP T7.30: BIORETENTION CELLS, SWALES, AND PLANTER BOXES, WITH THE EXCEPTION THAT THE COMPOST MAY HAVE UP TO 35% BIOSOLIDS OR MANURE. THE COMPOST MUST ALSO HAVE AN ORGANIC MATTER CONTENT OF 40% TO 65%, AND A CARBON TO NITROGEN RATIO BELOW 25:1. THE CARBON TO NITROGEN RATIO MAY BE AS HIGH AS 35:1 FOR PLANTINGS COMPOSED ENTIRELY OF PLANTS NATIVE TO THE PUGET SOUND LOWLANDS REGION.
- CALCULATED AMENDMENT RATES MAY BE MET THROUGH USE OF COMPOSTED MATERIAL MEETING ABOVE; OR OTHER ORGANIC MATERIALS AMENDED TO MEET THE CARBON TO NITROGEN RATIO REQUIREMENTS, AND NOT EXCEEDING THE CONTAMINANT LIMITS IDENTIFIED ON TABLE 220-B, TESTING PARAMETERS, IN WAC 173-350-220.
   THE RESULTING SOIL SHOULD BE CONDUCTIVE TO THE TYPE OF VEGETATION TO

BE ESTABLISHED. IMPLEMENTATION OPTIONS: THE SOIL QUALITY DESIGN GUIDELINES LISTED ABOVE CAN BE MET BY USING ONE OF THE METHODS LISTED BELOW: A. LEAVE UNDISTURBED NATIVE VEGETATION AND SOIL, AND PROTECT FROM

- COMPACTION DURING CONSTRUCTION. B. AMEND EXISTING SITE TOPSOIL OR SUBSOIL EITHER AT DEFAULT "PRE-APPROVED" RATES, OR AT CUSTOM CALCULATED RATES BASED ON
- TESTS OF THE SOIL AND AMENDMENT. C. STOCKPILE EXISTING TOPSOIL DURING GRADING, AND REPLACE IT PRIOR TO PLANTING. STOCKPILED TOPSOIL MUST ALSO BE AMENDED IF NEEDED TO MEET THE ORGANIC MATTER OR DEPTH REQUIREMENTS, EITHER AT A DEFAULT
- "PRE-APPROVED" RATE OR AT A CUSTOM CALCULATED RATE. D. IMPORT TOPSOIL MIX OF SUFFICIENT ORGANIC CONTENT AND DEPTH TO MEET THE REQUIREMENTS.

MORE THAN ONE METHOD MAY BE USED ON DIFFERENT PORTIONS OF THE SAME SITE. SOIL THAT ALREADY MEETS THE DEPTH AND ORGANIC MATTER QUALITY STANDARDS, AND IS NOT COMPACTED, DOES NOT NEED TO BE AMENDED. MAINTENANCE

- A. ESTABLISH SOIL QUALITY AND DEPTH TOWARD THE END OF CONSTRUCTION AND ONE ESTABLISHED, PROTECT FROM COMPACTION, SUCH AS FROM LARGE MACHINERY USE, AND FROM EROSION.
- B. PLANT VEGETATION AND MULCH THE AMENDED SOIL AREA AFTER INSTALLATION.
- C. LEAVE PLANT DEBRIS OR ITS EQUIVALENT ON THE SOIL SURFACE TO REPLENISH ORGANIC MATTER.
- D. REDUCE AND ADJUST, WHERE POSSIBLE, THE USE OF IRRIGATION, FERTILIZERS, HERBICIDES AND PESTICIDES, RATHER THAT CONTINUING TO IMPLEMENT FORMERLY ESTABLISHED PRACTICES.

REFERENCE VOLUME V-5.3.1, BMP T5.13 OF THE 2014 STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON.

#### APPROVED

COM

ering.

CITY OF PUYALLUP

DEVELOPMENT ENGINEERING

NOTE: THIS APPROVAL IS VOID AFTER 180 DAYS FROM APPROVAL

THE CITY WILL NOT BE RESPONSIBLE FOR ERRORS AND/OR OMISSIONS ON THESE

PLANS. FIELD CONDITIONS MAY DICTATE CHANGES TO THESE PLANS AS DETERMINED BY THE

DETERMINED BY THE DEVELOPMENT ENGINEERING MANAGER.

![](_page_11_Picture_33.jpeg)

#### CALL BEFORE YOU DIG 1-800-424-5555 OR 811

File: Z:\Shared\McInnis Engineering Files\2024 Proposals-Projects\24-166 - 2401 Inter - Redesign Project\Engineering\CAD\ME\24-166 - SDEV - 2401 INTER - REV(V1)\24-166 - SDEV - 240PldNeder - 1234/2512 NOTES & DETARL Sydwg-