


PRMH20250744



## CUSTOMER SPECIFICATION REPORT

**PROJECT NUMBER:**

NC-020866

**UNIT LABEL:**

CU1

**UNIT DESCRIPTION:**

CO1 FREEZER

**DATE:**

2024-09-11

**CUSTOMER INFORMATION**

CUSTOMER NAME: T0342

STORE NAME:

STORE NUMBER:

ADDRESS 1:

ADDRESS 2: PUYALLUP, WA USA

**FACTORY INFORMATION**

FACTORY UNIT ID: A

SALESMAN:

AE LEAD: JTRACHTA

SUBMITTER: JAN TRACHTA

**PERFORMANCE INFORMATION****NOMENCLATURE ENDS WITH "D" WHEN****DOE COMPLIANT**

AWEF RATING: 3.15

**LOAD:**

27.60 MBH

**MID SUCT:**

-26 °F

**CAPACITY:**

33.49MBH

**AMB TEMP:**

100 °F

**POWER:**

7.1 kW

**MID COND:**

111.4 °F

**% LOAD:**

82%

**TD:**

11.3 °F

**MECHANICAL OPTIONS****NOMENCLATURE HDHD-0900LRK-FF-D**

UNIT: D-OUTDOOR HE

BASE: H-HBASELHOD

COMPRESSOR: D-3D

HP: 0900-9 HP

APPLICATION: L-LOW TEMP

REFRIGERANT: R-R449A

RCVR INSUL/HTR: Y-YES HEAT+INSUL

BALL VLV REC INLET: YES

LIQUID DRIER: STD-STD SEALED D

SUCTION ACCUM: Y-YES, ACCUMULAT

SUCTION FILTER: STD-STD SEALED F

OIL SEPARATOR: NO

OIL SAFETY:

PHASE MONITOR:

COMPR UNLOAD:

COMPR HEAD FAN:

DISCHARGE CHECK VLV:

PRESSURE RELIEF: R-RELIEF VALVESTD ELECTRICAL P

UNIT VOLTAGE: K-208-230V/3P/60

CONDENSER: F-COND F Electrofin

RECEIVER: F-F 10-3/4X30

CONTROL VOLTAGE: D-208V/1P/60HZ

LOGO: H-HUSSMANN

SHIPPING: S-SKID

CABINET SIZE: LARGE

BASE LOCATION: NO

LOWER BASE: M-MEDIUM

ESTIMATED WEIGHT: 1250

OIL REG: NO

CRANKCASE HEATER: Y-YES

FIN MATERIAL: E-ELECTROFIN

FAN CYCLING: 2HU-2 STEP HE-UL

FAN CYCLING CONFIG: UG-1N-2Y-34A-U

MOUNTING TYPE: S-SPRING MOUNT

HEAD PRESSURE: A-ADJUSTABLE

HIGH PRESSURE: MC-MANUAL CARTRI

LOW PRESSURE: AU-ADJ - ULTRACA

DIMENSIONS: 6' 8 9/16 "L x 2' 11 5/64 "W x 4' 1 31/64 "H

HAIL GUARD: S-SHIPLOOSE

PUMPDOWN SWITCH: NO

INSULATION: NO

THERMOSTAT: NO

HEAT RECLAIM VALVE: NO

HOT GAS BYPASS: NO

CS RELAY: NO

DRAIN OIL: NO

ECM FAN MOTOR: NO

COMPRESSOR MODEL: 3DF3F40KE

DOE COMPLIANT: Y-YES

HIGH WIND OPTION: NO

**ELECTRICAL OPTIONS**

ELECTRICAL CONN: S-SINGLE POINT

PROTECTION TYPE: F-FUSES

CONTACTOR TYPE: D-DP (DEFINITE P

CONTACTOR BRAND: S-SQUARE D

DEFROST TIMER: NO

ADJ TIME DELAY RELAY Y-66FB

CONTROLLER: NO

MAIN PROTECTION 1: NF-NON-FUSE DISC

MAIN PROTECTION 2: NO

MOPD 1: 80

MOPD 2: NO

MAIN VOLTAGE: K-208-230V/3P/60Hz

MCA 1: 58

MCA 2: 0

2ND VOLTAGE: N/A

SINGLE DEFROST VOLT: K-208-230/3/60

D1 AMP/POLE: 44 A 3P

D2 AMP/POLE: NO A NO

D3 AMP/POLE: NO A NO

D4 AMP/POLE: NO A NO

UNIT COOLER VOLT: NO

U1 AMP/POLE: NO A NO

U2 AMP/POLE: NO A NO

U3 AMP/POLE: NO A NO

U4 AMP/POLE: NO A NO

MULTI DEFROST VOLT: NO

S PROT MAIN: NO

S CONT MAIN: NO

S1 AMP/POLE: NO A NO

S2 AMP/POLE: NO A NO

S3 AMP/POLE: NO A NO

S4 AMP/POLE: NO A NO

S5 AMP/POLE: NO A NO

S6 AMP/POLE: NO A NO

S7 AMP/POLE: NO A NO

S8 AMP/POLE: NO A NO

ACCESSORIES AND SHIP LOOSE ITEMS

PROJECT NUMBER: NC-020866 UNIT LABEL: HSERIES- 1 UNIT DESCRIPTION: CO1 FREEZER DATE: 2024-09-11

MECHANICAL SPECIAL KITS

SOLENOID VLV INST: SPECIAL 1 KIT: SCA80 XDCRS KIT TGT 1 SPECIAL 2 KIT: SPECIAL 3 KIT: SPECIAL 4 KIT: SPECIAL 5 KIT:

ELECTRICAL SPECIAL KITS

SPECIAL 6 KIT: SPECIAL 7 KIT: SPECIAL 8 KIT: SPECIAL 9 KIT: SPECIAL 10 KIT:

SHIP LOOSE SPECIAL KIT

SOLENOID VLV SL: 50SV SOLENOID 1/2 ME10S240 120V SPECIAL 11 KIT: SPECIAL 12 KIT: SPECIAL 13 KIT: SPECIAL 14 KIT: SPECIAL 15 KIT:

COD SPECIAL KITS

SPECIAL 16 KIT:

FQS COMMISSIONING SUPPORT NO

FIELD QUALITY SERVICE IS CHARGED ARE PER QUOTE NOT PER UNIT

NOTES:

