


PRMH20250744



CUSTOMER SPECIFICATION REPORT

PROJECT NUMBER:

NC-020866

UNIT LABEL:

CU2

UNIT DESCRIPTION:

D01 COOLER

DATE:

2024-09-11

CUSTOMER INFORMATION

CUSTOMER NAME: T0342

STORE NAME:

STORE NUMBER:

ADDRESS 1:

ADDRESS 2: PUYALLUP, WA USA

FACTORY INFORMATION

FACTORY UNIT ID: B

SALESMAN:

AE LEAD: JTRACHTA

SUBMITTER: JAN TRACHTA

PERFORMANCE INFORMATION**NOMENCLATURE ENDS WITH "D" WHEN****DOE COMPLIANT**

AWEF RATING: 7.6

LOAD:

21.50 MBH

MID SUCT:

22 °F

CAPACITY:

24.90MBH

AMB TEMP:

100 °F

POWER:

3.13 kW

MID COND:

114.6 °F

% LOAD:

86%

TD:

14.58 °F

MECHANICAL OPTIONS**NOMENCLATURE HDHZ-0300MRK-DE-D**

UNIT: D-OUTDOOR HE

BASE: H-HBASEMHOD

COMPRESSOR: Z-SCROLL

HP: 0300-3 HP

APPLICATION: M-MEDIUM TEMP

REFRIGERANT: R-R449A

RCVR INSUL/HTR: Y-YES HEAT+INSUL

BALL VLV REC INLET: YES

LIQUID DRIER: STD-STD SEALED D

SUCTION ACCUM: Y-YES, ACCUMULAT

SUCTION FILTER: STD-STD SEALED F

OIL SEPARATOR: NO

OIL SAFETY: NO

PHASE MONITOR: NO

COMPR UNLOAD: NO

COMPR HEAD FAN: NO

DISCHARGE CHECK VLV: NO

PRESSURE RELIEF: R-RELIEF VALVESTD ELECTRICAL P

UNIT VOLTAGE: K-208-230V/3P/60

CONDENSER: D-COND D Electrofin

RECEIVER: E-E 8-5/8X30

CONTROL VOLTAGE: D-208V/1P/60HZ

LOGO: H-HUSSMANN

SHIPPING: S-SKID

CABINET SIZE: MEDIUM

BASE LOCATION: NO

LOWER BASE: M-MEDIUM

ESTIMATED WEIGHT: 650

OIL REG: NO

CRANKCASE HEATER: Y-YES

FIN MATERIAL: E-ELECTROFIN

FAN CYCLING: 1H-1 STEP HE-AMB

FAN CYCLING CONFIG: HC-1N-2A

MOUNTING TYPE: H-HARD MOUNT

HEAD PRESSURE: A-ADJUSTABLE

HIGH PRESSURE: MC-MANUAL CARTRI

LOW PRESSURE: AU-ADJ - ULTRACA

DIMENSIONS: 3' 8 9/16 "L x 2' 11 7/64 "W x 4' 1 33/64 "H

HAIL GUARD: S-SHIPLOOSE

PUMPDOWN SWITCH: NO

INSULATION: NO

THERMOSTAT: NO

HEAT RECLAIM VALVE: NO

HOT GAS BYPASS: NO

CS RELAY: NO

DRAIN OIL: NO

ECM FAN MOTOR: NO

COMPRESSOR MODEL: ZB21KCE

DOE COMPLIANT: Y-YES

HIGH WIND OPTION: NO

ELECTRICAL OPTIONS

ELECTRICAL CONN: S-SINGLE POINT

PROTECTION TYPE: F-FUSES

CONTACTOR TYPE: D-DP (DEFINITE P

CONTACTOR BRAND: S-SQUARE D

DEFROST TIMER: NO

ADJ TIME DELAY RELAY Y-66FB

CONTROLLER: NO

MAIN PROTECTION 1: NF-NON-FUSE DISC

MAIN PROTECTION 2: NO

MOPD 1: 25

MOPD 2: NO

MAIN VOLTAGE: K-208-230V/3P/60Hz

MCA 1: 18.7

MCA 2: 0

2ND VOLTAGE: N/A

SINGLE DEFROST VOLT: NO

D1 AMP/POLE: NO A NO

D2 AMP/POLE: NO A NO

D3 AMP/POLE: NO A NO

D4 AMP/POLE: NO A NO

UNIT COOLER VOLT: NO

U1 AMP/POLE: NO A NO

U2 AMP/POLE: NO A NO

U3 AMP/POLE: NO A NO

U4 AMP/POLE: NO A NO

MULTI DEFROST VOLT: NO

S PROT MAIN: NO

S CONT MAIN: NO

S1 AMP/POLE: NO A NO

S2 AMP/POLE: NO A NO

S3 AMP/POLE: NO A NO

S4 AMP/POLE: NO A NO

S5 AMP/POLE: NO A NO

S6 AMP/POLE: NO A NO

S7 AMP/POLE: NO A NO

S8 AMP/POLE: NO A NO

ACCESSORIES AND SHIP LOOSE ITEMS

PROJECT NUMBER: NC-020866 UNIT LABEL: HSERIES- 2 UNIT DESCRIPTION: D01 COOLER DATE: 2024-09-11

MECHANICAL SPECIAL KITS

SOLENOID VLV INST: SPECIAL 1 KIT: SCA80 XDCRS KIT TGT 1 SPECIAL 2 KIT: SPECIAL 3 KIT: SPECIAL 4 KIT: SPECIAL 5 KIT:

ELECTRICAL SPECIAL KITS

SPECIAL 6 KIT: SPECIAL 7 KIT: SPECIAL 8 KIT: SPECIAL 9 KIT: SPECIAL 10 KIT:

SHIP LOOSE SPECIAL KIT

SOLENOID VLV SL: 99ZA SOLENOID 1/2 ME6S140 120V SPECIAL 11 KIT: SPECIAL 12 KIT: SPECIAL 13 KIT: SPECIAL 14 KIT: SPECIAL 15 KIT:

COD SPECIAL KITS

SPECIAL 16 KIT:

FQS COMMISSIONING SUPPORT NO

FIELD QUALITY SERVICE IS CHARGED ARE PER QUOTE NOT PER UNIT

NOTES:

