

Sign Spacing												Legend																																																																																																																																																																																																														
<table border="1"> <thead> <tr> <th colspan="3">10 Feet</th> <th colspan="3">11 Feet</th> <th colspan="3">12 Feet</th> <th colspan="3">Shoulder Tapers</th> </tr> <tr> <th>MPH</th> <th>Merge</th> <th>Cone</th> <th>Shift</th> <th>Cone</th> <th>Merge</th> <th>Cone</th> <th>Shift</th> <th>Cone</th> <th>Merge</th> <th>Cone</th> <th>Shift</th> <th>Cone</th> <th>MPH</th> <th>Length</th> <th>Cone</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>70</td> <td>6</td> <td>35</td> <td>3</td> <td>75</td> <td>6</td> <td>40</td> <td>3</td> <td>80</td> <td>6</td> <td>40</td> <td>3</td> <td>20</td> <td>25</td> <td>3</td> </tr> <tr> <td>25</td> <td>105</td> <td>6</td> <td>55</td> <td>4</td> <td>115</td> <td>7</td> <td>60</td> <td>4</td> <td>125</td> <td>7</td> <td>65</td> <td>4</td> <td>25</td> <td>35</td> <td>3</td> </tr> <tr> <td>30</td> <td>150</td> <td>8</td> <td>75</td> <td>5</td> <td>165</td> <td>9</td> <td>85</td> <td>5</td> <td>180</td> <td>10</td> <td>90</td> <td>5</td> <td>30</td> <td>50</td> <td>3</td> </tr> <tr> <td>35</td> <td>205</td> <td>8</td> <td>105</td> <td>5</td> <td>225</td> <td>9</td> <td>115</td> <td>5</td> <td>245</td> <td>9</td> <td>125</td> <td>5</td> <td>35</td> <td>70</td> <td>4</td> </tr> <tr> <td>40</td> <td>270</td> <td>10</td> <td>135</td> <td>6</td> <td>295</td> <td>11</td> <td>150</td> <td>6</td> <td>320</td> <td>12</td> <td>160</td> <td>6</td> <td>40</td> <td>90</td> <td>4</td> </tr> <tr> <td>45</td> <td>450</td> <td>16</td> <td>225</td> <td>9</td> <td>495</td> <td>18</td> <td>250</td> <td>9</td> <td>540</td> <td>19</td> <td>270</td> <td>10</td> <td>45</td> <td>150</td> <td>6</td> </tr> <tr> <td>50</td> <td>500</td> <td>14</td> <td>250</td> <td>8</td> <td>550</td> <td>15</td> <td>275</td> <td>8</td> <td>600</td> <td>16</td> <td>300</td> <td>9</td> <td>50</td> <td>170</td> <td>6</td> </tr> <tr> <td>55</td> <td>550</td> <td>15</td> <td>275</td> <td>8</td> <td>605</td> <td>16</td> <td>305</td> <td>9</td> <td>660</td> <td>18</td> <td>330</td> <td>9</td> <td>55</td> <td>185</td> <td>6</td> </tr> <tr> <td>60</td> <td>600</td> <td>16</td> <td>300</td> <td>9</td> <td>660</td> <td>18</td> <td>330</td> <td>9</td> <td>720</td> <td>19</td> <td>360</td> <td>10</td> <td>60</td> <td>200</td> <td>6</td> </tr> <tr> <td>65</td> <td>650</td> <td>17</td> <td>325</td> <td>9</td> <td>715</td> <td>19</td> <td>370</td> <td>10</td> <td>780</td> <td>21</td> <td>390</td> <td>11</td> <td>65</td> <td>220</td> <td>7</td> </tr> <tr> <td>70</td> <td>700</td> <td>19</td> <td>350</td> <td>10</td> <td>770</td> <td>20</td> <td>385</td> <td>11</td> <td>840</td> <td>22</td> <td>420</td> <td>12</td> <td>70</td> <td>235</td> <td>7</td> </tr> </tbody> </table>												10 Feet			11 Feet			12 Feet			Shoulder Tapers			MPH	Merge	Cone	Shift	Cone	Merge	Cone	Shift	Cone	Merge	Cone	Shift	Cone	MPH	Length	Cone	20	70	6	35	3	75	6	40	3	80	6	40	3	20	25	3	25	105	6	55	4	115	7	60	4	125	7	65	4	25	35	3	30	150	8	75	5	165	9	85	5	180	10	90	5	30	50	3	35	205	8	105	5	225	9	115	5	245	9	125	5	35	70	4	40	270	10	135	6	295	11	150	6	320	12	160	6	40	90	4	45	450	16	225	9	495	18	250	9	540	19	270	10	45	150	6	50	500	14	250	8	550	15	275	8	600	16	300	9	50	170	6	55	550	15	275	8	605	16	305	9	660	18	330	9	55	185	6	60	600	16	300	9	660	18	330	9	720	19	360	10	60	200	6	65	650	17	325	9	715	19	370	10	780	21	390	11	65	220	7	70	700	19	350	10	770	20	385	11	840	22	420	12	70	235	7	Freeways & Expressways 55/70 MPH 1500' +/- Rural Highways 60/65 MPH 800' +/- Rural Roads 45/55 MPH 500' +/- Rural Roads & Urban Arterials 35/40 MPH 350' +/- Rural Roads, Urban Streets Residential & Business Districts 25/30 MPH 200' +/- Urban Streets 25 MPH or LESS 100' +/-		Arrowboard Bucket Truck Cone UPO UPO Car W3-4 Be Prepared To Stop W4-2 Road Narrows W20-1 Road Work Ahead W20-3 Left Lane Closed Ahead W20-7 Flagger
10 Feet			11 Feet			12 Feet			Shoulder Tapers																																																																																																																																																																																																																	
MPH	Merge	Cone	Shift	Cone	Merge	Cone	Shift	Cone	Merge	Cone	Shift	Cone	MPH	Length	Cone																																																																																																																																																																																																											
20	70	6	35	3	75	6	40	3	80	6	40	3	20	25	3																																																																																																																																																																																																											
25	105	6	55	4	115	7	60	4	125	7	65	4	25	35	3																																																																																																																																																																																																											
30	150	8	75	5	165	9	85	5	180	10	90	5	30	50	3																																																																																																																																																																																																											
35	205	8	105	5	225	9	115	5	245	9	125	5	35	70	4																																																																																																																																																																																																											
40	270	10	135	6	295	11	150	6	320	12	160	6	40	90	4																																																																																																																																																																																																											
45	450	16	225	9	495	18	250	9	540	19	270	10	45	150	6																																																																																																																																																																																																											
50	500	14	250	8	550	15	275	8	600	16	300	9	50	170	6																																																																																																																																																																																																											
55	550	15	275	8	605	16	305	9	660	18	330	9	55	185	6																																																																																																																																																																																																											
60	600	16	300	9	660	18	330	9	720	19	360	10	60	200	6																																																																																																																																																																																																											
65	650	17	325	9	715	19	370	10	780	21	390	11	65	220	7																																																																																																																																																																																																											
70	700	19	350	10	770	20	385	11	840	22	420	12	70	235	7																																																																																																																																																																																																											

Flaggers to watch for pedestrians and provide safe passage around work zone.

4. Maintain 11ft lane width

Puyallup construction restriction zones and routes shall be in effect during special events in downtown Puyallup or at the Washington State Fair. No work is allowed in the public right-of-way as defined by the Puyallup "Construction Restriction Zone & Routes Map."

Uniformed Police Officer is Required to be on site to control the intersection with the signal in flash. Call City Inspectors 48 hours prior to working to schedule flash operations.

The applicant/contractor shall contact Meghan Genge, Puyallup Police Department Project Coordinator, at 253-841-5436 or MGenge@puyallupwa.gov to coordinate traffic support with a Puyallup uniformed police officer at least 24 hours of job start.

SPEED LIMIT
35

Notes:

1. All signs and spacing to conform to the MUTCD and WSDOT guidelines.
2. Notify property owners in advance. Contractor shall coordinate with residents for DWY access
3. "Road Work Ahead" signs to side roads/driveways if needed.
4. Maintain 10' minimum lane widths at all times.
5. Traffic control devices shall not encroach into adjacent lanes.
6. The distances shown on the traffic control plans are desirable minimum requirements. Device spacing, buffer space and sign spacing might require adjustments based on field conditions.
7. Work to take place between 9 a.m and 4p.m unless otherwise specified. All work for arterials and major roadways will be from 9 a.m to 3 p.m.

Date: 8/1/2025 **Author:** Christian Matthews **Project:** E Pioneer & Shaw Road E, Puyallup, WA
Company: McKee **Contact:** Chris Roberts **Phone:** 253.350.9870

Comments:

This TCP is "stand alone" and shall not be active concurrently with any other TCP.

MAXIMUM CHANNELIZATION DEVICE SPACING (feet)

MPH	TAPER	TANGENT
50/65	40	80
35/45	30	60
20/30	20	40

Permit:

Night Work Hours:
9 PM - 5 AM

Page 1 of 1