




Cables should enter the vault so that all of the cables will lay in the same direction.


J-BOX CABLE ENTRY DETAIL NOT TO SCALE 12kV CABLE ROUTING




TYPICAL NOTCH-OUT FOR TRANSFORMER, & SECONDARY PEDESTAL/HANDHOLE








SECONDARY PEDESTAL DETAIL





- CURB OR EDGE OF PAVEMENT

OIL-FILLED EQUIPMENT


Oil-Filled Equipment Clearances per PSE Std 0700.1500

TRANSFORMER AREA

# MINIMUM CLEARANCES FOR PSE EQUIPMENT


#### If the oil-filled equipment is adjacent to.. Combustible walls or roof (including stucco). 10 FT Noncombustible walls, soffits, and roofs (including brick, concrete steel and stone) providing the side of the transformer facing the w does not have doors. Materials that pass UBC Std. 2-1 or ASTM E136-79 are considered to be noncombustible. 3 FT Fire sprinkler valves, standpipes, and fire hydrants. 6 FT Doors, windows, vents, fire escapes, or other building openings. 10 FT The water's edge of a swimming pool or any body of water. 15 FT Individual domestic and irrigation wells. Clearance not required on pole mounted transformers (pole placement still applies as stated in 6450.3000). ITUT's installed in sealed vaults, 7200V single-phase padmount transformers 50kva or less, and ones with reduced 100 FT Facilities used to dispense or store LP, hazardous liquids, or fuel. 20 FT

3 FT



# NOTES: 1. If the final backfill contains rocks *greater than 8 inches in diameter*, install 12 inches compacted sand shading across the full width of the trench. \* 1. If the final backfill contains rocks *greater than 8 inches in diameter*, install 12 inches compacted sand shading across the full width of the trench. \* 2. Rocks *greater than 10 inches diameter* are not permitted in the final backfill. 3. Sand bedding is required under PSE gas pipe. Bedding is not required for the full width of the trench, it shall extend from the side of the trench nearest to where the gas main/service is installed to a minimum of 6 inches on the opposite side of the gas line. 4. Utilities shall not be stacked over the gas line in the trench. 5. If wet utilities will be included in the trench, please contact PSE or local power company directly for clearance requirements. 6. Reduced clearance of 4 inches between power and communication, must have approval of the communications companies. \* Alternatives to full-width trench shading require PSE approval.

JOINT TRENCH DETAIL Primary & Secondary & Communications (NTS)



All switching arrangements and/or outage arrangements are to be made with the Project Manager at least three (3) working days in advance.

3. Contact the Utilities Underground Location Center (1-800-424-5555) at least 48 hours prior to commencing work to get the underground facilities located.

4. STAKING: The customer will provide all staking (transformer, handhole, trench, grade, lot, pole, sidewalk etc.). See sketch and details for locations. Equipment locations must be approved by the Project Manager

5. SITE PREPARATION: The work area will be at or near finished grade, clear of trench spoils or construction materials which would restrict construction and/or equipment access, before work can begin.

6. Roads shall be paved or have a compacted, crushed rock base in place.

7. CLEARANCES: Transformers require a minimum of 6 feet from fire fighting equipment, 10 feet from combustible walls, overhangs, doors, and windows, and a minimum of 5 feet from the back of curb (or guard posts will be required per PSE standards). All conduits and vaults are to be at least 5 feet away from water, storm and sewer lines when paralleling them in the right of way, and at least 1 foot when crossing them.

8. All work is to be done in accordance with local municipal and county permit requirements as applicable

9. Customer/Developer is responsible to provide, install and maintain all secondary service cables, conduits and crossings from the individual unit's meter base to the designated connection point.

10. Inclement weather conditions may cause delays in construction times and dates


11. EXCAVATION: The customer is to provide all trenching, backfill, vault excavations, compaction and restoration per this sketch and per PSE standards. A minimum protective cover of 36" is required over PSE's primary voltage equipment and 24" is required of PSE's secondary voltage equipment. The customer will provide any and all shoring or they will side slope the trench to 1:1.



#### **EROSION & SEDIMENT CONTROL REQUIREMENTS**

EROSION & SEDIMENT CONTROL SHALL BE PER PSE STANDARD PRACTICE 0150.3200 TECHNIQUES FOR TEMPORARY EROSION & SEDIMENT CONTROL & ANY ADDITIONAL LOCAL JURISDICTION REQUIREMENTS & ANY ADDITIONAL LOCAL JURISDICTION REQUIREMENTS.

(LOCAL JURISDICTIONS MAY HAVE ADDITIONAL REQUIREMENTS INCLUDING NOTES DETAILING WHERE EROSION OR SEDIMENT CONTROL STRUCTURES ARE TO BE INSTALLED, CROSS SECTION DETAILS OF THE TYPICAL EROSION STRUCTURES, & SPECIAL REQUIREMENTS FOR WORK IN SENSITIVE AREAS.)




BRADLEY HEIGHTS SS, LLC 614 BOYLSTON AVE E SEATTLE, WA 98102 ATTN: ELAINE PALACIOS DON BETTENCOURT

or contacts below dial 1-888-CALL PSE (225-5773

CALL (800) 424-555 2 BUSINESS DAYS BEFORE YOU DI Flagging Required CONTACT PHONE NO DATE REV# DATE BY DESCRIPTIO D HLETKO PIERCE HECKED BY C. Gestring 08.25.25 03NW-T19N-R04E REMAN #1 1904E008 FRU-22 CONTAC

PHONE **PUGET** SOUND

BRADLEY HEIGHTS STREET LIGHT CONVERSION 202 27TH AVE SE, PUYALLUP, WA 98374




ROAD SIDE (PREFERRED)

CLEAR WORKING SPACE FOR VAULTS NOT TO SCALE

6 FT

Gas service meter relief vent.

CIRCUIT FEET ADDED: 10' SCHED. 17 0 SQ. FT. MAX LRC = 75 AMPS



### SECONDARY HH/PEDESTAL TABLE

Site	Pedestal or Handhole	Number of Positions Required	Remarks
H1A	PEDESTAL	2	- SEPS3 6050.1000 , 3-22

PRIMARY CABLE & CONDUIT TABLE

LOCA	TION	CONDUIT CABLE								CABLE				ASBUILT INFORMATION - FOREMAN COMPLETE									
FROM	то	SIZE	QTY.	DESIGN		BENDS			PULL	PULL REV	CABLE	DESIGN LENGTH	PHASE - ID TAG			RECORD			RECORD PHASE TAPPED & ACTUAL FOOTAGE INSTALLED LUBRICAL			NT (Gal.)	
FROM	10	(IN)		QII.	(FT)	90°	45°	22°	11°	(LBS)	(LBS) SIZ	SIZE	(FT)	Α	В	С	MANUFACTURER	COMPOUND	YEAR	NOTES	CONDUIT	CABLE	EST.
J01	V01	2	1	10	-	-	-	-	31	31	1/0 AL JKT	20	EKJ199						-			0.7	
2" PVC (FT) & BENDS = 10 0 0 0 1/0 AL JKT TOTAL (FT) = 20 TTL (Gal.) 11.2											11.2												

SECONDARY CABLE & CONDUIT TABLE

			CABLE		CONDUIT						VOL.	TAGE	ASBUILT INFORMATION			
LOCA	LOCATION		LENGTH	ASSUMED	SIZE	LENGTH		BENDS		DROP	FLICKER	Foreman - Complete				
FROM	то	(1/0,4/0,350)	Design (ft)	Lot Corner to Meter (ft)	(in)	(in) Design (ft) 90° 45° 22° 11° (Percent) (Perce		(Percent)	Actual Amount Installed	Cable	Conduit					
V01	H1A	350	20	-	2	10	1	-	-	-	2.5	1.3				
	350 UG	Triplex (ft) =	20	2" PVC & BEN	DS (ff)=	10	1	0	0	٥	0.1					


TOTAL QTS OF GLUE 0.1

VAULT & EQUIPMENT TABLE


		VAULT SIZE &	TYPE & SIZE EQUIPMENT IN	PRIM BUSH	IARY INGS	TRANSFORMER ID NUMBERS	AS-BUILT INFORMATION				
SITE #	GRID#			LB	DC	(COMPANY ID)	FOREMAN: INCLUDE PHASE TAPPED				
V01	567342 155491	42"x48"x38" Unistrut HH Matid: 7663001	25KVA MP TRF 120/240 Matid: 6247000	2	-		MINU1SL 6045.1010 AØ 3-19A				

### CIRCUIT LOADING TABLE


CIRCUIT: AS OF	FRU-22 06.26.24	A PHASE	B PHASE	C PHASE
EXIST, PE	EAK LOAD	303	326	317
EST. NEV	V LOAD	1	0	0
TOTAL		304	326	317




SITE PLAN 1" = 50'



**NEW CONDUIT DIAGRAM** 





pment & Permitting S ISSUED PERMIT Building


# NEW PRIMARY UNDERGROUND CIRCUIT ONE-LINE DIAGRAM

## SITE SPECIFIC NOTES

AT P01 (567337-155494) 40' CLASS 3, 1972 -DISCONNECT AND ABANDON CUSTOMER OWNED WIRE AT IP1 -EXPOSE EXISTING CUSTOMER OWNED WIRE AND ROUTE TO NEW HAND HOLE

EX OVERHEAD CIRCUIT MAP 1904E008

LABOR UNITS



AØ14607 BØ14608 CØ14609

EX UNDERGROUND CIRCUIT MAP 1904E010

CALL (800) 424-5555 2 BUSINESS DAYS BEFORE YOU DIG

F								STATE/EASEN	PERMIT			
						F	REDT#( RW-	PUYALLUP				
3							FUNCT	ION	CONTACT	PHONE NO	DATE	
2							PROJE	CT MGR	D. BETTENCOURT	206.445.5958		
1							ENGR-	POWER	D. HLETKO		08.21.25	
REV#	DATE	BY	DES	CRIPTIO	N		ENGR -	GAS	N/A		N/A	
OUNTY		Emer Sect	Emer Sect Gas Wk Ctr			WK CTR	DRAWN	I BY	D. HLETKO		08.21.25	
PIERO	Œ	N/A		N/A		QSWPRE		ED BY	C. Gestring		08,25,25	
4 SEC		OP MAP			PLAT M	AP	APPROVED BY		0			
03NW-T19I	V-R04E	N/A				N/A	FOREMAN #1					
-MAP NO (F	OWER)	OH CKT MA	OH CKT MAP UG CKT			MAP CIRCUIT NO		AN #2				
1904E0	010	1904E008 1904			E010	FRU-22	MAPPING					
JOINT FACILITIES ARRANGEMENTS												
	UTILITIES	CC	MCA	ST		LUMEN		RIGHT OF WAY				
(	CONTACT	BAR	TSIS	TEK				DARBY BROYLES				
	PHONE#	425	293,1	340				360.7	66,5489			

PUGET SOUND ENERGY

BRADLEY HEIGHTS STREET LIGHT CONVERSION 202 27TH AVE SE, PUYALLUP, WA 98374