

G42000XX

Technical Specifications

PANEL

Active Display Area	42" (1040 x 260 mm)
Backlight	LED
Resolution	1920 x 480 px
Pixel Pitch (mm)	0.53 mm (H) x 0.53 mm (V)
Brightness	1200 cd/m ² (Typ)
Contrast Ratio	4000:1
Viewing Angle	178° (H) 178° (V)
Display Colours	16.7 Million colours (Max)

CONNECTIVITY

Video	N/D
Power Consumption	300 W (Max)
Power Input	110 - 240 VAC, 0 - 60 Hz of input voltage
External Controls	N/D
Diagnostic	Remote screen Monitoring for Screen Activity, performance, internal Temperature, fan performance

MECHANICAL STRUCTURE

Dimensions (W-H-D)	1106.3 x 436 x 250.9 mm
Weight	45 Kg
Wall VESA Mounting	N/D
Protective Glass	Optically bonded 6mm harden glass
Self-Standing Mounting	N/A
External Colour	Satin black
Operating Temperature	-20°C to +40°C (direct sunlight) -40°C to +40°C (with the addition of internal heating strap)

SPECIAL FEATURES

Bezel	N/D
Special Features	4 air flow temperature monitoring sensors, an internal display sensor, an internal enclosure sensor, two air circulation sensors MTBF 50000 hours
Touch Screen Module	N/D
Media Player Option Type	N/D
IP Rate	IP54

EMBEDDED PC

Please contact GDS for available details

CERTIFICATION

CE, UL

ACCESSORIES

Please contact GDS for available details

