
codes and regulations of the local government.


METAL INSULATED PANELS

FREEZER / COOLER WALLS (SIO)

BUILDING/PLUMBING/MECHANICAL PERMIT 2018 CODES



1201 39TH AVENUE SW PUYALLUP, WA 98373



THE OPERATIONAL PHASING.

PROVIDE TEMPORARY UTILITIES AS REQUIRED DURING PHASING.

ILLUMINATION FOR THE TEMPORARY SIGN. CONFIRM LOCATIONS WITH THE OWNER.

WHEN THE WORK INCLUDES DEMOLITION OF OR TEMPORARILY COVERING OF THE EXISTING EXTERIOR SIGNAGE, THE

CONTRACTOR SHALL PROVIDE A TEMPORARY "COSTCO WHOLESALE" SIGNAGE (OF SIZE COMPARABLE TO EXISTING

SIGN) UNTIL PERMANENT SIGN IS INSTALLED. THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS. PROVIDE

SUPPLIED AND INSTALLED BY VENDOR

SUPPLIED BY OWNER INSTALLED BY VENDOR

SUPPLIED BY OWNER INSTALLED BY

SERVICE SINK, SANITARY SEWER

CONTRACTOR

SQUARE

WOOD BLOCKING

WOOD MEMBER

PUYALLUP, WA

LOCATION #660

1201 39TH AVENUE SW

PUYALLUP, WA 98373

COSTCO WHOLESALE

999 LAKE DRIVE ISSAQUAH, WA 98027 T: 425.313.8100 www.costco.com

CORPORATION






03/11/22 PERMIT ISSUE 03.29.22 BID ADDENDA 01 05.09.22 PERMIT RESUBMITTAL


TS101

PRC 1120220498

Engineering

Public Works





PLYWOOD SUBFLOOR———

'SIMPSON' LSCZ - SEE

2- C8 HEADER WITH

TRACK - SEE

STRUCTURAL DWGS —

STRUCTURAL DWGS —

(2) LAYERS 1/2" TYPE "C" GWB

UL L544

— 1-HOUR RATED ASSEMBLY AT USABLE SPACE UNDER STAIRS


3/4" PLYWOOD AS REQUIRED —


1x3 FURRING STRIP @ 16" —


(2) LAYERS 5/8" TYPE "X" GWB


— 1-HOUR RATED ASSEMBLY AT


WOOD STAIR DETAIL AT LANDING

















NOTE:
AT EXTERIOR STAIRS ALL TREADS
ARE TO HAVE WARNING STRIPES

WOOD STAIR DETAIL AT FLOOR SCALE: 1-1/2" = 1'-0"


2x6 D.F. #2 CONNECT TO 2x16 WITH 2 ROWS OF 10D NAILS AT 4" O.C.


2X16 WOOD STAIR STRINGER

STAGGERED ----


RUBBER STRINGER

SKIRT AT WALL ----





SCALE: 1/2" = 1'-0"



City of Postering City of Ci	
Building	Planning
Engineering	Public Works
Fire OF W	Traffic

SIGNAGE LOCATIONS					
LOCATION	ROOM NAME	NO.			
OFFICE CORE	QUIET ROOM	137			
	OFFICE	152			
	EMPLOYEE LOCKER ROOM (LVL 1)	153			
	QUIET ROOM	237			
	CONFERENCE ROOM	252			
	EMPLOYEE LOCKER ROOM	253			

ACCESSIBILITY GENERAL NOTES:

- THE GENERAL CONTRACTOR IS RESPONSIBLE FOR THE CORRECT INSTALLATION OF ALL ACCESSIBILITY FEATURES ON SHEET G101, INCLUDING BUT NOT LIMITED TO THE ACCESSIBLE PARKING CROSS SLOPES, LONGITUDINAL SLOPES, SIGNAGE, STRIPING, MOUNTING HEIGHTS, AND ALL REQUIRED CLEARANCES.
- 2. THE ARCHITECT WILL CONDUCT AN ACCESSIBILITY SURVEY AT THE TIME OF SUBSTANTIAL COMPLETION TO VERIFY FULL CONFORMANCE.
- ALL OPERABLE PARTS REQUIRED TO BE ACCESSIBLE SHALL BE OPERABLE WITH ONE HAND AND SHALL NOT REQUIRE TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST. THE FORCE REQUIRED TO
- ACTIVATE OPERABLE PARTS SHALL BE 5.0 POUNDS (22.2N) MAXIMUM. ALL WALL OR POST MOUNTED ITEMS IN CIRCULATION PATHS MUST BE LOCATED WITHIN PROTRUSION LIMITS, SEE DIAGRAM ON G101
- ALL NON-CONFORMING ITEMS WILL BE DOCUMENTED AND SUBMITTED TO THE GC FOR CORRECTIVE ACTION.
- FINAL PAYMENT AND RETAINAGE WILL BE HELD BY THE OWNER UNTIL ALL ITEMS HAVE BEEN CORRECTED AND THE SURVEY HAS BEEN CERTIFIED BY THE ARCHITECT.



PUYALLUP, WA LOCATION #660

1201 39TH AVENUE SW

PUYALLUP, WA 98373


COSTCO WHOLESALE

CORPORATION 999 LAKE DRIVE ISSAQUAH, WA 98027 T: 425.313.8100 www.costco.com



BID SET

KEY PLAN




BRIAN J. BONAR, ARCHITECT





	© MG2. All rights reserved. No part of this document may be reproduced in any form or by any means without permission in writing from MG2.					
\triangle	DATE	DESCRIPTION				
	03.11.22	PERMIT ISSUE				
	03.22.22	BID ISSUE				
	03.29.22	BID ADDENDA 01				
1	05.09.22	PERMIT RESUBMITTAL 1				

PM: WILLIE MAK DRAWN: JP


EGRESS PLAN, STAIR DETAILS, AND ACCESSIBILITY FEATURES G101







──4" RUBBER



DOOR SCHEDULE

MATERIAL

WOOD

WOOD

WOOD

WOOD

MATERIAL

STEEL

STEEL

STEEL

3 HINGES

DOOR HARDWARE SCHEDULE

DOOR

HEIGHT

7'-0"

TYPE

NO.

WIDTH

3'-0"

3'-0"

3'-0"

3'-0"

HARDWARE SET #17 (SINGLE)

IVES 5BB1 [IVES 5BB1 BSC SWING CLEAR] 652

LOCATION

BREAK ROOM

BREAK ROOM -


QUIET ROOM

MEZZANINE -


CONFERENCE ROOM

MEZZANINE - QUIET

3 HINGES



0212



A502.2

PRCTI20220498

DOOR TYPE

LOUVER - WHERE

NOTED ON MECH.

KICKPLATE

NOTED ON ME DRAWINGS

SINGLE

TYPICAL INTERIOR

REMARKS

PAINT METAL FRAME TO MATCH WALL COLOR

HARDWARE SET #19 (SINGLE)

IVES 5BB1 [IVES 5BB1 BSC SWING CLEAR] 652



MARK

HD1

HD2

GENERAL NOTE

THE FOLLOWING NOTES APPLY UNLESS NOTED OTHERWISE - ASTM'S NOTED ARE TO BE LATEST EDITION.

Building Name & Site Location - Costco Wholesale - Puyallup, WA - Breakroom remodel

2. DESIGN CODE AND STANDARDS

Applicable Code (Edition/Name) - 2018 International Building Code (IBC) Other documents referenced by these notes shall be the specific edition referenced by the building code

specified above, or if not specified, shall be the latest edition. Code supplement & Date - ASCE 7-16

3. DESIGN LOADS

a.	I. Roof Live Load	See snow load
	II. Slab Live load	350 psf
	III. Mezzanine Live Load	100 psf at employee breakroom (not reducible)
b.	Snow Load	Basic ground snow load - Pg = 20 psf
		Basic roof snow load - Pf = 25 psf
		Thermal factor - Ct = 1.0
		Importance factor - Is = 1.0,
		Snow exposure factor - Ce = 1.0

Drifting snow is not required in the design. c. Seismic Risk Category II $S_S = 1.267$, $S_1 = 0.437$, le = 1.0, Site Class D S_{DS} = 0.845, S_{D1} = 0.543.

Seismic Design Category = D Basic Seismic Force Resisting System = Light-frame (cold-formed steel) walls sheathed with wood structural panels rated for shear resistance or

 $C_s = 0.13$ (LRFD), R = 6.5 Equivalent Lateral Force Procedure used. Mech. & Refrigeration unit loads will be picked up at the point of the units

and transferred into the lateral system. Sprinkler lines will be braced to top of girders or top chord of steel truss, by the sprinkler contractor.

d. Wind Load Risk Category II Basic wind speed (3 sec. gust) V_{IIIT} = 95 mph , V_{ASD} =73 mph Kzt= 1.0 Ke= 1.0

Kd=0.85 (Per ASCE 7, Table 26.6-1) Internal pressure coefficient GCpi - + 0.18 e. Dead loads Weight of structure. f. Special Loads The following special loads are to be considered: Mechanical equipment on roof.

Sprinkler lines & other reactions as noted on structural drawings. q. Load Combinations All Code required load combinations are to be used in the building design.

OSHA STANDARDS

THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR ALL PROVISIONS OF THE CURRENT OSHA STANDARDS. THE GENERAL CONTRACTOR SHALL REVIEW THESE STRUCTURAL DRAWINGS FOR ANY NONCOMPLIANCE WITH OSHA STANDARDS, TAKING INTO ACCOUNT THE GENERAL CONTRACTOR'S MEANS AND METHODS. THE GENERAL CONTRACTOR SHALL INFORM ENW OF ANY NONCOMPLIANCE SO THE DRAWINGS MAY BE MODIFIED FOR COMPLIANCE PRIOR TO CONSTRUCTION. THE GENERAL CONTRACTOR IS TOTALLY RESPONSIBLE FOR MEANS AND METHODS AS WELL AS JOBSITE SAFETY ON THIS PROJECT.

FOUNDATION

THE FOUNDATION WAS DESIGNED WITH AN ALLOWABLE SOIL BEARING CAPACITY OF 3000 PSF IN ACCORDANCE WITH SOILS REPORT 0975-056-00-1130/062399 DATED JUNE 23,1999 PREPARED BY GEO ENGINEERS, INC PREPARE THE SITE PER SOILS ENGINEER'S RECOMMENDATIONS. BEAR ALL FOOTINGS AND SLABS ON PROPERLY PREPARED NATIVE SOILS OR ON COMPACTED STRUCTURAL FILL, SEE SOILS REPORT. COMPACT ALL STRUCTURAL FILL AND BACKFILL PER SOILS ENGINEER'S RECOMMENDATIONS. DETERMINE MAXIMUM DENSITY BY ASTM D 1557. EXTEND BOTTOM OF ALL EXTERIOR FOOTINGS 18" MIN. BELOW FINAL FINISHED GRADE. FOOTING STEP LOCATIONS SHOWN ON PLANS ARE APPROXIMATE. CONTRACTOR TO VERIFY AND COORDINATE FOOTING STEPS WITH CIVIL ENGINEER TO FINISH GRADE PLANS. ADD FOOTING STEPS AS REQUIRED. SEE ARCH. AND SOILS REPORT FOR SLAB ON GRADE UNDERLAYMENT.

F'c=4000 PSI. @ 28 DAYS 5-1/2 SACKS MINIMUM CEMENT PER CUBIC YARD FOR ALL CONCRETE SLABS

F'c=3000 PSI. @ 28 DAYS 5-1/2 SACKS MINIMUM CEMENT PER CUBIC YARD FOR ALL OTHER. USE TYPE I/II CEMENT. USE TYPE III (HIGH EARLY STRENGTH) CEMENT FOR PLATFORM. FOR SPECIAL CONDITIONS ANOTHER TYPE CEMENT MAY BE REQUIRED. SUBMIT FOR APPROVAL. ULTIMATE STRENGTH DESIGN METHOD USED. MIXING AND PLACING OF ALL CONCRETE AND SELECTION OF MATERIALS SHALL BE IN ACCORDANCE WITH THE ACI CODE 318. PROPORTIONING OF AGGREGATE TO CEMENT SHALL BE SUCH AS TO PRODUCE A DENSE WORKABLE MIX WITH 4" MAXIMUM SLUMP (UNLESS SUPERPLASTICIZERS ARE USED) WHICH CAN BE PLACED WITHOUT SEGREGATION OR EXCESS FREE SURFACE WATER. FOR ADMIXTURES, SEE SPECIFICATIONS. MAXIMUM WATER/CEMENT RATIO = 0.49. 3/4" CHAMFER ALL EXPOSED EDGES, UNLESS INDICATED OTHERWISE ON ARCHITECTURAL DRAWINGS. WATER CURING SHALL BE USED. AIR ENTRAIN ALL HORIZONTAL CONCRETE EXPOSED TO WEATHER WITH 3% TO 6% AIR BY VOLUME. DO NOT USE AIR ENTRAINMENT FOR INTERIOR SLABS ON GRADE. LIMIT WATER CEMENT RATIO TO 0.45 AND USE TYPE V CEMENT WHERE SOILS "WATER SOLUBLE SULFATE EXCEEDS 0.20 PERCENT BY WT. ADD NO WATER TO CONCRETE AT SITE. IF INCREASED WORKABILITY IS REQUIRED, CONTRACTOR IS TO SUBMIT A MIX DESIGN THAT WILL ALLOW THE ADDITION OF A FIXED AMOUNT WATER REDUCING AGENT OR A FIXED AMOUNT OF SUPER-PLASTICIZER AT

A.DO NOT USE FLY ASH, SLAG OR OTHER SUPPLEMENTARY CEMENTITIOUS MATERIALS IN CONCRETE EXPOSED TO VIEW INCLUDING, BUT NOT LIMITED TO, INTERIOR FLOOR SLABS, ENTRY CANOPY SLABS, LOADING DOCK SLABS AND STAIRS, STEM WALLS, LOADING DOCK WALLS, COLUMNS OR PILASTERS, AND EXTERIOR WALKS

- a. FLY ASH, SLAG AND OTHER SUPPLEMENTARY CEMENTITIOUS MATERIALS MAY BE USED ONLY IN BELOW GRADE CONCRETE SUCH AS FOOTINGS, FOUNDATION WALLS, GRADE BEAMS, AND SIMILAR CONCEALED
- b. FLY ASH, SLAG AND OTHER SUPPLEMENTARY CEMENTITIOUS MATERIALS MAY BE USED IF DETERMINED THAT THE USE OF SUPPLEMENTARY CEMENTITIOUS MATERIALS WOULD IMPROVE RESISTANCE TO ALKALI-AGGREGATE REACTIVITY IN CONCRETE. OBTAIN WRITTEN APPROVAL FROM OWNER PRIOR TO

ACI 306R IS TO BE FOLLOWED FOR COLD WEATHER CONCRETING. ACI 305R IS TO BE FOLLOWED FOR HOT WEATHER CONCRETING. THE TESTING LAB MUST APPROVE THE CONTRACTORS METHOD OF COMPLIANCE AND CERTIFY THEIR APPROVAL WITH EACH CONCRETE TEST CYLINDER THEY CAST. TESTING LAB TO NOTIFY THE ARCHITECT IMMEDIATELY BY FAX AND PHONE OF ANY NONCOMPLIANCE.

CONCRETE AND MASONRY ANCHORS (BOLTS, THREADED RODS AND REBAR DOWELS)

HILTI KWIK BOLT TZ2 PER ESR-4266 TZ2 ESR-4266 CONCRETE HILTI KWIK BOLT 3 PER ESR-1385

ADHESIVE ANCHORS: HILTI HIT-RE 500 V3 PER ESR-3814 AND HILTI HIT-HY 200-R PER ESR-3187 CONCRETE

HILTI HIT-HY 270 PER ESR-4143 CMU UNREINFORCED

MASONRY HILTI HIT-HY 270 PER ESR-4144 CAST IN PLACE ANCHORS:

CONCRETE EMBED PER PLANS AND SECTIONS CMU EMBED PER PLANS AND SECTIONS

SCREW ANCHORS: CONCRETE HILTI KWIK HUS-EZ (KH-EZ) AND HUS-EZ I (KH-EZ I) PER ESR-3027 HILTI KWIK HUS-EZ (KH-EZ) PER ESR-3056

ADHESIVE ANCHORS SHALL BE INSTALLED IN CONCRETE HAVING A MINIMUM AGE OF 21 DAYS AT TIME OF INSTALLATION PER ACI 318 - 14 SECTION 17.1.2 INSTALLATION OF ADHESIVE ANCHORS HORIZONTALLY OR UPWARDLY INCLINED TO SUPPORT SUSTAINED TENSION LOADS SHALL BE PERFORMED BY CERTIFIED PERSONNEL IN CONFORMANCE TO ACI 318 - 14 SECTION 17.8.2.2.

FOLLOW INSTALLATION PROCEDURES OF REPORT AND MANUFACTURER'S INSTRUCTIONS. PROVIDE SPECIAL INSPECTION AS NOTED AND/OR REQUIRED BY ESR REPORT. SUBSTITUTIONS ARE NOT ALLOWED UNLESS WRITTEN APPROVAL BY ENW IS RECEIVED. SUBSTITUTIONS MUST BE SUBMITTED TO ENW FOR REVIEW PRIOR TO CONSTRUCTION. PROVIDE STAINLESS STEEL OR GALVANIZED ANCHORS FOR EXTERIOR APPLICATIONS AS REQUIRED. ANCHORS RATED FOR DRY INTERIOR CONDITIONS MAY NOT BE USED FOR EXTERIOR APPLICATIONS PER ESR REPORT.

INISTRUT SHAPES, FITTINGS, NUTS, AND BOLTS ARE PER LATEST EDITION OF UNISTRUT GENERAL ENGINEERING CATALOG. ALL UNISTRUT FRAMING AND CONNECTIONS TO BE INSTALLED AS SHOWN ON DRAWINGS. ALL HOLE PATTERN STYLES FOR FRAMING MEMBERS SHALL BE AS SPECIFIED ON DRAWING, WITH ORIENTATION AS SHOWN. ALL NUTS, BOLTS, AND HARDWARE SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS, WITH TORQUE AS SPECIFIED IN LATEST EDITION OF UNISTRUT CATALOG. ALL FITTINGS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS, WITH ORIENTATION AS SHOWN ON DRAWINGS. FITTINGS, HARDWARE, AND FRAMING FINISH SHALL BE EITHER STAINLESS STEEL OR HOT-DIPPED GALVANIZED FOR EXTERIOR OR CORROSIVE ENVIRONMENT APPLICATIONS. FINISH FOR INTERIOR APPLICATIONS SHALL BE PERMA-GREEN II, UNLESS NOTED OTHERWISE BY ARCHITECT. SUBSTITUTION OF OTHER STRUT SYSTEMS IS NOT PERMITTED WITHOUT REVIEW AND WRITTEN APPROVAL BY ENW.

LIGHT GAGE STEEL FRAMING

STUDS AND TRACKS CONFORM WITH ASTM C 955. MATERIAL CONFORM WITH ASTM A 653, GRADE 33 FOR 18 GAGE AND LIGHTER, GRADE 50 FOR 16 GAGE AND HEAVIER. GALVANIZED PER G60. SIZES AS NOTED ON DRAWINGS.

WOOD STRUCTURAL PANELS

CONFORM WITH U.S. DEPARTMENT OF COMMERCE VOLUNTARY PRODUCT STANDARDS, PS1-09, STRUCTURAL PLYWOOD OR PS 2-18, PERFORMANCE STANDARD FOR WOOD BASED STRUCTURAL-USE PANELS . ALL PANELS RATED EXPOSURE 1. SEE PLANS FOR SCREW SPACING. WALL SHEATHING: 23/32", CDX 48/24 STRUCTURAL 1. NAIL WITH #12 SCREWS

SPACE SREWS AT 6" ON CENTER AT ALL EDGES AND 12" ON CENTER FIELD. BLOCK UNSUPPORTED EDGES WITH COLD-FORMED TRACK SAME DEPTH AS VERTICAL STUDS UNLESS NOTED OTHERWISE ON PLANS OR DIAPHRAGM SCHEDULE.

FLOOR SHEATHING: SEE NOTES ON PLAN.

WINDOW WALLS

WINDOW WALL SHOP DRAWINGS WITH CALCULATIONS, ALL STAMPED AND SIGNED BY A LICENSED WASHINGTON STATE STRUCTURAL ENGINEER. SHALL BE SUBMITTED TO ARCHITECT FOR REVIEW PRIOR TO FABRICATION. SHOP DRAWINGS SHALL SHOW ALL ADDITIONAL FRAMING, BRACING, CONNECTIONS, ETC., REQUIRED FOR WINDOW WALL SUPPORT. A LETTER SHALL BE SENT TO THE CITY FROM ENGINEERS NORTHWEST STATING THAT THE SHOP DRAWINGS AND CALCULATIONS FOR THE WINDOW WALLS HAVE BEEN REVIEWED AND ARE COMPATIBLE WITH THE BASIC STRUCTURE.

SUSPENDED CEILINGS

CEILING SYSTEMS AND THEIR CONNECTIONS TO THE BUILDING STRUCTURE SHALL BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH THE CISCA RECOMMENDATIONS FOR CISCA SEISMIC ZONES 3-4 AND THE ADDITIONAL REQUIREMENTS OF ASCE 7-16 SECTION 13.5.6.2.2. PROVIDE SPECIAL INSPECTION AS REQUIRED BY CODE.

NOTE TO MECHANICAL AND ELECTRICAL TRADES

CONTRACTOR SHALL SUBMIT PLANS SHOWING LOCATION, LOAD AND ANCHORAGE OF ALL HANGERS SUPPORTING ANY MECHANICAL, ELECTRICAL, PLUMBING OR SPRINKLER LOADS IN EXCESS OF 50 POUNDS. ANY ROOF MOUNTED EQUIPMENT SHALL BE INCLUDED IN THESE PLANS AND SHALL SHOW LOADS AND LOCATIONS. THESE SHALL BE SUBMITTED TO ENGINEERS NORTHWEST FOR APPROVAL PRIOR TO INSTALLATION OF ANY OF THIS EQUIPMENT. ALL DETAILS OF CONNECTIONS TO THE STRUCTURE FOR EQUIPMENT SHALL BE BY THE SUPPLIER OF THAT EQUIPMENT. IF THE BUILDING DEPARTMENT REQUIRES A SUBMITTAL REGARDING THE DESIGN OF THESE DETAILS, IT WILL BE THE RESPONSIBILITY OF THE EQUIPMENT SUPPLIER TO PROVIDE THIS SUBMITTAL

SPECIAL CONDITIONS

CONTRACTOR SHALL VERIFY ALL DIMENSIONS IN THE FIELD AND SHALL PROVIDE ADEQUATE SHORING AND BRACING OF ALL STRUCTURAL MEMBERS DURING CONSTRUCTION. CONTRACTOR SHALL NOTIFY ENGINEER OF ALL FIELD CHANGES PRIOR TO INSTALLATION.

SHOP DRAWINGS

SUBMIT 4 SETS OF PRINTS (U.N.O. BY ARCHITECT) OR ELECTRONIC PDF FILES, OF SHOP DRAWINGS TO ENGINEER FOR REVIEW AFTER CONTRACTOR HAS REVIEWED & STAMPED FOR COMPLIANCE AND PRIOR TO FABRICATION FOR: GLU-LAMS. STRUCTURAL STEEL. MISCELLANEOUS STEEL. REINFORCING STEEL AND TRUSSES. "SHOP DRAWINGS ARE AN ERECTION AID, AND STRUCTURAL DRAWINGS SHALL TAKE PRECEDENT OVER THE SHOP DRAWINGS...".

SPECIAL INSPECTIONS AND TESTS

INSPECTIONS ARE TO BE PER IBC CHAPTER 17 AND ARE TO BE BY AN INDEPENDENT TESTING AGENCY. THE SPECIAL INSPECTION AGENCY AND SPECIAL INSPECTION INSPECTORS SHALL BE REGISTERED WITH THE WASHINGTON ASSOCIATION OF BUILDING OFFICIAL (WABO), AND SHALL BE APPROVED BY THE BUILDING OFFICIAL

CONC. EXPANSION

PRIOR TO CONSTRUCTION.

& DRILLED-IN DOWELS: COPY OF ICC REPORT FOR ANCHORS OR ADHESIVE SYSTEM USED MUST BE AVAILABLE AT JOB SITE. VERIFY ANCHORS OR ADHESIVE SYSTEM INSTALLATION IN ACCORDANCE WITH REPORT. VERIFY CERTIFICATION OF INSTALLER FOR

CONSTRUCTION: CONTINUOUS INSPECTION:

KIP (1000 POUNDS)

ADHESIVE ANCHORS.

HIGH-LOAD DIAPHRAGMS NOTED ON PLANS.

SCREWS AND PLYWOOD LAYOUT CALL ENGINEER FOR SCREW REVIEW PRIOR TO COVERING SHEAR WALLS AND DIAPHRAGMS.

LONG WAY

WELD HEAD STUD

AT CENTER LINE

FRAMING: VERIFY SIZE, GAGE AND SPACING. INSPECT WELDING. VERIFY CERTIFICATION OF WELDERS. FABRICATORS: SPECIAL INSPECTION OF STRUCTURAL FABRICATORS IS NOT REQUIRED IF FABRICATOR IS REGISTERED AND APPROVED TO DO

REPORTS: PROVIDE REPORTS IN ACCORDANCE WITH IBC SECTION 1704.2.4 OF AND QUALITY ASSURANCE SECTION OF THESE GENERAL NOTES.

SUCH WORK WITHOUT SPECIAL INSPECTION.

RESISTANCE: ALL WALLS AND MEZZANINE ELEMENTS ARE PART OF THE SEISMIC-FORCE-RESISTING SYSTEM, AND SHALL BE INSPECTED AS DESCRIBED

ABBREVIATIONS

VDDIZEAIVI			20110 11711
ARCH.	ARCHITECT	M.B.S.	METAL BLDG. SUPPLIER
BAL.	BALANCE	M.O.	MASONRY OPENING
B. OR BOT.	BOTTOM	N.F.	NEAR FACE
BTWN.	BETWEEN	N.T.S.	NOT TO SCALE
BLDG.	BUILDING	OC	ON CENTER
BRG.	BEARING	O.F.	OUTSIDE FACE
C.I.P.	CAST IN PLACE	O.S.	OUTSIDE
C.J.	CONSTRUCTION JOINT	O.T.O.	OUT TO OUT
C.L.	CENTERLINE	QTY.	QUANTITY
CLR.	CLEAR	REINF.	REINFORCING
CMU	CONCRETE MASONRY UNIT	REM.	REMAINDER
COL.	COLUMN	R.O.	ROUGH OPENING
CONC.	CONCRETE	SECT.	SECTIONS
C.S.J.	CLOSURE STRIP JOINT	SIM.	SIMILAR
EA.	EACH	S.J	SHRINKAGE JOINT
E.E.	EACH END	STL.	STEEL
E.F.	EACH FACE	SW	SHEARWALL
E.J.	EXPANSION JOINT	SYMM.	SYMMETRICAL
EL. OR ELEV.		T.	TOP
	ENGINEERS NORTHWEST	T.B.	TOP OF BEAM
EQ.	EQUAL	T.F.	TOP OF FOOTING
E.S.	EACH SIDE	T.S.	TOP OF STEEL
E.W.	EACH WAY		TOP OF SLAB
F.O.C.	FACE OF CONCRETE	T.W.	TOP OF WALL
F.O.S.	FACE OF STUD	TYP.	TYPICAL
F.O.W.	FACE OF WALL	U.N.O.	UNLESS NOTED OTHERWISE
FTG.	FOOTING	V.E.F.	VERTICAL EACH FACE
GA.	GAGE	VERT.	VERTICAL
GALV.	HOT DIP GALVANIZED	V.F.F.	VERTICAL FAR FACE
G.B.	GYPSUM WALL BOARD	VFY.	VERIFY
H. OR HORIZ.	HORIZONTAL	V.I.F.	VERTICAL INSIDE FACE
I.B.C.	INTERNATIONAL BUILDING CODE	V.N.F.	VERTICAL NEAR FACE
I.C.C.	INTERNATIONAL CODE COUNCIL	V.N.F.	VERTICAL OUTSIDE FACE
I.F	INSIDE FACE	w/	WITH
INC.	INCLUDING	w/o	WITH OUT
		/// LI C	WELD HEAD STUD

WALL BRACING SCHEDULE NUMBER OF SCREWS STRAP GUSSET TO GUSSET TO GUSSET TO (50 k.s.i.) DOWN T&B OF TRACK DOUBLE... STRAP UNBLOCKED SCREW @ 7"oc EDGES & 7"oc (NO STRAP NONE REQUIRED) (2) 2" x 16GA. 18 │ 〈 3 〉 │ 3" x 16GA. │ S/LTT20 │ 25

SCREWS MUST BE PLACED AT LEAST 3/4" APART AND MUST BE 3/4" FROM LEDGE OR END OF ALL METAL PIECES.

HOLD DOWN SCHEDULE						
HOLD DOWN	ANCHORS	SCREWS				
SIMPSON S/LTT20	1/2"Ø SIMPSON TITEN HD (EMBED 3 1/4") INSPECTED INSTALLATION I.C.C. ESR	(8) #10				
SIMPSON S/HTT4	5/8"Ø SIMPSON TITEN HD (EMBED 3 1/4") INSPECTED INSTALLATION I.C.C. ESR	(18) #10				

JOIST TYPE AND SPACING SCHEDULE					
JOIST MARK	JOIST TYPE	JOIST SPACING			
J1	8" x 1 5/8" x 16GA.	48" oc			
J2	8" x 1 5/8" x 16GA.	16" oc			

WALL STUD WIDTH SCHEDULE

ALL WALLS ARE 3 5/8" UNLESS NOTED PER MARK ABOVE.

SEE LIGHT GAGE PARTS SCHEDULE FOR GAGE AND

MINIMUM PROPERTIES.

STUD WIDTH

		LIGHT GAGE BEAM SCHEDULE	
MARK	BUILT UP BEAM	TRACKS AND SCREWS	NOTES:
В0	(2) C8 x 2 x 16GA HEADER	3 5/8" x 1 1/4" x 16GA. TRACK T. & B. w/2 SCREWS @ 16"oc	
B1	(2) C8 x 2 x 16GA HEADER	6" x 1 1/4" x 16GA. TRACK T. & B. w/2 SCREWS @ 16"oc	WHERE BEAM IS USED IN WALL BOTTOM TRACK MAY TURNED FLANGE DOWN FOR
B2	(2) C8 x 2 x 16GA HEADER	8" x 1 1/4" x 16GA. TRACK T. & B. w/2 SCREWS @ 16"oc	WALL STUDS. 2. SEE LIGHT GAGE PARTS SCHEDULE FOR
В3	(2) C12 x 2 x 16GA HEADER	6" x 1 1/4" x 16GA. TRACK T. & B. w/2 SCREWS @ 16"oc	MINIMUM PROPERTIES AND REMAINDER OF DETAILS. 3. SEE APPLICABLE SECTIONS FOR
B4	(2) C12 x 2 x 12GA HEADER	6" x 1 1/4" x 12GA. TRACK T. & B. w/2 SCREWS @ 4"oc SEE NOTE #4	CONNECTIONS EACH END. 4. #12 SCREWS REQUIRED FOR ALL 12GA.
B5	(2) C16 x 2 x 12GA HEADER	16" x 2" x 12GA. TRACK T. & B. w/2 SCREWS @ 4"oc SEE NOTE #4	MEMBERS

LIGHT LIGHT GAGE AND MISC. PARTS SCHEDULE									
ODOUD	ITEM	OALLOUT		MINIMU	JM PROPE	RTIES		*APPROVED SUF	PPLIERS & THEIR THESE ITEMS
GROUP	ITEM	CALLOUT	Fy (K.S.i.)	l(in.⁴)	S(in.³)	A(in.²)	ry	SSMA I.C.C	. ESR-3064P
	C12 HEADERS** (38'-0" MAX. SPAN)	(2) 12" x 2" x 12GA.	50	60.80	9.80	3.35		SSMA I.C.C	. ESR-3064P
	C12 HEADERS** (22'-8" MAX. SPAN)	(2) 12" x 1 5/8" x 14GA.	50	36.80	5.29	2.24	1.44	(2)1200S162 - 68 (50ksi)	
HEADERS.	C12 HEADERS**	(2) 12" x 2" x 14GA.	50	41.72	5.93	2.38	1.74	(2)1200S200) - 68 (50ksi)
DEIMILO	C12 (SPCL.) HEADER CAPS T. & B.	4" x 1 1/4" x 16GA.	50	0.90	0.43	0.37	0.37	400T125	54 (50ksi)
S2.1	C8 HEADERS ** (TYP. U.N.O.) (12'-0" MAX. SPAN)	(2) 8" x 1 5/8" x 16GA.	50	11.20	2.46	1.34	1.39	(2)800S162	- 54 (50ksi)
	C8 HEADERS **	(2) 8" x 2" x 16GA.	50	13.15	3.00	1.45	1.67	(2)800S200	- 54 (50ksi)
	RIM JOISTS & BLKG.**	8" x 1 1/4" x 16GA.	50	4.75	1.16	0.59	0.31	800T125 -	54 (50ksi)
JOISTS	CEILING JOIST**	8" x 1 5/8" x 16GA.	50	5.74	1.43	0.67	0.54	800S162 -	54 (50ksi)
	CEILING TRACK**	8" x 1 1/4" x 16GA.	50	4.75	1.16	0.59	0.31	800T125 -	54 (50ksi)
	WALL TOP TRACK** (U.N.O.)	3 5/8" x 1 1/4" x 16GA.	50	0.72	0.38	0.35	0.37	362T125 - 54 (50ksi)	
	WALL TOP TRACK** (SPCL.)	3 5/8" x 1 1/4" x 16GA.	50	1.34	0.67	0.62	0.36	362T125 - 97 (50ksi)	
	WALL BOT. TRACK** (U.N.O.)	3 5/8" x 1 1/4" x 16GA.	50	0.72	0.38	0.35	0.37	362T125 - 54 (50ksi)	
	WALL STUDS	3 5/8" x 1 5/8" x 20GA.	33	0.55	0.30	0.26	0.61	362S162 - 33	
	WALL TOP TRACK**	6" x 1 1/4" x 16GA.	50	2.34	0.76	0.48	0.34	600T125 - 54 (50ksi)	
WALLS. SEE	WALL BOTTOM TRACK**	6" x 1 1/4" x 16GA.	50	2.34	0.76	0.48	0.34	600T125 - 54 (50ksi)	
DETAILS SHEET S2.1	B5 HDR TOP & BOT. TRACK	6" x 2" x 12GA.	50	3.145	1.105	0.565	0.60	600S162 - 33	
	6 WALL STUDS	6" x 2" x 16GA.	50	3.32	1.106	0.613	0.732	2 600S200 - 54	
	1 1/2" x 20GA. BRACING STRAPS (HORIZ. IN WALLS)	1 1/2" WIDE x 20GA. FLAT STRAP ALT. 1 1/2" x 16GA	33					_	-
	16GA. STRAPS (DIAGONAL IN WALLS)	16GA. FLAT STRAP	50					STRAP WIDTH PER WALL BRACING SCHEDULE	
	A 16GA. STRAPS (IN CEILING)	16GA. FLAT STRAP ALT. 1 1/2" x 16GA. C.R.C.	50					STRAP WIDTH BRACING S	PER CEILING SCHEDULE
	2" x 2" ANGLE	GAGE TO MATCH SUPPORTED MEMBER	33					-	-
	STEEL DECK	1 1/2" DEEP x 22GA. TYPE "B"	33	0.175	0.184			VERCO TYPE HSB-SS I.C.C. ER-2078	WHEELING TYPE HS BW I.C.C. ESR-1116
	SCREWS (MTL. TO MTL.) TYPICAL	#10-16 x 1" HWH #3 OR PPH #3			HILTI	w/ 5/16"ø MIN. HEAD			
MISC.	SCREWS (MTL TO MTL.) FOR 12GA. ONLY	#12-14 x 1" HWH						HILTI	w/5/16"ø MIN. HEAD
	SCREWS (G.W.B. TO MTL.)	#10-24 x 1 1/2" PWH #3						HILTI	
	SCREWS (PLYWOOD TO MTL.)	#10-18 x 1 1/2" PWH #3						HILTI	6"oc EDGES & 12"oc FIELD
	WALL & BOTTOM TRACK ANCHORS	#DS37P10 (0.177"ø x 1 1/2" LOW VELOCITY DRIVE PINS						HILTI	I.C.C. ESR-1663
	UNISTRUT P1001								

1.) * SUBSTITUTION OF OTHER SUPPLIERS FOR THESE ITEMS NOT ALLOWED. ** THESE JOIST & TRACK MEMBERS TO BE UNPUNCHED. .) SINGLE FRAMING MEMBER SHOWN THUS: [.) DOUBLE FRAMING MEMBER SHOW THUS: (U.N.O.) []

(2) #8 @ 12"oc TOP & BOT.

(2) #8 @ 3"oc TOP & BOT.

(2) #8 @ 8"oc TOP & BOT.

HEADER INTERCONNECTION SCHEDULE HEADER (HDR) SCREW AND SPACING

1.) ALL SPCL. HDRS. REQUIRE WEB STIFFENERS EACH END AND EACH FACE; 4"xHDR DEPTH MINUS 2"x16GA TRACK

C12 HDR


C12 HDR SPCL.


C16 HDR SPCL.


	STRAP/CRC	NUMBER OF SCREWS					
MARK	(50 k.s.i.)	GUSSET TO TRACK	GUSSET TO STRAP	STRAP SPLICE			
$\langle A \rangle$	1 1/2" x 16GA.	2	2	2			
$\langle B \rangle$	2" x 16GA.	3	3	3			
C 3" x 16GA. 4 4 4							


SCREWS MUST BE PLACED AT LEAST 3/4" APART AND MUST BE 3/4" FROM EDGE OR END OF ALL METAL PIECES. FOR BALANCE OF INFO. SEE SECTION 1/S2.1

City of Puyallup Development & Permitting Services ISSUED PERMIT						
Building Planning						
Engineering	Public Works					
Fire						


















JOB NO:	99090014-3
NGINEER:	N. AHMED
RAWN:	C. HUH
DATE:	02-16-2020
SHEET NO:	








	DATE			03-11-2022	03-22-2022		
	DRAWING REVISIONS		DRAWING SUBMITTALS	SUBMIT FOR PERMIT	SUBMIT FOR BID	SUBMIT FOR CONSTRUCTION	
	NO.						
[22					Ì

DATE	05-05-2022			
DRAWING REVISIONS	PERMIT RESUBMITTAL			
N O	₹			







SHEET CEILING FRAMING PLAN CONTENTS:	COSTCO	MEZZANINE REMODEL 1201 39TH STREET PUYALLUP, WA. 98373
--------------------------------------	--------	--


JOB NO:	99090014-3
ENGINEER:	N. AHMED
DRAWN:	C. HUH
DATE:	02-16-2020
SHEET NO:	


S1.1





CONTRACTOR'S OPTION OF WALL SHEATHING ON ONE SIDE AND X-BRACE ON THE BACK SIDE. SEE SECTION 3a AND 4a ON SHEET S2.2






ALT. OPTION w/SHEATHING ON INSIDE AND X-BRACE ON OUTSIDE






ON	DRAWING REVISIONS	DATE
	DRAWING SUBMITTALS	
	SUBMIT FOR PERMIT	03-11-2022
	SUBMIT FOR BID	03-22-2022
	SUBMIT FOR CONSTRUCTION	
		1

DATE	05-05-2022			
DRAWING REVISIONS	PERMIT RESUBMITTAL			
NO.				





ALTERNATIVE PARTIAL CEILING FRAMING PLAN AND SECTIONS	COSTCO	MEZZANINE REMODEL 1201 39TH STREET PUYALLUP, WA. 98373
SHEET CONTENTS:		

JOB NO: 99090014-3 ENGINEER: N. AHMED DRAWN: C. HUH DATE: 02-16-2020 SHEET NO:		
DRAWN: C. HUH DATE: 02-16-2020	JOB NO:	99090014-3
DATE: 02-16-2020	ENGINEER:	N. AHMED
SHEET NO:	DRAWN:	C. HUH
SHEET NO:	DATE:	02-16-2020
	SHEET NO:	\$2.2 \\ \frac{1}{3}

City of Puyallup
Development & Permitting Services

