


Reference complete
equipment manufactures
specification.

5T Package Unit Specifications



AFUE Rating 81%

Compressor Type SCROLL

Cooling Capacity 58000 Btu/h

Crated Dimensions 50" H x 47" D x 62" W

Drain Conn. Size 3/4" FEMALE NPT

EER/SEER 11.50/14.00

F.L. Amps/L.R. Amps 1.7 / 3.5 (Outdoor) / 6.9 (Indoor)

Face Area 22.99 sq. ft. (Outdoor) / 5.0 sq. ft. (Indoor)

FLA 0.25

Gas Pipe Size 1/2"

Indoor Airflow 1760 CFM

Indoor Coil Type PLATE FIN

Input 115000 Btu/h

Max. Amps 60

MCA 39.1

Outdoor Coil Type SPINE-FIN

Power Connection 208-230/1/60

Power Input 4.94 kW

R.L. Amps - L.R. Amps 24.4 / 144.2

Refrigerant R410A

Refrigerant Charge 9.65 lbs

Refrigerant Control EXPANSION VALVE

Shipping Weight 586 lbs

Sound Rating 73 dB(A)

Tube Size 3/8"

Uncrated Dimensions 40" H x 45" D x 59" W

Weight 482 lbs

THE APPROVED CONSTRUCTION PLANS, DOCUMENTS AND ALL ENGINEERING MUST BE POSTED ON THE JOB AT ALL INSPECTIONS IN A VISIBLE AND READILY ACCESSIBLE LOCATION.

FULL SIZED LEDGIBLE COLOR PLANS ARE REQUIRED TO BE PROVIDED BY THE PERMITEE ON SITE FOR INSPECTION